Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **1** of **19**



1. PRODUCT AND COMPANY IDENTIFICATION

Product name : W-POLI HPD 45 1 R T BLUE 49245 COMPONENT A

Code : 15333543

Main recommended uses : Coating for maintenance sector

Address : Rodovia BR 280 - km 50

CEP 89270-000, Guaramirim - SC

Telephone : +55 47 3276-4000

Emergency telephone

number

: 0800 720 8000

E-mail / site : tintas@weg.net | www.weg.net

2. HAZARD IDENTIFICATION

Mixture classification

Skin Corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 2A

Skin sensitization : Category 1

Specific target organ toxicity - :

Repeated exposure

Category 2

Hazardous to the aquatic

environment - Acute

Category 3

Hazardous to the aquatic

environment - Cronic

Category 1

Classification according to NBR 14725-2/2019

Labelling Elements

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **2** of **19**









Warning phrase : Warning

Hazard phrases : H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or

repeated exposure.

H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Caution Phrases

Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowedout of

the workplace.

P273 Avoid release to the environment.

Reaction:

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to

do - continue rinsing.

P314 Get Medical advice/attention if you feel unwell.

P333+P313 If skin irritation or a rash occurs: Get

medicaladvice/attention.

P337+P313 If eye irritation persists get medical

advice/attention.

P362+P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Treatmentand disposal of waste:

P501 Dispose of contents/container as chapter 13 of the

MSDS.

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **3** of **19**



3. COMPOSITION AND INFORMATION ABOUT THE INGRENDIENTS

Product type: : Mixture

Product type: : Mixture

Ingrendients that contribute to danger:

Product name	CAS No.	Risck classification	Concentration [%]
AMINO RESIN FUNCTIONAL	136210-32-7	Skin sensitization , Category 1 Hazardous to the aquatic environment - Cronic , Category 1	>= 30 - < 50
AMINO RESIN FUNCTIONAL	136210-30-5	Skin sensitization, Category 1 Hazardous to the aquatic environment - Cronic, Category 3	>= 10 - < 20
12- HYDROXYOCTADECANOI C ACID, REACTION PRODUCTS WITH 1,3- BENZENEDIMETHANAMI NE AND HEXAMETHYLENEDIAMIN E	220926-97-6	Acute toxicity Inhalation, Category 4 Hazardous to the aquatic environment - Cronic , Category 4 Specific target organ toxicity - Repeated exposure , Category 2	>= 1 - < 5

4. FIRST AID MEASURES

Inhalation : Take the victim to fresh air, keeping them rested and warm. If

breathing is irregular or has stopped, apply artificial respiration. Do not give anything orally. Seek medical assistance immediately, bringing the product label whenever

possible.

Take the victim to fresh air, keeping them rested and warm. If breathing is irregular or has stopped, apply artificial respiration. Do not give anything orally. Seek medical assistance immediately, bringing the product label whenever

possible.

Contact with the skin : Remove all contaminated clothing immediately. Wash affected

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **4** of **19**

Шед

area with plenty of soap and water.

Remove all contaminated clothing immediately. Wash affected area with plenty of soap and water.

Contact with the eyes

: Remove contact lenses, if wearing any. Flush the eyes with running water for at least 15 minutes, holding the eyelids apart. Seek medical assistance immediately, bringing the product label with you.

Remove contact lenses, if wearing any. Flush the eyes with running water for at least 15 minutes, holding the eyelids apart. Seek medical assistance immediately, bringing the product label with you.

Ingestion

: Do not provoke vomiting. Consult with a doctor immediately.

Do not provoke vomiting. Consult with a doctor immediately.

Most important symptoms and effects, both acute and delayed

: Headaches, dizziness, fatigue and in extreme cases, loss of consciousness.

Headaches, dizziness, fatigue and in extreme cases, loss of consciousness.

Notes for the doctor

: Treat symptomatically. Do not induce vomiting because of risk of aspiration of gastric contents into the lungs. Gastric lavage is recommended when the patient ingests large quantities, more than 5ml of the substance in its pure form. The toxic potential of the quantity consumed must be evaluated in relation to the risk of aspiration during gastric lavage. Activated coal in solution could be useful. However, in some cases the coal induces vomiting.

Treat symptomatically. Do not induce vomiting because of risk of aspiration of gastric contents into the lungs. Gastric lavage is recommended when the patient ingests large quantities, more than 5ml of the substance in its pure form. The toxic potential of the quantity consumed must be evaluated in relation to the risk of aspiration during gastric lavage. Activated coal in solution could be useful. However, in some cases the coal induces vomiting.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing methods

 Water in mist form Carbon dioxide (CO2) Foam alcohol resistent Dry chemical powder

Water in mist form Carbon dioxide (CO2) Foam alcohol resistent Dry chemical powder

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: 5 of 19



Extinguishing methods not: Direct water jet.

recommended

Direct water jet.

Specific dangers

: The finely dispersed particles form explosive mixtures in air, in the presence of sparks. Burning forms a thick black smoke. Inhalation of dangerous products of decomposition may cause serious damage to health.

The finely dispersed particles form explosive mixtures in air, in the presence of sparks. Burning forms a thick black smoke. Inhalation of dangerous products of decomposition may cause serious damage to health.

Protective measures of the fire fighting team.

: The personnel involved in firefighting should wear self contained breathing apparatus with positive pressure and full protection clothes.

The personnel involved in firefighting should wear self contained breathing apparatus with positive pressure and full protection clothes.

Specific methods

: Evacuate and isolate the area. Approach from fire with wind at your back. Fight the fire to a secure distance. Remove the packaging of the product from the fire area if this can be made with safety. Chill sideways with water in form of fog all the closed packaging near the fire. Avoid that the resulting water from fire fighting reaches drains or waterways. Use dikes to contain this water and eliminate it according to environmental regulations.

Evacuate and isolate the area. Approach from fire with wind at your back. Fight the fire to a secure distance. Remove the packaging of the product from the fire area if this can be made with safety. Chill sideways with water in form of fog all the closed packaging near the fire. Avoid that the resulting water from fire fighting reaches drains or waterways. Use dikes to contain this water and eliminate it according to environmental regulations.

6. SPILL / LEAK CONTROL PROCEDURES

Personal precautions, protective equipment and emergency procedures

For the emergency service staff

: If specialized clothing is needed to combat the leak/spillage, Section 8 should be consulted. All precautions described in

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **6** of **19**

Weg

the following section must be followed.

: If specialized clothing is needed to combat the leak/spillage, Section 8 should be consulted. All precautions described in the following section must be followed.

For staff who are not part of the emergency services

No action should be taken that may generate danger to people without adequate training and qualifications. Understand the dangers of leaked/spilled products. Use appropriate personal protective equipment - see section 8. Evacuate surrounding areas. Isolate area and keep onlookers away. Do not touch or walk through spilled material. Eliminate all sources of ignition. Avoid breathing vapor or mist. Provide adequate ventilation if possible. Wear appropriate respiratory mask when ventilation is inadequate. In accordance with characteristics of the location and/or area and in relation to the amount of spilled/leaked product, additional emergency measures may be taken under the supervision of a trained professional.

: No action should be taken that may generate danger to people without adequate training and qualifications. Understand the dangers of leaked/spilled products. Use appropriate personal protective equipment - see section 8. Evacuate surrounding areas. Isolate area and keep onlookers away. Do not touch or walk through spilled material. Eliminate all sources of ignition. Avoid breathing vapor or mist. Provide adequate ventilation if possible. Wear appropriate respiratory mask when ventilation is inadequate. In accordance with characteristics of the location and/or area and in relation to the amount of spilled/leaked product, additional emergency measures may be taken under the supervision of a trained professional.

Environmental precautions

: Prevent the product or the water used in the service reaches waterways,

channels, drains, or galleries. In case of significant spill, retain

lied liquid with inert material such as sand or earth. In approprieate,

use absorbent materials such as rags, vermiculites, etc.

Prevent the product or the water used in the service reaches waterways.

channels, drains, or galleries. In case of significant spill, retain spi

lled liquid with inert material such as sand or earth. In approprieate,

use absorbent materials such as rags, vermiculites, etc.

Methods and materials for containment and cleaning

Large spills / leaks

: Understand the dangers of leaked/spilled products. Approaching the site with the wind from behind. Stop leak if this can be done safely. Confine the spill in a dike away from the leak point for later disposal. Remove local packaging from the spills site. Preferably use anti sparkling tools to collect the

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **7** of **19**



product. All equipment used when handling the product must be electrically grounded. Soak up with an inert dry material (sand, vermiculite) placing the same in a suitable container for later disposal - see chapter 13.

Understand the dangers of leaked/spilled products. Approaching the site with the wind from behind. Stop leak if this can be done safely. Confine the spill in a dike away from the leak point for later disposal. Remove local packaging from the spills site. Preferably use anti sparkling tools to collect the product. All equipment used when handling the product must be electrically grounded. Soak up with an inert dry material (sand, vermiculite) placing the same in a suitable container for later disposal - see chapter 13.

Small spills / leaks

: Stop the leak if this can be done safely. Cover up spillage in a tarp to prevent the spread by wind or rain. Use antifaiscantes tools and explosion-proof equipment properly grounded to collect the product. Place the material collected in dry, clean and properly identified containers. Cap the container loosened so removing them from the spill site. Avoid formation of dust. Remove the packaging from the spill site. If there is product disposal need refer to chapter 13

Contain and collect the material of the leak with absorbent materials and non-combustible, such as sand, earth, vermiculite, calcined diatomite, etc. in a waste container in accordance with local regulations.

Stop the leak if this can be done safely. Cover up spillage in a tarp to prevent the spread by wind or rain. Use antifaiscantes tools and explosion-proof equipment properly grounded to collect the product. Place the material collected in dry, clean and properly identified containers. Cap the container loosened so removing them from the spill site. Avoid formation of dust. Remove the packaging from the spill site. If there is product disposal need refer to chapter 13

Contain and collect the material of the leak with absorbent materials and non-combustible, such as sand, earth, vermiculite, calcined diatomite, etc. in a waste container in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Instructions for safe treatment

: Use individual protective equipment. Emergency showers and eye wash basins must be installed in locations of use and storage.

Use individual protective equipment. Emergency showers and

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **8** of **19**



eye wash basins must be installed in locations of use and storage.

Precautions for safe handling

Use appropriate personal protective equipment - see section 8; The product handling should occur in places with good natural ventilation or with the presence of local exhaust ventilation; The electrical installations must comply with the International Electrical Commission Standards (IEC), ABNT Standards (Brazilian Association of Technical Standards), taking into account the results of the classification area study for the local and/or product instalation.

Use anti-sparking tools when handling the product; In transfer operations, metal containers must be used and all containers must be properly grounded to avoid sparkling by the accumulation of static energy; Handle and use away from hot surfaces, sparks, open flames, and other sources of ignition. Do not smoke; Do not ingest. Avoid inhalation of vapors or smoke as well as avoid contact with eyes, skin and clothing: Eating and drinking should be prohibited in the area where the material is handled, stored and processed. Workers should wash their hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering food areas; After use keep the product in its original packaging, sealed; Empty containers may be hazardous and should be disposed of properly. Do not reuse the packaging; Emergency showers and eye washer should be installed in the use and storage places.

Do not handle the product until you have read and understood all safety precautions contained in this document.

Use appropriate personal protective equipment - see section 8; The product handling should occur in places with good natural ventilation or with the presence of local exhaust ventilation; The electrical installations must comply with the International Electrical Commission Standards (IEC), ABNT Standards (Brazilian Association of Technical Standards), taking into account the results of the classification area study for the local and/or product instalation.

Use anti-sparking tools when handling the product; In transfer operations, metal containers must be used and all containers must be properly grounded to avoid sparkling by the accumulation of static energy; Handle and use away from hot surfaces, sparks, open flames, and other sources of ignition. Do not smoke; Do not ingest. Avoid inhalation of vapors or smoke as well as avoid contact with eyes, skin and clothing; Eating and drinking should be prohibited in the area where the material is handled, stored and processed. Workers should wash their hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering food areas; After use keep the product in its original packaging, sealed; Empty containers may be hazardous and should be disposed of properly. Do not reuse the packaging; Emergency showers and eye washer should be installed in the use and storage places.

Do not handle the product until you have read and understood all safety precautions contained in this document.

Fire protection

: Only use in well-ventilated locations, to prevent accumulation of vapors in explosive concentrations.All conductive elements

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A





of the system, in contact with the product, must be electrically grounded Keep away from heat and sources of ignition. Tools that do not produce sparks should be used. Do not smoke.

Only use in well-ventilated locations, to prevent accumulation of vapors in explosive concentrations. All conductive elements of the system, in contact with the product, must be electrically grounded Keep away from heat and sources of ignition. Tools that do not produce sparks should be used. Do not smoke.

Storage conditions

Substances to be avoid

: Keep away from oxidising agents, strong acid solutions and strong alkaline solutions.

Keep away from oxidising agents, strong acid solutions and strong alkaline solutions.

Storage conditions

: The electrical installation must comply with NEC(National Electrical Code) or IEC (International Electrical Commission) standards and/or those of the ABNT (Brazilian Association of Technical Standards). The floor of the storage area must be impermeable, non-combustible and must have ditches that allow run off into the containment reservoir. Storage tanks must be surrounded by embankments and have drains in case of leakage.

The electrical installation must comply with NEC(National Electrical Code) or IEC (International Electrical Commission) standards and/or those of the ABNT (Brazilian Association of Technical Standards). The floor of the storage area must be impermeable, non-combustible and must have ditches that allow run off into the containment reservoir. Storage tanks must be surrounded by embankments and have drains in case of leakage.

Appropriate storage conditions

: Store the material in covered, dry, well ventilated and identified areasKeep out of direct sunlight.Store in a closed container.

Store the material in covered, dry, well ventilated and identified areasKeep out of direct sunlight. Store in a closed container.

Inappropriate storage conditions

: Exposed to elevated temperatures, sun and rain. Close to oxidizing agents. Close to food. Close to sources of heat and ignition.

Exposed to elevated temperatures, sun and rain. Close to oxidizing agents. Close to food. Close to sources of heat and ignition.

Materials to avoid

: Do not store with explosive materials, flammableand/or toxic gases, oxidizing, corrosive substances, or materials that may generate spontaneous combustion.

Do not store with explosive materials, flammableand/or toxic gases, oxidizing, corrosive substances, or materials that may

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: 10 of 19



generate spontaneous combustion.

Secure packaging materials

Recommended packaging

materials

Coated metal packaging

Plastic packaging

Coated metal packaging

Plastic packaging

Packaging materials to be

avoided

: Uncoated metal packaging

Uncoated metal packaging

8. EXPOSURE CONTROL - PERSONAL PROTECTION

The information in this chapter contain general guidelines. Chapter 1 should be consulted for any information on the recommended use of this product in different scenarios of exposure.

Engineering control measures

Preferably use the product in adequate application cabin. In case it is not possible, provide exhaustion/ventilation enough to keep the concentration of the agents indicated in this section under the limits of tolerance (L.T.), otherwise, use adequate respiratory protection equipment. The engineering controls should keep the concentrations

of gas/vapour under the limit of LEL - Lower Explosive Limit (see section 9). Use equipment explosion proof.

Engineering control measures

Preferably use the product in adequate application cabin. In case it is not possible, provide exhaustion/ventilation enough to keep the concentration of the agents indicated in this section under the limits of tolerance (L.T.), otherwise, use adequate respiratory protection equipment. The engineering controls should keep the concentrations of gas/vapour under the limit of LEL - Lower Explosive

Limit (see section 9). Use equipment explosion proof.

Control parameters

Occupational Exposure Limits

Name	CAS No.	TLV/TWA	TLV/STEL	TLV/TETO	Source
AMINO RESIN	136210-32-7				

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A





FUNCTIONAL				
AMINO RESIN	136210-30-5			
FUNCTIONAL				
12- HYDROXYOCTADECAN OIC ACID, REACTION PRODUCTS WITH 1,3- BENZENEDIMETHANA MINE AND HEXAMETHYLENEDIA	220926-97-6	10 mg/m³		ACGIH
MINE AND				

^{*}PPM - parts of vapour or gas per million of parts of contaminated air

Personal protective equipment required

Respiratory protection: In case of the concentrations are above the indicated

tolerance limits, the use of appropriated mask is necessary for this goal (half-face mask or full face mask

with filter to organic vapors and acid gases).

Respiratory protection: In case of the concentrations are above the indicated

tolerance limits, the use of appropriated mask is necessary for this goal (half-face mask or full face mask

with filter to organic vapors and acid gases).

Eye protection: Use hermetic goggles to protect against liquid splashes.

Eye protection : Use hermetic goggles to protect against liquid splashes.

Body and skin protection : It is recommended the use of apron barber type to

protecting upper limbs, trunk and lower limbs in case of splash. In case of risk of static electricity generation the

cloth should be antistatic, includin the apron.

Body and skin protection : It is recommended the use of apron barber type to

protecting upper limbs, trunk and lower limbs in case of splash. In case of risk of static electricity generation the

cloth should be antistatic, includin the apron.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid

Liquid

State of matter : Liquid

Liquid

Color : Blue

Odour : Distinctive

^{**}MG/m3 - miligrams per cubic meter of air.

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **12** of **19**

Distinctive

Odour limit : Not applicable

Not applicable

pH : 8 - 10

8 - 10

Melting point : Data not available.

Data not available.

Boiling point : Data not available.

Data not available.

Flash Point (Open cup) : > 97 °CNot flammable

> 97 °CNot flammable

Evaporation rate : Data not available.

Data not available.

Inflammation point : Method: Data not available.

Method: Data not available.

Upper explosive limit

Data not available.

Data not available.

Lower explosive limit

Data not available.

Data not available.

Vapor pressure : Data not available.

Data not available.

Density : 1,22 - 1,32 g/cm³

1,22 - 1,32 g/cm³

Solubility(ies) : Soluble in water

Soluble in water

N-octano /water partition

coefficient

Data not available.

Data not available.

Auto flammability : Data not available.

Data not available.

Cinematic viscosity (25°C) : 20 - 25 s CF4

W-POLI HPD 45 1 R T BLUE 49245 Product name Code 15333543

COMPONENT A

12.02.2020 Last revision:

Page: 13 of 19

20 - 25 s CF4

Vapor density Data not available.

Data not available.

Decomposition temperature :

10. STABILITY AND REACTIVITY

Reactivity Presents no reactivity at room temperature and under normal

conditions of use.

Presents no reactivity at room temperature and under normal

conditions of use.

Chemical stability Stable at room temperature and under normal conditions of

use. Unstable at temperatures above the flash point.

Stable at room temperature and under normal conditions of

use. Unstable at temperatures above the flash point.

Possibility of dangerous

reactions

Presents no reactivity at room temperature and under normal

conditions of use.

None when the product is stored, applied and processed

correctly.

Presents no reactivity at room temperature and under normal

conditions of use.

None when the product is stored, applied and processed

correctly.

Need to add additives and

inhibitors

Not necessary.

Not necessary.

Conditions to avoid Extreme heat and open flame.

Extreme heat and open flame.

Incompatible materials Do not store with explosive materials, flammableand/or toxic

gases, oxidizing, corrosive substances, or materials that may

generate spontaneous combustion.

Do not store with explosive materials, flammableand/or toxic gases, oxidizing, corrosive substances, or materials that may

generate spontaneous combustion.

Dangerous products of

decomposition

Produces noxious gases such as carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx). Produces

noxious gases such as carbon monoxide (CO), carbon dioxide

(CO2) and nitrogen oxides (NOx).



Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **14** of **19**



11. TOXICOLOGICAL INFORMATION

Rat

Data not available.

Components

AMINO RESIN FUNCTIONAL

Acute toxicity by oral : Test species

use DL50 2.000 mg/kg

Observations

Acute toxicity by : Test species Rat

inhalation DL50 4.224 mg/l

Observations

Acute toxicity by : Test species Rabbit

cutaneous use DL50 2.000 mg/kg

Observations

Acute toxicity (other : Test species methods of DL50

administration) LC50

Non-standard unit value

Corrosion/irritation of

skin

Serious eye damage/eye

irritation

: Data not available.

: Data not available.

Respiratory or dermal

sensitivity

: Category 1

Mutageneses : Data not available.

Carcinogenicity : Data not available.

Toxic effects for

reproduction

: Data not available.

Specific target organ

toxicity (STOT) - single

: Data not available.

exposure

Specific target organ toxicity (STOT) - repeat

toxicity (3101) - Tep

: Data not available.

exposure

Aspiration hazard : Data not available.

AMINO RESIN FUNCTIONAL

Acute toxicity by oral : Test species Data not available.

use DL50

Observations

Acute toxicity by : Test species Data not available.

inhalation DL50

PAUMAR S.A. INDÚSTRIA E COMÉRCIO – GRUPO WEG

W-POLI HPD 45 1 R T BLUE 49245 Product name Code 15333543

COMPONENT A

12.02.2020 Last revision: Page: 15 of 19

Observations

Data not available.

Data not available.

Data not available.

: Test species Acute toxicity by

cutaneous use

DL50

Observations

Acute toxicity (other : Test species methods of DL50

LC50

Non-standard unit value

Corrosion/irritation of

administration)

skin

: Data not available.

Serious eye damage/eye

irritation

: Data not available.

Respiratory or dermal

sensitivity

: Category 1

Mutageneses : Data not available.

Carcinogenicity : Data not available.

Toxic effects for

reproduction

: Data not available.

Specific target organ toxicity (STOT) - single

exposure

: Data not available.

Specific target organ toxicity (STOT) - repeat

exposure

: Data not available.

Aspiration hazard

: Data not available.

12-HYDROXYOCTADECANOIC ACID, REACTION PRODUCTS WITH 1,3-BENZENEDIMETHANAMINE AND HEXAMETHYLENEDIAMINE

Acute toxicity by oral : Test species Rat

DL50 use

2.000 mg/kg Observations

Acute toxicity by : Test species Rat

inhalation DL50 3,56 mg/l4 h

Observations

Acute toxicity by : Test species

cutaneous use DL50 2.000 mg/kg

Observations

Acute toxicity (other : Test species methods of DL50 administration) LC50

Non-standard unit value

Corrosion/irritation of

skin

: Data not available.





W-POLI HPD 45 1 R T BLUE 49245 Product name Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: 16 of 19

Serious eye damage/eye

: Data not available.

irritation

Respiratory or dermal

sensitivity

: Data not available.

Mutageneses

: Data not available.

Carcinogenicity

: Data not available.

Toxic effects for reproduction

: Data not available.

Specific target organ toxicity (STOT) - single

exposure

: Data not available.

Specific target organ toxicity (STOT) - repeat

exposure

: Data not available.

Aspiration hazard

: Data not available.

12. ECOLOGICAL INFORMATION

Stability in soil The product easily infiltrates into the soil

The product easily infiltrates into the soil

Other toxicological

observations

Data not available.

Data not available.

Ecotoxicity Contaminates the ground water.

> Detrimental to the fauna Detrimental to the flora.

Contaminates the ground water.

Detrimental to the fauna Detrimental to the flora.

13. DIOSPOSAL AND TREATMENT CONSIDERATIONS

Recommended methods for final disposal

Product Class I Waste - Dispose of in industrial landfill or a facility

authorized for recycling in accordance with federal, stateor

local regulations

Class I Waste - Dispose of in industrial landfill or a facility **Product**

authorized for recycling in accordance with federal, stateor

local regulations



Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **17** of **19**

णस

Waste : Class I Waste - Dispose of in industrial landfill or a facility

authorized for recycling in accordance with federal, stateor

local regulations

Waste Class I Waste - Dispose of in industrial landfill or a facility

authorized for recycling in accordance with federal, stateor

local regulations

Used packaging : Clean packaging should be sent for recycling. Packaging with

class I waste should be disposed of in industrial landfill or a facility authorized for recycling in accordance with federal,

state or local regulations.

Clean packaging should be sent for recycling. Packaging with class I waste should be disposed of in industrial landfill or a facility authorized for recycling in accordance with federal,

state or local regulations.

14. TRANSPORTATION INFORMATION

fNational and international regulations

Land : Not classified as a dangerous good under transport regulations.

Shipping : Not classified as a dangerous good under transport regulations.

Air transport : Not classified as a dangerous good under transport regulations.

15. REGULATORY INFORMATION

This MSDS (Material Safety Data Sheet) was generated according to the criteria of NBR 14725/2014. (Brazilian standard that defines the GHS).

Specific Regulations for the Chemical Product.

Federal Decree No. 2657, July 3rd , 1998.

Ordinance No. 229, May 24th, 2011 - Changes to Regulatory

Standard No. 26.

ABNT NBR 14725: 2014 - valid from 19/12/2014 -

Amendment 1 (19/11/2014).


Law No. 12305, August 2nd 2010 (Solid Waste National

Policy).

Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A





16. ADDITIONAL INFORMATION

Acronyms Used:

Legenda:

CAS	Chemical Abstract Service
VO	Organic Vapors
NEC	National Eletrical code/Código Nacional de Eletricidade
IEC:	International Eletrical Commision
ABNT	Brazilian Association of Technical Standards
ACGIH	American Conference of Governmental Industrial Hygienists
TLV	Threshold Limit Values
TLV/TWA	Time Weighted Average
TLV/STEL	Short Term Exposure Limit
TLC/C:	Tolerance Limit - Ceiling Value
EPI:	Individual Protective Equipment
CA	Approval Certificate
PPRA	Environmental Risk Prevention Program
NR	Regulatory Standard
NFPA	National Fire Protection Agency
mmHg	Millimeters of mercury - pressure unit
DL50	Lethal Dose average
CL50	Lethal Concentration average
ppm	Parts per million
N.d	Not available
A+B	Viscosity of the mixture of component A + component B

Important information, but not specifically described in the previous sections:

This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical.

We reserve the right to change the information contained in this document without prior



Product name W-POLI HPD 45 1 R T BLUE 49245 Code 15333543

COMPONENT A

Last revision: 12.02.2020 Page: **19** of **19**



notice, due to the improvement and continuous evolution of the product and technical knowledge.

References : Data not available.

Vertical lines in the left hand margin indicate changes from the current version