| Product name | LACKPOXI N COMPONENT | 2198 R OXYDE RED | Code | 10002948 |
|------------------------------|-------------------------|---|-----------------------------|----------|
| | 06.09.2017 | | Page: 1 of 17 | |
| | 1. PROD | UCT AND COMPANY IDEN | TIFICATION | |
| Product name | : | LACKPOXI N 2198 R OXY | DE RED COMPO | NENT A |
| Code | : | 10002948 | | |
| Main recommended | luses : | Coating for maintenance | sector | |
| Address | : | Rodovia BR 280 - km 50 CEP 89270-000, Guaram | irim - SC | |
| | | | | |
| Telephone | : | +55 47 3276-4000 | | |
| Emergency telephor number | ne : | 0800 720 8000 | | |
| E-mail / site | : | tintas@weg.net www. | weg.net | |

2. HAZARD IDENTIFICATION

| Mixture classification Flammable liquids | : | Category 3 |
|---|---|--|
| Acute toxicity (Ingestion) | : | Category 5 |
| Acute toxicity (Inhalation) | : | Category 5 |
| Skin Corrosion/irritation | : | Category 3 |
| Serious eye damage/eye irritation | : | Category 2A |
| Skin sensitization | : | Category 1 |
| Germ cell mutagenicity | : | Category 2 |
| Carcinogenicity | : | Category 1B |
| Reproductive toxicity | : | Category 1B |
| Specific target organ toxicity - Single exposure | : | Category 3 (May cause respiratory irritation.) |
| Specific target organ toxicity - Repeated exposure | : | Category 2 |

| | MATER | IAL SAFETY DATA | SHEET - MSD | S | | |
|---------------------------------------|-----------------------------|-----------------|-------------|----------------|--------------|-----|
| Product name | LACKPOXI N 2198 R OXYDE RED | | | Code | 10002948 | шео |
| | COMPONEN | IT A | | | | |
| Last revision: | 06.09.2017 | | | Page: 2 | of 17 | |
| Aspiration hazard | : | Category 1 | | | | |
| Hazardous to the a environment - Acut | • | Category 3 | | | | |
| Classification accor | ding to NBR 1 | 4725-2/2009 | | | | |
| Labelling Element | S | | | | | |



| Warning phrase | Danger |
|------------------|--|
| Hazard phrases : | H226 Flammable liquid and vapour. H303 May be harmful if swallowed. H333 May be harmful if inhaled. H316 Causes mild skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects. H350 May cause cancer. H360 May damage fertility or the unborn child. H335 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H402 Harmful to aquatic life. |
| Caution Phrases | Prevention: |
| | P201 Obtain special instructions before use. |
| | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| | P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| | P273 Avoid release to the environment. |
| | P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| | Reaction: P301+P310 IF SWALLOWED: Immediately call a POISON CENTER. |
| | P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| | P308+P313 IF exposed or concerned: Call a doctor. |

P331 Do not induce vomiting.

P333+P313 If skin irritation or a rash occurs: Get medicaladvice/attention.

P337+P313 If eye irritation persists get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use as chapter 5 of MSDS to extinguish.

Storage:

P403+P233 Store in a well ventilated place. Keep containertightly closed.

Treatmentand disposal of waste:

P501 Dispose of contents/container as chapter 13 of the MSDS.

Other hazard : When heated above its flash point, this material will release toxic vapors and flames, and can burn in open area if exposed to an ignition source.

3. COMPOSITION AND INFORMATION ABOUT THE INGRENDIENTS

Product type:

: Mixture

Ingrendients that contribute to danger:

| Product name | CAS No. | Risck classification | Concentration [%] |
|-------------------------|------------|---|-------------------|
| SOLVENT ALKYLBENZENE | 64742-95-6 | Flammable liquids , Category 3 Aspiration hazard , Category 1 Specific target organ toxicity - Single exposure , Category 3 Skin Corrosion/irritation , Category 3 Germ cell mutagenicity , Category 2 Carcinogenicity , Category 1B Hazardous to the aquatic environment - Acute , Category 2 | >= 20 - < 30 |

 PAUMAR S.A. INDÚSTRIA E COMÉRCIO – GRUPO WEG

 Rua Dr. Ulisses Guimarães, 918 – 09372-050 – Mauá – SP – Fone: + 55 (11) 4541-6100

 Rodovia Br 280 – Km 50, 6.918 – Bloco A – 89270-000 – Guaramirim – SC – Fone: + 55 (47) 3276-4000

 Rua Via VII, 314 – 54590-000 – Cabo de Santo Agostinho – PE – Fone: + 55 (81) 3512-3000

 EMERGÊNCIA: +55 0800 720 8000 – E-mail: <u>tintas@weg.net</u> - <u>www.weg.net</u>

LACKPOXI N 2198 R OXYDE RED

Product name

Code



| COMPON | I IN 2198 K UXTUE KI | ED Code | 10002948 |
|-------------------------------------|----------------------|---|--------------|
| Last revision: 06.09.202 | | Page: 4 c | of 17 |
| | | Acute toxicity Ingestion, Category 5 Specific target organ toxicity - Repeated exposure , Category 2 Aspiration hazard , Category 1 | |
| SOLVENT METHYL ETHYL KETONE | 78-93-3 | Flammable liquids , Category 3 Serious eye damage/eye irritation , Category 2A Specific target organ toxicity - Single exposure , Category 3 | >= 10 - < 20 |
| SOLVENT METHYLISOBUTYLKETO NE | 108-10-1 | Flammable liquids , Category 3 Acute toxicity Inhalation, Category 4 Serious eye damage/eye irritation , Category 2A Specific target organ toxicity - Single exposure , Category 3 | >= 5 - < 10 |
| SOLVENT ETHYL GLYCOL | 110-80-5 | Flammable liquids , Category 3 Acute toxicity Ingestion, Category 4 Acute toxicity Inhalation, Category 3 Reproductive toxicity , Category 1B | >= 1 - < 5 |
| RHEOLOGICAL ADDITIVE | 71011-24-0 | Skin sensitization , Category 1 | >= 1 - < 5 |

4. FIRST AID MEASURES

Inhalation

: Take the victim to fresh air, keeping them rested and warm. If breathing is irregular or has stopped, apply artificial respiration. Do not give anything orally. Seek medical assistance immediately, bringing the product label whenever possible.

| | MAILN | 17 | | 5 | | - |
|--|------------|----|---|---|--|------------------|
| Product name | LACKPOXI N | 12 | 198 R OXYDE RED | Code | 10002948 | Ш: |
| COMPONEN | | ΙT | A | | | |
| Last revision: | 06.09.2017 | | | Page: 5 c | of 17 | |
| Contact with the | skin | : | Remove the product with veg wash the skin thoroughly with solvents or thinners. Seek me irritation or other symptoms. | h plenty o | of water. Do not use | ; |
| Contact with the | eyes | : | Remove contact lenses, if we running water for at least 15 apart. Seek medical assistan product label with you. | 5 minutes | , holding the eyelide | 6 |
| Ingestion | | : | Do not provoke vomiting. Cons | ult with a | doctor immediately. | |
| Most important s and effects, both delayed | | : | Headaches, dizziness, fatigue consciousness. | and in ex | xtreme cases, loss o | f |
| Notes for the doc | tor | : | Treat symptomatically. Do not of aspiration of gastric content is recommended when the p more than 5ml of the substar potential of the quantity con relation to the risk of asp Activated coal in solution coul cases the coal induces vomitin | s into the atient ing- nce in its sumed m iration du d be usef | lungs. Gastric lavage ests large quantities pure form. The toxic nust be evaluated in uring gastric lavage |) ; ;) |

5. FIRE-FIGHTING MEASURES

| Suitable extinguishing methods | : | Water in mist form Carbon dioxide (CO2) Foam alcohol resistent Dry chemical powder |
|--|---|---|
| Extinguishing methods not recommended | : | Direct water jet. |
| Specific dangers | : | Flammable liquid and vapour. Dangerous when exposed to heat or ignition source. Exposed packaging to the fire may rupture due to the increased pressure with risk of a subsequent explosion. The vapours are havier than the air and spread close to the ground and it can move to the ignition source and provoke fire or backspace of the flames. Avoid the accumulation of vapours in depressions on the ground, manholes, basement etc. The vapours and/or the particles finely divided (spray) may form explosive mixtures with the air. In case of burning of the product, it forms carbon and nitrogen compounds. The inhalation of these subproducts may cause damage to health. |
| Protective measures of the fire fighting team. | : | The personnel involved in firefighting should wear self contained breathing apparatus with positive pressure and full protection clothes. |
| Specific methods | : | Evacuate and isolate the area. Approach from fire with wind at |

| | MATERI | AL SAFETY DATA SHEET | - MSDS | | |
|----------------|------------|---|---|--|----|
| Product name | LACKPOXI N | 2198 R OXYDE RED | Code | 10002948 | ШЕ |
| | COMPONEN | ГА | | | |
| Last revision: | 06.09.2017 | | Page: 6 c | of 17 | _ |
| | | your back. Fight the fire packaging of the produc with safety. Chill sidewa closed packaging near the from fire fighting reached contain this water and ed regulations. | ct from the fire are ays with water in f the fire. Avoid tha s drains or water | ea if this can be mad orm of fog all the t the resulting water ways. Use dikes to | ſ |

6. SPILL / LEAK CONTROL PROCEDURES

Personal precautions, protective equipment and emergency procedures

| For the emergency service : staff | If specialized clothing is needed to combat the leak/spillage, Section 8 should be consulted. All precautions described in the following section must be followed. |
|--|--|
| For staff who are not part : of the emergency services | No action should be taken that may generate danger to people without adequate training and qualifications.Understand the dangers of leaked/spilled products. Use appropriate personal protective equipment - see section 8. Evacuate surrounding areas. Isolate area and keep onlookers away. Do not touch or walk through spilled material. Eliminate all sources of ignition.Avoid breathing vapor or mist. Provide adequate ventilation if possible. Wear appropriate respiratory mask when ventilation is inadequate.In accordance with characteristics of the location and/or area and in relation to the amount of spilled/leaked product, additional emergency measures may be taken under the supervision of a trained professional. |
| Environmental precautions : | Prevent the product or the water used in the service reaches waterways, channels, drains, or galleries. In case of significant spill, retain spi lled liquid with inert material such as sand or earth. In approprieate, use absorbent materials such as sawdust, rags, vermiculites, etc. |

Methods and materials for containment and cleaning

Large spills / leaks : Understand the dangers of leaked/spilled products. Approaching the site with the wind from behind. Stop leak if this can be done safely. Prevent from entering holes / depressions in the floor. If this happens to provide ventilation. Confine the spill in a dike away from the leak point for later disposal. Remove local packaging from the spills site. Use anti sparkling tools and explosion-proof equipment to collect the product. All equipment used when handling the product must be electrically grounded. Soak up with an inert dry material (sand, vermiculite) placing the same in a suitable container for

| | MATERI | AL SAFETY DATA SHEET | - MSDS | | |
|------------------------|------------|--|---|---|--|
| Product name | LACKPOXI N | 2198 R OXYDE RED | Code | 10002948 | |
| | COMPONEN | ΓA | | | |
| Last revision: | 06.09.2017 | | Page: 7 c | of 17 | |
| | | later disposal - see chap | oter 13. | | |
| Small spills / leaks : | | Stop the leak if this can tarp to prevent the sprea tools and explosion-proc collect the product. Plac and properly identified c so removing them from Remove the packaging disposal need refer to ch | ad by wind or rain of equipment prop e the material co ontainers. Cap th the spill site. Avo from the spill site | b. Use antifaiscantes perly grounded to llected in dry, clean be container loosened id formation of dust. | |
| | | Contain and collect the materials and non-comb vermiculite, calcined dia | oustible, such as | sand, earth, | |

accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

| Instructions for safe treatment | : | Use individual protective equipment. Emergency showers and eye wash basins must be installed in locations of use and storage. |
|----------------------------------|---|--|
| Precautions for safe handling | : | Use appropriate personal protective equipment - see section 8; The product handling should occur in places with good natural ventilation or with the presence of local exhaust ventilation; The electrical installations must comply with the International Electrical Commission Standards (IEC), ABNT Standards (Brazilian Association of Technical Standards), taking into account the results of the classification area study for the local and/or product instalation. Use anti-sparking tools when handling the product; In transfer operations, metal containers must be used and all containers must be properly grounded to avoid sparkling by the accumulation of static energy; Handle and use away from hot surfaces, sparks, open flames, and other sources of ignition. Do not smoke;Do not ingest. Avoid inhalation of vapors or smoke as well as avoid contact with eyes, skin and clothing; Eating and drinking should be prohibited in the area where the material is handled, stored and processed. Workers should wash their hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering food areas; After use keep the product in its original packaging, sealed; Empty containers may be hazardous and should be disposed of properly. Do not reuse the packaging;Emergency showers and eye washer should be installed in the use and storage places. Do not handle the product until you have read and understood all safety precautions contained in this document. |
| Fire protection | : | Only use in well-ventilated locations, to prevent accumulation of vapors in explosive concentrations.All conductive elements |

| | MATERI | AL SAFETY DATA SHEET - MSD | S | |
|---------------------------------|--------------|---|--|--|
| Product name | LACKPOXI N 2 | 2198 R OXYDE RED | Code | 10002948 |
| Last revision: | 06.09.2017 | | Page: 8 of | 17 |
| | | of the system, in contact with the grounded Keep away from heat that do not produce sparks show | at and source | ces of ignition.Tools |
| Storage condition | S | | | |
| Substances to be | avoid : | Keep away from oxidising age strong alkaline solutions. | ents, strong | acid solutions and |
| Storage condition | ns : | The electrical installation mu Electrical Code) or IEC (Intern standards and/or those of the a Technical Standards). The floc impermeable, non-combustible allow run off into the contain must be surrounded by embank of leakage. | ational Ele ABNT (Braz or of the sto and must ment reser | ctrical Commission) zilian Association of prage area must be t have ditches that voir. Storage tanks |
| Appropriate stora conditions | age : | Store the material in cover- identified areasKeep out of dir container. | | |
| Inappropriate sto conditions | rage : | Exposed to elevated tempera oxidizing agents.Close to food ignition. | | |
| Materials to avoid | d : | Do not store with explosive magases, oxidizing, corrosive sub generate spontaneous combust | stances, or | |
| Secure packaging | materials | | | |
| Recommended p materials | ackaging : | Amber type glass. Metal packaging | | |
| Packaging mater avoided | ials to be : | Certain plastic materials | | |

8. EXPOSURE CONTROL – PERSONAL PROTECTION

The information in this chapter contain general guidelines. Chapter 1 should be consulted for any information on the recommended use of this product in different scenarios of exposure.

Engineering control measures : Preferably use the product in adequate application cabin. In case it is not possible, provide exhaustion/ventilation enough to keep the concentration of the agents indicated in this section under the limits of tolerance (L.T.), otherwise, use adequate respiratory protection equipment. The engineering controls should keep the concentrations of gas/vapour under the limit of LEL - Lower Explosive

| | MATERIAL SAFETY DATA SHEET | - MSDS | | |
|----------------|-----------------------------|------------------|--------------|-----|
| Product name | LACKPOXI N 2198 R OXYDE RED | Code | 10002948 | Шер |
| | COMPONENT A | | | |
| Last revision: | 06.09.2017 | Page: 9 c | of 17 | |
| | | | | |

Limit (see section 9). Use equipment explosion proof.

Control parameters

Occupational Exposure Limits

| Name | CAS No. | TLV/TWA | TLV/STEL | TLV/TETO | Source |
|-------------------------------------|------------|----------------------|----------|----------|--------|
| SOLVENT ALKYLBENZENE | 64742-95-6 | 50 ppm | | | ACGIH |
| SOLVENT METHYL ETHYL KETONE | 78-93-3 | 200 ppm | 300 ppm | | ACGIH |
| SOLVENT METHYLISOBUTYLKET ONE | 108-10-1 | 20 ppm | | | ACGIH |
| SOLVENT ETHYL GLYCOL | 110-80-5 | 5 ppm | | | ACGIH |
| RHEOLOGICAL ADDITIVE | 71011-24-0 | 10 mg/m ³ | | | ACGIH |

*PPM - parts of vapour or gas per million of parts of contaminated air

**MG/m³ - miligrams per cubic meter of air.

| Personal protective equipment | required |
|-------------------------------|--|
| Respiratory protection | In case of the concentrations are above the indicated tolerance limits, the use of appropriated mask is necessary for this goal (half-face mask or full face mask with filter to organic vapors and acid gases). |
| Hand protection | Use nitrilic gloves associated with the use of the adequate protection cream |
| Eye protection | Use hermetic goggles to protect against liquid splashes. |
| Body and skin protection | It is recommended the use of apron barber type to protecting upper limbs, trunk and lower limbs in case of splash. In case of risk of static electricity generation the cloth should be antistatic, includin the apron. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Form | : | Liquid |
|-----------------|---|----------------|
| State of matter | : | Liquid |
| Color | : | Red |
| Odour | : | Distinctive |
| Odour limit | : | Not applicable |

| | | L SAFETY DATA SHEET - IVIS | DS | | |
|-----------------------------------|-------------|-------------------------------|-----------------|--------------|-----|
| | | 198 R OXYDE RED | Code | 10002948 | шец |
| | COMPONENT | A | | 6 . – | |
| Last revision: | 06.09.2017 | | Page: 10 | of 17 | |
| рН | : | Not applicable | | | |
| Melting point | : | Data not available. | | | |
| Boiling point | : | Data not available. | | | |
| Flash Point (Open | cup) : | 31 °C | | | |
| Evaporation rate | : | Data not available. | | | |
| Inflammation point | t : | Method: Data not available. | | | |
| Upper explosive li | mit · | | | | |
| | | Data not available. | | | |
| Lower explosive li | mit : | Data nat available | | | |
| | | Data not available. | | | |
| Vapor pressure | : | Data not available. | | | |
| Density | : | 1,05 - 1,15 g/cm ³ | | | |
| Solubility(ies) | : | Water-insoluble | | | |
| N-octano /water pa coefficient | artition : | Data not available. | | | |
| Auto flammability | : | Data not available. | | | |
| Cinematic viscosit | zy (25°C) : | 18 - 22 s CF4 | | | |
| Vapor density | | Data not available. | | | |
| | • | | | | |

10. STABILITY AND REACTIVITY

| Reactivity | Presents no reactivity at room temperature and under normal conditions of use. |
|---|---|
| Chemical stability : | Stable at room temperature and under normal conditions of use. Unstable at temperatures above the flash point. |
| Possibility of dangerous : reactions | Presents no reactivity at room temperature and under normal conditions of use. None when the product is stored, applied and processed correctly. |
| Need to add additives and inhibitors | Not necessary. |
| Conditions to avoid | Extreme heat and open flame. |
| Incompatible materials : | Do not store with explosive materials, flammableand/or toxic gases, oxidizing, corrosive substances, or materials that may generate spontaneous combustion. Plastic materials soluble in Xylene. |

| | MATERIAL SAFETY DATA SHEET | - MSDS | | _ |
|----------------|-----------------------------|-----------------|--------------|----|
| Product name | LACKPOXI N 2198 R OXYDE RED | Code | 10002948 | Ше |
| | COMPONENT A | | | |
| Last revision: | 06.09.2017 | Page: 11 | of 17 | |
| | | | | |

Dangerous products of decomposition

: Produces noxious gases such as carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Components SOLVENT ALKYLBENZENE

| Acute toxicity by oral use | : | Test species DL50 Observations | Rat 2.908,7 mg/kg |
|---|-----|---|--------------------------------|
| Acute toxicity by inhalation | : | Test species DL50 Observations | Rat Data not available. |
| | | | |
| Acute toxicity by cutaneous use | : | Test species DL50 Observations | Rabbit Data not available. |
| Acute toxicity (other methods of administration) | : | Test species DL50 LC50 Non-standard unit value | Data not available. |
| Corrosion/irritation of skin | : | Category 3 | |
| | | | |
| Serious eye damage/eye irritation | : | Data not available. | |
| Respiratory or dermal sensitivity | : | Data not available. | |
| Mutageneses | : | Chemicals considered to induc germ cells | e heritable mutations in human |
| Carcinogenicity | : | Presumed to have carcinogeni | c potential for humans. |
| Toxic effects for reproduction | : | Suspected of causing reproduce development | ctive toxicity or human |
| Specific target organ toxicity (STOT) - single exposure | : | Passengers effects on organ ta alter human function for a shor | |
| Specific target organ toxicity (STOT) - repeat exposure | : | Substance based on evidence animals can probably present a human health on repeated exp | a potential to be harmful to |
| SOLVENT METHYL ETHYL | - K | ETONE | |
| Acute toxicity by oral use | : | Test species DL50 Observations | Rat 2.400 - 3.400 mg/kg |
| Acute toxicity by | : | Test species | |

| duct name | | 210 | 98 R OXYDE RED | Code | 10002948 |
|---|------------|-----|---|---------------|------------------------|
| | COMPONENT | | | couc | 10002540 |
| revision: | 06.09.2017 | | | Page: | 12 of 17 |
| inhalation | | | DL50 Observations | Data | not available. |
| Acute toxicity cutaneous us | | : | Test species DL50 Observations | Rabb 13.00 | bit 00 mg/kg |
| Acute toxicity methods of administratio | | : | Test species DL50 LC50 Non-standard unit value | Data | not available. |
| Corrosion/irr skin | itation of | : | Data not available. | | |
| Serious eye o | damage/eye | : | Category 2A | | |
| Respiratory o sensitivity | or dermal | : | Data not available. | | |
| Mutageneses | i | : | Data not available. | | |
| Carcinogenic | ity | : | Data not available. | | |
| Toxic effects reproduction | | : | Data not available. | | |
| Specific targe toxicity (STO exposure | | : | Passengers effects on or alter human function for a | | |
| Specific targe toxicity (STO exposure | | : | Data not available. | | |
| - | THYLISOBUT | YL | KETONE | | |
| Acute toxicity use | y by oral | : | Test species DL50 Observations | Rat 2.08 | 0 mg/kg |
| Acute toxicity inhalation | y by | : | Test species DL50 Observations | 4.00 | 0 mg/l |
| Acute toxicity cutaneous us | | : | Test species DL50 Observations | Rabb 20.00 | bit 00 mg/kg |
| Acute toxicity methods of administratio | - | : | Test species DL50 LC50 Non-standard unit value | Data | not available. |
| Corrosion/irr skin | itation of | : | Category 2 | | |
| Serious eye o | lamage/eye | : | Category 2A | | |

| duct name | LACKPOXI N 2 | 219 | 8 R OXYDE RED | Code | 10002948 |
|---|-------------------------|-----|--|--------------|------------------------|
| t revision: | COMPONENT 06.09.2017 | A | | Page: | 13 of 17 |
| Respiratory of sensitivity | or dermal | : | Data not available. | | |
| Mutageneses | 5 | : | Data not available. | | |
| Carcinogenic | city | : | Data not available. | | |
| Toxic effects reproduction | | : | Data not available. | | |
| Specific targe toxicity (STO exposure | | | Passengers effects on organ alter human function for a sho | | |
| Specific targe toxicity (STO exposure | | : | Data not available. | | |
| SOLVENT ET | HYL GLYCOL | | | | |
| Acute toxicity use | y by oral | | Test species DL50 Observations | Rat 2.13 | 0 mg/kg |
| Acute toxicity | y by | | Test species DL50 Observations | Data | a not available. |
| Acute toxicity cutaneous us | | | Test species DL50 Observations | Rabl 3.30 | bit 0 mg/kg |
| Acute toxicity methods of administratio | | | Test species DL50 LC50 Non-standard unit value | Data | a not available. |
| Corrosion/irr skin | itation of | : | Data not available. | | |
| Serious eye o | damage/eye | : | Data not available. | | |
| Respiratory o sensitivity | or dermal | : | Data not available. | | |
| Mutageneses | 5 | : | Data not available. | | |
| Carcinogenic | city | : | Data not available. | | |
| Toxic effects reproduction | | | That is assumed that produce fitness or reproductive capaci beings | | |
| Specific targe toxicity (STO exposure | | : | Data not available. | | |
| Specific targe toxicity (STO exposure | | : | Data not available. | | |

| Code 10002948 Page: 14 of 17 |
|---|
| Page: 14 of 17 |
| Page: 14 of 17 |
| |
| |
| Data not available. |
| Rat 10 mg/l |
| Data not available. |
| Data not available. |
| |
| |
| |
| |
| |
| |
| |
| |
| |

Not classified in terms of toxicity based on the data available.

12. ECOLOGICAL INFORMATION

| Stability in soil | : | The product easily infiltrates into the soil |
|-------------------------------------|---|--|
| Other toxicological observations | : | Data not available. |
| Ecotoxicity | : | Contaminates the ground water. Detrimental to the fauna |



Detrimental to the flora.

13. DIOSPOSAL AND TREATMENT CONSIDERATIONS

Recommended methods for final disposal

| Product | : | Class I Waste - Dispose of in industrial landfill or a facility authorized for recycling in accordance with federal, stateor local regulations |
|------------------|---|---|
| Waste | : | Class I Waste - Dispose of in industrial landfill or a facility authorized for recycling in accordance with federal, stateor local regulations |
| Used packaging : | | Clean packaging should be sent for recycling. Packaging with class I waste should be disposed of in industrial landfill or a facility authorized for recycling in accordance with federal, state or local regulations. |

14. TRANSPORTATION INFORMATION

| Land | | |
|----------------------------------|---|-------|
| ONU | : | 1263 |
| Class of risk | : | 3 |
| Risk number | : | 30 |
| Packaging group | : | III |
| Name | | Tinta |
| Shipping | | |
| ONU | : | 1263 |
| Class of risk | : | 3 |
| Packaging group | : | III |
| EmS | | F-E |
| MFAG | | 310 |
| Appropriate name for dispatch | | Tinta |
| Air transport | | |
| ONU | : | 1263 |
| Class of risk | : | 3 |
| Packaging group | : | III |
| Appropriate name for dispatch | | Tinta |



15. REGULATORY INFORMATION

This MSDS (Material Safety Data Sheet) was generated according to the criteria of NBR 14725/2014. (Brazilian standard that defines the GHS).

| Specific Regulations for the | Federal Decree No. 2657, July 3rd , 1998. | |
|------------------------------|--|--|
| Chemical Product. | Law No. 12305, August 2nd 2010 (Solid Waste National Policy). | |
| | Decree No. 7404, December 23rd , 2010. | |
| | Ordinance No. 229, May 24th, 2011 - Changes to Regulatory Standard No. 26. | |
| | ABNT NBR 14725: 2014. | |

16. ADDITIONAL INFORMATION

Acronyms Used:

Legenda:

| CAS | |
|----------|---|
| 0.10 | Chemical Abstract Service |
| VO | Organic Vapors |
| NEC | National Eletrical code/Código Nacional de Eletricidade |
| IEC: | International Eletrical Commision |
| ABNT | Brazilian Association of Technical Standards |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| TLV | Threshold Limit Values |
| TLV/TWA | Time Weighted Average |
| TLV/STEL | Short Term Exposure Limit |
| TLC/C: | Tolerance Limit - Ceiling Value |
| EPI: | Individual Protective Equipment |
| CA | Approval Certificate |
| PPRA | Environmental Risk Prevention Program |
| NR | Regulatory Standard |
| NFPA | National Fire Protection Agency |
| mmHg | Millimeters of mercury - pressure unit |
| DL50 | Lethal Dose average |
| CL50 | Lethal Concentration average |

PAUMAR S.A. INDÚSTRIA E COMÉRCIO – GRUPO WEG

| MATERIAL SAFETT DATA SHEET - MISDS | | | | | |
|--|-------------------------------|-----------------|--------------|----|--|
| Product nam | e LACKPOXI N 2198 R OXYDE RED | Code | 10002948 | Ш2 | |
| | COMPONENT A | | | | |
| Last revision | 06.09.2017 | Page: 17 | of 17 | | |
| ppm | Parts per million | | | | |
| N.d | Not available | | | | |
| A+B Viscosity of the mixture of component A + component B | | | | | |

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical.

We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

Vertical lines in the left hand margin indicate changes from the current version