POLITHERM 10 SM BLACK 71310 BR Product name Code 10004768 Last revision: 06.09.2017 Page: 1 of 9 **1. PRODUCT AND COMPANY IDENTIFICATION** Product name POLITHERM 10 SM BLACK 71310 BR 10004768 Code : Main recommended uses : Electrostatic powder paint for surface coating. Address Rodovia BR 280 - km 50 CEP 89270-000, Guaramirim - SC

Telephone	:	+55 47 3276-4000
Emergency telephone number	:	0800 720 8000
E-mail / site	:	tintas@weg.net   www.weg.net

### 2. HAZARD IDENTIFICATION

The product does not require classification according to the GHS criteria.

Other hazard

: The finely dispersed particles form explosive mixtures in air, in the presence of sparks. Burning forms a thick black smoke. Inhalation of dangerous products of decomposition may cause serious damage to health.

#### 3. COMPOSITION AND INFORMATION ABOUT THE INGRENDIENTS

Product type:

Mixture

#### 4. FIRST AID MEASURES

Inhalation

: Take the victim to fresh air, keeping them rested and warm. If breathing is irregular or has stopped, apply artificial

Product name

POLITHERM 10 SM BLACK 71310 BR Code 10004768

Last revision:	06.09.2017	Page: <b>2</b> of <b>9</b>			
		respiration. Do not give anything orally. Seek medical assistance immediately, bringing the product label whenever possible.			
Contact with th	ne skin	Remove all contaminated clothing immediately. Wash affecte area with plenty of soap and water.			
Contact with th	ne eyes :	: Remove contact lenses, if wearing any. Flush the eyes with running water for at least 15 minutes, holding the eyelids apart. Seek medical assistance immediately, bringing the product label with you.			
Ingestion	:	: Do not provoke vomiting. Consult with a doctor immediately.			
Notes for the d	octor	: Treat symptomatically. Do not induce vomiting because of ri of aspiration of gastric contents into the lungs. Gastric lava is recommended when the patient ingests large quantities the substance.			

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing : methods	Water in mist form Carbon dioxide (CO2) Foam alcohol resistent Dry chemical powder
Extinguishing methods not recommended	Direct water jet.
Specific dangers :	The finely dispersed particles form explosive mixtures in air, in the presence of sparks. Burning forms a thick black smoke. Inhalation of dangerous products of decomposition may cause serious damage to health.
Protective measures of the time fighting team.	The personnel involved in firefighting should wear self contained breathing apparatus with positive pressure and full protection clothes.
Specific methods :	Evacuate and isolate the area. Approach from fire with wind at your back. Fight the fire to a secure distance. Remove the packaging of the product from the fire area if this can be made with safety. Chill sideways with water in form of fog all the closed packaging near the fire. Avoid that the resulting water from fire fighting reaches drains or waterways. Use dikes to contain this water and eliminate it according to environmental regulations.

71310 BR	Code	10004768	Ш

Product name POLITHERM 10 SM BLACK 7

Last revision:	06.09.2017	Page: <b>3</b> of <b>9</b>
	6. SPILL / LI	EAK CONTROL PROCEDURES

## Personal precautions, protective equipment and emergency procedures

For the emergency service staff	:	If specialized clothing is needed to combat the leak/spillage, Section 8 should be consulted. All precautions described in the following section must be followed.
For staff who are not part of the emergency services	:	No action should be taken that may generate danger to people without adequate training and qualifications. Use appropriate personal protective equipment - see section 8. Evacuate surrounding areas. Isolate area and keep onlookers away. Do not touch or walk through spilled material. Eliminate all sources of ignition. Avoid breathing vapor or mist. Provide adequate ventilation if possible. Wear appropriate respiratory mask when ventilation is inadequate. In accordance with characteristics of the location and/or area and in relation to the amount of spilled/leaked product, additional emergency measures may be taken under the supervision of a trained professional.
Environmental precautions	:	Prevent spilled/leaked product from contact withsoil, waterways, drains and sewers. Inform the relevant authorities in accordance with current legislation if the product causes environmental damage.
Methods and materials for con	nta	ainment and cleaning
Large spills / leaks	:	Stop the leak if this can be done safely.Cover up spillage in a tarp to prevent the spread by wind or rain. Use antifaiscantes tools and explosion-proof equipment properly grounded to collect the product. Place the material collected in dry, clean and properly identified containers. Cap the container loosened so removing them from the spill site. Avoid formation of dust. Remove the packaging from the spill site. If there is product disposal need refer to chapter 13
Small spills / leaks	:	The collected material can return to the process if you are in favorable conditions. Otherwise should be referred for appropriate disposal.
Dust control	:	Consult section 13.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Instructions for safe	:	Avoid co	ntact wit	h eyes, s	kin an	d clothes.Do not	han	dle the
treatment		product	before	reading	and	understanding	all	safety

POLITHERM 10 SM BLACK 71310 BR

Code 10004768

Product name	POLITHERM	10 SM BLACK 71310 BR	Code	10004768	ш
Last revision:	06.09.2017		Page: <b>4</b> o	of <b>9</b>	
		precautions.Do not re-us instructions before use.Avoi eat, drink or smoke during u	d inhalation	g.Refer to of the powder.	
Precautions for handling	safe :	Use individual protective ed that will be used for electro must provide controlled ventilation it must be ensu scope is be healthy from a Section 8). Avoid sources of environment. Antistatic cloth Emergency showers and ey locations of use and storage	ostatic spray ventilation. Ired that the health point ignition and hes and shoe e wash basin	ing of powder Through con air in the inh of view (see li dust deposition is are recomm	paints ntrolled nalation imits in n in the ended.
Fire protection	:	Tools that do not produce s from heat and sources accumulation of electrostation of the system, in contact with groundedOnly use in well accumulation of powder in e	of ignition.D c charges.All th the produc l-ventilated	o not smoke conductive elect t, must be elect ocations, to p	e.Avoid ements ctrically
Storage conditio	ons				
Substances to be	e avoid :	Keep away from oxidising strong alkaline solutions.	agents, stron	g acid solutio	ns and
Storage condition	ons :	The electrical installation Electrical Code) or IEC (Int standards and/or those of the Technical Standards). The impermeable, non-combusti	ernational El he ABNT (Br floor of the s	ectrical Comm azilian Associa	nission) ation of
Appropriate sto conditions	rage :	Store the material in co- identified areasStore at a te closed container.Keep out o	emperature b	elow 30°C.Sto	
Inappropriate st conditions	orage :	Exposed to elevated temp oxidizing agents.Close to for ignition.			
Materials to avo	id :	Do not store with explosive gases, oxidizing, corrosive s generate spontaneous comb	substances, o		
Secure packagin	g materials				
Recommended materials	packaging :	Must be stored in plastic bag	gs packed in o	cardboard box	es.
Packaging mate avoided	erials to be :	Glass containers.			

MATERIAL SAFETY DATA SHEET - MSDS POLITHERM 10 SM BLACK 71310 BR

Code 10004768

3 🔟

Last revision: 06.09.2017 Page: **5** of **9** 

8. EXPOSURE CONTROL – PERSONAL PROTECTION

The information in this chapter contain general guidelines. Chapter 1 should be consulted for any information on the recommended use of this product in different scenarios of exposure.

Engineering control measures	: Preferably use the product in adequate application cabin. In case it is not possible, provide exhaustion/ventilation enough to keep the concentration of the agents indicated in this section under the limits of tolerance (L.T.), otherwise, use adequate respiratory protection equipment. The engineering controls should keep the concentrations of gas/yapour under the limit of LEL - Lower Explosive
	of gas/vapour under the limit of LEL - Lower Explosive Limit (see section 9). Use equipment explosion proof.

### **Control parameters**

Product name

### **Occupational Exposure Limits**

The product does not have ingredientes with exposure limits based on the data available.

Personal	protective	eaui	pment	required
	p. 01001.10		P	

Respiratory protection	:	If the powder is above the tolerance limits (seeengineering control measures, above) a dust mask must be used, suitable for this purpose (P2 particle filter). Occasionally other respiratory protective equipment may be used.
Hand protection	:	Protective creams can be used to protect exposed skin areas together with latex or nitrile gloves (never used after the exposure has occurred).
Eye protection	:	Use hermetic goggles to protect against powder spray.
Body and skin protection	:	Antistatic clothes and shoes are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Dust
State of matter	: Solid
Color	: Black
Odour	: Weak and distinctive
Odour limit	: Not applicable
рН	: Not applicable

#### PAUMAR S.A. INDÚSTRIA E COMÉRCIO – GRUPO WEG

POLITHERM 10 SM BLACK 71310 BR

Product name

Code 10004768

	-	
		-

Last revision: 0	06.09.2017	Page: <b>6</b> of <b>9</b>
Melting point	:	Not applicable
Boiling point	:	Not applicable
Evaporation rate	:	Not applicable
Inflammation point	:	Method: Not applicable
Upper explosive lir	nit :	70 g/m³
Lower explosive lir	nit :	40 g/m³
Vapor pressure	:	Not applicable
Density	:	1,8 g/cm <sup>3</sup>
Solubility(ies)	:	Insoluble in water, partially soluble in some solvents and thinners oxygen as acetone, ethyl acetate, methyl ethyl ketone, among others.
N-octano /water pa coefficient	rtition :	Not applicable
Auto flammability	:	400 °C
Cinematic viscosit	<b>y (25°C)</b> :	Not applicable
Vapor density	:	Not applicable

### **10. STABILITY AND REACTIVITY**

Reactivity	:	Presents no reactivity at room temperature and under normal conditions of use.
Chemical stability	:	Stable at room temperature and under normal conditions of use.
Possibility of dangerous reactions	:	Presents no reactivity at room temperature and under normal conditions of use. None when the product is stored, applied and processed correctly. Otherwise, the mixture powder air mixture could ignite.
Need to add additives and inhibitors	:	Not necessary.
Conditions to avoid	:	Extreme heat and open flame.
Incompatible materials	:	Do not store with explosive materials, flammableand/or toxic gases, oxidizing, corrosive substances, or materials that may generate spontaneous combustion.

POLITHERM 10 SM BLACK 71310 BR

Code 10004768



Last revision:	06.09.2017	Page: <b>7</b> of <b>9</b>

Dangerous products of : decomposition

Product name

High temperatures (above 300°C) could result in dangerous products of decomposition, such as carbon dioxide and smoke.

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Powder coatings are generally inert dusts . No data are available on acute toxicity for the product. Powder coatings can cause irritation located in the skin , especially in skin folds or use of tight clothes . People allergic or respiratory problems should not work in the powder application. Repeated or prolonged contact with the product may cause removal of natural fat from the skin , resulting in non allergic contact dermatitis and skin absorption . The product that comes into contact with the eyes can cause irritation.

#### Chronic toxicity

On the skin , prolonged contact leads to degreasing , may cause fissures , dryness , dermatitis and eczema. The respiratory system may be affected by chronic bronchitis and decreased respiratory volume. Exposure of pregnant women to concentrations above the limit can present threat of abortion. In contact with eyes, do not rub , wash with running water for at the least 15 minutes.

Not classified in terms of toxicity based on the data available.

## 12. ECOLOGICAL INFORMATION

Stability in soil	:	Data not available.
Elimination of chemical physical ability	:	Not considered potentially bioaccumulative.
Other toxicological observations	:	Data not available.
Ecotoxicity	:	Detrimental to the flora. Detrimental to the fauna Contaminates the ground water.

#### 13. DIOSPOSAL AND TREATMENT CONSIDERATIONS

#### Recommended methods for final disposal

Product	:	Class II Waste - Dispose of in industrial landfill or a facility authorized for recycling in accordance with federal, state or local regulations.
Waste	:	Class II Waste - Dispose of in industrial landfill or a facility authorized for recycling in accordance with federal, state

Product name	POLITHERM	10 SM BLACK 71310 BR	Code	10004768	ШЕ
Last revision:	06.09.2017		Page: 8	of <b>9</b>	
		or local regulations.			-
Used packaging	:	Clean packaging should be class II waste should be d facility authorized for recy state orlocal regulations	isposed of in	industrial landfill or	ra

### 14. TRANSPORTATION INFORMATION

### National and international regulations

- Land : Not classified as a dangerous good under transport regulations.
- Shipping : Not classified as a dangerous good under transport regulations.
- Air transport : Not classified as a dangerous good under transport regulations.

## 15. REGULATORY INFORMATION

This MSDS (Material Safety Data Sheet) was generated according to the criteria of NBR 14725/2014. (Brazilian standard that defines the GHS).

Specific Regulations for the Chemical Product.	Federal Decree No. 2657, July 3rd , 1998.
	Law No. 12305, August 2nd 2010 (Solid Waste National Policy).
	Decree No. 7404, December 23rd , 2010.
	Ordinance No. 229, May 24th, 2011 - Changes to Regulatory Standard No. 26.
	ABNT NBR 14725: 2014.

## 16. ADDITIONAL INFORMATION

#### Acronyms Used:

Legenda:

Product name

POLITHERM 10 SM BLACK 71310 BR

Code 10004768

	•	
		-

Last revision	: 06.09.2017 Page: <b>9</b> of <b>9</b>
CAS	Chemical Abstract Service
VO	Organic Vapors
NEC	National Eletrical code/Código Nacional de Eletricidade
IEC:	International Eletrical Commision
ABNT	Brazilian Association of Technical Standards
ACGIH	American Conference of Governmental Industrial Hygienists
TLV	Threshold Limit Values
TLV/TWA	Time Weighted Average
TLV/STEL	Short Term Exposure Limit
TLC/C:	Tolerance Limit - Ceiling Value
EPI:	Individual Protective Equipment
CA	Approval Certificate
PPRA	Environmental Risk Prevention Program
NR	Regulatory Standard
NFPA	National Fire Protection Agency
mmHg	Millimeters of mercury - pressure unit
DL50	Lethal Dose average
CL50	Lethal Concentration average
ppm	Parts per million
N.d	Not available
A+B	Viscosity of the mixture of component A + component B

Important information, but not specifically described in the previous sections:

This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical.

We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

Vertical lines in the left hand margin indicate changes from the current version

PAUMAR S.A. INDÚSTRIA E COMÉRCIO – GRUPO WEG