

W-POXI 3085 B COMPONENT

Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 4/23/2025 Revision date: 1/29/2026 Version: 4.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : W-POXI 3085 B COMPONENT
Product code : 14166214
Type of product : Catalyst
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Uses in coatings - Curing agent for component A.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Acute toxicity (oral), Category 5
Acute toxicity (dermal), Category 4
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 1
Skin sensitisation, Category 1
Carcinogenicity, Category 2
Specific target organ toxicity — Single exposure, Category 3, Narcosis
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Hazardous to the aquatic environment - Acute Hazard, Category 3
Hazardous to the aquatic environment - Chronic Hazard, Category 3

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H303 - May be harmful if swallowed
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer.
H412 - Harmful to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.

Precautionary statements (GHS BR)

:

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P310 - Immediately call a POISON CENTER or a doctor.
P312 - Call a POISON CENTER or a doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
SOLVENT ISOBUTHANOL	CAS-No.: 78-83-1	50 – 60	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK	CAS-No.: 108-10-1	20 – 40	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 2, H305
DIETHYLENTRIAMINO PROPYLTRIMETHOXYSILANE	CAS-No.: 35141-30-1	10 – 20	Acute Tox. 5 (Dermal), H313 Eye Dam. 1, H318

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
			Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye damage. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: Suspected carcinogen.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire	: Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
-----------------------------	---

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Firefighting instructions	: Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.
6.1.2. For emergency responders	
Protective equipment	: Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures	: Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	: Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Flammable vapours may accumulate in the container.
Precautions for safe handling	: Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. When heated, material emits highly irritating vapours, affecting the eyes. Ensure

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Hygiene measures

good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
: Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials

: combustible materials.

Packaging materials

: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SOLVENT ISOBUTHANOL 78-83-1

USA - OSHA - Occupational Exposure Limits

Local name	Isobutyl alcohol
OSHA PEL TWA	300 mg/m ³ 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

Skin and body protection:

Long sleeved protective clothing. Or chemical resistant apron. Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless
Odour	: characteristic
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 30 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 0.81 – 0.871 g/cm³
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE35141-30-1

Boiling point	149 °C Source: KOSHANET
Flash point	137 °C Source: KOSHANET
Vapour pressure	0.015 Pa Temp.: 25 °C

SOLVENT ISOBUTHANOL78-83-1

Boiling point	108 °C Source: ChemIDPlus
Flash point	28 °C Source: ECHA
Auto-ignition temperature	415 °C Source: ECHA
Vapour pressure	1.2 kPa at 20°C Source: CHemIDplus

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1

Boiling point	116.5 °C Source: CHemIDplus
---------------	-----------------------------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1

Flash point	14 °C Source: ICSC
Auto-ignition temperature	460 °C Source: ICSC
Vapour pressure	2.1 kPa at 20°C Source: ICSC

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed.
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Not available

W-POXI 3085 B COMPONENT

ATE BR (oral)	2752.722 mg/kg bodyweight
ATE BR (dermal)	1821.975 mg/kg bodyweight

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE (35141-30-1)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
--------------------	---

SOLVENT ISOBUTHANOL (78-83-1)

LD50 oral rat	2460 mg/kg Source: ECHA
LD50 dermal rabbit	2460 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	19.6 mg/l Source: ECHA

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA

Skin corrosion/irritation	: Causes skin irritation.
---------------------------	---------------------------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not available
Carcinogenicity	: Suspected of causing cancer.

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity	: Not available
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

SOLVENT ISOBUTHANOL (78-83-1)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not available
------------------------	-----------------

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE (35141-30-1)

NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard	: Not available
-------------------	-----------------

SOLVENT ISOBUTHANOL (78-83-1)

Viscosity, kinematic	5 mm²/s
----------------------	---------

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye damage. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: Suspected carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects. Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE35141-30-1	
LC50 - Fish [1]	423.217 mg/l Source: Ecological Structure Activity Relationships
EC50 - Crustacea [1]	81 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	352 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	126 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	2.148 mg/l Source: Ecological Structure Activity Relationships
SOLVENT ISOBUTHANOL78-83-1	
LC50 - Fish [1]	1430 mg/l Source: ECHA
EC50 - Crustacea [1]	1100 mg/l Source: ECHA
EC50 72h - Algae [1]	593 mg/l Source: ECHA
4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1	
LC50 - Fish [1]	672 mg/l Source: ECHA
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

W-POXI 3085 B COMPONENT	
Persistence and degradability	Not rapidly degradable
DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE35141-30-1	
Persistence and degradability	Not rapidly degradable
SOLVENT ISOBUTHANOL78-83-1	
Persistence and degradability	Not rapidly degradable
4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE35141-30-1	
Partition coefficient n-octanol/water (Log Pow)	-2.19 Source: Ecological Structure Activity Relationships
SOLVENT ISOBUTHANOL78-83-1	
Partition coefficient n-octanol/water (Log Pow)	0.8 Source: ChemIDPlus
4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1	
Partition coefficient n-octanol/water (Log Pow)	1.31 Source: ChemIDPlus

12.4. Mobility in soil

DIETHYLENETRIAMINO PROPYLTRIMETHOXYSILANE35141-30-1	
Mobility in soil	0.4025 Source: EPI Suite

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

Other adverse effects : May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

SECTION 13: Disposal considerations

Waste treatment methods : Must follow special treatment according to local regulation.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1263	1263	1263
UN Proper Shipping Name		
MATERIAL RELACIONADO COM TINTAS	PAINT RELATED MATERIAL	Paint related material
Transport document description		
Not applicable	UN 1263 PAINT RELATED MATERIAL, 3, III (30°C c.c.)	UN 1263 Paint related material, 3, III
Transport hazard class(es)		
3	3	3
Danger labels		
3	3	3
		
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
30	Not applicable	Not applicable
Packing group		
III	III	III
Special provisions		
163,223,367	163,223,367,955	A3,A72,A192
Dangerous for the environment		
No	No	No

14.2 Other informations

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-POXI 3085 B COMPONENT

14166214

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

12/12