

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet



according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 4/10/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : W-POXI RRP 325 MX B COMPONENT
Product code : 18310980

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Uses in coatings - Curing agent for component A.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

1.5. Emergency phone number

Emergency number :

| 24-HOUR EMERGENCY - AMBIPAR | | 0800 117 2020 | |
|--------------------------------------|-----------|----------------------------------|------------------|
| CHEMTREC international number | | +1-703-527-3887 e 1-800-424-9300 | |
| Country | City | Local Number | Toll-Free Number |
| Austria | Vienna | +43-1-3649237 | |
| Austria | | | 0800 293702 |
| China | | 400 120 4937 | |
| France | | +33-975181407 | |
| Germany | | | 0800-181-7059 |
| India | Bangalore | +91 8071 279 207 | |
| India | | | 000 800 1007 141 |
| Italy | Milan | +39-02 4555 7031 | |
| Italy | | | 800 789 767 |
| Netherlands | | +31-85 888 0596 | |
| South Africa | | | 080-001-4676 |
| United Kingdom | London | +44 20 3807 3798 | |
| South korea | | | 080-880-0454 |
| Japan | | | 0800-300-5842 |

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

| | | | |
|--|------|--------------------------------------|-----------------------|
| Flammable liquid, Category 3 | H226 | Flammable liquid and vapour. | On basis of test data |
| Skin corrosion/irritation, Category 2 | H315 | Causes skin irritation. | Calculation method |
| Serious eye damage/eye irritation, Category 1 | H318 | Causes serious eye damage. | Calculation method |
| Skin sensitization, Category 1 | H317 | May cause an allergic skin reaction. | Calculation method |
| Carcinogenicity, Category 2 | H351 | Suspected of causing cancer. | Calculation method |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 | May cause drowsiness or dizziness. | Calculation method |
| Full text of H-statements: see section 16 | | | |

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer.

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|--------------------------------|--------------------|---------|--|
| SOLVENT METHYL ISOBUTYL KETONE | CAS-No.: 108-10-1 | 30 – 50 | Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H336 |

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

| Name | Product identifier | % | GHS US classification |
|----------------------|--------------------|--------|--|
| SOLVENT BUTANOL | CAS-No.: 71-36-3 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335 |
| TRIETHYLENETETRAMINE | CAS-No.: 112-24-3 | 1 – 5 | Acute Tox. 3 (Dermal), H311 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 |

Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |
| Self protection of the first-aider | : First aid workers will be equipped with suitable personal protective equipment. |

4.2. Most important symptoms/effects, acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after inhalation | : None under normal conditions. |
| Symptoms/effects after skin contact | : Irritation. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : None under normal conditions. |

4.3. Indication of immediate medical attention and special treatment needed, if necessary

| | |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Specific hazards arising from the chemical

| | |
|--|--------------------------------|
| Fire hazard | : Flammable liquid and vapour. |
| Explosion hazard | : No direct explosion hazard. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|---|
| Firefighting instructions | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

| |
|--|
| Hand protection: |
| Protective gloves |
| Eye protection: |
| Safety glasses |
| Skin and body protection: |
| Wear suitable protective clothing |
| Respiratory protection: |
| In case of insufficient ventilation, wear suitable respiratory equipment |

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : Colourless
Odour : characteristic
Odour threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : 75 °F
Flammability (solid, gas) : Not applicable.
Vapour pressure : No data available
Relative vapour density at 20°C : No data available
Relative density : No data available
Density : 0.81 – 0.91 g/cm³
Solubility : Material insoluble in water.
Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Explosive limits : No data available
Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 10 Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : No data available
Acute toxicity (dermal) : No data available
Acute toxicity (inhalation) : No data available

| SOLVENT BUTANOL (71-36-3) | |
|---|---------------------------|
| LD50 dermal rabbit | 3430 mg/kg Source: ECHA |
| LC50 Inhalation - Rat [ppm] | 8000 ppm Source: ECHA |
| ATE US (oral) | 500 mg/kg bodyweight |
| ATE US (dermal) | 3430 mg/kg bodyweight |
| ATE US (gases) | 8000 ppmv/4h |
| TRIETHYLENETETRAMINE (112-24-3) | |
| LD50 oral rat | 2500 mg/kg |
| LD50 dermal rabbit | 805 mg/kg |
| ATE US (oral) | 2500 mg/kg bodyweight |
| ATE US (dermal) | 805 mg/kg bodyweight |
| SOLVENT METHYL ISOBUTYL KETONE (108-10-1) | |
| LD50 oral rat | 2080 mg/kg Source: ECHA |
| LD50 dermal rabbit | ≥ 2000 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Vapours) | 11.6 mg/l Source: ECHA |
| ATE US (oral) | 2080 mg/kg bodyweight |
| ATE US (dermal) | 1100 mg/kg bodyweight |

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|------------------|--------------|
| ATE US (vapours) | 11.6 mg/l/4h |
|------------------|--------------|

Skin corrosion/irritation : Causes skin irritation.

TRIETHYLENETETRAMINE (112-24-3)

| | |
|----|----|
| pH | 14 |
|----|----|

Serious eye damage/irritation : Causes serious eye damage.

TRIETHYLENETETRAMINE (112-24-3)

| | |
|----|----|
| pH | 14 |
|----|----|

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : No data available

Carcinogenicity : Suspected of causing cancer.

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|------------|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
|------------|--------------------------------------|

Reproductive toxicity : No data available

STOT-single exposure : May cause drowsiness or dizziness.

SOLVENT BUTANOL (71-36-3)

| | |
|----------------------|--|
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
|----------------------|--|

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

STOT-repeated exposure : No data available

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|--|--|
| LOAEL (oral, rat, 90 days) | 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEL (oral, rat, 90 days) | 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEC (inhalation, rat, vapour, 90 days) | 4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |

Aspiration hazard : No data available

SOLVENT BUTANOL (71-36-3)

| | |
|----------------------|--------------------------|
| Viscosity, kinematic | 3.684 mm ² /s |
|----------------------|--------------------------|

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Hazardous to the aquatic environment, short-term (acute) : No data available

Hazardous to the aquatic environment, long-term (chronic) : No data available

| SOLVENT BUTANOL (71-36-3) | |
|---------------------------|------------------------|
| LC50 - Fish [1] | 1376 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 1983 mg/l Source: ECHA |
| EC50 96h - Algae [1] | 225 mg/l Source: ECHA |

| SOLVENT METHYL ISOBUTYL KETONE (108-10-1) | |
|---|--|
| LC50 - Fish [1] | 672 mg/l Source: ECHA |
| EC50 - Crustacea [1] | > 200 mg/l Test organisms (species): Daphnia magna |

12.2. Persistence and degradability

W-POXI RRP 325 MX B COMPONENT

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

SOLVENT BUTANOL (71-36-3)

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

TRIETHYLENETETRAMINE (112-24-3)

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

12.3. Bioaccumulative potential

SOLVENT BUTANOL (71-36-3)

| | |
|---|----------------|
| Partition coefficient n-octanol/water (Log Pow) | 1 Source: ECHA |
|---|----------------|

TRIETHYLENETETRAMINE (112-24-3)

| | |
|---|-------|
| Partition coefficient n-octanol/water (Log Pow) | -2.65 |
|---|-------|

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

| | |
|---|-------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.31 Source: ChemIDPlus |
|---|-------------------------|

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : No data available
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

W-POXI RRP 325 MX B COMPONENT





Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

| DOT | TDG | IMDG | IATA |
|---|---|--|---|
| 14.1. UN number | | | |
| UN1263 | UN1263 | 1263 | 1263 |
| 14.2. Proper Shipping Name | | | |
| Paint related material | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | Paint related material |
| Transport document description | | | |
| UN1263 Paint related material, 3, III | UN1263 PAINT RELATED MATERIAL, 3, III | UN 1263 PAINT RELATED MATERIAL, 3, III (75°F c.c.) | UN 1263 Paint related material, 3, III |
| 14.3. Transport hazard class(es) | | | |
| 3 | 3 | 3 | 3 |
|  |  |  |  |
| 14.4. Packing group | | | |
| III | III | III | III |
| 14.5. Environmental hazards | | | |
| Dangerous for the environment: No | Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No |
| No supplementary information available | | | |

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

| | |
|---------------------------------------|---|
| DOT | |
| UN-No. (DOT) | : UN1263 |
| TDG | |
| UN-No. (TDG) | : UN1263 |
| Emergency Response Guide (ERG) Number | : 128 |
| IMDG | |
| Special provisions (IMDG) | : 163, 223, 367, 955 |
| Limited quantities (IMDG) | : 5 L |
| Excepted quantities (IMDG) | : E1 |
| Packing instructions (IMDG) | : P001, LP01 |
| Special packing provisions (IMDG) | : PP1 |
| IBC packing instructions (IMDG) | : IBC03 |
| Tank instructions (IMDG) | : T2 |
| Tank special provisions (IMDG) | : TP1, TP29 |
| EmS-No. (Fire) | : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS |
| EmS-No. (Spillage) | : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER |

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

IATA

Special provisions (IATA) : A3, A72, A192
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
ERG code (IATA) : 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| | | |
|--------------------------------|------------------|----------|
| SOLVENT BUTANOL | CAS-No. 71-36-3 | 5 – 10% |
| SOLVENT METHYL ISOBUTYL KETONE | CAS-No. 108-10-1 | 30 – 50% |

SOLVENT BUTANOL (71-36-3)

CERCLA RQ 5000 lb

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

SOLVENT BUTANOL (71-36-3)

Listed on the Canadian DSL (Domestic Substances List)

TRIETHYLENETETRAMINE (112-24-3)

Listed on the Canadian DSL (Domestic Substances List)

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

National regulations

SOLVENT BUTANOL (71-36-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

TRIETHYLENETETRAMINE (112-24-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations



WARNING:

This product can expose you to chemicals including Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date

: 4/10/2026

Full text of hazard classes and H-statements

| | |
|------|---|
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |
| H351 | Suspected of causing cancer. |

Abbreviations and acronyms

| | |
|---------|---|
| CAS-No. | Chemical Abstracts Service number |
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| BCF | Bioconcentration factor |
| EC50 | Median effective concentration |

W-POXI RRP 325 MX B COMPONENT

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

| Abbreviations and acronyms | |
|----------------------------|--|
| LC50 | Median lethal concentration |
| VOC | Volatile Organic Compounds |
| LD50 | Median lethal dose |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| COD | Chemical oxygen demand (COD) |
| ATE | Acute Toxicity Estimate |
| IMDG | International Maritime Dangerous Goods |
| IATA | International Air Transport Association |
| EC-No. | European Community number |
| vPvB | Very Persistent and Very Bioaccumulative |
| WGK | Water Hazard Class |
| IOELV | Indicative Occupational Exposure Limit Value |
| BLV | Biological limit value |
| TRGS | Technical Rules for Hazardous Substances |
| TLM | Median Tolerance Limit |
| IARC | International Agency for Research on Cancer |

Safety Data Sheet (SDS), USA - weg

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.