

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 2/5/2024 Revision date: 5/19/2025 Version: 8.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B  
Product code : 15719532  
Type of product : Catalyst  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Uses in coatings - Curing agent for component A.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |
| Germany                              |             |                                  | 0800-181-7059           |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| Russia         |           |                  | 8(800)100-63-46  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3

Acute toxicity (oral), Category 3

Skin corrosion/irritation, Category 1C

Skin sensitisation, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity — Repeated exposure, Category 2

Hazardous to the aquatic environment - Chronic Hazard, Category 3

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H301 - Toxic if swallowed  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects  
P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P310 - Immediately call a POISON CENTER or a doctor.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                  | GHS Product identifier | %       | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                           |
|-------------------------------------------------------|------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| ALIPHATIC AMINES (MODIFIED)                           | CAS-No.: 25707-70-4    | 20 – 40 | Skin Corr. 1, H314<br>Eye Dam. 1, H318                                                                                                              |
| FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED | CAS-No.: 135108-88-2   | 20 – 40 | Acute Tox. 3 (Oral), H301<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br>Aquatic Chronic 3, H412            |
| BENZYL ALCOHOL                                        | CAS-No.: 100-51-6      | 20 – 40 | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Inhalation), H332                                                                                        |
| EPOXI HARDENER                                        | CAS-No.: 140-31-8      | 5 – 10  | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Skin Corr. 1, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412 |
| Industrial secret                                     | -                      | 1 – 5   | Flam. Liq. 1, H224<br>Skin Irrit. 2, H315<br>Muta. 1A, H340<br>Carc. 1A, H350                                                                       |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

| Name                                  | GHS Product identifier | %          | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                 |
|---------------------------------------|------------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                       |                        |            | STOT RE 1, H372<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401                                                                                             |
| 4,4'-METHYLENEBISCYCLOHEXYLAMINE      | CAS-No.: 1761-71-3     | 1 – 5      | Acute Tox. 4 (Oral), H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>STOT RE 2, H373                                            |
| 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL | CAS-No.: 90-72-2       | 1 – 5      | Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319                                                                                   |
| ÉTHYLÈNEDIAMINE                       | CAS-No.: 107-15-3      | 1 – 5      | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Skin Corr. 1B, H314<br>Resp. Sens. 1, H334<br>Skin Sens. 1, H317        |
| ISOPHORONE DIAMINE                    | CAS-No.: 2855-13-2     | 1 – 5      | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Skin Corr. 1, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412       |
| BENZENE-1,3-DIMETHANEAMINE            | CAS-No.: 1477-55-0     | 1 – 5      | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Inhalation), H332<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412 |
| 4-TERT-BUTYLPHENOL                    | CAS-No.: 98-54-4       | 0.25 – 0.5 | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Repr. 2, H361<br>Aquatic Chronic 1, H410                                                                       |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.                                                                                                                                                                          |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Give oxygen or artificial respiration if necessary.                                                                                                                                                                 |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact  | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.                                                                                                                                                                                            |
| First-aid measures after ingestion    | : If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting because of corrosive effects.                                                                                                                                                                                        |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. Swallowing a small quantity of this material presents some health hazard. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.                         |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Symptoms/effects after skin contact | : Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering). Cracking of the skin.                                                                                                                                                                                                               |
| Symptoms/effects after eye contact  | : stinging. Redness. Causes serious eye burns. redness, itching, tears.                                                                                                                                                                                                                                                         |
| Symptoms/effects after ingestion    | : Harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                                                                                                           |
| Chronic symptoms                    | : Suspected carcinogen.                                                                                                                                                                                                                                                                                                         |

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Suitable extinguishing media   | : Dry chemical, CO2, or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                   |

### 5.2. Specific hazards arising from the chemical

|                  |                                                                                                                                                                                                                                                                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard      | : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. In case of fire, corrosive gases come free. |
| Explosion hazard | : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.                                                                                                                                                                                                                                      |

### 5.3. Special protective actions for fire-fighters

|                                |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary measures fire    | : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.                                                                                                                                                                                                                                 |
| Firefighting instructions      | : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.                                                                                                                                                                                                                                                                  |
| Other information              | : In case of fire, corrosive and harmful gases come free. High temperature decomposition products are harmful by inhalation.                                                                                                                                                                                                                  |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures | : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### 6.1.1. For non-emergency personnel

- |                      |                                                                                                                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Wear recommended personal protective equipment.                                                                                                                                                                                                             |
| Emergency procedures | : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities. |

### 6.1.2. For emergency responders

- |                      |                                                                                                                                                                                                                                                                                                                                                        |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection. |
| Emergency procedures | : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.                                                                                                                                                                                      |

## 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and materials for containment and cleaning up

- |                         |                                                                                                                                                                                                                                                                             |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For containment         | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.                                                                                       |
| Methods for cleaning up | : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Absorb spillage to prevent material damage. Take up liquid spill into absorbent material. |

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- |                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional hazards when processed | : Flammable vapours may accumulate in the container.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Precautions for safe handling     | : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not eat, drink or smoke when using this product. When heated, material emits highly irritating vapours, affecting the eyes. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood. |
| Hygiene measures                  | : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

### 7.2. Conditions for safe storage, including any incompatibilities

- |                        |                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Technical measures     | : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers. |
| Storage conditions     | : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.               |
| Incompatible materials | : combustible materials.                                                                                                      |
| Packaging materials    | : Store always product in container of same material as original container.                                                   |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| BENZENE-1,3-DIMETHANEAMINE 1477-55-0       |                                                              |
|--------------------------------------------|--------------------------------------------------------------|
| USA - ACGIH - Occupational Exposure Limits |                                                              |
| Local name                                 | m-Xylene α,α'-diamine                                        |
| ACGIH® TLV® C                              | 0.018 ppm                                                    |
| Remark (ACGIH)                             | TLV® Basis: Eye, skin, & GI irr. Notations: Skin             |
| Regulatory reference                       | ACGIH 2024                                                   |
| ÉTHYLÈNEDIAMINE 107-15-3                   |                                                              |
| USA - ACGIH - Occupational Exposure Limits |                                                              |
| Local name                                 | Ethylenediamine                                              |
| ACGIH® TLV® TWA                            | 10 ppm                                                       |
| Remark (ACGIH)                             | Notations: Skin; A4 (Not classifiable as a Human Carcinogen) |
| Regulatory reference                       | ACGIH 2024                                                   |
| USA - OSHA - Occupational Exposure Limits  |                                                              |
| Local name                                 | Ethylenediamine                                              |
| OSHA PEL TWA                               | 25 mg/m³                                                     |
|                                            | 10 ppm                                                       |
| Regulatory reference (US-OSHA)             | OSHA Annotated Table Z-1                                     |

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Corrosionproof clothing.

|                                                                                                       |
|-------------------------------------------------------------------------------------------------------|
| Hand protection:                                                                                      |
| Protective gloves made of PVC. Nitrile rubber gloves                                                  |
| Eye protection:                                                                                       |
| Wear closed safety glasses                                                                            |
| Skin and body protection:                                                                             |
| Safety shoes. Long sleeved protective clothing. Or chemical resistant apron                           |
| Respiratory protection:                                                                               |
| Where exposure through inhalation may occur from use, respiratory protection equipment is recommended |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Physical state                                  | : Liquid                       |
| Appearance                                      | : Liquid.                      |
| Colour                                          | : Colourless                   |
| Odour                                           | : characteristic               |
| Odour threshold                                 | : Not available                |
| pH                                              | : Not applicable               |
| Melting point                                   | : Not available                |
| Freezing point                                  | : Not available                |
| Boiling point                                   | : Not available                |
| Flash point                                     | : 60 °C                        |
| Relative evaporation rate (butylacetate=1)      | : Not available                |
| Flammability                                    | : Not available                |
| Explosive limits                                | : Not available                |
| Vapour pressure                                 | : Not available                |
| Relative vapour density at 20°C                 | : Not available                |
| Relative density                                | : Not available                |
| Density                                         | : 0.96 – 1.02 g/cm³            |
| Solubility                                      | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                |
| Auto-ignition temperature                       | : Not available                |
| Decomposition temperature                       | : Not available                |
| Viscosity, kinematic                            | : Not available                |
| Particle size                                   | : Not applicable               |
| Particle size distribution                      | : Not applicable               |
| Particle shape                                  | : Not applicable               |
| Particle aspect ratio                           | : Not applicable               |
| Particle specific surface area                  | : Not applicable               |

#### BENZENE-1,3-DIMETHANEAMINE1477-55-0

|               |        |
|---------------|--------|
| Boiling point | 272 °C |
| Flash point   | 142 °C |

#### FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2

|                 |          |
|-----------------|----------|
| Boiling point   | 220 °C   |
| Flash point     | > 200 °C |
| Vapour pressure | 0.055 Pa |

#### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2

|             |        |
|-------------|--------|
| Flash point | 148 °C |
|-------------|--------|

### 9.2. Data relevant with regard to physical hazard classes

No additional information available

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)



# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                       |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products   | : May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.                                                                          |
| Incompatible materials             | : Combustible materials.                                                                                                                                                        |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                     |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                            |
| Handling temperature               | : No additional information available                                                                                                                                           |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                       |
|-----------------------------|-----------------------|
| Acute toxicity (oral)       | : Toxic if swallowed. |
| Acute toxicity (dermal)     | : Not available       |
| Acute toxicity (inhalation) | : Not available       |

#### LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

|               |                          |
|---------------|--------------------------|
| ATE BR (oral) | 297.547 mg/kg bodyweight |
|---------------|--------------------------|

#### BENZENE-1,3-DIMETHANEAMINE (1477-55-0)

|                       |              |
|-----------------------|--------------|
| LD50 oral rat         | 930 mg/kg    |
| LD50 dermal rabbit    | > 3100 mg/kg |
| LC50 Inhalation - Rat | 1.34 mg/l    |

#### 4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

|               |                      |
|---------------|----------------------|
| LD50 oral rat | 380 mg/kg bodyweight |
|---------------|----------------------|

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Skin corrosion/irritation | : Causes severe skin burns.<br>pH: Not applicable |
|---------------------------|---------------------------------------------------|

#### EPOXI HARDENER (140-31-8)

|    |    |
|----|----|
| pH | 12 |
|----|----|

#### 4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

|    |      |
|----|------|
| pH | 11.6 |
|----|------|

#### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)

|    |    |
|----|----|
| pH | 11 |
|----|----|

#### ISOPHORONE DIAMINE (2855-13-2)

|    |      |
|----|------|
| pH | 11.6 |
|----|------|

|                               |                                                             |
|-------------------------------|-------------------------------------------------------------|
| Serious eye damage/irritation | : Assumed to cause serious eye damage<br>pH: Not applicable |
|-------------------------------|-------------------------------------------------------------|

#### EPOXI HARDENER (140-31-8)

|    |    |
|----|----|
| pH | 12 |
|----|----|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### 4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

|    |      |
|----|------|
| pH | 11.6 |
|----|------|

### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)

|    |    |
|----|----|
| pH | 11 |
|----|----|

### ISOPHORONE DIAMINE (2855-13-2)

|    |      |
|----|------|
| pH | 11.6 |
|----|------|

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| Respiratory or skin sensitisation | : May cause an allergic skin reaction.                               |
| Germ cell mutagenicity            | : Not available                                                      |
| Carcinogenicity                   | : Suspected of causing cancer.                                       |
| Reproductive toxicity             | : Not available                                                      |
| STOT-single exposure              | : Not available                                                      |
| STOT-repeated exposure            | : May cause damage to organs through prolonged or repeated exposure. |

### BENZENE-1,3-DIMETHANEAMINE (1477-55-0)

|                                              |                      |
|----------------------------------------------|----------------------|
| NOAEL (subacute, oral, animal/male, 28 days) | 150 mg/kg bodyweight |
|----------------------------------------------|----------------------|

### FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED (135108-88-2)

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--------------------------------------------------------------------|

### 4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

|                                              |                     |
|----------------------------------------------|---------------------|
| NOAEL (subacute, oral, animal/male, 28 days) | 15 mg/kg bodyweight |
|----------------------------------------------|---------------------|

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--------------------------------------------------------------------|

### Industrial secret

|                        |                                                                 |
|------------------------|-----------------------------------------------------------------|
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |
|------------------------|-----------------------------------------------------------------|

|                   |                 |
|-------------------|-----------------|
| Aspiration hazard | : Not available |
|-------------------|-----------------|

### BENZENE-1,3-DIMETHANEAMINE (1477-55-0)

|                      |            |
|----------------------|------------|
| Viscosity, kinematic | 6.78 mm²/s |
|----------------------|------------|

## 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. Swallowing a small quantity of this material presents some health hazard. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.                         |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Symptoms/effects after skin contact | : Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering). Cracking of the skin.                                                                                                                                                                                                               |
| Symptoms/effects after eye contact  | : stinging. Redness. Causes serious eye burns. redness, itching, tears.                                                                                                                                                                                                                                                         |
| Symptoms/effects after ingestion    | : Harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                                                                                                           |
| Chronic symptoms                    | : Suspected carcinogen.                                                                                                                                                                                                                                                                                                         |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                          |                 |
|----------------------------------------------------------|-----------------|
| Hazardous to the aquatic environment, short-term (acute) | : Not available |
|----------------------------------------------------------|-----------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.  
(chronic)

### FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2

|                      |           |
|----------------------|-----------|
| LC50 - Fish [1]      | 63 mg/l   |
| EC50 - Crustacea [1] | 15.4 mg/l |
| EC50 72h - Algae [1] | 43.9 mg/l |

## 12.2. Persistence and degradability

### LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 4-TERT-BUTYLPHENOL98-54-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### BENZENE-1,3-DIMETHANEAMINE1477-55-0

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ALIPHATIC AMINES (MODIFIED)25707-70-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ÉTHYLÈNEDIAMINE107-15-3

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### BENZYL ALCOHOL100-51-6

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### EPOXI HARDENER140-31-8

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 4,4'-METHYLENEBISCYCLOHEXYLAMINE1761-71-3

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### Industrial secret

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ISOPHORONE DIAMINE2855-13-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

## 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available  
Other adverse effects : May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

## SECTION 13: Disposal considerations

Regional waste regulation : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.  
Waste treatment methods : Must follow special treatment according to local regulation.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                                                                | IMDG                                                                                | IATA                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>UN number</b>                                                                    |                                                                                     |                                                                                       |
| 2735                                                                                | 2735                                                                                | 2735                                                                                  |
| <b>UN Proper Shipping Name</b>                                                      |                                                                                     |                                                                                       |
| AMINAS, CORROSIVAS, LÍQUIDAS, N.E.                                                  | AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINES (MODIFIED))                     | Amines, liquid, corrosive, n.o.s. (ALIPHATIC AMINES (MODIFIED))                       |
| <b>Transport document description</b>                                               |                                                                                     |                                                                                       |
| Not applicable                                                                      | UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINES (MODIFIED)), 8, III     | UN 2735 Amines, liquid, corrosive, n.o.s. (ALIPHATIC AMINES (MODIFIED)), 8, III       |
| <b>Transport hazard class(es)</b>                                                   |                                                                                     |                                                                                       |
| 8                                                                                   | 8                                                                                   | 8                                                                                     |
| <b>Danger labels</b>                                                                |                                                                                     |                                                                                       |
| 8                                                                                   | 8                                                                                   | 8                                                                                     |
|  |  |  |
| <b>Subsidiary risk</b>                                                              |                                                                                     |                                                                                       |
| Not applicable                                                                      | Not applicable                                                                      | Not applicable                                                                        |
| <b>Risk Number</b>                                                                  |                                                                                     |                                                                                       |
| 80                                                                                  | Not applicable                                                                      | Not applicable                                                                        |
| <b>Packing group</b>                                                                |                                                                                     |                                                                                       |
| III                                                                                 | III                                                                                 | III                                                                                   |
| <b>Special provisions</b>                                                           |                                                                                     |                                                                                       |
| 223,274                                                                             | 223,274                                                                             | A3,A803                                                                               |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI 76 WET SURFACE N 2680 LC COMPONENT B

15719532

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/19/2025

### Dangerous for the environment

|    |    |    |
|----|----|----|
| No | No | No |
|----|----|----|

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations : Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

## SECTION 16: Other information

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)