

W-CRIL SEV 625 PRO VARNISH RD CA-557



PRODUCT DESCRIPTION		
Oven-cured acrylic varnish with high weathering resistance.		
RECOMMENDED USE		
Suitable for painting painted wheels.		
CHARACTERISTICS		
Color		Colorless.
Gloss		Ultra-Matte
VOC content		561.19 g/l
Volume Solids		NOT RELEVANT
Flash Point		31 °C
Shelf Life		12 months
Dry Film Thickness		35 µm - 40 µm
Theoretical Coverage		without dilution at a dry film thickness of 38 µm. Loss factors during application are not considered.
Specific Gravity		Min: 0.95 Max: 1.05 g/cm³
Viscosity		22 - 24" CF4
Supply Viscosity		25 - 30" CF4

DRYING		
Drying		25 °C
Touch		Not relevant
Manipulation		Not relevant
Final		Not relevant

SURFACE PREPARATION

Standard Surface Preparation
 The performance of this product is related to the degree of surface preparation. In case of doubts, for more information, consult WEG's Technical Department.

For more information, consult the WEG Coatings Technical Department.

Degreasing
 Thoroughly degrease the part to be repainted; Avoid excessive thickness; Clean the application equipment with acrylic/polyurethane diluents.

APPLICATION PREPARATION		
Mixing Ratio		MONOCOMPONENT
Thinner		ELECTROSTATIC DILUENT
Dilution		Consult WEG Tintas Technical Department.
Pot Life		Not relevant.

APPLICATION METHODS		
Conventional Spray Gun		Conventional or Electrostatic Spray Gun.
Cleaning of the equipments:		ELECTROSTATIC DILUENT
Notes		It is considered good practice to periodically wash the spraying equipment during the day. The cleaning



frequency depends on the amount sprayed, temperature, and elapsed time, including all delays.

SAFETY PRECAUTIONS

Product developed for industrial use intended for handling by qualified professionals. Carefully read all information contained in the SDS of this product, available at: www.weg.net.
Store in a covered and well-ventilated place. Keep the container tightly closed and away from sources of heat or ignition.
Use only in well-ventilated areas, avoiding the accumulation of flammable vapors. Keep the product away from heat and sources of ignition.
Do not inhale mists/vapors/aerosols generated during handling and/or application. Use protective gloves/protective clothing/eye protection/face protection.
Empty containers and materials with paint residues must be disposed of according to current legislation. Take care of the environment.

NOTE

The information contained in this technical bulletin is based on the experience and knowledge acquired in the field by WEG's technical team.
In the event of using the product without prior consultation with WEG regarding its suitability for the purpose for which the customer intends to use it, the customer acknowledges that the use will be at their own exclusive responsibility, and WEG is not liable for the behavior, safety, suitability, or durability of the product.
Some information mentioned in this bulletin is only an estimate and may vary due to factors beyond the manufacturer's control. Therefore, WEG does not guarantee and assumes no responsibility for performance, efficiency, or any material or personal damages resulting from the incorrect use of the products in question or from the information contained in this Technical Bulletin.
The information contained in this technical bulletin is subject to periodic modifications, without prior notice, due to our policy of continuous improvement and evolution of our products and services, providing quality solutions to meet the needs of our customers.
