CPTW Series Control Power Transformers Compact and Economical Solutions


VOLTAGE TABLE

VA	Primary Voltage	Secondary Voltage	Part Number
3000	220 x 440, 230 x 460, 240 x 480	110, 115, 120	CPTW3K0-ASC
Max Depth	Max Width	Max Height	Mounting Depth
7.82"	9.00"	7.62"	4.25"
Mounting Width	Mounting Hole Depth	Mounting Hole Width	Phase
6.50"	0.44"	1.00"	1
Frequency	Shipping Weight	Voltage Group	
50/60 Hz	53.0 lbs.	A	

Þ[c∿∙K

- ∇ R*{]^¦ÁŠa]∖Ása) åÁØ*•^ÁÔ|a] Á@∘a* @AÁ[ÓA§J&]*å^å
- ∇ Olā à Ă ĐTÎ +Áţ Ác@ ÁÖ^] c@ÁCEDÁ @} Áו^Á&jā Ást^Áş &| a^a ÁC €Ác@ ÁH €XOE
- ∇ CEååÁFÁHÐ +ÁI ÁS@ÁP^ã @ÁÇÖDÁ @}Á*•^Ás∥[&\Ás Ás &|`å^åÁÇFÉGÉzez) åÁHÁ [|^•DÁÇ €Ás@`ÁHÍ €XCED

DIAGRAM



SPECIFICATIONS

 Class 180°C (356°F) insulation system with 115°C (239°F) temperature rise.

www.weg.net | 1-800-ASK-4WEG

- All transformers up to 750VA come with pre-installed secondary fuse kits, ready to accept 13/32" x 1 1/2" midget or Class CC fuses.
- Two parallel jumper links come standard with transformers with dual primary voltages.
- All transformers up to 3kVA include a built-in mounting adapter for fuse blocks.