

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 4/29/2025 Revision date: 5/28/2025 Version: 3.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-POLI HPD 45 1 R T YELLOW COMPONENT A  
Product code : 15437700  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for maintenance sector

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number

:  
**24-HOUR EMERGENCY - AMBIPAR** 0800 117 2020  
**CHEMTREC international number** +1-703-527-3887 e 1-800-424-9300  

| Country | City   | Local Number  | Toll-Free Number |
|---------|--------|---------------|------------------|
| Austria | Vienna | +43-1-3649237 |                  |
| Austria |        |               | 0800 293702      |
| China   |        | 400 120 4937  |                  |
| France  |        | +33-975181407 |                  |
| Germany |        |               | 0800-181-7059    |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| Russia         |           |                  | 8(800)100-63-46  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3

Skin corrosion/irritation, Category 3

Serious eye damage/eye irritation, Category 2

Skin sensitisation, Category 1

Hazardous to the aquatic environment - Acute Hazard, Category 2

Hazardous to the aquatic environment - Chronic Hazard, Category 3

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Warning

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour

H316 - Causes mild skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H401 - Toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                      | GHS Product identifier      | %          | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                     |
|-----------------------------------------------------------|-----------------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| HARDENER PU                                               | CAS-No.: 152637-10-0        | 10 – 20    | Skin Sens. 1, H317<br>Aquatic Chronic 3, H412                                                                                                 |
| n-butyl acetate                                           | CAS-No.: 123-86-4           | 5 – 10     | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Aquatic Acute 3, H402                                                                                |
| INORGANIC PIGMENT BI/ISOINDOL VANADATE YELLOW             | CAS-No.: 14059-33-7         | 1 – 5      | STOT RE 2, H373                                                                                                                               |
| FUMARIC ACID DIETHYL ESTER                                | CAS-No.: 623-91-6           | 1 – 5      | Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>STOT SE 3, H335                                                     |
| GLYCIDOXYPROPYL TRIMETHOXYSILANE                          | CAS-No.: 2530-83-8          | 1 – 5      | Acute Tox. 5 (Dermal), H313<br>Acute Tox. 3 (Inhalation:vapour), H331<br>Eye Dam. 1, H318<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412 |
| ADDITIVE RHEOLOGIC                                        | CAS-No.: segredo industrial | 1 – 5      | Flam. Sol. 1, H228<br>Aquatic Acute 1, H400<br>Aquatic Chronic 2, H411                                                                        |
| Zeolite, silica rich, crystalline, synthetic, non-fibrous | CAS-No.: 1318-02-1          | 1 – 5      | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313                                                                                      |
| BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE          | CAS-No.: 41556-26-7         | 1 – 5      | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                        |
| trizinc bis(orthophosphate)                               | CAS-No.: 7779-90-0          | 0.5 – 1    | STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                           |
| METIL AND 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE      | CAS-No.: 82919-37-7         | 0.25 – 0.5 | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                        |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SECTION 4: First-aid measures

#### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                        |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : People with over sensibility problems are not allowed to work or be exposed to the product.                                                                                          |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing.                                                                                                                       |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact  | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                                                                                        |
| First-aid measures after ingestion    | : Do NOT induce vomiting. Rinse mouth out with water.                                                                                                                                  |

#### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause an allergic skin reaction.                                                                                                  |
| Symptoms/effects after inhalation   | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.                                                     |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                          |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract.                                                                                          |

#### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Suitable extinguishing media   | : Dry chemical, CO2, or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                   |

#### 5.2. Specific hazards arising from the chemical

|                  |                                                                                                                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard      | : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. |
| Explosion hazard | : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.                                                                                                                                                                                          |

#### 5.3. Special protective actions for fire-fighters

|                                |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary measures fire    | : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.                                                                                                                                                                                                                                 |
| Firefighting instructions      | : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.                                                                                                                                                                                                                                                                  |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                                                                                                                                                                                                                                                                                            |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures | : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

### 6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Equip cleanup crew with proper protection.  
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

## 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Flammable vapours may accumulate in the container.  
Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.  
Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.  
Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.  
Incompatible materials : combustible materials.  
Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

5/13

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### n-butyl acetate 123-86-4

#### USA - ACGIH - Occupational Exposure Limits

|                      |                           |
|----------------------|---------------------------|
| Local name           | n-Butyl acetate           |
| ACGIH® TLV® TWA      | 50 ppm                    |
| ACGIH® TLV® STEL     | 150 ppm                   |
| Remark (ACGIH)       | TLV® Basis: Eye & URT irr |
| Regulatory reference | ACGIH 2024                |

#### USA - OSHA - Occupational Exposure Limits

|                                |                                  |
|--------------------------------|----------------------------------|
| Local name                     | n-Butyl-acetate                  |
| OSHA PEL TWA                   | 710 mg/m <sup>3</sup><br>150 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1         |

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

## 8.3. Individual protection measures

### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Nitrile rubber gloves

#### Eye protection:

Wear closed safety glasses

#### Skin and body protection:

Chemical resistant safety shoes. Long sleeved protective clothing. Or chemical resistant apron

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : Yellow

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

|                                                 |                                                           |
|-------------------------------------------------|-----------------------------------------------------------|
| Odour                                           | : characteristic                                          |
| Odour threshold                                 | : Not available                                           |
| pH                                              | : 8 – 10                                                  |
| Melting point                                   | : Not available                                           |
| Freezing point                                  | : Not available                                           |
| Boiling point                                   | : Not available                                           |
| Flash point                                     | : 60 °C                                                   |
| Relative evaporation rate (butylacetate=1)      | : Not available                                           |
| Flammability                                    | : Not available                                           |
| Explosive limits                                | : Not available                                           |
| Vapour pressure                                 | : Not available                                           |
| Relative vapour density at 20°C                 | : Not available                                           |
| Relative density                                | : Not available                                           |
| Density                                         | : 1.35 – 1.45 g/cm³                                       |
| Solubility                                      | : Material insoluble in water.<br>Water: Soluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                                           |
| Auto-ignition temperature                       | : Not available                                           |
| Decomposition temperature                       | : Not available                                           |
| Viscosity, kinematic                            | : Not available                                           |
| Viscosity, dynamic                              | : 95 – 105 ku/kg                                          |
| Particle size                                   | : Not applicable                                          |
| Particle size distribution                      | : Not applicable                                          |
| Particle shape                                  | : Not applicable                                          |
| Particle aspect ratio                           | : Not applicable                                          |
| Particle specific surface area                  | : Not applicable                                          |

### n-butyl acetate123-86-4

|               |                                |
|---------------|--------------------------------|
| Boiling point | 126.2 °C Atm. press.: 1013 hPa |
| Flash point   | 27 °C Atm. press.: 1013 hPa    |

### GLYCIDOXYPROPYL TRIMETHOXYSILANE2530-83-8

|                           |                                   |
|---------------------------|-----------------------------------|
| Boiling point             | 260.4 °C Atm. press.: 1013,25 hPa |
| Flash point               | 136 °C Atm. press.: 101,3 kPa     |
| Auto-ignition temperature | 400 °C                            |
| Vapour pressure           | 1.1 Pa Temp.: 25 °C               |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                       |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products   | : May liberate toxic gases.                                                                                                                                                     |
| Incompatible materials             | : Combustible materials.                                                                                                                                                        |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                     |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                            |
| Handling temperature               | : No additional information available                                                                                                                                           |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not available  
Acute toxicity (dermal) : Not available  
Acute toxicity (inhalation) : Not available

##### Zeolite, silica rich, crystalline, synthetic, non-fibrous (1318-02-1)

|                       |                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat         | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)                          |
| LD50 dermal rabbit    | > 2000 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat | > 3.35 mg/kg Source: Echa                                                                                         |

##### trizinc bis(orthophosphate) (7779-90-0)

|                       |                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------|
| LD50 oral rat         | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LC50 Inhalation - Rat | > 5700 mg/m³ Source: ECHA                                                                |

##### GLYCIDOXYPROPYL TRIMETHOXSILANE (2530-83-8)

|                                 |                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------|
| LD50 oral rat                   | 7010 mg/kg Source: SIDS                                                               |
| LD50 dermal rabbit              | 3970 mg/kg Source: SIDS                                                               |
| LC50 Inhalation - Rat           | > 5.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
| LC50 Inhalation - Rat (Vapours) | > 5.3 mg/l Source: SIDS                                                               |

Skin corrosion/irritation : Causes mild skin irritation.  
pH: 8 – 10

##### ADDITIVE RHEOLOGIC (segredo industrial)

|    |     |
|----|-----|
| pH | 7.8 |
|----|-----|

##### n-butyl acetate (123-86-4)

|    |                                         |
|----|-----------------------------------------|
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
|----|-----------------------------------------|

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 8 – 10

##### ADDITIVE RHEOLOGIC (segredo industrial)

|    |     |
|----|-----|
| pH | 7.8 |
|----|-----|

##### n-butyl acetate (123-86-4)

|    |                                         |
|----|-----------------------------------------|
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
|----|-----------------------------------------|

Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not available  
Carcinogenicity : Not available

##### Zeolite, silica rich, crystalline, synthetic, non-fibrous (1318-02-1)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

Reproductive toxicity : Not available  
STOT-single exposure : Not available

##### FUMARIC ACID DIETHYL ESTER (623-91-6)

|                      |                                   |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

| n-butyl acetate (123-86-4)                                 |                                                                                                                                                                                                                                                              |
|------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STOT-single exposure                                       | May cause drowsiness or dizziness.                                                                                                                                                                                                                           |
| STOT-repeated exposure                                     | : Not available                                                                                                                                                                                                                                              |
| INORGANIC PIGMENT BI/ISOINDOL VANADATE YELLOW (14059-33-7) |                                                                                                                                                                                                                                                              |
| NOAEL (subacute, oral, animal/male, 28 days)               | 200 mg/kg bodyweight                                                                                                                                                                                                                                         |
| STOT-repeated exposure                                     | May cause damage to organs through prolonged or repeated exposure.                                                                                                                                                                                           |
| trizinc bis(orthophosphate) (7779-90-0)                    |                                                                                                                                                                                                                                                              |
| LOAEL (oral, rat, 90 days)                                 | 53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)                                                                                                                                       |
| NOAEL (oral, rat, 90 days)                                 | 31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)                                                                                                                                      |
| STOT-repeated exposure                                     | May cause damage to organs through prolonged or repeated exposure.                                                                                                                                                                                           |
| n-butyl acetate (123-86-4)                                 |                                                                                                                                                                                                                                                              |
| LOAEL (oral, rat, 90 days)                                 | 500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)                                                                                                                                                              |
| NOAEL (oral, rat, 90 days)                                 | 125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)                                                                                                                                                              |
| GLYCIDOXYPROPYL TRIMETHOXYSILANE (2530-83-8)               |                                                                                                                                                                                                                                                              |
| NOAEL (oral, rat, 90 days)                                 | ≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other: |
| Aspiration hazard                                          | : Not available                                                                                                                                                                                                                                              |
| W-POLI HPD 45 1 R T YELLOW COMPONENT A                     |                                                                                                                                                                                                                                                              |
| Viscosity, kinematic                                       | 1.979 – 2.349 mm²/s                                                                                                                                                                                                                                          |
| n-butyl acetate (123-86-4)                                 |                                                                                                                                                                                                                                                              |
| Viscosity, kinematic                                       | 0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'                                                                                                                                                                                         |
| GLYCIDOXYPROPYL TRIMETHOXYSILANE (2530-83-8)               |                                                                                                                                                                                                                                                              |
| Viscosity, kinematic                                       | 3.43 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'                                                                                                                                                                                         |

### 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause an allergic skin reaction.                                                                                                  |
| Symptoms/effects after inhalation   | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.                                                     |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                          |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract.                                                                                          |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                      |
|-----------------------------------------------------------|------------------------------------------------------|
| Hazardous to the aquatic environment, short-term (acute)  | : Toxic to aquatic life.                             |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### Zeolite, silica rich, crystalline, synthetic, non-fibrous1318-02-1

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| LC50 - Fish [1]      | 1800 mg/l Source: International Uniform Chemical Information Database      |
| EC50 - Crustacea [1] | 1000 mg/l Source: International Uniform Chemical Information Database      |
| EC50 96h - Algae [1] | 560 mg/l Source: International Uniform Chemical Information Database       |
| LOEC (chronic)       | 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'          |
| NOEC (chronic)       | 32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'           |
| NOEC chronic fish    | > 86.7 mg/l Test organisms (species): Pimephales promelas Duration: '30 d' |

### ADDITIVE RHEOLOGICsegredo industrial

|                      |              |
|----------------------|--------------|
| LC50 - Fish [1]      | > 0.2 mg/l   |
| EC50 - Crustacea [2] | > 0.2 mg/l   |
| ErC50 algae          | > 0.025 mg/l |

### trizinc bis(orthophosphate)7779-90-0

|                      |                     |
|----------------------|---------------------|
| LC50 - Fish [1]      | 2 (0.14 – 2.6) mg/l |
| EC50 - Crustacea [1] | 2.44 mg/l           |
| EC50 72h - Algae [1] | 0.14 mg/l           |

### n-butyl acetate123-86-4

|                      |                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]      | 18 mg/l Test organisms (species): Pimephales promelas                                                                                    |
| EC50 - Crustacea [1] | 44 mg/l Test organisms (species): Daphnia sp.                                                                                            |
| EC50 72h - Algae [1] | 397 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| LOEC (chronic)       | 47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |
| NOEC (chronic)       | 23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |

### GLYCIDOXYPROPYL TRIMETHOXYSILANE2530-83-8

|                        |                                                                                                                                          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]        | 55 mg/l Test organisms (species): Cyprinus carpio                                                                                        |
| EC50 - Crustacea [1]   | 710 mg/l Source: SIDS                                                                                                                    |
| EC50 96h - Algae [1]   | 350 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 96h - Algae [2]   | 250 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| ErC50 algae            | 350 mg/l Source: SIDS                                                                                                                    |
| LOEC (chronic)         | > 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                      |
| NOEC (chronic)         | ≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                      |
| NOEC chronic crustacea | 82 mg/l                                                                                                                                  |
| NOEC chronic algae     | 107 mg/l                                                                                                                                 |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### 12.2. Persistence and degradability

| W-POLI HPD 45 1 R T YELLOW COMPONENT A                             |                        |
|--------------------------------------------------------------------|------------------------|
| Persistence and degradability                                      | Not rapidly degradable |
| FUMARIC ACID DIETHYL ESTER623-91-6                                 |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| Zeolite, silica rich, crystalline, synthetic, non-fibrous1318-02-1 |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| ADDITIVE RHEOLOGICsegredo industrial                               |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| INORGANIC PIGMENT BI/ISOINDOL VANADATE YELLOW14059-33-7            |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| trizinc bis(orthophosphate)7779-90-0                               |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| HARDENER PU152637-10-0                                             |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| n-butyl acetate123-86-4                                            |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE41556-26-7         |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| METIL AND 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE82919-37-7     |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| GLYCIDOXYPROPYL TRIMETHOXYSILANE2530-83-8                          |                        |
| Persistence and degradability                                      | Not rapidly degradable |

### 12.3. Bioaccumulative potential

| ADDITIVE RHEOLOGICsegredo industrial            |       |
|-------------------------------------------------|-------|
| Partition coefficient n-octanol/water (Log Pow) | > 6.5 |
| GLYCIDOXYPROPYL TRIMETHOXYSILANE2530-83-8       |       |
| Partition coefficient n-octanol/water (Log Pow) | -0.92 |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

Regional waste regulation : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.  
Waste treatment methods : Must follow special treatment according to local regulation.

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

- Sewage disposal recommendations
- Product/Packaging disposal recommendations
- Additional information
- : Disposal must be done according to official regulations.
- : Disposal must be done according to official regulations.
- : Flammable vapours may accumulate in the container. Do not re-use empty containers.

### SECTION 14: Transport information

#### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                                                                | IMDG                                                                                | IATA                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| UN number                                                                           |                                                                                     |                                                                                       |
| 1263                                                                                | 1263                                                                                | 1263                                                                                  |
| UN Proper Shipping Name                                                             |                                                                                     |                                                                                       |
| TINTA                                                                               | PAINT                                                                               | Paint                                                                                 |
| Transport document description                                                      |                                                                                     |                                                                                       |
| Not applicable                                                                      | UN 1263 PAINT, 3, III (60°C c.c.)                                                   | UN 1263 Paint, 3, III                                                                 |
| Transport hazard class(es)                                                          |                                                                                     |                                                                                       |
| 3                                                                                   | 3                                                                                   | 3                                                                                     |
| Danger labels                                                                       |                                                                                     |                                                                                       |
| 3                                                                                   | 3                                                                                   | 3                                                                                     |
|  |  |  |
| Subsidiary risk                                                                     |                                                                                     |                                                                                       |
| Not applicable                                                                      | Not applicable                                                                      | Not applicable                                                                        |
| Risk Number                                                                         |                                                                                     |                                                                                       |
| 30                                                                                  | Not applicable                                                                      | Not applicable                                                                        |
| Packing group                                                                       |                                                                                     |                                                                                       |
| III                                                                                 | III                                                                                 | III                                                                                   |
| Special provisions                                                                  |                                                                                     |                                                                                       |
| 163,223,367                                                                         | 163,223,367,955                                                                     | A3,A72,A192                                                                           |
| Dangerous for the environment                                                       |                                                                                     |                                                                                       |
| No                                                                                  | No                                                                                  | No                                                                                    |

#### 14.2 Other informations

No additional information available

### SECTION 15: Regulatory information

#### 15.1. National regulations

- Brazil Local Regulations
- : Standard ABNT NBR 14725.
- Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México  
E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POLI HPD 45 1 R T YELLOW COMPONENT A

15437700

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

Republic of Brazil.

Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials

Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

## SECTION 16: Other information

### Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

**WEG TINTAS LTDA – GRUPO WEG.**

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)