

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet



according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : POLITHERM 46 WF R SM WHITE 60807 MB  
Product code : 19450068

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Electrostatic powder paint for surface coating.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 1.5. Emergency phone number

Emergency number :

**24-HOUR EMERGENCY - AMBIPAR** 0800 117 2020

**CHEMTREC international number** +1-703-527-3887 e 1-800-424-9300

Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059
India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

## SECTION 2 Hazard identification

### 2.1. Classification of the substance or mixture

#### GHS US classification

Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.	Calculation method
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.	Calculation method
Germ cell mutagenicity, Category 1B	H340	May cause genetic defects.	Calculation method
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.	Calculation method

Full text of H-statements: see section 16

### 2.2. Label elements

#### GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H340 - May cause genetic defects.

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust, fume, gas, mist, vapours, spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

P302+P352 - If on skin: Wash with plenty of water.

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a poison center or doctor.  
P314 - Get medical advice or attention if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
HARDENER POLYESTER 100-108	CAS-No.: 2451-62-9	1 – 5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Inhalation:dust,mist), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : If you feel unwell, seek medical advice.

Self protection of the first-aiders : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye damage.
Symptoms/effects after inhalation	: Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: Causes serious eye damage. stinging. redness, itching, tears.
Symptoms/effects after ingestion	: May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: May cause heritable genetic damage.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. earth, sand, dry chemical powder or foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: In case of fire, corrosive and harmful gases come free.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
------------------	---

#### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

#### For emergency responders

Protective equipment	: Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Do not allow to enter drains or water courses. Harmful to aquatic life. Do not allow product to spread into the environment.

### 6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak without risks if possible. Using a clean shovel, put the material in a dry container and cover without compressing it.
-----------------	--

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methods for cleaning up : Clear up rapidly by scoop or vacuum. Clean up immediately by sweeping or vacuum. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. When heated, material emits highly irritating vapours, affecting the eyes. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Always wash hands after handling the product. Do not eat, drink or smoke when using this product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Store in a well-ventilated place. Keep cool.

Packaging materials : Always store product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Nitrile rubber gloves. Protective gloves made of PVC
<b>Eye protection:</b>
Wear closed safety glasses
<b>Skin and body protection:</b>
Long sleeved protective clothing. Or chemical resistant apron. Safety shoes
<b>Respiratory protection:</b>
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Dusty powder.
Colour	: white
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 1.52 g/cm <sup>3</sup>
Solubility	: Not soluble in water alone.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: 300 °C
Viscosity, kinematic	: No data available
Explosive limits	: 50 – 70 g/m <sup>3</sup>
Particle characteristics	: Particle size : 25 — 60 µm

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

No additional information available.

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 10.6. Hazardous decomposition products

On exposure to high temperature, may decompose, releasing corrosive gases.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : No data available  
Acute toxicity (dermal) : No data available  
Acute toxicity (inhalation) : No data available

#### HARDENER POLYESTER 100-108 (2451-62-9)

LD50 oral rat	200 mg/kg Source: Existing Chemical Safety Safety Test of NIER
LD50 dermal rat	> 2000 mg/kg Source: IPCS
LC50 Inhalation - Rat (Dust/Mist)	0.65 mg/l
ATE US (oral)	200 mg/kg bodyweight
ATE US (dust,mist)	0.65 mg/l/4h

Skin corrosion/irritation : No data available

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : No data available

Reproductive toxicity : No data available

STOT-single exposure : No data available

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

#### HARDENER POLYESTER 100-108 (2451-62-9)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : No data available

Symptoms/effects : May cause an allergic skin reaction. Causes serious eye damage.

Symptoms/effects after inhalation : Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : Causes serious eye damage. stinging. redness, itching, tears.

Symptoms/effects after ingestion : May be harmful if swallowed. Ingestion may cause nausea and vomiting.

Chronic symptoms : May cause heritable genetic damage.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life.

Hazardous to the aquatic environment, short-term (acute) : No data available

Hazardous to the aquatic environment, long-term (chronic) : No data available

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

HARDENER POLYESTER 100-108 (2451-62-9)	
LC50 - Fish [1]	> 77 mg/l Source: ECHA
EC50 72h - Algae [1]	29 – 30 mg/l Source: ECHA

### 12.2. Persistence and degradability

POLITHERM 46 WF R SM WHITE 60807 MB	
Persistence and degradability	Not rapidly degradable

HARDENER POLYESTER 100-108 (2451-62-9)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

HARDENER POLYESTER 100-108 (2451-62-9)	
Partition coefficient n-octanol/water (Log Pow)	-0.8 Source: National Library of Medicine/Hazardous Substances Data BankNLM/HSDB

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone	: No data available
Other adverse effects	: May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. Proper Shipping Name</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>			
Not applicable	Not applicable	Not applicable	Not applicable

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

DOT	TDG	IMDG	IATA
<b>14.5. Environmental hazards</b>			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not applicable

#### TDG

Not applicable

#### IMDG

Not applicable

#### IATA

Not applicable

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

PP 46 R LI BLAN 60807 MB	CAS-No.	100%
--------------------------	---------	------

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16 Other Information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H301	Toxic if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage

# POLITHERM 46 WF R SM WHITE 60807 MB

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H331	Toxic if inhaled
H340	May cause genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure

Abbreviations and acronyms	
CAS-No.	Chemical Abstracts Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration factor
EC50	Median effective concentration
LC50	Median lethal concentration
VOC	Volatile Organic Compounds
LD50	Median lethal dose
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
COD	Chemical oxygen demand (COD)
ATE	Acute Toxicity Estimate
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
EC-No.	European Community number
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class
IOELV	Indicative Occupational Exposure Limit Value
BLV	Biological limit value
TRGS	Technical Rules for Hazardous Substances
TLM	Median Tolerance Limit
IARC	International Agency for Research on Cancer

Safety Data Sheet (SDS), USA - weg

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.