

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT



## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 9/29/2023 Revision date: 2/19/2026 Version: 33.0

### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT  
Product code : 15498380  
Type of product : Spray Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for industrial sector

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| Germany        |           |                  | 0800-181-7059    |
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Aerosol, Category 2  
Acute toxicity (dermal), Category 5  
Skin corrosion/irritation, Category 2  
Skin sensitisation, Category 1  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Repeated exposure, Category 2  
Aspiration hazard, Category 1  
Hazardous to the aquatic environment - Acute Hazard, Category 2  
Hazardous to the aquatic environment - Chronic Hazard, Category 3

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H223 - Flammable aerosol  
H229 - Pressurized container: may burst if heated  
H304 - May be fatal if swallowed and enters airways  
H313 - May be harmful in contact with skin  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H335 - May cause respiratory irritation  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H401 - Toxic to aquatic life  
H412 - Harmful to aquatic life with long lasting effects  
Precautionary statements (GHS BR) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                  | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------|------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% | CAS-No.: 1330-20-7     | 40 – 50       | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 3, H412 |
| DIMETHYL ETHER                                                        | CAS-No.: 115-10-6      | 20 – 40       | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280                                                                                                                                                                                                                                                    |
| ESTERIFIED RESIN (N)                                                  | CAS-No.: 94581-15-4    | 1 – 5         | Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 4, H413                                                                                                                                                                                                                               |
| SOLVENT ACETONE                                                       | CAS-No.: 67-64-1       | 1 – 5         | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                                                                                                                                                                                                                                      |
| 2-methoxy-1-methylethyl acetate                                       | CAS-No.: 108-65-6      | 1 – 5         | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Aquatic Acute 3, H402                                                                                                                                                                                                                        |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

| Name                                 | GHS Product identifier | Conc.<br>(% w/w) | Classification according to GHS<br>BR (ABNT NBR 14725: 2023)                                                        |
|--------------------------------------|------------------------|------------------|---------------------------------------------------------------------------------------------------------------------|
| 2-ethylhexanoic acid, zirconium salt | CAS-No.: 22464-99-9    | 0.1 – 0.25       | Acute Tox. 5 (Dermal), H313<br>Repr. 2, H361<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                    |
| Aluminium                            | CAS-No.: 7429-90-5     | 0.1 – 0.25       | Flam. Sol. 1, H228<br>Pyr. Liq. 1, H250<br>Water-react. 2, H261<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                                                                                              |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : People with over sensibility problems are not allowed to work or be exposed to the product.                                                                                                                                                                                |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.                                                                                                                |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact  | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                                                                                                                                                                              |
| First-aid measures after ingestion    | : Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.                                                                                                                                                                                                     |

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                             |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. May cause respiratory irritation. May be fatal if swallowed and enters airways.   |
| Symptoms/effects after inhalation   | : May cause drowsiness or dizziness. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).                                                                     |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact  | : May cause eye irritation.                                                                                                                                                                 |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract. Risk of lung oedema.                                                                                                                         |

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

|                                |                                                                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media   | : DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED.<br>Dry chemical, CO <sub>2</sub> , or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                                                                                                        |

### 5.2. Specific hazards arising from the chemical

|             |                                                                                                                                                                |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard | : Flammable aerosol. Pressurised container: May burst if heated. Heating may cause a fire or explosion. In case of fire and/or explosion do not breathe fumes. |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

Explosion hazard : Explosion risk in case of fire. Heating may cause an explosion.

### 5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.  
Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Self-contained breathing apparatus. Use self-contained breathing apparatus and chemically protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

#### 6.1.2. For emergency responders

Protective equipment : Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Equip cleanup crew with proper protection.  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid discharge to atmosphere. Do not allow to enter drains or water courses. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and materials for containment and cleaning up

For containment : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Clean contaminated surfaces with an excess of water. Absorb spillage to prevent material damage. Absorb spilled material with sand or earth. Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.  
Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Wear personal protective equipment. Keep only in original container. Do not handle until all safety precautions have been read and understood.  
Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

### 7.2. Conditions for safe storage, including any incompatibilities

|                     |                                                                                                                                                                                                                                                                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Storage conditions  | : Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep cool. Protect from sunlight. Keep cool. |
| Packaging materials | : Always store product in container of same material as original container.                                                                                                                                                                                                                                                                                 |

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### SOLVENT ACETONE 67-64-1

##### USA - OSHA - Occupational Exposure Limits

|                                |                                    |
|--------------------------------|------------------------------------|
| Local name                     | Acetone                            |
| OSHA PEL TWA                   | 2400 mg/m <sup>3</sup><br>1000 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1           |

### 8.2. Appropriate engineering controls

|                                  |                                                                                                                                                                               |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

#### Eye protection:

Wear security glasses which protect from splashes

#### Skin and body protection:

Chemical resistant safety shoes. Long sleeved protective clothing. Or chemical resistant apron

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

### SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Physical state                                  | : Liquid                       |
| Appearance                                      | : Compressed liquid.           |
| Colour                                          | : Beige                        |
| Odour                                           | : characteristic               |
| Odour threshold                                 | : Not available                |
| pH                                              | : Not applicable               |
| Melting point                                   | : Not available                |
| Freezing point                                  | : Not available                |
| Boiling point                                   | : Not available                |
| Flash point                                     | : -70 °C                       |
| Relative evaporation rate (butylacetate=1)      | : Not available                |
| Flammability                                    | : Not available                |
| Explosive limits                                | : Not available                |
| Vapour pressure                                 | : Not available                |
| Relative vapour density at 20°C                 | : Not available                |
| Relative density                                | : Not available                |
| Density                                         | : 0.96 – 1.06 g/cm³            |
| Solubility                                      | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                |
| Auto-ignition temperature                       | : Not available                |
| Decomposition temperature                       | : Not available                |
| Viscosity, kinematic                            | : 13 – 15 Seconds              |
| Particle size                                   | : Not applicable               |
| Particle size distribution                      | : Not applicable               |
| Particle shape                                  | : Not applicable               |
| Particle aspect ratio                           | : Not applicable               |
| Particle specific surface area                  | : Not applicable               |

#### 2-ethylhexanoic acid, zirconium salt22464-99-9

|             |                    |
|-------------|--------------------|
| Flash point | 40 °C Source: ECHA |
|-------------|--------------------|

#### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7

|                           |                                |
|---------------------------|--------------------------------|
| Boiling point             | 138 °C Source: ICSC            |
| Flash point               | 30 °C (ASTM D 93)              |
| Auto-ignition temperature | ≥ 528 °C Source: SRC           |
| Vapour pressure           | 8.84 mm Hg at 25°C Source: SRC |

#### 2-methoxy-1-methylethyl acetate108-65-6

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Boiling point             | 145.8 °C Atm. press.: 760 mm Hg Decomposition: 'no'                |
| Flash point               | 45.5 °C Atm. press.: 101,3 kPa                                     |
| Auto-ignition temperature | 315 °C Source: International Uniform Chemical Information Database |
| Vapour pressure           | 3.75 mm Hg Source: National Institute of Technology and Evaluation |

#### ESTERIFIED RESIN (N)94581-15-4

|               |                            |
|---------------|----------------------------|
| Boiling point | ≥ 163 °C Source: ECHA Chem |
|---------------|----------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

### ESTERIFIED RESIN (N)94581-15-4

|                 |                       |
|-----------------|-----------------------|
| Vapour pressure | < 1 mbar Temp.: 20 °C |
|-----------------|-----------------------|

### Aluminium7429-90-5

|                           |                      |
|---------------------------|----------------------|
| Boiling point             | 2327 °C Source: HSDB |
| Auto-ignition temperature | 590 °C Source: ICSC  |
| Vapour pressure           | 1 Temp.: 1284 °C     |

### DIMETHYL ETHER115-10-6

|                           |                                                      |
|---------------------------|------------------------------------------------------|
| Boiling point             | -23.6 °C Source: International Chemical Safety Cards |
| Flash point               | -80 °C                                               |
| Auto-ignition temperature | 350 °C Source: International Chemical Safety Cards   |

### SOLVENT ACETONE67-64-1

|                           |                                  |
|---------------------------|----------------------------------|
| Boiling point             | 56.1 °C at 760 mmHg Source: HSDB |
| Flash point               | -18 °C Source: ICSC              |
| Auto-ignition temperature | 465 °C Source: ICSC              |
| Vapour pressure           | 240 hPa at 20°C Source: ECHA     |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : Flammable aerosol. Pressurised container: May burst if heated.                                                                                                                                   |
| Conditions to avoid                | : High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                                                                 |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.                                                                                             |
| Incompatible materials             | : Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials. |
| Possibility of hazardous reactions | : May mass explode in fire. Heating may cause a fire or explosion.                                                                                                                                 |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                                               |
| Handling temperature               | : No additional information available                                                                                                                                                              |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                                        |
|-----------------------------|----------------------------------------|
| Acute toxicity (oral)       | : Not available                        |
| Acute toxicity (dermal)     | : May be harmful in contact with skin. |
| Acute toxicity (inhalation) | : Not available                        |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

### W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

|                 |                           |
|-----------------|---------------------------|
| ATE BR (dermal) | 2527.974 mg/kg bodyweight |
|-----------------|---------------------------|

### 2-ethylhexanoic acid, zirconium salt (22464-99-9)

|               |                                                                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method) |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                 |                                                                                            |
|-----------------|--------------------------------------------------------------------------------------------|
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
|-----------------|--------------------------------------------------------------------------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|               |                         |
|---------------|-------------------------|
| LD50 oral rat | 3523 mg/kg Source: ECHA |
|---------------|-------------------------|

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
|--------------------|---------------------------------------------------------|

|                             |          |
|-----------------------------|----------|
| LC50 Inhalation - Rat [ppm] | 5922 ppm |
|-----------------------------|----------|

### 2-methoxy-1-methylethyl acetate (108-65-6)

|               |                                                                        |
|---------------|------------------------------------------------------------------------|
| LD50 oral rat | 8532 mg/kg Source: International Uniform Chemical Information Database |
|---------------|------------------------------------------------------------------------|

|                 |                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------|
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
|-----------------|--------------------------------------------------------------------------------------------------------------|

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| LD50 dermal rabbit | > 5000 mg/kg Source: International Uniform Chemical Information Database |
|--------------------|--------------------------------------------------------------------------|

### ESTERIFIED RESIN (N) (94581-15-4)

|               |                                                                                                                                         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method) |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------|

|           |                                                      |
|-----------|------------------------------------------------------|
| LD50 oral | > 2000 mg/kg bodyweight Animal: , Animal sex: female |
|-----------|------------------------------------------------------|

|                 |                                                                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------|

### Aluminium (7429-90-5)

|               |                            |
|---------------|----------------------------|
| LD50 oral rat | > 15900 mg/kg Source: ECHA |
|---------------|----------------------------|

|                                   |                           |
|-----------------------------------|---------------------------|
| LC50 Inhalation - Rat (Dust/Mist) | > 0.888 mg/l Source: ECHA |
|-----------------------------------|---------------------------|

### DIMETHYL ETHER (115-10-6)

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| LC50 Inhalation - Rat | 308.5 mg/l Source: International Uniform Chemical Information Database |
|-----------------------|------------------------------------------------------------------------|

### SOLVENT ACETONE (67-64-1)

|               |                         |
|---------------|-------------------------|
| LD50 oral rat | 5800 mg/kg Source: ECHA |
|---------------|-------------------------|

|                    |                           |
|--------------------|---------------------------|
| LD50 dermal rabbit | > 7400 mg/kg Source: ECHA |
|--------------------|---------------------------|

|                                 |                      |
|---------------------------------|----------------------|
| LC50 Inhalation - Rat (Vapours) | 76 mg/l Source: ECHA |
|---------------------------------|----------------------|

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### SOLVENT ACETONE (67-64-1)

|    |                |
|----|----------------|
| pH | 5 Source: ECHA |
|----|----------------|

Serious eye damage/irritation : Not available

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

pH: Not applicable

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### SOLVENT ACETONE (67-64-1)

|    |                |
|----|----------------|
| pH | 5 Source: ECHA |
|----|----------------|

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

### Aluminium (7429-90-5)

|                           |                                                                                                                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F0/P) | 1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Reproductive toxicity : Not available

STOT-single exposure : May cause respiratory irritation.

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|                      |                                   |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

### SOLVENT ACETONE (67-64-1)

|                      |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### 2-ethylhexanoic acid, zirconium salt (22464-99-9)

|                                                |                                                                         |
|------------------------------------------------|-------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/male, 90 days) | 180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other: |
|------------------------------------------------|-------------------------------------------------------------------------|

|                                                  |                                                                           |
|--------------------------------------------------|---------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/female, 90 days) | 205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other: |
|--------------------------------------------------|---------------------------------------------------------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|                            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--------------------------------------------------------------------|

### 2-methoxy-1-methylethyl acetate (108-65-6)

|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|

### ESTERIFIED RESIN (N) (94581-15-4)

|                            |                                                                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (oral, rat, 90 days) | 300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Aluminium (7429-90-5)

|                                                |                                                                                                                                              |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/male, 90 days) | 1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents) |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|

|                                                  |                                                                                                                                                |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/female, 90 days) | 1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents) |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|

Aspiration hazard : May be fatal if swallowed and enters airways.

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

10/15

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

| W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT                       |                                                                                                  |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Viscosity, kinematic                                                              | 13 – 15 mm <sup>2</sup> /s                                                                       |
| REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7) |                                                                                                  |
| Viscosity, kinematic                                                              | ≈ 0.76 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)' |
| 2-methoxy-1-methylethyl acetate (108-65-6)                                        |                                                                                                  |
| Viscosity, kinematic                                                              | 1.182 mm <sup>2</sup> /s                                                                         |
| SOLVENT ACETONE (67-64-1)                                                         |                                                                                                  |
| Viscosity, kinematic                                                              | 0.418 mm <sup>2</sup> /s                                                                         |

### 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                                                                             |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. May cause respiratory irritation. May be fatal if swallowed and enters airways.   |
| Symptoms/effects after inhalation   | : May cause drowsiness or dizziness. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).                                                                     |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact  | : May cause eye irritation.                                                                                                                                                                 |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract. Risk of lung oedema.                                                                                                                         |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                                             |
|-----------------------------------------------------------|-----------------------------------------------------------------------------|
| Ecology - general                                         | : Harmful to aquatic life with long lasting effects. Toxic to aquatic life. |
| Hazardous to the aquatic environment, short-term (acute)  | : Toxic to aquatic life.                                                    |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects.                        |

| 2-ethylhexanoic acid, zirconium salt22464-99-9                                 |                                                                                                            |
|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]                                                                | 100 mg/l Test organisms (species): Oryzias latipes                                                         |
| EC50 - Crustacea [1]                                                           | 0.17 mg/l Test organisms (species): Daphnia magna                                                          |
| EC50 72h - Algae [1]                                                           | 49.3 mg/l Source: ECHA                                                                                     |
| LOEC (chronic)                                                                 | 63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                           |
| NOEC (chronic)                                                                 | 25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                           |
| REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7 |                                                                                                            |
| LC50 - Fish [1]                                                                | 2.6 mg/l Source: ECHA                                                                                      |
| EC50 - Crustacea [1]                                                           | 3.4 mg/l Test organisms (species): Ceriodaphnia dubia                                                      |
| ErC50 algae                                                                    | 2.2 mg/l                                                                                                   |
| LOEC (chronic)                                                                 | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                         |
| NOEC chronic fish                                                              | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

|                                                |                                                                                                                                           |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>2-methoxy-1-methylethyl acetate108-65-6</b> |                                                                                                                                           |
| LC50 - Fish [1]                                | 100 mg/l Test organisms (species): Oryzias latipes                                                                                        |
| EC50 - Crustacea [1]                           | 500 mg/l Test organisms (species): Daphnia magna                                                                                          |
| EC50 72h - Algae [1]                           | 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| NOEC (chronic)                                 | ≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |
| NOEC chronic fish                              | 47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'                                                                      |
| <b>ESTERIFIED RESIN (N)94581-15-4</b>          |                                                                                                                                           |
| LC50 - Fish [1]                                | > 400 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)                                                       |
| EC50 - Crustacea [1]                           | > 100 mg/l Source: ECHA Chem                                                                                                              |
| LC50 - Fish [2]                                | > 400 mg/l Test organisms (species):                                                                                                      |
| EC50 72h - Algae [1]                           | > 100 mg/l Source: ECHA Chem                                                                                                              |
| <b>Aluminium7429-90-5</b>                      |                                                                                                                                           |
| EC50 72h - Algae [1]                           | 1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2]                           | 0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)  |
| <b>SOLVENT ACETONE67-64-1</b>                  |                                                                                                                                           |
| LC50 - Fish [1]                                | 5540 mg/l Source: ECHA                                                                                                                    |

## 12.2. Persistence and degradability

|                                                                                       |                        |
|---------------------------------------------------------------------------------------|------------------------|
| <b>W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT</b>                    |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>2-ethylhexanoic acid, zirconium salt22464-99-9</b>                                 |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7</b> |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>2-methoxy-1-methylethyl acetate108-65-6</b>                                        |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>ESTERIFIED RESIN (N)94581-15-4</b>                                                 |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>Aluminium7429-90-5</b>                                                             |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>DIMETHYL ETHER115-10-6</b>                                                         |                        |
| Persistence and degradability                                                         | Not rapidly degradable |
| <b>SOLVENT ACETONE67-64-1</b>                                                         |                        |
| Persistence and degradability                                                         | Not rapidly degradable |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

### 12.3. Bioaccumulative potential

| REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7 |                                                                  |
|--------------------------------------------------------------------------------|------------------------------------------------------------------|
| Partition coefficient n-octanol/water (Log Pow)                                | 3.15 Source: HSDB                                                |
| 2-methoxy-1-methylethyl acetate108-65-6                                        |                                                                  |
| Partition coefficient n-octanol/water (Log Pow)                                | 0.43 Source: International Uniform Chemical Information Database |
| ESTERIFIED RESIN (N)94581-15-4                                                 |                                                                  |
| Partition coefficient n-octanol/water (Log Pow)                                | 4.5 Source: ECHA Chem                                            |
| DIMETHYL ETHER115-10-6                                                         |                                                                  |
| Partition coefficient n-octanol/water (Log Pow)                                | 0.1 Source: International Chemical Safety Cards                  |
| SOLVENT ACETONE67-64-1                                                         |                                                                  |
| Partition coefficient n-octanol/water (Log Pow)                                | -0.24 Source: ICSC                                               |

### 12.4. Mobility in soil

| DIMETHYL ETHER115-10-6 |                                                                        |
|------------------------|------------------------------------------------------------------------|
| Mobility in soil       | 27 Source: National Library of Medicine/Hazardous Substances Data Bank |

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

|                                            |                                                                |
|--------------------------------------------|----------------------------------------------------------------|
| Waste treatment methods                    | : Must follow special treatment according to local regulation. |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.     |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations.     |
| Additional information                     | : Do not re-use empty containers.                              |

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                           | IMDG                  | IATA                             |
|--------------------------------|-----------------------|----------------------------------|
| UN number                      |                       |                                  |
| 1950                           | 1950                  | 1950                             |
| UN Proper Shipping Name        |                       |                                  |
| AEROSSÓIS                      | AEROSOLS              | Aerosols, flammable              |
| Transport document description |                       |                                  |
| Not applicable                 | UN 1950 AEROSOLS, 2.1 | UN 1950 Aerosols, flammable, 2.1 |
| Transport hazard class(es)     |                       |                                  |
| 2.1                            | 2                     | 2                                |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

| Danger labels                                                                     |                                                                                   |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 2.1                                                                               | 2.1                                                                               | 2.1                                                                                 |
|  |  |  |
| Subsidiary risk                                                                   |                                                                                   |                                                                                     |
| Not applicable                                                                    | Not applicable                                                                    | Not applicable                                                                      |
| Risk Number                                                                       |                                                                                   |                                                                                     |
| Not applicable                                                                    | Not applicable                                                                    | Not applicable                                                                      |
| Packing group                                                                     |                                                                                   |                                                                                     |
| Not applicable                                                                    | Not applicable                                                                    | Not applicable                                                                      |
| Special provisions                                                                |                                                                                   |                                                                                     |
| 63,190,277,327,344                                                                | 63,190,277,327,344,381,959                                                        | A145,A167,A802                                                                      |
| Dangerous for the environment                                                     |                                                                                   |                                                                                     |
| No                                                                                | No                                                                                | No                                                                                  |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.  
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK SRA 11 1 R SPRAY WHITE WI MUNSELL N9,5 MONOCOMPONENT

15498380

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/19/2026

DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

---

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)