

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A



Safety Data Sheet

According to ABNT NBR 14725: 2023
Issue date: 4/28/2025 Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A
Product code : 12248826
Type of product : Paint
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 – Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

| | | | |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| 24-HOUR EMERGENCY - AMBIPAR | | 0800 117 2020 | |
| CHEMTREC international number | | +1-703-527-3887 e 1-800-424-9300 | |
| Country | City | Local Number | Toll-Free Number |
| Austria | Vienna | +43-1-3649237 | |
| Austria | | | 0800 293702 |
| China | | 400 120 4937 | |
| France | | +33-975181407 | |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A 12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| | | | |
|----------------|-----------|------------------|------------------|
| Germany | | | 0800-181-7059 |
| India | Bangalore | +91 8071 279 207 | |
| India | | | 000 800 1007 141 |
| Italy | Milan | +39-02 4555 7031 | |
| Italy | | | 800 789 767 |
| Netherlands | | +31-85 888 0596 | |
| Russia | | | 8(800)100-63-46 |
| South Africa | | | 080-001-4676 |
| United Kingdom | London | +44 20 3807 3798 | |
| South korea | | | 080-880-0454 |
| Japan | | | 0800-300-5842 |

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Skin corrosion/irritation, Category 2
Germ cell mutagenicity, Category 1B
Carcinogenicity, Category 1B
Reproductive toxicity, Category 1B
Specific target organ toxicity — Repeated exposure, Category 2
Aspiration hazard, Category 1
Hazardous to the aquatic environment - Acute Hazard, Category 2
Hazardous to the aquatic environment - Chronic Hazard, Category 3

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H340 - May cause genetic defects.
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS BR) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

P264 - Wash hands, forearms and face thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P314 - Get medical advice or attention as appropriate.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | GHS Product identifier | % | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|--|------------------------|---------|---|
| MIXED XYLENES | CAS-No.: 1330-20-7 | 10 – 20 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Light aromatic naphtha (petroleum) solvent | CAS-No.: 64742-95-6 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| SOLVENT METHYL ETHYL KETONE | CAS-No.: 78-93-3 | 1 – 5 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| SOLVENT ETHYL GLYCOL ACETATE | CAS-No.: 111-15-9 | 1 – 5 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| Name | GHS Product identifier | % | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|---|------------------------|------------|--|
| | | | Acute Tox. 4 (Inhalation), H332 Repr. 1B, H360 |
| Aluminium | CAS-No.: 7429-90-5 | 1 – 5 | Flam. Sol. 1, H228 Pyr. Liq. 1, H250 Water-react. 2, H261 Aquatic Acute 1, H400 |
| Aliphatic solvent | CAS-No.: 64742-47-8 | 1 – 5 | Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Acute Tox. 3 (Inhalation:vapour), H331 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] | CAS-No.: 64742-48-9 | 0.1 – 0.25 | Flam. Liq. 2, H225 Acute Tox. 5 (Dermal), H313 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)]stannane | CAS-No.: 77-58-7 | 0.1 – 0.25 | Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Muta. 2, H341 Repr. 1B, H360 STOT RE 1, H372 Aquatic Acute 1, H400 |

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| First-aid measures after ingestion | : Do not induce vomiting/risk of damage to lungs exceeds poisoning risk. |

4.2. Most important symptoms and effects, acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May be fatal if swallowed and enters airways. |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering). |
| Symptoms/effects after eye contact | : May cause eye irritation. stinging. Redness. |
| Symptoms/effects after ingestion | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema. |
| Chronic symptoms | : May cause cancer. May cause heritable genetic damage. May damage fertility. May damage the unborn child. |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A 12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Equip cleanup crew with proper protection.
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.
- Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- Incompatible materials : combustible materials.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| MIXED XYLENES 1330-20-7 | |
|--|---|
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Xylene, mixed isomers (Dimethylbenzene) |
| ACGIH® TLV® TWA | 20 ppm |
| Remark (ACGIH) | TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Xylenes (o-, m-, p-isomers) |
| OSHA PEL TWA | 435 mg/m ³ |
| | 100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| SOLVENT METHYL ETHYL KETONE 78-93-3 | |
|--|--|
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Methyl ethyl ketone (MEK) |
| ACGIH® TLV® TWA | 75 ppm |
| ACGIH® TLV® STEL | 150 ppm |
| Remark (ACGIH) | TLV® Basis: Embryo/fetal dam; URT irr; headache; dizziness. Notations: Skin; BEI |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | 2-Butanone (Methyl ethyl ketone) |
| OSHA PEL TWA | 590 mg/m ³ 200 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| SOLVENT ETHYL GLYCOL ACETATE 111-15-9 | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | 2-Ethoxyethyl acetate |
| ACGIH® TLV® TWA | 5 ppm |
| Remark (ACGIH) | TLV® Basis: Male repro dam. Notations: Skin; BEI |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | 2-Ethoxyethyl acetate (Cellosolve acetate) |
| OSHA PEL TWA | 540 mg/m ³ 100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| Aluminium 7429-90-5 | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Aluminum metal and insoluble compounds |
| ACGIH® TLV® TWA | 1 mg/m ³ (R - Respirable particulate matter) |
| Remark (ACGIH) | TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity. Notations: A4 (Not classifiable as a Human Carcinogen) |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Aluminum Metal (as Al) |
| OSHA PEL TWA | 15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction) |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC

Eye protection:

Wear closed safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

| | |
|---|----------------------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Colour | : Aluminium |
| Odour | : characteristic |
| Odour threshold | : Not available |
| pH | : Not applicable |
| Melting point | : Not available |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flash point | : 31 °C |
| Relative evaporation rate (butylacetate=1) | : Not available |
| Flammability | : Not available |
| Explosive limits | : Not available |
| Vapour pressure | : Not available |
| Relative vapour density at 20°C | : Not available |
| Relative density | : Not available |
| Density | : 0.91 – 0.971 g/cm ³ |
| Solubility | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| Viscosity, kinematic | : 18 – 20 Seconds |
| Particle size | : Not applicable |
| Particle size distribution | : Not applicable |
| Particle shape | : Not applicable |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A 12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

Particle aspect ratio : Not applicable
Particle specific surface area : Not applicable

| MIXED XYLENES1330-20-7 | |
|-------------------------------|-------------------|
| Boiling point | 139.6 °C |
| Flash point | 30 °C (ASTM D 93) |
| Auto-ignition temperature | 488 °C |
| Vapour pressure | 4.8 kPa 55°C |

| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
|---|--------------------------|
| Boiling point | 165.5 (156 – 175) °C |
| Flash point | 40 °C |
| Vapour pressure | ≤ 240 kPa Temp.: 37,8 °C |

| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane77-58-7 | |
|--|---------------------------------------|
| Boiling point | 205 °C Atm. press.: 1,3 kPa |
| Flash point | 189 – 193 °C Atm. press.: 101,325 kPa |
| Vapour pressure | 0.0000077 Pa Temp.: 25 °C |

| Aliphatic solvent64742-47-8 | |
|------------------------------------|---------------------------------------|
| Boiling point | 146 – 299 °C Atm. press.: 101,325 kPa |
| Flash point | 29 – 70 °C Atm. press.: 101,325 kPa |
| Auto-ignition temperature | 236 °C Source: ICSC |
| Vapour pressure | 1 – 3.7 kPa Temp.: 37,8 °C |

| Aluminium7429-90-5 | |
|---------------------------|----------------------|
| Boiling point | 2327 °C Source: HSDB |
| Auto-ignition temperature | 590 °C Source: ICSC |
| Vapour pressure | 1 Temp.: 1284 °C |

| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]64742-48-9 | |
|---|---------------------------------------|
| Boiling point | -20 – 260 °C Atm. press.: 101,325 kPa |
| Flash point | < -40 °C Atm. press.: 101,325 other: |
| Vapour pressure | ≤ 240 kPa Temp.: 37,8 °C |

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 10: Stability and reactivity

| | |
|------------------------------------|---|
| Chemical stability | : In use may form flammable/explosive vapour-air mixture. |
| Conditions to avoid | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products | : May liberate toxic gases. |
| Incompatible materials | : Combustible materials. |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials. |
| Reactivity | : The product is non-reactive under normal conditions of use, storage and transport. |
| Handling temperature | : No additional information available |

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|-----------------|
| Acute toxicity (oral) | : Not available |
| Acute toxicity (dermal) | : Not available |
| Acute toxicity (inhalation) | : Not available |

| | |
|--|---|
| MIXED XYLENES (1330-20-7) | |
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
| Light aromatic naphtha (petroleum) solvent (64742-95-6) | |
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rat | > 2000 mg/kg Source: ECHA |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 Inhalation - Rat (Vapours) | 5.16 mg/l Source: ECHA |
| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7) | |
| LD50 oral rat | 2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1207 - 5106 |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |
| Aliphatic solvent (64742-47-8) | |
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LD50 dermal rabbit | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat | > 5.28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 - |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.2 mg/l Source: IUCLID |
| Aluminium (7429-90-5) | |
| LC50 Inhalation - Rat (Dust/Mist) | > 0.888 mg/l Source: ECHA |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9) | |
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

10/16

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)

LD50 dermal rabbit > 3160 mg/kg Source: IUCLID

Skin corrosion/irritation : Causes skin irritation.
pH: Not applicable

MIXED XYLENES (1330-20-7)

pH 7

Serious eye damage/irritation : Not available
pH: Not applicable

MIXED XYLENES (1330-20-7)

pH 7

Respiratory or skin sensitisation : Not available
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

MIXED XYLENES (1330-20-7)

IARC group 3 - Not classifiable

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)

NOAEL (animal/male, F0/P) 1.9 – 2.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

NOAEL (animal/female, F0/P) 1.7 – 2.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Aliphatic solvent (64742-47-8)

NOAEL (animal/male, F0/P) ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

Aluminium (7429-90-5)

NOAEL (animal/male, F0/P) 1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Reproductive toxicity : May damage fertility or the unborn child.
STOT-single exposure : Not available

MIXED XYLENES (1330-20-7)

STOT-single exposure May cause respiratory irritation.

SOLVENT METHYL ETHYL KETONE (78-93-3)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

MIXED XYLENES (1330-20-7)

LOAEL (oral, rat, 90 days) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)

STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| Aliphatic solvent (64742-47-8) | |
|--|--|
| NOAEL (oral, rat, 90 days) | 750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEL (dermal, rat/rabbit, 90 days) | ≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |
| Aluminium (7429-90-5) | |
| NOAEL (subchronic, oral, animal/male, 90 days) | 1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents) |
| NOAEL (subchronic, oral, animal/female, 90 days) | 1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents) |

Aspiration hazard : May be fatal if swallowed and enters airways.

| PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A | |
|---|--|
| Viscosity, kinematic | 18 – 20 mm ² /s |
| MIXED XYLENES (1330-20-7) | |
| Viscosity, kinematic | ≈ 0.76 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)' |
| Light aromatic naphtha (petroleum) solvent (64742-95-6) | |
| Viscosity, kinematic | < 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' |
| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7) | |
| Viscosity, kinematic | 68.571 mm ² /s |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9) | |
| Viscosity, kinematic | < 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' |

11.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May be fatal if swallowed and enters airways. |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering). |
| Symptoms/effects after eye contact | : May cause eye irritation. stinging. Redness. |
| Symptoms/effects after ingestion | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema. |
| Chronic symptoms | : May cause cancer. May cause heritable genetic damage. May damage fertility. May damage the unborn child. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Hazardous to the aquatic environment, short-term (acute) | : Toxic to aquatic life. |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |

| MIXED XYLENES 1330-20-7 | |
|-------------------------|------------|
| LC50 - Fish [1] | ≈ 2.6 mg/l |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| MIXED XYLENES1330-20-7 | |
|---|---|
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| ErC50 algae | ≈ 2.2 mg/l |
| LOEC (chronic) | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| LC50 - Fish [1] | 9.22 mg/l Source: IUCLID |
| EC50 - Crustacea [1] | 6.14 mg/l Source: IUCLID |
| EC50 72h - Algae [1] | 19 mg/l Source: IUCLID |
| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane77-58-7 | |
| LC50 - Fish [1] | 21.2 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |
| EC50 - Crustacea [1] | 1.7 – 3.4 mg/l Test organisms (species): Daphnia magna |
| EC50 - Crustacea [2] | 463 µg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 1 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| Aliphatic solvent64742-47-8 | |
| LC50 - Fish [1] | 2.4 mg/l Source: ECOTOX |
| Aluminium7429-90-5 | |
| EC50 72h - Algae [1] | 1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]64742-48-9 | |
| LC50 - Fish [1] | 2200 mg/l Source: IUCLID |
| LC50 - Other aquatic organisms [1] | 2.6 mg/l Source: IUCLID |

12.2. Persistence and degradability

| PU ENAMEL ACRYLIC LEGRAND ALUMINUM 00000 COMPONENT A | |
|---|------------------------|
| Persistence and degradability | Not rapidly degradable |
| MIXED XYLENES1330-20-7 | |
| Persistence and degradability | Not rapidly degradable |
| SOLVENT METHYL ETHYL KETONE78-93-3 | |
| Persistence and degradability | Not rapidly degradable |
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| Persistence and degradability | Not rapidly degradable |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| | |
|--|------------------------|
| dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane77-58-7 | |
| Persistence and degradability | Not rapidly degradable |
| SOLVENT ETHYL GLYCOL ACETATE111-15-9 | |
| Persistence and degradability | Not rapidly degradable |
| Aliphatic solvent64742-47-8 | |
| Persistence and degradability | Not rapidly degradable |
| Aluminium7429-90-5 | |
| Persistence and degradability | Not rapidly degradable |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]64742-48-9 | |
| Persistence and degradability | Not rapidly degradable |

12.3. Bioaccumulative potential

| | |
|--|------------------------|
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| Partition coefficient n-octanol/water (Log Pow) | 2.1 – 6 Source: IUCLID |
| Aliphatic solvent64742-47-8 | |
| Partition coefficient n-octanol/water (Log Pow) | 3.3 – 6 Source: IUCLID |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]64742-48-9 | |
| Partition coefficient n-octanol/water (Log Pow) | 2.1 – 6 Source: IUCLID |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

| | |
|--|--|
| Regional waste regulation | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010. |
| Waste treatment methods | : Must follow special treatment according to local regulation. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. |
| Additional information | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México




E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

| ANTT | IMDG | IATA |
|---|---|---|
| UN number | | |
| 1263 | 1263 | 1263 |
| UN Proper Shipping Name | | |
| TINTA | PAINT | Paint |
| Transport document description | | |
| Not applicable | UN 1263 PAINT, 3, III (31°C c.c.) | UN 1263 Paint, 3, III |
| Transport hazard class(es) | | |
| 3 | 3 | 3 |
| Danger labels | | |
| 3 | 3 | 3 |
|  |  |  |
| Subsidiary risk | | |
| Not applicable | Not applicable | Not applicable |
| Risk Number | | |
| 30 | Not applicable | Not applicable |
| Packing group | | |
| III | III | III |
| Special provisions | | |
| 163,223,367 | 163,223,367,955 | A3,A72,A192 |
| Dangerous for the environment | | |
| No | No | No |

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.

Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.

Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials

Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

PU ENAMEL ACRYLIC LEGRAND ALUMINUM 0000 COMPONENT A

12248826

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.