

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT



## Safety Data Sheet

According to ABNT NBR 14725: 2023  
Issue date: 4/23/2025 Revision date: 1/29/2026 Version: 3.0

### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT  
Product code : 13986684  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| Germany        |           |                  | 0800-181-7059    |
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Acute toxicity (dermal), Category 5  
Acute toxicity (inhalation:dust,mist) Category 4  
Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 2  
Respiratory sensitisation, Category 1  
Germ cell mutagenicity, Category 1B  
Carcinogenicity, Category 1A  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Repeated exposure, Category 2  
Hazardous to the aquatic environment - Acute Hazard, Category 2  
Hazardous to the aquatic environment - Chronic Hazard, Category 2

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H313 - May be harmful in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects  
Precautionary statements (GHS BR) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P284 - Wear respiratory protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or a doctor.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name          | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                                                                                         |
|---------------|------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MIXED XYLENES | CAS-No.: 1330-20-7     | 20 – 40       | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 3, H412 |
| ETHYL ACETATE | CAS-No.: 141-78-6      | 5 – 10        | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319                                                                                                                                                                                                                                                         |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

| Name                                       | GHS Product identifier | Conc.<br>(% w/w) | Classification according to GHS<br>BR (ABNT NBR 14725: 2023)                                                                                                                                                                                         |
|--------------------------------------------|------------------------|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                            |                        |                  | STOT SE 3, H336                                                                                                                                                                                                                                      |
| SOLVENT ACETATO DE ETILA                   | CAS-No.: 141-78-6      | 5 – 10           | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                                                                                                                                                                                         |
| n-butyl acetate                            | CAS-No.: 123-86-4      | 5 – 10           | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412                                                                                                                                                            |
| Ethyl Alcohol, Anhydrous Alcohol, AEAC     | CAS-No.: 64-17-5       | 5 – 10           | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319                                                                                                                                                                                                             |
| ISOPENTYL ACETATE                          | CAS-No.: 123-92-2      | 1 – 5            | Flam. Liq. 3, H226<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412                                                                                                                                                                               |
| Hydrated aluminum silicate (KAOLIN)        | CAS-No.: 1332-58-7     | 1 – 5            | Acute Tox. 4 (Inhalation:dust,mist), H332<br>Resp. Sens. 1, H334                                                                                                                                                                                     |
| SOLVENT BUTYL GLYCOL (N)                   | CAS-No.: 111-76-2      | 1 – 5            | Flam. Liq. 4, H227<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 5 (Dermal), H313<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 3 (Inhalation:vapour), H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319                                            |
| Steam-cracked petroleum distillates        | CAS-No.: 68477-39-4    | 0.5 – 1          | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 5 (Dermal), H313<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Carc. 1A, H350<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 1, H410 |
| Naphtha (petroleum), refined light solvent | CAS-No.: 64741-84-0    | 0.5 – 1          | Flam. Liq. 2, H225<br>Acute Tox. 5 (Dermal), H313<br>Skin Irrit. 2, H315<br>Muta. 1B, H340<br>Carc. 1B, H350<br>Repr. 2, H361<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 1, H410                            |
| FATTY ACIDS                                | CAS-No.: 68647-95-0    | 0.5 – 1          | Acute Tox. 5 (Oral), H303<br>Skin Irrit. 2, H315<br>Skin Sens. 1B, H317<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                       |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

| Name                                      | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                      |
|-------------------------------------------|------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ZINC OXIDE                                | CAS-No.: 1314-13-2     | 0.5 – 1       | Acute Tox. 5 (Dermal), H313<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                                             |
| Nafta solvente (petróleo), aromático leve | CAS-No.: 64742-95-6    | 0.25 – 0.5    | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Muta. 1B, H340<br>Carc. 1B, H350<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| Cobalt bis(2-ethylhexanoate)              | CAS-No.: 136-52-7      | 0.1 – 0.25    | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 1B, H360<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412                                 |
| ZINC OCTOATE                              | CAS-No.: 136-53-8      | 0.1 – 0.25    | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Eye Irrit. 2, H319<br>Repr. 2, H361<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412                                                                            |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.                                                                                                                                                    |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Give oxygen or artificial respiration if necessary.                                               |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact  | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.                                                                          |
| First-aid measures after ingestion    | : Do NOT induce vomiting. Rinse mouth out with water.                                                                                                                                                       |

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                                                                                                                                              |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.                                                                         |
| Symptoms/effects after inhalation   | : May cause headache, nausea and irritation of respiratory tract. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation may cause irritation (cough, short breathing, difficulty in breathing). |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).                                                                                                                                                                                                    |

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| Symptoms/effects after eye contact | : stinging. Redness. Causes serious eye irritation. redness, itching, tears. |
| Symptoms/effects after ingestion   | : May cause irritation to the digestive tract.                               |
| Chronic symptoms                   | : May cause cancer. May cause heritable genetic damage.                      |

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Suitable extinguishing media   | : Dry chemical, CO2, or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                   |

### 5.2. Specific hazards arising from the chemical

|                  |                                                                                                                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard      | : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. |
| Explosion hazard | : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.                                                                                                                                                                                          |

### 5.3. Special protective actions for fire-fighters

|                                |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary measures fire    | : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.                                                                                                                                                                                                                                 |
| Firefighting instructions      | : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.                                                                                                                                                                                                                                                                  |
| Other information              | : On exposure to high temperature, may decompose, releasing toxic gases. In case of fire, corrosive and harmful gases come free. High temperature decomposition products are harmful by inhalation.                                                                                                                                           |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures | : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### 6.1.1. For non-emergency personnel

|                      |                                                                                                                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Wear recommended personal protective equipment.                                                                                                                                                                                                             |
| Emergency procedures | : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities. |

#### 6.1.2. For emergency responders

|                      |                                                                                                                                                                                                                                                                                                                                                        |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection. |
| Emergency procedures | : Keep away from combustible material. All equipment used when handling the product must                                                                                                                                                                                                                                                               |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and materials for containment and cleaning up

- For containment : Prevent dispersion by moistening spill with water or foam. Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Clear up rapidly by scoop or vacuum. Absorb spillage to prevent material damage. Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- Incompatible materials : combustible materials.
- Packaging materials : Always store product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| SOLVENT ACETATO DE ETILA 141-78-6         |                          |
|-------------------------------------------|--------------------------|
| USA - OSHA - Occupational Exposure Limits |                          |
| Local name                                | Ethyl acetate            |
| OSHA PEL TWA                              | 1400 mg/m <sup>3</sup>   |
|                                           | 400 ppm                  |
| Regulatory reference (US-OSHA)            | OSHA Annotated Table Z-1 |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

### ISOPENTYL ACETATE 123-92-2

#### USA - OSHA - Occupational Exposure Limits

|                                |                          |
|--------------------------------|--------------------------|
| Local name                     | Isomyl acetate           |
| OSHA PEL TWA                   | 525 mg/m <sup>3</sup>    |
|                                | 100 ppm                  |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC

#### Eye protection:

Wear closed safety glasses

#### Skin and body protection:

Safety shoes

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                                            |                  |
|--------------------------------------------|------------------|
| Physical state                             | : Liquid         |
| Appearance                                 | : Liquid.        |
| Colour                                     | : Grey           |
| Odour                                      | : Not available  |
| Odour threshold                            | : Not available  |
| pH                                         | : Not applicable |
| Melting point                              | : Not available  |
| Freezing point                             | : Not available  |
| Boiling point                              | : Not available  |
| Flash point                                | : 31 °C          |
| Relative evaporation rate (butylacetate=1) | : Not available  |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                                 |                                                             |
|-------------------------------------------------|-------------------------------------------------------------|
| Flammability                                    | : Not available                                             |
| Explosive limits                                | : Not available                                             |
| Vapour pressure                                 | : Not available                                             |
| Relative vapour density at 20°C                 | : Not available                                             |
| Relative density                                | : Not available                                             |
| Density                                         | : 1.04 – 1.1 g/cm³                                          |
| Solubility                                      | : Material insoluble in water.<br>Water: Insoluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                                             |
| Auto-ignition temperature                       | : Not available                                             |
| Decomposition temperature                       | : Not available                                             |
| Viscosity, kinematic                            | : 70 – 80 Seconds                                           |
| Particle size                                   | : Not applicable                                            |
| Particle size distribution                      | : Not applicable                                            |
| Particle shape                                  | : Not applicable                                            |
| Particle aspect ratio                           | : Not applicable                                            |
| Particle specific surface area                  | : Not applicable                                            |

### ETHYL ACETATE141-78-6

|                           |                                 |
|---------------------------|---------------------------------|
| Boiling point             | 77 °C Source: ICSC              |
| Flash point               | -4 °C Source: ICSC              |
| Auto-ignition temperature | 427 °C Source: ICSC             |
| Vapour pressure           | 93.2 mm Hg at 25°C Source: HSDB |

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                           |                               |
|---------------------------|-------------------------------|
| Boiling point             | 78.5 °C Source: HSDB          |
| Flash point               | 13 °C Source: HSDB            |
| Auto-ignition temperature | 400 °C Source: ICSC           |
| Vapour pressure           | 5.8 kPa at 20 °C Source: ICSC |

### Nafta solvente (petróleo), aromático leve64742-95-6

|                 |                              |
|-----------------|------------------------------|
| Boiling point   | 135 – 210 °C Source: NLM     |
| Flash point     | < 41 °C Source: IUCLID       |
| Vapour pressure | 8 hPa at 20°C Source: IUCLID |

### MIXED XYLENES1330-20-7

|                           |                                |
|---------------------------|--------------------------------|
| Boiling point             | 138 °C Source: ICSC            |
| Flash point               | 30 °C (ASTM D 93)              |
| Auto-ignition temperature | ≥ 528 °C Source: SRC           |
| Vapour pressure           | 8.84 mm Hg at 25°C Source: SRC |

### FATTY ACIDS68647-95-0

|             |                       |
|-------------|-----------------------|
| Flash point | 121.5 °C Source: ECHA |
|-------------|-----------------------|

### SOLVENT BUTYL GLYCOL (N)111-76-2

|               |                       |
|---------------|-----------------------|
| Boiling point | 168.4 °C Source: HSDB |
|---------------|-----------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

### SOLVENT BUTYL GLYCOL (N)111-76-2

|                           |                                 |
|---------------------------|---------------------------------|
| Flash point               | 63 °C Source: ECHA              |
| Auto-ignition temperature | 230 °C Source: ECHA             |
| Vapour pressure           | 0.88 mm Hg at 25°C Source: hSDB |

### SOLVENT ACETATO DE ETILA141-78-6

|                           |                                 |
|---------------------------|---------------------------------|
| Boiling point             | 77 °C Source: ICSC              |
| Flash point               | -4 °C Source: ICSC              |
| Auto-ignition temperature | 427 °C Source: ICSC             |
| Vapour pressure           | 93.2 mm Hg at 25°C Source: HSDB |

### ZINC OXIDE1314-13-2

|                 |                      |
|-----------------|----------------------|
| Vapour pressure | 0 mm Hg Source: HSDB |
|-----------------|----------------------|

### Naphtha (petroleum), refined light solvent64741-84-0

|                           |                            |
|---------------------------|----------------------------|
| Boiling point             | 35 – 165 °C Source: IUCLID |
| Flash point               | < 21 °C Source: IUCLID     |
| Auto-ignition temperature | ≥ 280 – ≤ 465              |

### Steam-cracked petroleum distillates68477-39-4

|                 |                                         |
|-----------------|-----------------------------------------|
| Boiling point   | 145 – 300 °C at 1013 hPa Source: IUCLID |
| Vapour pressure | 2133 Pa Temp.: 20 °C                    |

### Cobalt bis(2-ethylhexanoate)136-52-7

|                 |                               |
|-----------------|-------------------------------|
| Boiling point   | 90 °C 1 atm Source: ECHA      |
| Flash point     | 23 – 55 °C Atm. press.: 1 atm |
| Vapour pressure | < 110 kPa Temp.: 20 °C        |

### ZINC OCTOATE136-53-8

|                 |                                    |
|-----------------|------------------------------------|
| Boiling point   | 200 °C Source: ECHA                |
| Vapour pressure | 0.000000127 mm Hg Source: EPISUITE |

### Hydrated aluminum silicate (KAOLIN)1332-58-7

|                 |                       |
|-----------------|-----------------------|
| Vapour pressure | 0 mm Hg Source: CAMEO |
|-----------------|-----------------------|

### ISOPENTYL ACETATE123-92-2

|                           |                                |
|---------------------------|--------------------------------|
| Boiling point             | 142 °C                         |
| Flash point               | 25 °C Source: ECHA             |
| Auto-ignition temperature | 379 °C Source: ECHA            |
| Vapour pressure           | 4.5 mm Hg at 20°C Source: ECHA |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

### n-butyl acetate123-86-4

|                           |                                 |
|---------------------------|---------------------------------|
| Boiling point             | 126.2 °C Atm. press.: 1013 hPa  |
| Flash point               | 27 °C Atm. press.: 1013 hPa     |
| Auto-ignition temperature | 420 °C Source: ICSC             |
| Vapour pressure           | 11.5 mm Hg at 25°C Source: hSDB |

### 9.2. Data relevant with regard to physical hazard classes

No additional information available

### 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                                          |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.                    |
| Hazardous decomposition products   | : May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.                                                                                             |
| Incompatible materials             | : Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials. |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                                        |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                                               |
| Handling temperature               | : No additional information available                                                                                                                                                              |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Acute toxicity (oral)       | : Not available                             |
| Acute toxicity (dermal)     | : May be harmful in contact with skin.      |
| Acute toxicity (inhalation) | : Inhalation:dust,mist: Harmful if inhaled. |

### SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

|                    |                          |
|--------------------|--------------------------|
| ATE BR (dermal)    | 2688.98 mg/kg bodyweight |
| ATE BR (dust,mist) | 3.292 mg/l/4h            |

### ETHYL ACETATE (141-78-6)

|               |                         |
|---------------|-------------------------|
| LD50 oral rat | 11.3 ml/kg Source: ECHA |
|---------------|-------------------------|

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|                                 |                                     |
|---------------------------------|-------------------------------------|
| LD50 oral rat                   | 7060 mg/kg Source: ECHA             |
| LD50 oral                       | 8300 mg/kg bodyweight Animal: mouse |
| LC50 Inhalation - Rat (Vapours) | 116.9 mg/l Source: ECHA             |

### Nafta solvente (petróleo), aromático leve (64742-95-6)

|                    |                           |
|--------------------|---------------------------|
| LD50 oral rat      | 8400 mg/kg Source: RTECS  |
| LD50 dermal rat    | > 2000 mg/kg Source: ECHA |
| LD50 dermal rabbit | > 2000 mg/kg              |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                                                |                                                                                                                                                        |
|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Nafta solvente (petróleo), aromático leve (64742-95-6)</b>  |                                                                                                                                                        |
| LC50 Inhalation - Rat (Vapours)                                | 5.16 mg/l Source: ECHA                                                                                                                                 |
| <b>MIXED XYLENES (1330-20-7)</b>                               |                                                                                                                                                        |
| LD50 oral rat                                                  | 3523 mg/kg Source: ECHA                                                                                                                                |
| LD50 dermal rabbit                                             | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male                                                                                                |
| LC50 Inhalation - Rat [ppm]                                    | 5922 ppm                                                                                                                                               |
| <b>FATTY ACIDS (68647-95-0)</b>                                |                                                                                                                                                        |
| LD50 oral rat                                                  | > 2000 mg/kg Source: ECHA                                                                                                                              |
| LD50 dermal rabbit                                             | > 5000 mg/kg Source: ECHA                                                                                                                              |
| <b>SOLVENT BUTYL GLYCOL (N) (111-76-2)</b>                     |                                                                                                                                                        |
| LD50 dermal rat                                                | > 2000 mg/kg Source: ECHA                                                                                                                              |
| <b>SOLVENT ACETATO DE ETILA (141-78-6)</b>                     |                                                                                                                                                        |
| LD50 oral rat                                                  | 11.3 ml/kg Source: ECHA                                                                                                                                |
| <b>ZINC OXIDE (1314-13-2)</b>                                  |                                                                                                                                                        |
| LD50 oral rat                                                  | > 5000 mg/kg Source: ECHA                                                                                                                              |
| LD50 dermal rat                                                | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                                             |
| LC50 Inhalation - Rat                                          | > 5700 mg/m³ Source: ECHA                                                                                                                              |
| <b>Naphtha (petroleum), refined light solvent (64741-84-0)</b> |                                                                                                                                                        |
| LD50 oral rat                                                  | > 7000 mg/kg Source: IUCLID                                                                                                                            |
| LD50 dermal rabbit                                             | > 2000 mg/kg Source: IUCLID                                                                                                                            |
| LC50 Inhalation - Rat                                          | ≥ 43767 mg/m³                                                                                                                                          |
| LC50 Inhalation - Rat (Dust/Mist)                              | > 5.04 mg/l Source: IUCLID                                                                                                                             |
| <b>Steam-cracked petroleum distillates (68477-39-4)</b>        |                                                                                                                                                        |
| LD50 oral rat                                                  | > 2000 mg/kg Source: IUCLID                                                                                                                            |
| LD50 dermal rat                                                | > 2000 mg/kg Source: IUCLID                                                                                                                            |
| LD50 dermal rabbit                                             | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)                                                            |
| LC50 Inhalation - Rat                                          | Animal: rat, Guideline: EPA OTS 798.1150 (Acute inhalation toxicity)                                                                                   |
| LC50 Inhalation - Rat (Vapours)                                | 7.5 mg/l Source: IUCLID                                                                                                                                |
| <b>Cobalt bis(2-ethylhexanoate) (136-52-7)</b>                 |                                                                                                                                                        |
| LD50 oral rat                                                  | 3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000 |
| LD50 dermal rat                                                | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                                             |
| LC50 Inhalation - Rat                                          | > 2000 mg/kg                                                                                                                                           |
| <b>ZINC OCTOATE (136-53-8)</b>                                 |                                                                                                                                                        |
| LD50 oral rat                                                  | > 2000 mg/kg Source: ECHA                                                                                                                              |
| LD50 dermal rat                                                | > 2000 mg/kg Source: ECHA                                                                                                                              |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

### ZINC OCTOATE (136-53-8)

|                                   |                         |
|-----------------------------------|-------------------------|
| LC50 Inhalation - Rat (Dust/Mist) | > 5.7 mg/l Source: ECHA |
|-----------------------------------|-------------------------|

### Hydrated aluminum silicate (KAOLIN) (1332-58-7)

|                                   |                           |
|-----------------------------------|---------------------------|
| LD50 oral rat                     | > 5000 mg/kg Source: HSDB |
| LD50 dermal rat                   | > 5000 mg/kg Source: HSDB |
| LC50 Inhalation - Rat (Dust/Mist) | ≥ 5 mg/l                  |

### ISOPENTYL ACETATE (123-92-2)

|                    |                                 |
|--------------------|---------------------------------|
| LD50 dermal rabbit | > 5000 mg/kg Source: ChemIDPLUS |
|--------------------|---------------------------------|

### n-butyl acetate (123-86-4)

|                                 |                            |
|---------------------------------|----------------------------|
| LD50 oral rat                   | 3200 ml/kg Source: ECHA    |
| LD50 dermal rabbit              | > 17600 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Vapours) | 1802 mg/l Source: ECHA     |

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |                        |
|----|------------------------|
| pH | 7 Source: chemicalbook |
|----|------------------------|

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### ZINC OXIDE (1314-13-2)

|    |                   |
|----|-------------------|
| pH | 6.95 Source: HSDB |
|----|-------------------|

### Hydrated aluminum silicate (KAOLIN) (1332-58-7)

|    |                  |
|----|------------------|
| pH | 4.5 Source: hsdh |
|----|------------------|

### ISOPENTYL ACETATE (123-92-2)

|    |                |
|----|----------------|
| pH | Not applicable |
|----|----------------|

### n-butyl acetate (123-86-4)

|    |                                         |
|----|-----------------------------------------|
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
|----|-----------------------------------------|

Serious eye damage/irritation : Causes serious eye irritation.  
pH: Not applicable

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |                        |
|----|------------------------|
| pH | 7 Source: chemicalbook |
|----|------------------------|

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### ZINC OXIDE (1314-13-2)

|    |                   |
|----|-------------------|
| pH | 6.95 Source: HSDB |
|----|-------------------|

### Hydrated aluminum silicate (KAOLIN) (1332-58-7)

|    |                  |
|----|------------------|
| pH | 4.5 Source: hsdh |
|----|------------------|

### ISOPENTYL ACETATE (123-92-2)

|    |                |
|----|----------------|
| pH | Not applicable |
|----|----------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

| n-butyl acetate (123-86-4)                              |                                                                                                                                                                                         |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pH                                                      | 6.2 Temp.: 20 °C Concentration: 5,3 g/L                                                                                                                                                 |
| Respiratory or skin sensitisation                       | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.                                                                                                            |
| Germ cell mutagenicity                                  | : May cause genetic defects.                                                                                                                                                            |
| Carcinogenicity                                         | : May cause cancer.                                                                                                                                                                     |
| Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)        |                                                                                                                                                                                         |
| IARC group                                              | 1 - Carcinogenic to humans                                                                                                                                                              |
| MIXED XYLENES (1330-20-7)                               |                                                                                                                                                                                         |
| IARC group                                              | 3 - Not classifiable                                                                                                                                                                    |
| SOLVENT BUTYL GLYCOL (N) (111-76-2)                     |                                                                                                                                                                                         |
| IARC group                                              | 3 - Not classifiable                                                                                                                                                                    |
| Reproductive toxicity                                   | : Not available                                                                                                                                                                         |
| STOT-single exposure                                    | : May cause respiratory irritation.                                                                                                                                                     |
| ETHYL ACETATE (141-78-6)                                |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause drowsiness or dizziness.                                                                                                                                                      |
| Nafta solvente (petróleo), aromático leve (64742-95-6)  |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause respiratory irritation.                                                                                                                                                       |
| MIXED XYLENES (1330-20-7)                               |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause respiratory irritation.                                                                                                                                                       |
| SOLVENT ACETATO DE ETILA (141-78-6)                     |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause drowsiness or dizziness.                                                                                                                                                      |
| Naphtha (petroleum), refined light solvent (64741-84-0) |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause drowsiness or dizziness.                                                                                                                                                      |
| Steam-cracked petroleum distillates (68477-39-4)        |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause drowsiness or dizziness. May cause respiratory irritation.                                                                                                                    |
| n-butyl acetate (123-86-4)                              |                                                                                                                                                                                         |
| STOT-single exposure                                    | May cause drowsiness or dizziness.                                                                                                                                                      |
| STOT-repeated exposure                                  | : May cause damage to organs through prolonged or repeated exposure.                                                                                                                    |
| Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)        |                                                                                                                                                                                         |
| NOAEL (subchronic, oral, animal/male, 90 days)          | < 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)                                                                |
| NOAEL (subchronic, oral, animal/female, 90 days)        | > 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)                                                              |
| MIXED XYLENES (1330-20-7)                               |                                                                                                                                                                                         |
| LOAEL (oral, rat, 90 days)                              | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure                                  | May cause damage to organs through prolonged or repeated exposure.                                                                                                                      |
| FATTY ACIDS (68647-95-0)                                |                                                                                                                                                                                         |
| NOAEL (subchronic, oral, animal/male, 90 days)          | 12.5 mg/kg bodyweight                                                                                                                                                                   |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

### FATTY ACIDS (68647-95-0)

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--------------------------------------------------------------------|

### ZINC OXIDE (1314-13-2)

|                                     |                                                                                                                         |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| LOAEL (dermal, rat/rabbit, 90 days) | 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)         |
| NOAEL (oral, rat, 90 days)          | 31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| STOT-repeated exposure              | May cause damage to organs through prolonged or repeated exposure.                                                      |

### Steam-cracked petroleum distillates (68477-39-4)

|                                          |                                                                                                      |
|------------------------------------------|------------------------------------------------------------------------------------------------------|
| NOAEC (inhalation, rat, vapour, 90 days) | 2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study) |
|------------------------------------------|------------------------------------------------------------------------------------------------------|

### Cobalt bis(2-ethylhexanoate) (136-52-7)

|                                                  |                                                                                                                     |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| LOAEC (inhalation, rat, dust/mist/fume, 90 days) | 0.31 mg/l air Animal: rat                                                                                           |
| NOAEL (oral, rat, 90 days)                       | 3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| STOT-repeated exposure                           | Causes damage to organs through prolonged or repeated exposure.                                                     |

### n-butyl acetate (123-86-4)

|                            |                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents) |
| NOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents) |

Aspiration hazard : Not classified.

### SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

|                      |               |
|----------------------|---------------|
| Viscosity, kinematic | 70 – 80 mm²/s |
|----------------------|---------------|

### ETHYL ACETATE (141-78-6)

|                      |             |
|----------------------|-------------|
| Viscosity, kinematic | 0.494 mm²/s |
|----------------------|-------------|

### Nafta solvente (petróleo), aromático leve (64742-95-6)

|                      |                                                                       |
|----------------------|-----------------------------------------------------------------------|
| Viscosity, kinematic | < 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)' |
|----------------------|-----------------------------------------------------------------------|

### MIXED XYLENES (1330-20-7)

|                      |                                                                        |
|----------------------|------------------------------------------------------------------------|
| Viscosity, kinematic | ≈ 0.76 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' |
|----------------------|------------------------------------------------------------------------|

### Naphtha (petroleum), refined light solvent (64741-84-0)

|                      |                       |
|----------------------|-----------------------|
| Viscosity, kinematic | ≥ 0.35 – ≤ 0.45 mm²/s |
|----------------------|-----------------------|

### n-butyl acetate (123-86-4)

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| Viscosity, kinematic | 0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' |
|----------------------|----------------------------------------------------------------------|

## 11.2. Most important symptoms and effects, both acute and delayed

|                                   |                                                                                                                                                                                                                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                  | : May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.                                               |
| Symptoms/effects after inhalation | : May cause headache, nausea and irritation of respiratory tract. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation may cause irritation (cough, short breathing, |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                     |                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after skin contact | : difficulty in breathing).<br>: May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). |
| Symptoms/effects after eye contact  | : stinging. Redness. Causes serious eye irritation. redness, itching, tears.                                                             |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract.                                                                                           |
| Chronic symptoms                    | : May cause cancer. May cause heritable genetic damage.                                                                                  |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                                           |
|-----------------------------------------------------------|---------------------------------------------------------------------------|
| Ecology - general                                         | : Toxic to aquatic life with long lasting effects. Toxic to aquatic life. |
| Hazardous to the aquatic environment, short-term (acute)  | : Toxic to aquatic life.                                                  |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects.                        |

#### ETHYL ACETATE141-78-6

|                 |                       |
|-----------------|-----------------------|
| LC50 - Fish [1] | 230 mg/l Source: ECHA |
|-----------------|-----------------------|

#### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                 |                                                                  |
|-----------------|------------------------------------------------------------------|
| LC50 - Fish [1] | > 100 mg/l Source: SIDS 2005                                     |
| ErC50 algae     | 275 mg/l Source: ECHA                                            |
| NOEC (chronic)  | 9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d' |

#### Nafta solvente (petróleo), aromático leve64742-95-6

|                      |                          |
|----------------------|--------------------------|
| LC50 - Fish [1]      | 9.22 mg/l Source: IUCLID |
| EC50 - Crustacea [1] | 6.14 mg/l Source: IUCLID |
| EC50 72h - Algae [1] | 19 mg/l Source: IUCLID   |

#### MIXED XYLENES1330-20-7

|                      |                                                                                                            |
|----------------------|------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]      | 2.6 mg/l Source: ECHA                                                                                      |
| EC50 - Crustacea [1] | 3.4 mg/l Test organisms (species): Ceriodaphnia dubia                                                      |
| ErC50 algae          | 2.2 mg/l                                                                                                   |
| LOEC (chronic)       | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                         |
| NOEC chronic fish    | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |

#### FATTY ACIDS68647-95-0

|                        |                        |
|------------------------|------------------------|
| LC50 - Fish [1]        | 55 mg/l Source: ECHA   |
| EC50 - Crustacea [1]   | 34.5 mg/l Source: ECHA |
| EC50 72h - Algae [1]   | 0.393 mg/l             |
| NOEC chronic crustacea | 0.013 mg/l             |
| NOEC chronic algae     | 0.091 mg/l             |

#### SOLVENT BUTYL GLYCOL (N)111-76-2

|                      |                        |
|----------------------|------------------------|
| LC50 - Fish [1]      | 1474 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 1800 mg/l Source: ECHA |
| EC50 72h - Algae [1] | 911 mg/l Source: ECHA  |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

| SOLVENT ACETATO DE ETILA141-78-6                     |                                                                                                                                          |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]                                      | 230 mg/l Source: ECHA                                                                                                                    |
| Naphtha (petroleum), refined light solvent64741-84-0 |                                                                                                                                          |
| LC50 - Fish [1]                                      | 4.4 mg/l                                                                                                                                 |
| EC50 - Crustacea [1]                                 | 9.74 mg/l Source: IUCLID                                                                                                                 |
| EC50 72h - Algae [1]                                 | 6.5 mg/l Source: IUCLID                                                                                                                  |
| Steam-cracked petroleum distillates68477-39-4        |                                                                                                                                          |
| LC50 - Fish [1]                                      | 13.5 mg/l Source: IUCLID                                                                                                                 |
| EC50 - Crustacea [1]                                 | 1.2 mg/l Test organisms (species): Daphnia magna                                                                                         |
| EC50 72h - Algae [1]                                 | 2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)   |
| EC50 72h - Algae [2]                                 | 1.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| Cobalt bis(2-ethylhexanoate)136-52-7                 |                                                                                                                                          |
| LC50 - Fish [1]                                      | 1.512 mg/l Source: ECHA                                                                                                                  |
| EC50 - Crustacea [1]                                 | 5.89 mg/l Test organisms (species): Daphnia magna                                                                                        |
| EC50 72h - Algae [1]                                 | 0.654 mg/l Source: ECHA registration data                                                                                                |
| ZINC OCTOATE136-53-8                                 |                                                                                                                                          |
| LC50 - Fish [1]                                      | 100 mg/l Source: ECHA                                                                                                                    |
| EC50 - Crustacea [1]                                 | 0.131 – 1.06 mg/l Source: ECHA                                                                                                           |
| ISOPENTYL ACETATE123-92-2                            |                                                                                                                                          |
| LC50 - Fish [1]                                      | 36 mg/l Source: ECHA                                                                                                                     |
| EC50 - Crustacea [1]                                 | 42 mg/l Source: ECHA                                                                                                                     |
| n-butyl acetate123-86-4                              |                                                                                                                                          |
| LC50 - Fish [1]                                      | 18 mg/l Test organisms (species): Pimephales promelas                                                                                    |
| EC50 - Crustacea [1]                                 | 44 mg/l Test organisms (species): Daphnia sp.                                                                                            |
| EC50 72h - Algae [1]                                 | 397 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2]                                 | 246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| LOEC (chronic)                                       | 47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |
| NOEC (chronic)                                       | 23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |

## 12.2. Persistence and degradability

| SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT |                        |
|-----------------------------------------------|------------------------|
| Persistence and degradability                 | Not rapidly degradable |
| ETHYL ACETATE141-78-6                         |                        |
| Persistence and degradability                 | Not rapidly degradable |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                                             |                        |
|-------------------------------------------------------------|------------------------|
| <b>Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5</b>        |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>Nafta solvente (petróleo), aromático leve64742-95-6</b>  |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>MIXED XYLENES1330-20-7</b>                               |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>FATTY ACIDS68647-95-0</b>                                |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>SOLVENT BUTYL GLYCOL (N)111-76-2</b>                     |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>SOLVENT ACETATO DE ETILA141-78-6</b>                     |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>ZINC OXIDE1314-13-2</b>                                  |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>Naphtha (petroleum), refined light solvent64741-84-0</b> |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>Steam-cracked petroleum distillates68477-39-4</b>        |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>Cobalt bis(2-ethylhexanoate)136-52-7</b>                 |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>ZINC OCTOATE136-53-8</b>                                 |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>Hydrated aluminum silicate (KAOLIN)1332-58-7</b>         |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>ISOPENTYL ACETATE123-92-2</b>                            |                        |
| Persistence and degradability                               | Not rapidly degradable |
| <b>n-butyl acetate123-86-4</b>                              |                        |
| Persistence and degradability                               | Not rapidly degradable |

### 12.3. Bioaccumulative potential

|                                                            |                        |
|------------------------------------------------------------|------------------------|
| <b>ETHYL ACETATE141-78-6</b>                               |                        |
| Partition coefficient n-octanol/water (Log Pow)            | 0.73 Source: ICSC      |
| <b>Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5</b>       |                        |
| Partition coefficient n-octanol/water (Log Pow)            | -0.32 Source: ICSC     |
| <b>Nafta solvente (petróleo), aromático leve64742-95-6</b> |                        |
| Partition coefficient n-octanol/water (Log Pow)            | 2.1 – 6 Source: IUCLID |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                                             |                        |
|-------------------------------------------------------------|------------------------|
| <b>MIXED XYLENES1330-20-7</b>                               |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 3.15 Source: HSDB      |
| <b>SOLVENT BUTYL GLYCOL (N)111-76-2</b>                     |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 0.81 Source: ECHA      |
| <b>SOLVENT ACETATO DE ETILA141-78-6</b>                     |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 0.73 Source: ICSC      |
| <b>Naphtha (petroleum), refined light solvent64741-84-0</b> |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 2.1 – 6 Source: IUCLID |
| <b>Cobalt bis(2-ethylhexanoate)136-52-7</b>                 |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 2.96 Source: ECHA      |
| <b>ZINC OCTOATE136-53-8</b>                                 |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 5.7 Source: ECHA       |
| <b>ISOPENTYL ACETATE123-92-2</b>                            |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 2.13 Source: ICSC      |
| <b>n-butyl acetate123-86-4</b>                              |                        |
| Partition coefficient n-octanol/water (Log Pow)             | 1.78 Source: HSDB      |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

|                                            |                                                                                      |
|--------------------------------------------|--------------------------------------------------------------------------------------|
| Waste treatment methods                    | : Must follow special treatment according to local regulation.                       |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.                           |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations.                           |
| Additional information                     | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                  | IMDG                                                    | IATA                  |
|---------------------------------------|---------------------------------------------------------|-----------------------|
| <b>UN number</b>                      |                                                         |                       |
| 1263                                  | 1263                                                    | 1263                  |
| <b>UN Proper Shipping Name</b>        |                                                         |                       |
| TINTA                                 | PAINT                                                   | Paint                 |
| <b>Transport document description</b> |                                                         |                       |
| Not applicable                        | UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY | UN 1263 Paint, 3, III |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

|                                                                                   |                                                                                                                                                                        |                                                                                     |  |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--|
|                                                                                   | HAZARDOUS (31°C c.c.)                                                                                                                                                  |                                                                                     |  |
| Transport hazard class(es)                                                        |                                                                                                                                                                        |                                                                                     |  |
| 3                                                                                 | 3                                                                                                                                                                      | 3                                                                                   |  |
| Danger labels                                                                     |                                                                                                                                                                        |                                                                                     |  |
| 3                                                                                 | 3                                                                                                                                                                      | 3                                                                                   |  |
|  | <br> |  |  |
| Subsidiary risk                                                                   |                                                                                                                                                                        |                                                                                     |  |
| Not applicable                                                                    | Not applicable                                                                                                                                                         | Not applicable                                                                      |  |
| Risk Number                                                                       |                                                                                                                                                                        |                                                                                     |  |
| 30                                                                                | Not applicable                                                                                                                                                         | Not applicable                                                                      |  |
| Packing group                                                                     |                                                                                                                                                                        |                                                                                     |  |
| III                                                                               | III                                                                                                                                                                    | III                                                                                 |  |
| Special provisions                                                                |                                                                                                                                                                        |                                                                                     |  |
| 163,223,367                                                                       | 163,223,367,955                                                                                                                                                        | A3,A72,A192                                                                         |  |
| Dangerous for the environment                                                     |                                                                                                                                                                        |                                                                                     |  |
| Yes                                                                               | Yes                                                                                                                                                                    | Yes                                                                                 |  |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.  
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# SYNTHETIC ENAMEL NITRO SUB GRAY MONOCOMPONENT

13986684

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/29/2026

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

---

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)