

W-CAR SMALL REPAIR PUTTY

PRODUCT INFORMATION: Synthetic putty for correction of small imperfections. High solids, easy application, fast drying and excellent sandability.

RECOMMENDED USE: Recommended for repairing scratches, small imperfection on the surface and imperfections on the putty or primer.

COLOR: Greenish Grey.

	Hardener	-	
	Mixing Ratio (Volume)	-	
	Dilution	Ready for use	
	Application Viscosity (25°C)	-	
	Mixture's Operating Life - Pot Life (25°C)	-	
	Equipment	Celluloid / Spatula	
	Application	-	
	Drying Time	Air: Touch: 20 - 30 minutes.	Oven: -
	Sanding	20 – 30 minutes Use sandpaper 320 or 400	
	Additivation	-	

CÓPY FOR INFORMATION

WEG TINTAS LTDA - CNPJ 12.006.058/0001-21

Matriz: Rodovia BR 280, Km 50 - Fone: (+55) (47) 3276-4000 - Fax: (+55) (47) 3276-5500 - CEP 89270-000 - Guaramirim – SC

PAUMAR S.A. INDÚSTRIA E COMÉRCIO – CNPJ 60.621.141/0001-53

Rua Dr. Ulysses Guimarães, 918 - Fone: +55 (11) 4547-6100 – CEP 09372-050 - Mauá – SP

EMERGÊNCIA: (+55) 0800 720 8000 - E-mail: tintas@weg.net - www.weg.net

Página 1 de 2

Date:Nov/16

Review: 02

This Data Sheet cancels and replaces older versions and can be updated without prior notice

TECHNICAL PROCEDURES:

Surface Preparation

The surface to be coated must be dry and free of impurities as rust, dust, greases oils and any other contaminant that may compromise product performance.

Prepare the surface with W-CAR DEGREASER and dry it with a clean cloth. Sand the area to be recoated in order to remove peeled painting and rust.

Application Performance

Drying time may vary according to temperature and thickness of the applied product.

Do not apply the product under adverse conditions as well as relative air humidity above 85%, because it might occur appearance and color changings. Do not apply the product on condensed surfaces.

SAFETY PRECAUTIONS:

Before handling this product is mandatory a careful reading of all information contained in the Material Safety and Data Sheet (MSDS) of the product.

Further information can be obtained by consulting the Technical Department by phone or e-mail specified in the end of this Data Sheet.

CÓPY FOR INFORMATION

WEG TINTAS LTDA - CNPJ 12.006.058/0001-21

Matriz: Rodovia BR 280, Km 50 - Fone: (+55) (47) 3276-4000 - Fax: (+55) (47) 3276-5500 - CEP 89270-000 - Guaramirim – SC

PAUMAR S.A. INDÚSTRIA E COMÉRCIO – CNPJ 60.621.141/0001-53

Rua Dr. Ulysses Guimarães, 918 - Fone: +55 (11) 4547-6100 – CEP 09372-050 - Mauá – SP

EMERGÊNCIA: (+55) 0800 720 8000 - E-mail: tintas@weg.net - www.weg.net

Página 2 de 2