

# ETHYL SILICATE ZINC HS COMPONENT B

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 11/28/2023 Revision date: 4/24/2025 Version: 4.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : ETHYL SILICATE ZINC HS COMPONENT B  
Product code : 15440749  
Type of product : Catalyst  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Uses in coatings - Curing agent for component A.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |
| Germany                              |             |                                  | 0800-181-7059           |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| Russia         |           |                  | 8(800)100-63-46  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Pyrophoric Solids, Category 1

Substances and Mixtures which, in contact with water, emit flammable gases, Category 1

Hazardous to the aquatic environment - Acute Hazard, Category 1

Hazardous to the aquatic environment - Chronic Hazard, Category 1

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H250 - Catches fire spontaneously if exposed to air  
H260 - In contact with water releases flammable gases which may ignite spontaneously  
H410 - Very toxic to aquatic life with long lasting effects  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P222 - Do not allow contact with air.  
P223 - Do not allow contact with water.  
P231+P232 - Handle and store contents under inert gas. Protect from moisture.  
P233 - Keep container tightly closed.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P302+P335+P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water or wrap in wet bandages.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P402+P404 - Store in a dry place. Store in a closed container.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name                  | GHS Product identifier | %   | Classification according to GHS BR (ABNT NBR 14725: 2023)                                     |
|-----------------------|------------------------|-----|-----------------------------------------------------------------------------------------------|
| ZINC DUST, STABILIZED | CAS-No.: 7440-66-6     | 100 | Pyr. Sol. 1, H250<br>Water-react. 1, H260<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |

### SECTION 4: First-aid measures

#### 4.1. Description of necessary first-aid measures

|                                     |                                                                                                                                                                   |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general          | : If you feel unwell, seek medical advice.                                                                                                                        |
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. |
| First-aid measures after ingestion  | : Do NOT induce vomiting.                                                                                                                                         |

#### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after inhalation   | : Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing.                                                                                                                      |
| Symptoms/effects after eye contact  | : Risk of serious damage to eyes.                                                                                                                                                                                                              |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract.                                                                                                                                                                                                 |

#### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

|                                |                                                                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media   | : earth, sand, dry chemical powder or foam. Dry chemical, soda ash, lime or sand. Dry chemical, CO2, dry sand, or alcohol-resistant foam. |
| Unsuitable extinguishing media | : Do not use water. Water. Carbon dioxide (CO2). Foam.                                                                                    |

#### 5.2. Specific hazards arising from the chemical

|                            |                                                                                                                                                                                                                                                                                                     |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard                | : In case of fire and/or explosion do not breathe fumes. Catches fire spontaneously if exposed to air. In contact with water releases flammable gases which may ignite spontaneously. Attacks many metals forming flammable/explosive gas (HYDROGEN!). In case of fire, use sand - Never use water. |
| Explosion hazard           | : Heating may cause an explosion.                                                                                                                                                                                                                                                                   |
| Reactivity in case of fire | : Exothermic reaction with water. Spontaneously flammable (pyrophoric) solid.                                                                                                                                                                                                                       |

#### 5.3. Special protective actions for fire-fighters

|                             |                                                                                         |
|-----------------------------|-----------------------------------------------------------------------------------------|
| Precautionary measures fire | : Do not allow contact with air. Do not allow contact with water.                       |
| Firefighting instructions   | : Fight fire from safe distance and protected location. In case of major fire and large |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

Protection during firefighting

- quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
- : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

- : Do not allow contact with air. Eliminate every possible source of ignition. Do not allow contact with water. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

#### 6.1.1. For non-emergency personnel

Protective equipment

- : Wear recommended personal protective equipment.

Emergency procedures

- : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

#### 6.1.2. For emergency responders

Protective equipment

- : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Gloves. Equip cleanup crew with proper protection.

Emergency procedures

- : Cover spill with non combustible material, e.g.: sand/earth. Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Do not allow contact with water. Very toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Very toxic to aquatic life.

### 6.3. Methods and materials for containment and cleaning up

For containment

- : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Stop leak without risks if possible.

Methods for cleaning up

- : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean up immediately by sweeping or vacuum. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed

- : Catches fire spontaneously if exposed to air. DANGER : May be explosive if shocked, heated under confinement or mixed with water.

Precautions for safe handling

- : Do not allow contact with air. Handle and open container with care. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear fire/flame resistant/retardant clothing. Do not allow contact with water. Handle and open container with care. Handle under inert gas. Protect from moisture. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures

- : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

- : Store in a well-ventilated place. Keep container tightly closed. Store in tightly closed, leak-proof containers.

Storage conditions

- : Keep only in original container. Keep cool. Protect from sunlight. Store away from other materials. Store in a dry place. Store in a closed container. Store in a well-ventilated place.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

Packaging materials : Keep cool.  
: Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves

#### Eye protection:

Wear security glasses which protect from splashes

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

No respiratory protection needed under normal use conditions

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Solid  
Appearance : Liquid.  
Colour : Colourless  
Odour : characteristic  
Odour threshold : Not available  
pH : Not applicable  
Melting point : Not available  
Freezing point : 419 °C  
Boiling point : 907 °C  
Flash point : 30 °C  
Relative evaporation rate (butylacetate=1) : Not available  
Flammability : Not available

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

|                                                 |                                                             |
|-------------------------------------------------|-------------------------------------------------------------|
| Explosive limits                                | : Not available                                             |
| Vapour pressure                                 | : 1 mm Hg 487°C                                             |
| Relative vapour density at 20°C                 | : Not applicable                                            |
| Relative density                                | : Not available                                             |
| Density                                         | : 6.9 – 7.11 g/cm³                                          |
| Solubility                                      | : Material insoluble in water.<br>Water: Insoluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                                             |
| Auto-ignition temperature                       | : 540 °C resting powder                                     |
| Decomposition temperature                       | : Not available                                             |
| Viscosity, kinematic                            | : Not applicable                                            |
| Viscosity, dynamic                              | : Not applicable                                            |
| Particle size                                   | : Not available                                             |
| Particle size distribution                      | : Not available                                             |
| Particle shape                                  | : Not available                                             |
| Particle aspect ratio                           | : Not available                                             |
| Particle specific surface area                  | : Not available                                             |

### ZINC DUST, STABILIZED 7440-66-6

|                           |                          |
|---------------------------|--------------------------|
| Boiling point             | 907 °C Source: ECHA      |
| Auto-ignition temperature | 460 °C Source: ICSC      |
| Vapour pressure           | 0 Pa at 400 Source: ECHA |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : May ignite spontaneously in contact with air. Spontaneously flammable in presence of damp air.                               |
| Conditions to avoid                | : Avoid shock and friction. Do not allow contact with air. Do not allow water (or moist air) contact with this material.       |
| Hazardous decomposition products   | : May liberate toxic gases. Attacks many metals forming flammable/explosive gas (HYDROGEN!).                                   |
| Incompatible materials             | : Combustible materials. Incompatible with water, humid air. Aqueous solution.                                                 |
| Possibility of hazardous reactions | : Catches fire spontaneously if exposed to air. In contact with water releases flammable gases which may ignite spontaneously. |
| Reactivity                         | : Could react violently or explosively on contact with water.                                                                  |
| Handling temperature               | : No additional information available                                                                                          |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                 |
|-----------------------------|-----------------|
| Acute toxicity (oral)       | : Not available |
| Acute toxicity (dermal)     | : Not available |
| Acute toxicity (inhalation) | : Not available |

### ZINC DUST, STABILIZED (7440-66-6)

|               |                                                                                          |
|---------------|------------------------------------------------------------------------------------------|
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
|---------------|------------------------------------------------------------------------------------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### ZINC DUST, STABILIZED (7440-66-6)

|                       |                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------|
| LC50 Inhalation - Rat | > 5.41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
|-----------------------|----------------------------------------------------------------------------------------|

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Skin corrosion/irritation         | : Not available<br>pH: Not applicable |
| Serious eye damage/irritation     | : Not available<br>pH: Not applicable |
| Respiratory or skin sensitisation | : Not available                       |
| Germ cell mutagenicity            | : Not available                       |
| Carcinogenicity                   | : Not available                       |
| Reproductive toxicity             | : Not available                       |
| STOT-single exposure              | : Not available                       |
| STOT-repeated exposure            | : Not available                       |

### ZINC DUST, STABILIZED (7440-66-6)

|                            |                                                                                                                         |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------|
| NOAEL (oral, rat, 90 days) | 31.25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------|

|                   |                 |
|-------------------|-----------------|
| Aspiration hazard | : Not available |
|-------------------|-----------------|

### ETHYL SILICATE ZINC HS COMPONENT B

|                      |                |
|----------------------|----------------|
| Viscosity, kinematic | Not applicable |
|----------------------|----------------|

### ZINC DUST, STABILIZED (7440-66-6)

|                      |                |
|----------------------|----------------|
| Viscosity, kinematic | > 70.028 mm²/s |
|----------------------|----------------|

## 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                                                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after inhalation   | : Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing.                                                                                                                      |
| Symptoms/effects after eye contact  | : Risk of serious damage to eyes.                                                                                                                                                                                                              |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract.                                                                                                                                                                                                 |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                         |
|-----------------------------------------------------------|---------------------------------------------------------|
| Hazardous to the aquatic environment, short-term (acute)  | : Very toxic to aquatic life.                           |
| Hazardous to the aquatic environment, long-term (chronic) | : Very toxic to aquatic life with long lasting effects. |

### ZINC DUST, STABILIZED 7440-66-6

|                      |                   |
|----------------------|-------------------|
| LC50 - Fish [1]      | 0.182 – 2.01 mg/l |
| EC50 - Crustacea [1] | 0.065 – 35 mg/l   |
| ErC50 algae          | 0.106 – 2.05 mg/l |

### 12.2. Persistence and degradability

### ETHYL SILICATE ZINC HS COMPONENT B

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### ZINC DUST, STABILIZED7440-66-6

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 12.3. Bioaccumulative potential

### ZINC DUST, STABILIZED7440-66-6

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | -0.47 Source: NLM |
|-------------------------------------------------|-------------------|

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

|                                            |                                                                                                                         |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Regional waste regulation                  | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.                                      |
| Waste treatment methods                    | : Must follow special treatment according to local regulation.                                                          |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.                                                              |
| Product/Packaging disposal recommendations | : Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations. |
| Additional information                     | : Do not re-use empty containers.                                                                                       |

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                                                                | IMDG                                                                                       | IATA                                                                                  |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>UN number</b>                                                                    |                                                                                            |                                                                                       |
| 1263                                                                                | 1263                                                                                       | 1263                                                                                  |
| <b>UN Proper Shipping Name</b>                                                      |                                                                                            |                                                                                       |
| MATERIAL RELACIONADO COM TINTAS                                                     | PAINT RELATED MATERIAL                                                                     | Paint related material                                                                |
| <b>Transport document description</b>                                               |                                                                                            |                                                                                       |
| Not applicable                                                                      | UN 1263 PAINT RELATED MATERIAL, 4.3 (4.2), III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS | UN 1263 Paint related material, 4.3 (4.2), III, ENVIRONMENTALLY HAZARDOUS             |
| <b>Transport hazard class(es)</b>                                                   |                                                                                            |                                                                                       |
| 3                                                                                   | 3                                                                                          | 3                                                                                     |
| <b>Danger labels</b>                                                                |                                                                                            |                                                                                       |
| 3                                                                                   | 3                                                                                          | 3                                                                                     |
|  |         |  |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

| Subsidiary risk               |                 |                |
|-------------------------------|-----------------|----------------|
| 4.2                           | 4.2             | 4.2            |
| Risk Number                   |                 |                |
| 30                            | Not applicable  | Not applicable |
| Packing group                 |                 |                |
| III                           | III             | III            |
| Special provisions            |                 |                |
| 163,223,367                   | 163,223,367,955 | A3,A72,A192    |
| Dangerous for the environment |                 |                |
| Yes                           | Yes             | Yes            |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# ETHYL SILICATE ZINC HS COMPONENT B

15440749

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

TRGS - Technical Rules for Hazardous Substances

TLM - Median Tolerance Limit

IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

---

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)