

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 3/11/2024 Revision date: 4/23/2025 Version: 2.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-LACK ACA 11 3 R T GRAY MONOCOMPONENT  
Product code : 10589327  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for industrial sector

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |
| Germany                              |             |                                  | 0800-181-7059           |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| Russia         |           |                  | 8(800)100-63-46  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Acute toxicity (dermal), Category 5  
Acute toxicity (inhalation:dust,mist) Category 4  
Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 2  
Reproductive toxicity, Category 1B  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Repeated exposure, Category 2  
Hazardous to the aquatic environment - Acute Hazard, Category 2  
Hazardous to the aquatic environment - Chronic Hazard, Category 2

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H313 - May be harmful in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H360 - May damage fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                            | GHS Product identifier | %       | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                                               |
|---------------------------------|------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MIXED XYLENES                   | CAS-No.: 1330-20-7     | 20 – 40 | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| 2-methoxy-1-methylethyl acetate | CAS-No.: 108-65-6      | 5 – 10  | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313                                                                                                                                                                                                       |
| Aliphatic solvent               | CAS-No.: 64742-47-8    | 1 – 5   | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Acute Tox. 3 (Inhalation:vapour), H331<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411                                                                                    |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

| Name                                 | GHS Product identifier | %          | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                      |
|--------------------------------------|------------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SOLVENT BUTANOL                      | CAS-No.: 71-36-3       | 1 – 5      | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H336<br>STOT SE 3, H335                                                               |
| N-METHYLPYRROLIDONE SOLVENT (N)      | CAS-No.: 872-50-4      | 0.5 – 1    | Flam. Liq. 4, H227<br>Acute Tox. 5 (Oral), H303<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Repr. 1B, H360<br>STOT SE 3, H335                                                             |
| 2-ethylhexanoic acid, zirconium salt | CAS-No.: 22464-99-9    | 0.25 – 0.5 | Acute Tox. 5 (Dermal), H313<br>Repr. 2, H361<br>Aquatic Acute 1, H400                                                                                                                          |
| ZINC OCTOATE                         | CAS-No.: 136-53-8      | 0.1 – 0.25 | Eye Irrit. 2, H319<br>Repr. 2, H361<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412                                                                                                        |
| Cobalt bis(2-ethylhexanoate)         | CAS-No.: 136-52-7      | 0.1 – 0.25 | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 1B, H360<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412 |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.                                                                                                                                                    |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Give oxygen or artificial respiration if necessary.                                               |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact  | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                                                                                                             |
| First-aid measures after ingestion    | : Do NOT induce vomiting. Rinse mouth out with water.                                                                                                                                                       |

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                         |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled.<br>May cause severe burns. May cause respiratory irritation.                   |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).                                                               |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                                                          |
| Symptoms/effects after ingestion    | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                  |
| Chronic symptoms                    | : May damage fertility. May damage the unborn child.                                                                                                                    |

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical, CO<sub>2</sub>, or water spray or regular foam.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.  
Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

### 5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.  
Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.  
Other information : On exposure to high temperature, may decompose, releasing toxic gases.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

#### 6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Equip cleanup crew with proper protection.  
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### 6.3. Methods and materials for containment and cleaning up

- For containment : Prevent dispersion by moistening spill with water or foam. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Clear up rapidly by scoop or vacuum. Absorb spillage to prevent material damage. Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.
- Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- Incompatible materials : combustible materials.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| MIXED XYLENES 1330-20-7                    |                                                                                                                                                                                                             |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USA - ACGIH - Occupational Exposure Limits |                                                                                                                                                                                                             |
| Local name                                 | Xylene, mixed isomers (Dimethylbenzene)                                                                                                                                                                     |
| ACGIH® TLV® TWA                            | 20 ppm                                                                                                                                                                                                      |
| Remark (ACGIH)                             | TLV® Basis: URT & eye irr; hematologic eff; ototoxycity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI |
| Regulatory reference                       | ACGIH 2024                                                                                                                                                                                                  |
| USA - OSHA - Occupational Exposure Limits  |                                                                                                                                                                                                             |
| Local name                                 | Xylenes (o-, m-, p-isomers)                                                                                                                                                                                 |
| OSHA PEL TWA                               | 435 mg/m³                                                                                                                                                                                                   |
|                                            | 100 ppm                                                                                                                                                                                                     |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

|                                            |                                                                                                    |
|--------------------------------------------|----------------------------------------------------------------------------------------------------|
| MIXED XYLENES 1330-20-7                    |                                                                                                    |
| Regulatory reference (US-OSHA)             | OSHA Annotated Table Z-1                                                                           |
| SOLVENT BUTANOL 71-36-3                    |                                                                                                    |
| USA - ACGIH - Occupational Exposure Limits |                                                                                                    |
| Local name                                 | n-Butanol                                                                                          |
| ACGIH® TLV® TWA                            | 20 ppm                                                                                             |
| Remark (ACGIH)                             | TLV® Basis: Eye & URT irr                                                                          |
| Regulatory reference                       | ACGIH 2024                                                                                         |
| USA - OSHA - Occupational Exposure Limits  |                                                                                                    |
| Local name                                 | n-Butyl alcohol                                                                                    |
| OSHA PEL TWA                               | 300 mg/m³                                                                                          |
|                                            | 100 ppm                                                                                            |
| Regulatory reference (US-OSHA)             | OSHA Annotated Table Z-1                                                                           |
| N-METHYLPYRROLIDONE SOLVENT (N) 872-50-4   |                                                                                                    |
| USA - ACGIH - Biological Exposure Indices  |                                                                                                    |
| Local name                                 | N-Methyl-2-pyrrolidone                                                                             |
| BEI                                        | 100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: End of shift |
| Regulatory reference                       | ACGIH 2024                                                                                         |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

|                                                                                                       |
|-------------------------------------------------------------------------------------------------------|
| Hand protection:                                                                                      |
| Protective gloves made of PVC                                                                         |
| Eye protection:                                                                                       |
| Wear closed safety glasses                                                                            |
| Skin and body protection:                                                                             |
| Wear suitable protective clothing                                                                     |
| Respiratory protection:                                                                               |
| Where exposure through inhalation may occur from use, respiratory protection equipment is recommended |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México  
E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Physical state                                  | : Liquid                       |
| Appearance                                      | : Liquid.                      |
| Colour                                          | : Grey                         |
| Odour                                           | : characteristic               |
| Odour threshold                                 | : Not available                |
| pH                                              | : Not applicable               |
| Melting point                                   | : Not available                |
| Freezing point                                  | : Not available                |
| Boiling point                                   | : Not available                |
| Flash point                                     | : 31 °C                        |
| Relative evaporation rate (butylacetate=1)      | : Not available                |
| Flammability                                    | : Not available                |
| Explosive limits                                | : Not available                |
| Vapour pressure                                 | : Not available                |
| Relative vapour density at 20°C                 | : Not available                |
| Relative density                                | : Not available                |
| Density                                         | : 0.9 – 1.201 g/cm³            |
| Solubility                                      | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                |
| Auto-ignition temperature                       | : Not available                |
| Decomposition temperature                       | : Not available                |
| Viscosity, kinematic                            | : 70 – 80 CF4                  |
| Particle size                                   | : Not applicable               |
| Particle size distribution                      | : Not applicable               |
| Particle shape                                  | : Not applicable               |
| Particle aspect ratio                           | : Not applicable               |
| Particle specific surface area                  | : Not applicable               |

### 2-methoxy-1-methylethyl acetate108-65-6

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Boiling point             | 145.8 °C Atm. press.: 760 mm Hg Decomposition: 'no'                |
| Flash point               | 45.5 °C Atm. press.: 101,3 kPa                                     |
| Auto-ignition temperature | 315 °C Source: International Uniform Chemical Information Database |
| Vapour pressure           | 3.75 mm Hg Source: National Institute of Technology and Evaluation |

### MIXED XYLENES1330-20-7

|                           |                   |
|---------------------------|-------------------|
| Boiling point             | 139.6 °C          |
| Flash point               | 30 °C (ASTM D 93) |
| Auto-ignition temperature | 488 °C            |
| Vapour pressure           | 4.8 kPa 55°C      |

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### SOLVENT BUTANOL71-36-3

|             |       |
|-------------|-------|
| Flash point | 36 °C |
|-------------|-------|

### Aliphatic solvent64742-47-8

|                           |                                       |
|---------------------------|---------------------------------------|
| Boiling point             | 146 – 299 °C Atm. press.: 101,325 kPa |
| Flash point               | 29 – 70 °C Atm. press.: 101,325 kPa   |
| Auto-ignition temperature | 236 °C Source: ICSC                   |
| Vapour pressure           | 1 – 3.7 kPa Temp.: 37,8 °C            |

### Cobalt bis(2-ethylhexanoate)136-52-7

|                 |                               |
|-----------------|-------------------------------|
| Flash point     | 23 – 55 °C Atm. press.: 1 atm |
| Vapour pressure | < 110 kPa Temp.: 20 °C        |

### N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

|                           |                                     |
|---------------------------|-------------------------------------|
| Boiling point             | 204.3 °C at 1015.8 hPa Source: ECHA |
| Flash point               | 91 °C Source: ECHA                  |
| Auto-ignition temperature | 245 °C Source: ECHA                 |
| Vapour pressure           | 0.32 hPa at 20°C Source: ECHA       |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                       |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products   | : May liberate toxic gases.                                                                                                                                                     |
| Incompatible materials             | : Combustible materials.                                                                                                                                                        |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                     |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                            |
| Handling temperature               | : No additional information available                                                                                                                                           |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Acute toxicity (oral)       | : Not available                             |
| Acute toxicity (dermal)     | : May be harmful in contact with skin.      |
| Acute toxicity (inhalation) | : Inhalation:dust,mist: Harmful if inhaled. |

### W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

|                    |                           |
|--------------------|---------------------------|
| ATE BR (dermal)    | 2513.152 mg/kg bodyweight |
| ATE BR (dust,mist) | 3.824 mg/l/4h             |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### 2-methoxy-1-methylethyl acetate (108-65-6)

|                    |                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------|
| LD50 oral rat      | 8532 mg/kg Source: International Uniform Chemical Information Database                                       |
| LD50 dermal rat    | > 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LD50 dermal rabbit | > 5000 mg/kg Source: International Uniform Chemical Information Database                                     |

### MIXED XYLENES (1330-20-7)

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
|--------------------|---------------------------------------------------------|

### Aliphatic solvent (64742-47-8)

|                                   |                                                                                                                                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat                     | > 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LD50 dermal rabbit                | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)              |
| LC50 Inhalation - Rat             | > 5.28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -                                                           |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.2 mg/l Source: IUCLID                                                                                                                                       |

### Cobalt bis(2-ethylhexanoate) (136-52-7)

|                 |                                                                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat   | 3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000 |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                                             |

### 2-ethylhexanoic acid, zirconium salt (22464-99-9)

|                 |                                                                                                                                                                                                                         |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat   | > 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method) |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                                                                                                              |

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|                                   |                                                                                       |
|-----------------------------------|---------------------------------------------------------------------------------------|
| LD50 oral rat                     | 4150 mg/kg Source: ECHA                                                               |
| LD50 dermal rat                   | > 5000 mg/kg Source: ECHA                                                             |
| LC50 Inhalation - Rat             | > 5.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.1 mg/l Source: ECHA                                                               |

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|    |          |
|----|----------|
| pH | 8.5 – 10 |
|----|----------|

Serious eye damage/irritation : Causes serious eye irritation.  
pH: Not applicable

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|    |          |
|----|----------|
| pH | 8.5 – 10 |
|----|----------|

|                                   |                 |
|-----------------------------------|-----------------|
| Respiratory or skin sensitisation | : Not available |
| Germ cell mutagenicity            | : Not available |
| Carcinogenicity                   | : Not available |

### MIXED XYLENES (1330-20-7)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|                                               |                                                                                                                                                                                                                    |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (chronic, oral, animal/male, 2 years)   | ≈ 89 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)    |
| NOAEL (chronic, oral, animal/female, 2 years) | ≈ 221 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity) |

### Aliphatic solvent (64742-47-8)

|                           |                                                                                                                                                           |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F0/P) | ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)] |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|                             |                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (animal/female, F0/P) | 500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |
| NOAEL (animal/male, F0/P)   | ≥ 500 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |
| NOAEL (animal/female, F0/P) | 350 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |

|                       |                                             |
|-----------------------|---------------------------------------------|
| Reproductive toxicity | : May damage fertility or the unborn child. |
| STOT-single exposure  | : May cause respiratory irritation.         |

### MIXED XYLENES (1330-20-7)

|                      |                                   |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

### SOLVENT BUTANOL (71-36-3)

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
|----------------------|----------------------------------------------------------------------|

### N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

|                      |                                   |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

|                        |                                                                      |
|------------------------|----------------------------------------------------------------------|
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
|------------------------|----------------------------------------------------------------------|

### 2-methoxy-1-methylethyl acetate (108-65-6)

|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|

### MIXED XYLENES (1330-20-7)

|                            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure     | May cause damage to organs through prolonged or repeated exposure.                                                                                                                      |

### Aliphatic solvent (64742-47-8)

|                            |                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------|
| NOAEL (oral, rat, 90 days) | 750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 |
|----------------------------|-------------------------------------------------------------------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

| Aliphatic solvent (64742-47-8)                    |                                                                                                                                        |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
|                                                   | (Repeated Dose 90-Day Oral Toxicity Study in Rodents)                                                                                  |
| NOAEL (dermal, rat/rabbit, 90 days)               | ≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)                           |
| Cobalt bis(2-ethylhexanoate) (136-52-7)           |                                                                                                                                        |
| LOAEC (inhalation, rat, dust/mist/fume, 90 days)  | 0.31 mg/l air Animal: rat                                                                                                              |
| NOAEL (oral, rat, 90 days)                        | 3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)                    |
| STOT-repeated exposure                            | Causes damage to organs through prolonged or repeated exposure.                                                                        |
| 2-ethylhexanoic acid, zirconium salt (22464-99-9) |                                                                                                                                        |
| NOAEL (subchronic, oral, animal/male, 90 days)    | 180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:                                                                |
| NOAEL (subchronic, oral, animal/female, 90 days)  | 205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:                                                              |
| N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)        |                                                                                                                                        |
| LOAEL (dermal, rat/rabbit, 90 days)               | 1653 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| NOAEL (dermal, rat/rabbit, 90 days)               | 826 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)  |

Aspiration hazard : Not classified.

| W-LACK ACA 11 3 R T GRAY MONOCOMPONENT     |                                                                        |
|--------------------------------------------|------------------------------------------------------------------------|
| Viscosity, kinematic                       | 280 – 320 mm²/s                                                        |
| 2-methoxy-1-methylethyl acetate (108-65-6) |                                                                        |
| Viscosity, kinematic                       | 1.182 mm²/s                                                            |
| MIXED XYLENES (1330-20-7)                  |                                                                        |
| Viscosity, kinematic                       | ≈ 0.76 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' |
| N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4) |                                                                        |
| Viscosity, kinematic                       | 1.613 mm²/s                                                            |

### 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                                                         |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled.<br>May cause severe burns. May cause respiratory irritation.                   |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).                                                               |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                                                          |
| Symptoms/effects after ingestion    | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                  |
| Chronic symptoms                    | : May damage fertility. May damage the unborn child.                                                                                                                    |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                          |                                                    |
|----------------------------------------------------------|----------------------------------------------------|
| Hazardous to the aquatic environment, short-term (acute) | : Toxic to aquatic life.                           |
| Hazardous to the aquatic environment, long-term          | : Toxic to aquatic life with long lasting effects. |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

(chronic)

| 2-methoxy-1-methylethyl acetate108-65-6 |                                                                                                                                             |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]                         | > 100 mg/l Test organisms (species): Oryzias latipes                                                                                        |
| EC50 - Crustacea [1]                    | > 500 mg/l Test organisms (species): Daphnia magna                                                                                          |
| EC50 72h - Algae [1]                    | > 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| NOEC (chronic)                          | ≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                         |
| NOEC chronic fish                       | 47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'                                                                        |

| MIXED XYLENES1330-20-7 |                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]        | ≈ 2.6 mg/l                                                                                                 |
| EC50 - Crustacea [1]   | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia                                                    |
| ErC50 algae            | ≈ 2.2 mg/l                                                                                                 |
| LOEC (chronic)         | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                         |
| NOEC chronic fish      | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |

| Aliphatic solvent64742-47-8 |                         |
|-----------------------------|-------------------------|
| LC50 - Fish [1]             | 2.4 mg/l Source: ECOTOX |

| Cobalt bis(2-ethylhexanoate)136-52-7 |                                                   |
|--------------------------------------|---------------------------------------------------|
| EC50 - Crustacea [1]                 | 5.89 mg/l Test organisms (species): Daphnia magna |

| 2-ethylhexanoic acid, zirconium salt22464-99-9 |                                                                  |
|------------------------------------------------|------------------------------------------------------------------|
| LC50 - Fish [1]                                | > 100 mg/l Test organisms (species): Oryzias latipes             |
| EC50 - Crustacea [1]                           | > 0.17 mg/l Test organisms (species): Daphnia magna              |
| LOEC (chronic)                                 | 63 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic)                                 | 25 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

| N-METHYLPYRROLIDONE SOLVENT (N)872-50-4 |                                                                                                       |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]                         | 500 mg/l Source: ECHA                                                                                 |
| EC50 72h - Algae [1]                    | 600.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 72h - Algae [2]                    | 672.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| LOEC (chronic)                          | 25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                      |
| NOEC (chronic)                          | 12.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                    |

### 12.2. Persistence and degradability

| W-LACK ACA 11 3 R T GRAY MONOCOMPONENT  |                        |
|-----------------------------------------|------------------------|
| Persistence and degradability           | Not rapidly degradable |
| 2-methoxy-1-methylethyl acetate108-65-6 |                        |
| Persistence and degradability           | Not rapidly degradable |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### MIXED XYLENES1330-20-7

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### SOLVENT BUTANOL71-36-3

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### Aliphatic solvent64742-47-8

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ZINC OCTOATE136-53-8

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### Cobalt bis(2-ethylhexanoate)136-52-7

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 2-ethylhexanoic acid, zirconium salt22464-99-9

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

## 12.3. Bioaccumulative potential

### 2-methoxy-1-methylethyl acetate108-65-6

|                                                 |                                                                  |
|-------------------------------------------------|------------------------------------------------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 0.43 Source: International Uniform Chemical Information Database |
|-------------------------------------------------|------------------------------------------------------------------|

### Aliphatic solvent64742-47-8

|                                                 |                        |
|-------------------------------------------------|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.3 – 6 Source: IUCLID |
|-------------------------------------------------|------------------------|

### N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

|                                                 |                    |
|-------------------------------------------------|--------------------|
| Partition coefficient n-octanol/water (Log Pow) | -0.46 Source: ECHA |
|-------------------------------------------------|--------------------|

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

|                                            |                                                                                      |
|--------------------------------------------|--------------------------------------------------------------------------------------|
| Regional waste regulation                  | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.   |
| Waste treatment methods                    | : Must follow special treatment according to local regulation.                       |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.                           |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations.                           |
| Additional information                     | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

14/16

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

| ANTT                                  | IMDG                                                                          | IATA                                             |
|---------------------------------------|-------------------------------------------------------------------------------|--------------------------------------------------|
| <b>UN number</b>                      |                                                                               |                                                  |
| 1263                                  | 1263                                                                          | 1263                                             |
| <b>UN Proper Shipping Name</b>        |                                                                               |                                                  |
| TINTA                                 | PAINT                                                                         | Paint                                            |
| <b>Transport document description</b> |                                                                               |                                                  |
| Not applicable                        | UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (31°C c.c.) | UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS |
| <b>Transport hazard class(es)</b>     |                                                                               |                                                  |
| 3                                     | 3                                                                             | 3                                                |
| <b>Danger labels</b>                  |                                                                               |                                                  |
| 3                                     | 3                                                                             | 3                                                |
|                                       |                                                                               |                                                  |
| <b>Subsidiary risk</b>                |                                                                               |                                                  |
| Not applicable                        | Not applicable                                                                | Not applicable                                   |
| <b>Risk Number</b>                    |                                                                               |                                                  |
| 30                                    | Not applicable                                                                | Not applicable                                   |
| <b>Packing group</b>                  |                                                                               |                                                  |
| III                                   | III                                                                           | III                                              |
| <b>Special provisions</b>             |                                                                               |                                                  |
| 163,223,367                           | 163,223,367,955                                                               | A3,A72,A192                                      |
| <b>Dangerous for the environment</b>  |                                                                               |                                                  |
| Yes                                   | Yes                                                                           | Yes                                              |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.

Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.

Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials

Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK ACA 11 3 R T GRAY MONOCOMPONENT

10589327

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/23/2025

### SECTION 16: Other information

#### Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)