

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT



## Safety Data Sheet

According to ABNT NBR 14725: 2023  
Issue date: 3/6/2024 Revision date: 4/24/2025 Version: 2.0

### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT  
Product code : 14190076  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| Germany        |           |                  | 0800-181-7059    |
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| Russia         |           |                  | 8(800)100-63-46  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Acute toxicity (oral), Category 5  
Acute toxicity (dermal), Category 5  
Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 2  
Germ cell mutagenicity, Category 1B  
Carcinogenicity, Category 1B  
Specific target organ toxicity — Single exposure, Category 3, Narcosis  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Repeated exposure, Category 2  
Hazardous to the aquatic environment - Acute Hazard, Category 3  
Hazardous to the aquatic environment - Chronic Hazard, Category 3

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H303+H313 - May be harmful if swallowed or in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects  
Precautionary statements (GHS BR)  
: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                     | GHS Product identifier | %       | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                                               |
|--------------------------|------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MIXED XYLENES            | CAS-No.: 1330-20-7     | 20 – 40 | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| SOLVENT ACETATO DE ETILA | CAS-No.: 141-78-6      | 10 – 20 | Flam. Liq. 2, H225                                                                                                                                                                                                                                      |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

| Name                                       | GHS Product identifier | %          | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                      |
|--------------------------------------------|------------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                            |                        |            | Eye Irrit. 2A, H319<br>STOT SE 3, H336                                                                                                                                                         |
| Ethyl Alcohol, Anhydrous Alcohol, AEAC     | CAS-No.: 64-17-5       | 5 – 10     | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319                                                                                                                                                       |
| ETHYL ACETATE                              | CAS-No.: 141-78-6      | 1 – 5      | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                                                                                                                                   |
| SOLVENT ISOPROPANOL                        | CAS-No.: 67-63-0       | 1 – 5      | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                                                                                                                                   |
| SOLVENT BUTYL GLYCOL (N)                   | CAS-No.: 111-76-2      | 1 – 5      | Flam. Liq. 4, H227<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319                                                               |
| CALCIUM CARBONATE                          | CAS-No.: 471-34-1      | 1 – 5      | Acute Tox. 5 (Oral), H303                                                                                                                                                                      |
| SOLVENT BUTANOL                            | CAS-No.: 71-36-3       | 1 – 5      | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H336<br>STOT SE 3, H335                                                               |
| ZINC PHOSPHATE                             | CAS-No.: 7779-90-0     | 0.25 – 0.5 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                                                               |
| Light aromatic naphtha (petroleum) solvent | CAS-No.: 64742-95-6    | 0.1 – 0.25 | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Muta. 1B, H340<br>Carc. 1B, H350<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411                                 |
| FATTY ACIDS                                | CAS-No.: 68647-95-0    | 0.1 – 0.25 | Skin Irrit. 2, H315<br>Skin Sens. 1B, H317<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                              |
| Cobalt bis(2-ethylhexanoate)               | CAS-No.: 136-52-7      | 0.1 – 0.25 | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 1B, H360<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SECTION 4: First-aid measures

#### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.                                                                                                                                                    |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.                                               |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact  | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                                                                                                             |
| First-aid measures after ingestion    | : If you feel unwell, seek medical advice.                                                                                                                                                                  |

#### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                                                                                                           |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause respiratory irritation. May cause drowsiness or dizziness.                                                                                                         |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).                                                                                                                                                                 |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                                                                                                                                                            |
| Symptoms/effects after ingestion    | : May be harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                                              |
| Chronic symptoms                    | : May cause cancer. May cause heritable genetic damage.                                                                                                                                                                                                                   |

#### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| Suitable extinguishing media   | : Dry chemical, CO <sub>2</sub> , or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                                |

#### 5.2. Specific hazards arising from the chemical

|                  |                                                                                                                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard      | : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. |
| Explosion hazard | : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.                                                                                                                                                                                          |

#### 5.3. Special protective actions for fire-fighters

|                                |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary measures fire    | : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.                                                                                                                                                                                                                                 |
| Firefighting instructions      | : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.                                                                                                                                                                                                                                                                  |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

##### 6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Equip cleanup crew with proper protection.  
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Harmful to aquatic life. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Absorb spillage to prevent material damage. Take up liquid spill into absorbent material.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Flammable vapours may accumulate in the container.  
Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.  
Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE

## MONOCOMPONENT

14190076

### Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

|                        |                                                                                                                 |
|------------------------|-----------------------------------------------------------------------------------------------------------------|
| Storage conditions     | : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. |
| Incompatible materials | : combustible materials.                                                                                        |
| Packaging materials    | : Store always product in container of same material as original container.                                     |

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

|                                                |                                                                                                              |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Ethyl Alcohol, Anhydrous Alcohol, AEAC 64-17-5 |                                                                                                              |
| USA - ACGIH - Occupational Exposure Limits     |                                                                                                              |
| Local name                                     | Ethanol                                                                                                      |
| ACGIH® TLV® STEL                               | 1000 ppm                                                                                                     |
| Remark (ACGIH)                                 | TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)            |
| Regulatory reference                           | ACGIH 2024                                                                                                   |
| USA - OSHA - Occupational Exposure Limits      |                                                                                                              |
| Local name                                     | Ethyl alcohol (Ethanol)                                                                                      |
| OSHA PEL TWA                                   | 1900 mg/m³                                                                                                   |
|                                                | 1000 ppm                                                                                                     |
| Regulatory reference (US-OSHA)                 | OSHA Annotated Table Z-1                                                                                     |
| SOLVENT ACETATO DE ETILA 141-78-6              |                                                                                                              |
| USA - ACGIH - Occupational Exposure Limits     |                                                                                                              |
| Local name                                     | Ethyl acetate                                                                                                |
| ACGIH® TLV® TWA                                | 400 ppm                                                                                                      |
| Remark (ACGIH)                                 | TLV® Basis: URT & eye irr                                                                                    |
| Regulatory reference                           | ACGIH 2024                                                                                                   |
| USA - OSHA - Occupational Exposure Limits      |                                                                                                              |
| Local name                                     | Ethyl acetate                                                                                                |
| OSHA PEL TWA                                   | 1400 mg/m³                                                                                                   |
|                                                | 400 ppm                                                                                                      |
| Regulatory reference (US-OSHA)                 | OSHA Annotated Table Z-1                                                                                     |
| SOLVENT BUTYL GLYCOL (N) 111-76-2              |                                                                                                              |
| USA - ACGIH - Occupational Exposure Limits     |                                                                                                              |
| Local name                                     | 2-Butoxyethanol (EGBE)                                                                                       |
| ACGIH® TLV® TWA                                | 20 ppm                                                                                                       |
| Remark (ACGIH)                                 | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI |
| Regulatory reference                           | ACGIH 2024                                                                                                   |
| USA - OSHA - Occupational Exposure Limits      |                                                                                                              |
| Local name                                     | 2-Butoxyethanol                                                                                              |

WEG TINTAS LTDA – GRUPO WEG.

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SOLVENT BUTYL GLYCOL (N) 111-76-2

|                                |                          |
|--------------------------------|--------------------------|
| OSHA PEL TWA                   | 240 mg/m <sup>3</sup>    |
|                                | 50 ppm                   |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

### ETHYL ACETATE 141-78-6

#### USA - ACGIH - Occupational Exposure Limits

|                      |                           |
|----------------------|---------------------------|
| Local name           | Ethyl acetate             |
| ACGIH® TLV® TWA      | 400 ppm                   |
| Remark (ACGIH)       | TLV® Basis: URT & eye irr |
| Regulatory reference | ACGIH 2024                |

#### USA - OSHA - Occupational Exposure Limits

|                                |                          |
|--------------------------------|--------------------------|
| Local name                     | Ethyl acetate            |
| OSHA PEL TWA                   | 1400 mg/m <sup>3</sup>   |
|                                | 400 ppm                  |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

### MIXED XYLENES 1330-20-7

#### USA - ACGIH - Occupational Exposure Limits

|                      |                                                                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local name           | Xylene, mixed isomers (Dimethylbenzene)                                                                                                                                                                     |
| ACGIH® TLV® TWA      | 20 ppm                                                                                                                                                                                                      |
| Remark (ACGIH)       | TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI |
| Regulatory reference | ACGIH 2024                                                                                                                                                                                                  |

#### USA - OSHA - Occupational Exposure Limits

|                                |                             |
|--------------------------------|-----------------------------|
| Local name                     | Xylenes (o-, m-, p-isomers) |
| OSHA PEL TWA                   | 435 mg/m <sup>3</sup>       |
|                                | 100 ppm                     |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1    |

### SOLVENT ISOPROPANOL 67-63-0

#### USA - ACGIH - Occupational Exposure Limits

|                      |                                                                                                    |
|----------------------|----------------------------------------------------------------------------------------------------|
| Local name           | 2-Propanol                                                                                         |
| ACGIH® TLV® TWA      | 200 ppm                                                                                            |
| ACGIH® TLV® STEL     | 400 ppm                                                                                            |
| Remark (ACGIH)       | TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI |
| Regulatory reference | ACGIH 2024                                                                                         |

#### USA - OSHA - Occupational Exposure Limits

|            |                   |
|------------|-------------------|
| Local name | Isopropyl alcohol |
|------------|-------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)



# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SOLVENT ISOPROPANOL 67-63-0

|                                |                          |
|--------------------------------|--------------------------|
| OSHA PEL TWA                   | 980 mg/m³                |
|                                | 400 ppm                  |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

### SOLVENT BUTANOL 71-36-3

#### USA - ACGIH - Occupational Exposure Limits

|                      |                           |
|----------------------|---------------------------|
| Local name           | n-Butanol                 |
| ACGIH® TLV® TWA      | 20 ppm                    |
| Remark (ACGIH)       | TLV® Basis: Eye & URT irr |
| Regulatory reference | ACGIH 2024                |

#### USA - OSHA - Occupational Exposure Limits

|                                |                          |
|--------------------------------|--------------------------|
| Local name                     | n-Butyl alcohol          |
| OSHA PEL TWA                   | 300 mg/m³                |
|                                | 100 ppm                  |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## 8.3. Individual protection measures

### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC

#### Eye protection:

Wear closed safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### Personal protective equipment symbol(s):



### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

|                                                 |                                      |
|-------------------------------------------------|--------------------------------------|
| Physical state                                  | : Liquid                             |
| Appearance                                      | : Liquid.                            |
| Colour                                          | : Blue                               |
| Odour                                           | : characteristic                     |
| Odour threshold                                 | : Not available                      |
| pH                                              | : Not applicable                     |
| Melting point                                   | : Not available                      |
| Freezing point                                  | : Not available                      |
| Boiling point                                   | : Not available                      |
| Flash point                                     | : 24 °C                              |
| Relative evaporation rate (butylacetate=1)      | : Not available                      |
| Flammability                                    | : Not available                      |
| Explosive limits                                | : Not available                      |
| Vapour pressure                                 | : Not available                      |
| Relative vapour density at 20°C                 | : Not available                      |
| Relative density                                | : Not available                      |
| Density                                         | : 1.1 – 1.16 g/cm³                   |
| Solubility                                      | : Water: Material insoluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                      |
| Auto-ignition temperature                       | : Not available                      |
| Decomposition temperature                       | : Not available                      |
| Viscosity, kinematic                            | : 65 – 75 CF4                        |
| Particle size                                   | : Not applicable                     |
| Particle size distribution                      | : Not applicable                     |
| Particle shape                                  | : Not applicable                     |
| Particle aspect ratio                           | : Not applicable                     |
| Particle specific surface area                  | : Not applicable                     |

#### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                           |                                   |
|---------------------------|-----------------------------------|
| Boiling point             | 78.5 – 101.325 °C kPa (760 mm Hg) |
| Flash point               | 15 °C (vaso fechado)              |
| Auto-ignition temperature | 423 °C                            |
| Vapour pressure           | 5.9 kPa (44mmHg) a 20 °C          |

#### MIXED XYLENES1330-20-7

|                           |                   |
|---------------------------|-------------------|
| Boiling point             | 139.6 °C          |
| Flash point               | 30 °C (ASTM D 93) |
| Auto-ignition temperature | 488 °C            |
| Vapour pressure           | 4.8 kPa 55°C      |

#### SOLVENT ISOPROPANOL67-63-0

|               |                  |
|---------------|------------------|
| Boiling point | 82 °C (CHEMSAFE) |
| Flash point   | 21 °C            |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### Cobalt bis(2-ethylhexanoate)136-52-7

|                 |                               |
|-----------------|-------------------------------|
| Flash point     | 23 – 55 °C Atm. press.: 1 atm |
| Vapour pressure | < 110 kPa Temp.: 20 °C        |

### SOLVENT BUTANOL71-36-3

|             |       |
|-------------|-------|
| Flash point | 36 °C |
|-------------|-------|

### Light aromatic naphtha (petroleum) solvent64742-95-6

|                 |                          |
|-----------------|--------------------------|
| Boiling point   | 165.5 (156 – 175) °C     |
| Flash point     | 40 °C                    |
| Vapour pressure | ≤ 240 kPa Temp.: 37,8 °C |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                       |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products   | : May liberate toxic gases.                                                                                                                                                     |
| Incompatible materials             | : Combustible materials.                                                                                                                                                        |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                     |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                            |
| Handling temperature               | : No additional information available                                                                                                                                           |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                                        |
|-----------------------------|----------------------------------------|
| Acute toxicity (oral)       | : May be harmful if swallowed.         |
| Acute toxicity (dermal)     | : May be harmful in contact with skin. |
| Acute toxicity (inhalation) | : Not available                        |

### W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

|                 |                           |
|-----------------|---------------------------|
| ATE BR (oral)   | 4989.793 mg/kg bodyweight |
| ATE BR (dermal) | 4569.566 mg/kg bodyweight |

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|                                 |                                     |
|---------------------------------|-------------------------------------|
| LD50 oral rat                   | 7060 mg/kg Source: ECHA             |
| LD50 oral                       | 8300 mg/kg bodyweight Animal: mouse |
| LC50 Inhalation - Rat (Vapours) | 116.9 mg/l Source: ECHA             |

### MIXED XYLENES (1330-20-7)

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
|--------------------|---------------------------------------------------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### CALCIUM CARBONATE (471-34-1)

|                       |                                                                                                                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat         | 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)     |
| LD50 dermal rat       | 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))                                                                  |
| LC50 Inhalation - Rat | 3 mg/m <sup>3</sup> Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) |

### Cobalt bis(2-ethylhexanoate) (136-52-7)

|                 |                                                                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat   | 3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000 |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                                             |

### Light aromatic naphtha (petroleum) solvent (64742-95-6)

|                                 |                                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------|
| LD50 oral rat                   | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rat                 | > 2000 mg/kg Source: ECHA                                                                |
| LD50 dermal rabbit              | > 2000 mg/kg                                                                             |
| LC50 Inhalation - Rat (Vapours) | 5.16 mg/l Source: ECHA                                                                   |

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |       |
|----|-------|
| pH | 6 – 8 |
|----|-------|

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### CALCIUM CARBONATE (471-34-1)

|    |    |
|----|----|
| pH | 10 |
|----|----|

Serious eye damage/irritation : Causes serious eye irritation.  
pH: Not applicable

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |       |
|----|-------|
| pH | 6 – 8 |
|----|-------|

### MIXED XYLENES (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### CALCIUM CARBONATE (471-34-1)

|    |    |
|----|----|
| pH | 10 |
|----|----|

Respiratory or skin sensitisation : Not available  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|            |                            |
|------------|----------------------------|
| IARC group | 1 - Carcinogenic to humans |
|------------|----------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### SOLVENT BUTYL GLYCOL (N) (111-76-2)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

### MIXED XYLENES (1330-20-7)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

### SOLVENT ISOPROPANOL (67-63-0)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

Reproductive toxicity : Not available

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

### SOLVENT ACETATO DE ETILA (141-78-6)

|                      |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

### ETHYL ACETATE (141-78-6)

|                      |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

### MIXED XYLENES (1330-20-7)

|                      |                                   |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

### SOLVENT ISOPROPANOL (67-63-0)

|                      |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

### SOLVENT BUTANOL (71-36-3)

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
|----------------------|----------------------------------------------------------------------|

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|                                                |                                                                                                                          |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/male, 90 days) | < 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|

|                                                  |                                                                                                                            |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/female, 90 days) | > 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|

### MIXED XYLENES (1330-20-7)

|                            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--------------------------------------------------------------------|

### CALCIUM CARBONATE (471-34-1)

|                            |                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (oral, rat, 90 days) | 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                  |                                                                                                            |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| NOAEC (inhalation, rat, dust/mist/fume, 90 days) | ≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------|

### Cobalt bis(2-ethylhexanoate) (136-52-7)

|                                                  |                           |
|--------------------------------------------------|---------------------------|
| LOAEC (inhalation, rat, dust/mist/fume, 90 days) | 0.31 mg/l air Animal: rat |
|--------------------------------------------------|---------------------------|

|                            |                                                                                                                     |
|----------------------------|---------------------------------------------------------------------------------------------------------------------|
| NOAEL (oral, rat, 90 days) | 3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
|----------------------------|---------------------------------------------------------------------------------------------------------------------|

|                        |                                                                 |
|------------------------|-----------------------------------------------------------------|
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |
|------------------------|-----------------------------------------------------------------|

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

### FATTY ACIDS (68647-95-0)

|                                                |                                                                    |
|------------------------------------------------|--------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/male, 90 days) | 12.5 mg/kg bodyweight                                              |
| STOT-repeated exposure                         | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified.

### W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

|                      |                              |
|----------------------|------------------------------|
| Viscosity, kinematic | 260 – 300 mm <sup>2</sup> /s |
|----------------------|------------------------------|

### MIXED XYLENES (1330-20-7)

|                      |                                                                                                  |
|----------------------|--------------------------------------------------------------------------------------------------|
| Viscosity, kinematic | ≈ 0.76 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)' |
|----------------------|--------------------------------------------------------------------------------------------------|

### SOLVENT ISOPROPANOL (67-63-0)

|                      |                          |
|----------------------|--------------------------|
| Viscosity, kinematic | 3.077 mm <sup>2</sup> /s |
|----------------------|--------------------------|

### Light aromatic naphtha (petroleum) solvent (64742-95-6)

|                      |                                                                                                 |
|----------------------|-------------------------------------------------------------------------------------------------|
| Viscosity, kinematic | < 1 mm <sup>2</sup> /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)' |
|----------------------|-------------------------------------------------------------------------------------------------|

## 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                                                                                                                                                           |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause respiratory irritation. May cause drowsiness or dizziness.                                                                                                         |
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).                                                                                                                                                                 |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                                                                                                                                                            |
| Symptoms/effects after ingestion    | : May be harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.                                                                                                              |
| Chronic symptoms                    | : May cause cancer. May cause heritable genetic damage.                                                                                                                                                                                                                   |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                      |
|-----------------------------------------------------------|------------------------------------------------------|
| Hazardous to the aquatic environment, short-term (acute)  | : Harmful to aquatic life.                           |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                 |                                                                  |
|-----------------|------------------------------------------------------------------|
| LC50 - Fish [1] | > 100 mg/l Source: SIDS 2005                                     |
| ErC50 algae     | 275 mg/l Source: ECHA                                            |
| NOEC (chronic)  | 9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d' |

### MIXED XYLENES1330-20-7

|                      |                                                                                |
|----------------------|--------------------------------------------------------------------------------|
| LC50 - Fish [1]      | ≈ 2.6 mg/l                                                                     |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia                        |
| ErC50 algae          | ≈ 2.2 mg/l                                                                     |
| LOEC (chronic)       | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'             |
| NOEC chronic fish    | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

|                                                             |                                                                                                      |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>MIXED XYLENES1330-20-7</b>                               |                                                                                                      |
|                                                             | gairdneri) Duration: '56 d'                                                                          |
| <b>CALCIUM CARBONATE471-34-1</b>                            |                                                                                                      |
| EC50 72h - Algae [1]                                        | > 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| <b>Cobalt bis(2-ethylhexanoate)136-52-7</b>                 |                                                                                                      |
| EC50 - Crustacea [1]                                        | 5.89 mg/l Test organisms (species): Daphnia magna                                                    |
| <b>Light aromatic naphtha (petroleum) solvent64742-95-6</b> |                                                                                                      |
| LC50 - Fish [1]                                             | 9.22 mg/l Source: IUCLID                                                                             |
| EC50 - Crustacea [1]                                        | 6.14 mg/l Source: IUCLID                                                                             |
| EC50 72h - Algae [1]                                        | 19 mg/l Source: IUCLID                                                                               |
| <b>FATTY ACIDS68647-95-0</b>                                |                                                                                                      |
| LC50 - Fish [1]                                             | 55 mg/l                                                                                              |
| EC50 - Crustacea [1]                                        | 34.5 mg/l                                                                                            |
| EC50 72h - Algae [1]                                        | 0.393 mg/l                                                                                           |
| NOEC chronic crustacea                                      | 0.013 mg/l                                                                                           |
| NOEC chronic algae                                          | 0.091 mg/l                                                                                           |

## 12.2. Persistence and degradability

|                                                                    |                        |
|--------------------------------------------------------------------|------------------------|
| <b>W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT</b> |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5</b>               |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>SOLVENT ACETATO DE ETILA141-78-6</b>                            |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>SOLVENT BUTYL GLYCOL (N)111-76-2</b>                            |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>ETHYL ACETATE141-78-6</b>                                       |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>MIXED XYLENES1330-20-7</b>                                      |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>SOLVENT ISOPROPANOL67-63-0</b>                                  |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>CALCIUM CARBONATE471-34-1</b>                                   |                        |
| Persistence and degradability                                      | Not rapidly degradable |
| <b>Cobalt bis(2-ethylhexanoate)136-52-7</b>                        |                        |
| Persistence and degradability                                      | Not rapidly degradable |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

| ZINC PHOSPHATE7779-90-0                              |                        |
|------------------------------------------------------|------------------------|
| Persistence and degradability                        | Not rapidly degradable |
| SOLVENT BUTANOL71-36-3                               |                        |
| Persistence and degradability                        | Not rapidly degradable |
| Light aromatic naphtha (petroleum) solvent64742-95-6 |                        |
| Persistence and degradability                        | Not rapidly degradable |
| FATTY ACIDS68647-95-0                                |                        |
| Persistence and degradability                        | Not rapidly degradable |

### 12.3. Bioaccumulative potential

| Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5        |                        |
|------------------------------------------------------|------------------------|
| Partition coefficient n-octanol/water (Log Pow)      | -0.32 Source: ICSC     |
| Light aromatic naphtha (petroleum) solvent64742-95-6 |                        |
| Partition coefficient n-octanol/water (Log Pow)      | 2.1 – 6 Source: IUCLID |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

|                                            |                                                                                      |
|--------------------------------------------|--------------------------------------------------------------------------------------|
| Regional waste regulation                  | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.   |
| Waste treatment methods                    | : Must follow special treatment according to local regulation.                       |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.                           |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations.                           |
| Additional information                     | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                           | IMDG                              | IATA                  |
|--------------------------------|-----------------------------------|-----------------------|
| UN number                      |                                   |                       |
| 1263                           | 1263                              | 1263                  |
| UN Proper Shipping Name        |                                   |                       |
| TINTA                          | PAINT                             | Paint                 |
| Transport document description |                                   |                       |
| Not applicable                 | UN 1263 PAINT, 3, III (24°C c.c.) | UN 1263 Paint, 3, III |
| Transport hazard class(es)     |                                   |                       |
| 3                              | 3                                 | 3                     |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)



# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

| Danger labels                                                                     |                                                                                   |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 3                                                                                 | 3                                                                                 | 3                                                                                   |
|  |  |  |
| Subsidiary risk                                                                   |                                                                                   |                                                                                     |
| Not applicable                                                                    | Not applicable                                                                    | Not applicable                                                                      |
| Risk Number                                                                       |                                                                                   |                                                                                     |
| 30                                                                                | Not applicable                                                                    | Not applicable                                                                      |
| Packing group                                                                     |                                                                                   |                                                                                     |
| III                                                                               | III                                                                               | III                                                                                 |
| Special provisions                                                                |                                                                                   |                                                                                     |
| 163,223,367                                                                       | 163,223,367,955                                                                   | A3,A72,A192                                                                         |
| Dangerous for the environment                                                     |                                                                                   |                                                                                     |
| No                                                                                | No                                                                                | No                                                                                  |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-LACK HPP 135 PFD NOT APPLICABLE SAFETY BLUE MONOCOMPONENT

14190076

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/24/2025

DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

---

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)