



POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023
SAP export date: 2/23/2024

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR
Product code : 16860832
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Electrostatic powder paint for surface coating.

1.4. Supplier's details

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG
Rodovia BR 280 - km 50 CEP 89270-000, Guaramirim - Santa Catarina - Brasil

1.5. Emergency phone number

Emergency number :
SPILL/TOXICOLOGY WGRA 0800 720 8000
CHEMTREC international number + 1 703-741-5970

Country	City	Local Number	Toll-Free Number
Austria	Vienna	43-13649237	
China		4001-204937	
France		33-975181407	
Germany	Frankfurt	49-69643508409	0800-181-7059
India		000-800-100-7141	000-800-100-7141
Italy	Milan	39-0245557031	800-789-767
Italy		800-789-767	
Netherlands		31-858880596	
Russia		8-800-100-6346	8-800-100-6346
South Africa		0-800-983-611	0-800-983-611
United Kingdom	London	44-870-8200418	
United Kingdom		44-2038073798	
South korea			080-880-0468
Japan	tokyo		0800-300-5842

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725:2023)

Serious eye damage/eye irritation, Category 1
Respiratory sensitisation, Category 1
Skin sensitisation, Category 1
Carcinogenicity, Category 1B
Reproductive toxicity, Category 1A
Specific target organ toxicity — Repeated exposure, Category 2
Hazardous to the aquatic environment - Acute Hazard, Category 2
Hazardous to the aquatic environment - Chronic Hazard, Category 2

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P284 - Wear respiratory protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical attention.
P310 - Immediately call a POISON CENTER or a doctor.
P314 - Get medical advice or attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or a doctor.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)
2,2-DIMETHYL-1,3-PROPANEDIOL (N)	CAS-No.: 126-30-7	10 – 20
LEAD SULFOCHROMATE YELLOW	CAS-No.: 1344-37-2	10 – 20
C.I. PIGMENT RED 104	CAS-No.: 12656-85-8	1 – 5
TRIMELLITIC ANHYDRIDE	CAS-No.: 552-30-7	1 – 5
ADIPIC ACID	CAS-No.: 124-04-9	1 – 5

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. Causes severe burns. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Causes serious eye damage. stinging. redness, itching, tears.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May cause cancer. May damage fertility. May damage the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. earth, sand, dry chemical powder or foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
- Other information : In case of fire, corrosive and harmful gases come free. High temperature decomposition products are harmful by inhalation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

- Protective equipment : Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life.

6.3. Methods and materials for containment and cleaning up

- For containment : Using a clean shovel, put the material in a dry container and cover without compressing it. Stop leak without risks if possible.
- Methods for cleaning up : Clean up immediately by sweeping or vacuum. Clear up rapidly by scoop or vacuum. Clean contaminated surfaces with an excess of water. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. When heated, material emits highly irritating vapours, affecting the eyes. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store locked up. Store in tightly closed, leak-proof containers.
- Storage conditions : Keep cool. Protect from sunlight. Store in a well-ventilated place. Keep cool.
- Packaging materials : Store always product in container of same material as original container.

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TRIMELLITIC ANHYDRIDE (552-30-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Trimellitic anhydride
ACGIH OEL TWA	0.0005 mg/m ³ (IFV - Inhalable fraction and vapor)
ACGIH OEL STEL	0.002 mg/m ³ (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Resp sens. Notations: Skin; DSEN; RSEN
Regulatory reference	ACGIH 2024
ADIPIC ACID (124-04-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Adipic acid
ACGIH OEL TWA	5 mg/m ³
Remark (ACGIH)	TLV® Basis: URT irr; ANS impair
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Nitrile rubber gloves. Protective gloves made of PVC

Eye protection:

Wear closed safety glasses

Skin and body protection:

Long sleeved protective clothing. Chemical resistant apron. Wear impervious rubber safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Dusty powder.
Colour	:
Odour	: slight
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: 50 – 70 g/m ³
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not applicable
Relative density	: Not available
Density	: 1.53 g/cm ³
Solubility	: Insoluble in water, partially soluble in some solvents and thinners oxygen as acetone, ethyl acetate, methyl ethyl, ketone, among others.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: 300 °C
Viscosity, kinematic	: Not applicable
Particle size	: 25 — 60 µm
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle specific surface area	: Not available

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Consult supplier(s) of these materials for specific recommendations.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available
Skin corrosion/irritation	: Not available

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

ADIPIC ACID (124-04-9)	
pH	2.7

Serious eye damage/irritation : Causes serious eye damage.

ADIPIC ACID (124-04-9)	
pH	2.7

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not available

Carcinogenicity : May cause cancer.

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not available

TRIMELLITIC ANHYDRIDE (552-30-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

C.I. PIGMENT RED 104 (12656-85-8)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

LEAD SULFOCHROMATE YELLOW (1344-37-2)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not available

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. Causes severe burns. irritation (itching, redness, blistering).

Symptoms/effects after eye contact : Causes serious eye damage. stinging. redness, itching, tears.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic symptoms : May cause cancer. May damage fertility. May damage the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR	
Persistence and degradability	Not rapidly degradable

C.I. PIGMENT RED 104 (12656-85-8)	
Persistence and degradability	Not rapidly degradable

LEAD SULFOCHROMATE YELLOW (1344-37-2)	
Persistence and degradability	Not rapidly degradable

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

TRIMELLITIC ANHYDRIDE (552-30-7)	
Persistence and degradability	Not rapidly degradable

ADIPIC ACID (124-04-9)	
Persistence and degradability	Not rapidly degradable

2,2-DIMETHYL-1,3-PROPANEDIOL (N) (126-30-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available
Other adverse effects : May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

SECTION 13: Disposal considerations

Regional waste regulation : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods : Must follow special treatment according to local regulation.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
Not applicable	Not applicable	Not applicable
UN Proper Shipping Name		
Not applicable	Not applicable	Not applicable
Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
Danger labels		
Not applicable	Not applicable	Not applicable
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
Not applicable	Not applicable	Not applicable
Packing group		
Not applicable	Not applicable	Not applicable

POLITHERM 50 HB TX ORANGE W MUNSELL 2,5YR 6/14 BR

Safety Data Sheet

According to ABNT NBR 14725:2023

Special provisions		
Not applicable	Not applicable	Not applicable
Dangerous for the environment		
Yes	Not applicable	Not applicable

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations : Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

SECTION 16: Other information

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.