



W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015
Issue date: 7/14/2026 Version: 1.0

SECTION 1: Identification of the hazardous chemical or mixture and of the supplier or manufacturer

1.1. GHS product identifier

Product form : Mixture
Trade name : W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT
Product code : 19567243

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

1.5. Emergency phone number

Emergency number

:

EMERGENCIA 24 HORAS - AMBIPAR

0800 117 2020

CHEMTREC número internacional

+1-703-527-3887 e 1-800-424-9300

País	Ciudad	Número Local	Número gratuito
Chile	Santiago	+56 2 2581 4934	
Colombia	Bogota	+57 601 7942539	
Costa Rica		506-40003869	
Dominican Republic	Santo Domingo	1 (829) 956-7588	
El Salvador	San Salvador	+503 2136 7633	
Mexico			800-681-9531
Mexico	Mexico City	+52 55 8526 4930	
Panama		+507-832-2475	
Peru	Lima	+51-1 7071295	
Spain	Barcelona	+34-931768545	
Spain			900-868 538
Switzerland			0800 564 402
Switzerland	Zurich	41-435082011	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS MX classification

Flam. Liq. 3	H226	Flammable liquid and vapour.
Acute Tox. 5 (Oral)	H303	May be harmful if swallowed.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Muta. 1B	H340	May cause genetic defects.
Carc. 1A	H350	May cause cancer.
STOT RE 1	H372	Causes damage to organs through prolonged or repeated exposure.
Aquatic Acute 3	H402	Harmful to aquatic life.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS MX labelling

Hazard pictograms (GHS MX)

:



Signal word (GHS MX)

: Danger

Hazard statements (GHS MX)

: H226 - Flammable liquid and vapour.
H303 - May be harmful if swallowed.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

Precautionary statements (GHS MX)	H318 - Causes serious eye damage.
	H340 - May cause genetic defects.
	H350 - May cause cancer.
	H372 - Causes damage to organs through prolonged or repeated exposure.
	H402 - Harmful to aquatic life
	H411 - Toxic to aquatic life with long lasting effects.
	P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical/ventilating/lighting equipment.
	P242 - Use only non-sparking tools.
	P243 - Take action to prevent static discharges.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash hands, forearms and face thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 - IF exposed or concerned: get medical advice/attention.
	P310 - Immediately call a POISON CENTER or doctor.
	P312 - Call a POISON CENTER or doctor if you feel unwell.
	P314 - Get medical advice/attention if you feel unwell.
	P321 - Specific treatment (see supplemental first aid instruction on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P370+P378 - In case of fire: Use media other than water to extinguish.
	P391 - Collect spillage.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)	GHS MX classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	CAS-No.: 25068-38-6	30 – 50	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

Name	Product identifier	Conc. (% w/w)	GHS MX classification
BENZYL ALCOHOL	CAS-No.: 100-51-6	10 – 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 1, H372
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6	1 – 5	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Aquatic Acute 3, H402
ethylbenzene	CAS-No.: 100-41-4	1 – 5	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).]	CAS-No.: 64742-82-1	0.1 – 1	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM	CAS-No.: 64742-95-6	0.1 – 1	Flam. Liq. 2, H225 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye irritation.
------------------	---

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire	: Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions	: Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: In case of fire, corrosive and harmful gases come free.

SECTION 6: Measures to be taken in case of accidental spillage or accidental leakage

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection. |
| Emergency procedures | : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so. |

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material. |

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-----------------------------------|---|
| Additional hazards when processed | : Flammable vapours may accumulate in the container. |
| Precautions for safe handling | : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood. |
| Hygiene measures | : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|---|
| Storage conditions | : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. |
| Incompatible materials | : combustible materials. |
| Packaging materials | : Always store product in container of same material as original container. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- | | |
|----------------------------------|--|
| Appropriate engineering controls | : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. |
|----------------------------------|--|

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Wear recommended personal protective equipment.
Hand protection	: Protective gloves made of PVC. Nitrile rubber gloves
Eye protection	: Wear closed safety glasses
Skin and body protection	: Long sleeved protective clothing. Or chemical resistant apron. Safety shoes
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s)



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Grey
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 31 °C
Flammability (solid, gas)	: Flammable liquid and vapour.
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 0.99 – 1.09 g/cm³
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

10.2. Chemical stability

In use may form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Liquids/vapours may ignite or react with other materials.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.

10.5. Incompatible materials

Combustible materials.

10.6. Hazardous decomposition products

May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : May be harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 oral rat	8532 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg Source: International Uniform Chemical Information Database
ATE MX (dermal)	2500 mg/kg bodyweight

BENZYL ALCOHOL (100-51-6)

LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 oral rat	1610 mg/kg Source: OECD SIDS
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	> 4.178 mg/l

ethylbenzene (100-41-4)

LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)

LD50 oral rat	8400 mg/kg Source: RTECS
---------------	--------------------------

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	5.16 mg/l Source: ECHA
ATE MX (dermal)	2500 mg/kg bodyweight
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg Source: CHEMIDPLUS
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
Skin corrosion/irritation	: Causes skin irritation.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)	
pH	4.5 – 4.7
Serious eye damage/irritation	: Causes serious eye damage.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)	
pH	4.5 – 4.7
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
BENZYL ALCOHOL (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

naphtha (petroleum), hydrosulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrosulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)

Viscosity, kinematic	1.182 mm²/s
----------------------	-------------

BENZYL ALCOHOL (100-51-6)

Viscosity, kinematic	4.851 mm²/s
----------------------	-------------

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)

Viscosity, kinematic	< 1 mm²/s Temp.: 'other.' Parameter: 'kinematic viscosity (in mm²/s)'
----------------------	---

naphtha (petroleum), hydrosulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrosulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)

Viscosity, kinematic	< 1 mm²/s Temp.: 'other.' Parameter: 'kinematic viscosity (in mm²/s)'
----------------------	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate (108-65-6)

LC50 - Fish [1]	100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

BENZYL ALCOHOL (100-51-6)

LC50 - Fish [1]	10 mg/l
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76.828 mg/l Test organisms (species): other:
NOEC chronic fish	48.897 mg/l Test organisms (species): other: Duration: '30 d'

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l Source: IUCLID
EC50 - Crustacea [1]	6.14 mg/l Source: IUCLID
EC50 72h - Algae [1]	19 mg/l Source: IUCLID
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)	
LC50 - Fish [1]	1.41 mg/l Source: National Institute of Technology and Evaluation
EC50 - Crustacea [1]	1.7 mg/l Source: NITE
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)	
LC50 - Other aquatic organisms [1]	4.3 mg/l Source: IUCLID
12.2. Persistence and degradability	
W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
BENZYL ALCOHOL (100-51-6)	
Persistence and degradability	Not rapidly degradable
ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)	
Persistence and degradability	Not rapidly degradable
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)	
Persistence and degradability	Not rapidly degradable

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)

Partition coefficient n-octanol/water (Log Pow)	0.43 Source: International Uniform Chemical Information Database
---	--

BENZYL ALCOHOL (100-51-6)

Partition coefficient n-octanol/water (Log Pow)	1.1
---	-----

ethylbenzene (100-41-4)

Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB
---	-------------------

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

Partition coefficient n-octanol/water (Log Pow)	2821 Source: National Institute of Technology and Evaluation
---	--

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1)

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.

SECTION 14: Transport information

In accordance with NOM / UN RTDG / IMDG / IATA

NOM	UN RTDG	IMDG	IATA
14.1. UN number			
Not applicable	Not applicable	1263	1263

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

NOM	UN RTDG	IMDG	IATA
14.2. Proper Shipping Name			
Not applicable	Not applicable	PAINT	Paint
Transport document description			
Not applicable	Not applicable	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III
14.3. Transport hazard class(es)			
Not applicable	Not applicable	3	3
Not applicable	Not applicable		
14.4. Packing group			
Not applicable	Not applicable	III	III
14.5. Environmental hazards			
Not applicable	Not applicable	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

NOM

Not applicable

UN RTDG

Not applicable

IMDG

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

IATA

No data available

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

2-methoxy-1-methylethyl acetate (108-65-6):

Listed in the INSQ (National Inventory of Chemical Substances)

BENZYL ALCOHOL (100-51-6):

Listed in the INSQ (National Inventory of Chemical Substances)

ethylbenzene (100-41-4):

Listed in the INSQ (National Inventory of Chemical Substances)

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6):

Listed in the INSQ (National Inventory of Chemical Substances)

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1):

Listed in the INSQ (National Inventory of Chemical Substances)

15.2. International regulations

2-methoxy-1-methylethyl acetate (108-65-6):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

BENZYL ALCOHOL (100-51-6):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

ethylbenzene (100-41-4):

Listed on IARC (International Agency for Research on Cancer)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Subject to reporting requirements of United States SARA Section 313

Listed on the Canadian DSL (Domestic Substances List)

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens

Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446 °F).] (64742-82-1):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information including those related to the preparation and updating of safety data sheets

Issue date : 7/14/2026

Full text of hazard classes and H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. 5 (Dermal)	Acute toxicity (dermal), Category 5
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aquatic Acute 2	Hazardous to the aquatic environment – Acute Hazard, Category 2
Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

W-POXI HBA 30 1 MX T GRAY W RAL 7040 A COMPONENT

Safety Data Sheet

According to the NOM-018-STPS-2015

Full text of hazard classes and H-statements	
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), Mexico

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.