



POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

SECTION 1: Identification of the hazardous chemical or mixture and of the supplier or manufacturer

1.1. GHS product identifier

Product form : Mixture
Trade name : POLITHERM 26 R MT YELLOW SUBWAY 21294 UM
Product code : 19514097

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Electrostatic powder paint for surface coating.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

1.5. Emergency phone number

Emergency number

:

EMERGENCIA 24 HORAS - AMBIPAR

0800 117 2020

CHEMTREC número internacional

+1-703-527-3887 e 1-800-424-9300

País	Ciudad	Número Local	Número gratuito
Chile	Santiago	+56 2 2581 4934	
Colombia	Bogota	+57 601 7942539	
Costa Rica		506-40003869	
Dominican Republic	Santo Domingo	1 (829) 956-7588	
El Salvador	San Salvador	+503 2136 7633	
Mexico			800-681-9531
Mexico	Mexico City	+52 55 8526 4930	
Panama		+507-832-2475	
Peru	Lima	+51-1 7071295	
Spain	Barcelona	+34-931768545	
Spain			900-868 538
Switzerland			0800 564 402
Switzerland	Zurich	41-435082011	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS MX classification

Acute Tox. 5 (Oral)	H303	May be harmful if swallowed.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Muta. 1B	H340	May cause genetic defects.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS MX labelling

Hazard pictograms (GHS MX)

:



Signal word (GHS MX)

: Danger

Hazard statements (GHS MX)

: H303 - May be harmful if swallowed
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H340 - May cause genetic defects.
H373 - May cause damage to organs through prolonged or repeated exposure.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Precautionary statements (GHS MX)

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: get medical advice/attention.
P310 - Immediately call a POISON CENTER or doctor.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)	GHS MX classification
HARDENER POLYESTER 100-108	CAS-No.: 2451-62-9	1 – 5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Inhalation), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340 STOT RE 2, H373 Aquatic Chronic 3, H412

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye damage.
Symptoms/effects after inhalation	: Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: Causes serious eye damage. stinging, redness, itching, tears.
Symptoms/effects after ingestion	: May be harmful if swallowed. Ingestion may cause nausea and vomiting.

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

Chronic symptoms : May cause heritable genetic damage.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. earth, sand, dry chemical powder or foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : In case of fire and/or explosion do not breathe fumes.
Explosion hazard : No direct explosion hazard.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : In case of fire, corrosive and harmful gases come free.

SECTION 6: Measures to be taken in case of accidental spillage or accidental leakage

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Harmful to aquatic life. Do not allow product to spread into the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up : Clear up rapidly by scoop or vacuum. Clean up immediately by sweeping or vacuum. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. When heated, material emits highly irritating vapours, affecting the eyes. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Always wash hands after handling the product. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep cool. Protect from sunlight. Store in a well-ventilated place. Keep cool.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
----------------------------------	--

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Wear recommended personal protective equipment.
Hand protection	: Nitrile rubber gloves. Protective gloves made of PVC
Eye protection	: Wear closed safety glasses
Skin and body protection	: Long sleeved protective clothing. Or chemical resistant apron. Safety shoes
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s)



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Dusty powder.
Colour	: Yellow
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: 300 °C
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 1.65 g/cm ³
Solubility	: Not soluble in water alone.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 50 – 70 g/m ³
Particle size	: 25 — 60 µm

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

On exposure to high temperature, may decompose, releasing corrosive gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

HARDENER POLYESTER 100-108 (2451-62-9)

LD50 oral rat	200 mg/kg Source: Existing Chemical Safety Safety Test of NIER
---------------	--

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

LD50 dermal rat	> 2000 mg/kg Source: IPCS
LC50 Inhalation - Rat (Dust/Mist)	0.65 mg/l

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

HARDENER POLYESTER 100-108 (2451-62-9)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

HARDENER POLYESTER 100-108 (2451-62-9)

LC50 - Fish [1]	> 77 mg/l Source: ECHA
EC50 72h - Algae [1]	29 – 30 mg/l Source: ECHA

12.2. Persistence and degradability

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

HARDENER POLYESTER 100-108 (2451-62-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

HARDENER POLYESTER 100-108 (2451-62-9)

Partition coefficient n-octanol/water (Log Pow)	-0.8 Source: National Library of Medicine/Hazardous Substances Data BankNLM/HSDB
---	--

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.

SECTION 14: Transport information

In accordance with NOM / UN RTDG / IMDG / IATA

NOM	UN RTDG	IMDG	IATA
14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

NOM

Not applicable

UN RTDG

Not applicable

IMDG

Not applicable

IATA

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

No additional information available

POLITHERM 26 R MT YELLOW SUBWAY 21294 UM

Safety Data Sheet

According to the NOM-018-STPS-2015

15.2. International regulations

No additional information available

SECTION 16: Other information including those related to the preparation and updating of safety data sheets

Full text of hazard classes and H-statements

Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H301	Toxic if swallowed.
H303	May be harmful if swallowed
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H340	May cause genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), Mexico

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.