

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A



Safety Data Sheet

According to ABNT NBR 14725: 2023
Issue date: 4/23/2025 Revision date: 5/14/2025 Version: 2.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A
Product code : 13473035
Type of product : Paint
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

| | | | |
|--------------------------------------|----------------------------------|---------------------|-------------------------|
| 24-HOUR EMERGENCY - AMBIPAR | 0800 117 2020 | | |
| CHEMTREC international number | +1-703-527-3887 e 1-800-424-9300 | | |
| Country | City | Local Number | Toll-Free Number |
| Austria | Vienna | +43-1-3649237 | |
| Austria | | | 0800 293702 |
| China | | 400 120 4937 | |
| France | | +33-975181407 | |
| Germany | | | 0800-181-7059 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

| | | | |
|----------------|-----------|------------------|------------------|
| India | Bangalore | +91 8071 279 207 | |
| India | | | 000 800 1007 141 |
| Italy | Milan | +39-02 4555 7031 | |
| Italy | | | 800 789 767 |
| Netherlands | | +31-85 888 0596 | |
| Russia | | | 8(800)100-63-46 |
| South Africa | | | 080-001-4676 |
| United Kingdom | London | +44 20 3807 3798 | |
| South korea | | | 080-880-0454 |
| Japan | | | 0800-300-5842 |

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2A
Skin sensitisation, Category 1
Germ cell mutagenicity, Category 1B
Carcinogenicity, Category 1B
Specific target organ toxicity — Repeated exposure, Category 2
Aspiration hazard, Category 1
Hazardous to the aquatic environment - Acute Hazard, Category 3
Hazardous to the aquatic environment - Chronic Hazard, Category 2

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H340 - May cause genetic defects.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H402 - Harmful to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P314 - Get medical advice or attention as appropriate.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P331 - Do NOT induce vomiting.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | GHS Product identifier | % | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|--|------------------------|---------|---|
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | CAS-No.: 25068-38-6 | 20 – 40 | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 |
| PHENOL METHYLSTYRENATED | CAS-No.: 68512-30-1 | 10 – 20 | Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412 |
| MIXED XYLENES | CAS-No.: 1330-20-7 | 10 – 20 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

| Name | GHS Product identifier | % | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|--|------------------------|------------|--|
| ethylbenzene | CAS-No.: 100-41-4 | 1 – 5 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 |
| SOLVENT 1-METHOXY-2-PROPANOL | CAS-No.: 107-98-2 | 1 – 5 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| trizinc bis(orthophosphate) | CAS-No.: 7779-90-0 | 0.5 – 1 | STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Light aromatic naphtha (petroleum) solvent | CAS-No.: 64742-95-6 | 0.1 – 0.25 | Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.

4.2. Most important symptoms and effects, acute and delayed

- Symptoms/effects : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause an allergic skin reaction. Causes serious eye irritation. May be fatal if swallowed and enters airways.
- Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
- Symptoms/effects after skin contact : Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
- Symptoms/effects after eye contact : stinging. Redness. Causes serious eye irritation. redness, itching, tears.
- Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema.
- Chronic symptoms : May cause cancer. May cause heritable genetic damage.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

- Notes to physician : Treat symptomatically

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

- Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

- Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Harmful to aquatic life. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

Methods for cleaning up

- : prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

- : Flammable vapours may accumulate in the container.

Precautions for safe handling

- : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures

- : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

- : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.

Storage conditions

- : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials

- : combustible materials.

Packaging materials

- : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| MIXED XYLENES 1330-20-7 | |
|--|---|
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Xylene, mixed isomers (Dimethylbenzene) |
| ACGIH® TLV® TWA | 20 ppm |
| Remark (ACGIH) | TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Xylenes (o-, m-, p-isomers) |
| OSHA PEL TWA | 435 mg/m ³ 100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

| ethylbenzene 100-41-4 | |
|--|---|
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Ethyl benzene |
| OSHA PEL TWA | 435 mg/m ³ |
| | 100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| SOLVENT 1-METHOXY-2-PROPANOL 107-98-2 | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | 1-Methoxy-2-propanol |
| ACGIH® TLV® TWA | 50 ppm |
| ACGIH® TLV® STEL | 100 ppm |
| Remark (ACGIH) | TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen) |
| Regulatory reference | ACGIH 2024 |

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

Skin and body protection:

Long sleeved protective clothing. Or chemical resistant apron. Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

| | |
|---|--------------------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Colour | : Beige |
| Odour | : Not available |
| Odour threshold | : Not available |
| pH | : Not applicable |
| Melting point | : Not available |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flash point | : 31 °C |
| Relative evaporation rate (butylacetate=1) | : Not available |
| Flammability | : Not available |
| Explosive limits | : Not available |
| Vapour pressure | : Not available |
| Relative vapour density at 20°C | : Not available |
| Relative density | : Not available |
| Density | : 1.5 – 1.7 g/cm ³ |
| Solubility | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| Viscosity, kinematic | : Not available |
| Viscosity, dynamic | : 105 – 120 ku/kg |
| Particle size | : Not applicable |
| Particle size distribution | : Not applicable |
| Particle shape | : Not applicable |
| Particle aspect ratio | : Not applicable |
| Particle specific surface area | : Not applicable |

MIXED XYLENES1330-20-7

| | |
|---------------------------|-------------------|
| Boiling point | 139.6 °C |
| Flash point | 30 °C (ASTM D 93) |
| Auto-ignition temperature | 488 °C |
| Vapour pressure | 4.8 kPa 55°C |

ethylbenzene100-41-4

| | |
|---------------------------|---|
| Boiling point | 136.1 °C Atm. press.: 1013,3 mBar Decomposition: 'no' |
| Flash point | 23 °C Atm. press.: 1013 hPa |
| Auto-ignition temperature | 432 °C Source: ICSC |
| Vapour pressure | 9.52 mbar Temp.: 20 °C |

Light aromatic naphtha (petroleum) solvent64742-95-6

| | |
|-----------------|--------------------------|
| Boiling point | 165.5 (156 – 175) °C |
| Flash point | 40 °C |
| Vapour pressure | ≤ 240 kPa Temp.: 37,8 °C |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

SOLVENT 1-METHOXY-2-PROPANOL107-98-2

| | |
|-------------|-------|
| Flash point | 31 °C |
|-------------|-------|

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

| | |
|------------------------------------|---|
| Chemical stability | : In use may form flammable/explosive vapour-air mixture. |
| Conditions to avoid | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products | : May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases. |
| Incompatible materials | : Combustible materials. |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials. |
| Reactivity | : The product is non-reactive under normal conditions of use, storage and transport. |
| Handling temperature | : No additional information available |

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|-----------------|
| Acute toxicity (oral) | : Not available |
| Acute toxicity (dermal) | : Not available |
| Acute toxicity (inhalation) | : Not available |

MIXED XYLENES (1330-20-7)

| | |
|--------------------|---|
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
|--------------------|---|

ethylbenzene (100-41-4)

| | |
|-----------------------------|--|
| LD50 oral rat | ≈ 3500 mg/kg bodyweight Animal: rat |
| LD50 dermal rabbit | > 20000 mg/kg Source: ECHA |
| LC50 Inhalation - Rat [ppm] | 4000 ppm Source: ECHA, Harmonized classification of EU CLP |

trizinc bis(orthophosphate) (7779-90-0)

| | |
|-----------------------|--|
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LC50 Inhalation - Rat | > 5700 mg/m ³ Source: ECHA |

Light aromatic naphtha (petroleum) solvent (64742-95-6)

| | |
|---------------------------------|--|
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rat | > 2000 mg/kg Source: ECHA |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 Inhalation - Rat (Vapours) | 5.16 mg/l Source: ECHA |

| | |
|---------------------------|---|
| Skin corrosion/irritation | : Causes skin irritation. pH: Not applicable |
|---------------------------|---|

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

MIXED XYLENES (1330-20-7)

pH 7

SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

pH 4 – 8

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable

MIXED XYLENES (1330-20-7)

pH 7

SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

pH 4 – 8

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

MIXED XYLENES (1330-20-7)

IARC group 3 - Not classifiable

ethylbenzene (100-41-4)

IARC group 2B - Possibly carcinogenic to humans

Reproductive toxicity : Not available
STOT-single exposure : Not available

MIXED XYLENES (1330-20-7)

STOT-single exposure May cause respiratory irritation.

SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

MIXED XYLENES (1330-20-7)

LOAEL (oral, rat, 90 days) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

ethylbenzene (100-41-4)

NOAEL (oral, rat, 90 days) 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

trizinc bis(orthophosphate) (7779-90-0)

LOAEL (oral, rat, 90 days) 53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

NOAEL (oral, rat, 90 days) 31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

Viscosity, kinematic 1.865 – 2.416 mm²/s

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

MIXED XYLENES (1330-20-7)

Viscosity, kinematic ≈ 0.76 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Light aromatic naphtha (petroleum) solvent (64742-95-6)

Viscosity, kinematic < 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'

11.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects | : May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause an allergic skin reaction. Causes serious eye irritation. May be fatal if swallowed and enters airways. |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact | : stinging. Redness. Causes serious eye irritation. redness, itching, tears. |
| Symptoms/effects after ingestion | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema. |
| Chronic symptoms | : May cause cancer. May cause heritable genetic damage. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Hazardous to the aquatic environment, short-term (acute) | : Harmful to aquatic life. |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects. |

MIXED XYLENES1330-20-7

| | |
|----------------------|--|
| LC50 - Fish [1] | ≈ 2.6 mg/l |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| ErC50 algae | ≈ 2.2 mg/l |
| LOEC (chronic) | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |

ethylbenzene100-41-4

| | |
|----------------------|--|
| LC50 - Fish [1] | 5.1 mg/l Test organisms (species): Menidia menidia |
| EC50 72h - Algae [1] | 5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 4.9 mg/l Test organisms (species): Skeletonema costatum |
| EC50 96h - Algae [1] | 3.6 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 96h - Algae [2] | 7.7 mg/l Test organisms (species): Skeletonema costatum |
| LOEC (chronic) | 1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |
| NOEC (chronic) | 0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |

trizinc bis(orthophosphate)7779-90-0

| | |
|----------------------|---------------------|
| LC50 - Fish [1] | 2 (0.14 – 2.6) mg/l |
| EC50 - Crustacea [1] | 2.44 mg/l |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

| trizinc bis(orthophosphate)7779-90-0 | |
|---|--------------------------|
| EC50 72h - Algae [1] | 0.14 mg/l |
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| LC50 - Fish [1] | 9.22 mg/l Source: IUCLID |
| EC50 - Crustacea [1] | 6.14 mg/l Source: IUCLID |
| EC50 72h - Algae [1] | 19 mg/l Source: IUCLID |
| PHENOL METHYLSTYRENATED68512-30-1 | |
| NOEC chronic algae | 6 mg/l |

12.2. Persistence and degradability

| WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A | |
|---|------------------------|
| Persistence and degradability | Not rapidly degradable |
| MIXED XYLENES1330-20-7 | |
| Persistence and degradability | Not rapidly degradable |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6 | |
| Persistence and degradability | Not rapidly degradable |
| ethylbenzene100-41-4 | |
| Persistence and degradability | Not rapidly degradable |
| trizinc bis(orthophosphate)7779-90-0 | |
| Persistence and degradability | Not rapidly degradable |
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| Persistence and degradability | Not rapidly degradable |
| PHENOL METHYLSTYRENATED68512-30-1 | |
| Persistence and degradability | Not rapidly degradable |
| SOLVENT 1-METHOXY-2-PROPANOL107-98-2 | |
| Persistence and degradability | Not rapidly degradable |

12.3. Bioaccumulative potential

| ethylbenzene100-41-4 | |
|---|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.15 Source: HSDB |
| Light aromatic naphtha (petroleum) solvent64742-95-6 | |
| Partition coefficient n-octanol/water (Log Pow) | 2.1 – 6 Source: IUCLID |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025




SECTION 13: Disposal considerations

| | |
|--|--|
| Regional waste regulation | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010. |
| Waste treatment methods | : Must follow special treatment according to local regulation. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. |
| Additional information | : Flammable vapours may accumulate in the container. Do not re-use empty containers. |

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT | IMDG | IATA |
|---|---|---|
| UN number | | |
| 1263 | 1263 | 1263 |
| UN Proper Shipping Name | | |
| TINTA | PAINT | Paint |
| Transport document description | | |
| Not applicable | UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (31°C c.c.) | UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS |
| Transport hazard class(es) | | |
| 3 | 3 | 3 |
| Danger labels | | |
| 3 | 3 | 3 |
|  |  |  |
| Subsidiary risk | | |
| Not applicable | Not applicable | Not applicable |
| Risk Number | | |
| 30 | Not applicable | Not applicable |
| Packing group | | |
| III | III | III |
| Special provisions | | |
| 163,223,367 | 163,223,367,955 | A3,A72,A192 |
| Dangerous for the environment | | |
| Yes | Yes | Yes |

14.2 Other informations

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

13/14

WEGPOXI CVD 32 3 R BEGE METSO COMPONENT A

13473035

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/14/2025

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations : Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

SECTION 16: Other information

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

14/14