

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 9/11/2024 Revision date: 2/20/2026 Version: 5.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT
Product code : 16111605
Type of product : Paint
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Acute toxicity (oral), Category 5
Acute toxicity (dermal), Category 5
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2
Skin sensitisation, Category 1
Carcinogenicity, Category 2
Reproductive toxicity, Category 1B
Hazardous to the aquatic environment - Acute Hazard, Category 1
Hazardous to the aquatic environment - Chronic Hazard, Category 1

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H303+H313 - May be harmful if swallowed or in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer.
H360 - May damage fertility or the unborn child.
H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS BR)
: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	CAS-No.: 25068-38-6	60 – 80	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Quartz(SiO ₂)	CAS-No.: 14808-60-7	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
ALUMINIUM SILICATE	CAS-No.: 1327-36-2	5 – 10	Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation:dust,mist), H332
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2	1 – 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
MICA	CAS-No.: 12001-26-2	1 – 5	Eye Irrit. 2B, H320 Skin Sens. 1, H317
4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK	CAS-No.: 108-10-1	1 – 5	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
			Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 2, H305

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensitivity problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause an allergic skin reaction. Causes serious eye irritation.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: Suspected carcinogen. May damage fertility. May damage the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire	: Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions	: Get the package away from the fire if this can be done without risk. Fight fire from a safe

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Protection during firefighting

Other information

- distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
- : Use self-contained breathing apparatus and chemically protective clothing.
- : In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

- : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment

Emergency procedures

- : Wear recommended personal protective equipment.
- : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment

Emergency procedures

- : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
- : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Very toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment

Methods for cleaning up

- : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

- : Flammable vapours may accumulate in the container.
- : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

5/13

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials : combustible materials.

Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

Skin and body protection:

Long sleeved protective clothing. Or chemical resistant apron. Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

Colour : Colourless

Odour : characteristic

Odour threshold : Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

pH	: Not applicable
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 60 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1.25 – 1.45 g/cm³
Solubility	: Material insoluble in water. Water: Material insoluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 90 – 110 ku/kg
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

Quartz(SiO2)14808-60-7

Boiling point	2230 °C Source: GESTIS
---------------	------------------------

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6

Boiling point	> 260 °C
Flash point	> 249 °C

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.68609-97-2

Flash point	159 °C Source: ECHA
-------------	---------------------

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1

Boiling point	116.5 °C Source: CHemIDplus
Flash point	14 °C Source: ICSC
Auto-ignition temperature	460 °C Source: ICSC
Vapour pressure	2.1 kPa at 20°C Source: ICSC

MICA12001-26-2

Vapour pressure	0 mm Hg Source: HSDB
-----------------	----------------------

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed.
Acute toxicity (dermal)	: May be harmful in contact with skin.
Acute toxicity (inhalation)	: Not available

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

ATE BR (oral)	3261.53 mg/kg bodyweight
ATE BR (dermal)	3423.749 mg/kg bodyweight

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg Source: CHEMIDPLUS

ALUMINIUM SILICATE (1327-36-2)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 2.07 mg/l Source: ECHA

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat	17100 mg/kg Source: Corporate Solution From Thomson Micromedex
LC50 Inhalation - Rat (Dust/Mist)	5 mg/l

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
---------------------------	---

Quartz(SiO2) (14808-60-7)

pH	7
----	---

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

pH	4.5 – 4.7
----	-----------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

ALUMINIUM SILICATE (1327-36-2)

pH	4 – 8 Source: GESTIS
----	----------------------

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable

Quartz(SiO2) (14808-60-7)

pH	7
----	---

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

pH	4.5 – 4.7
----	-----------

ALUMINIUM SILICATE (1327-36-2)

pH	4 – 8 Source: GESTIS
----	----------------------

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not available
Carcinogenicity : Suspected of causing cancer.

Quartz(SiO2) (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

NOAEL (animal/female, F0/P)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)
-----------------------------	---

NOAEL (animal/female, F1)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)
---------------------------	---

Reproductive toxicity : May damage fertility or the unborn child.
STOT-single exposure : Not available

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not available

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK (108-10-1)

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	--

Aspiration hazard : Not available

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

Viscosity, kinematic	1.874 – 2.658 mm²/s
----------------------	---------------------

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause an allergic skin reaction. Causes serious eye irritation.
Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Symptoms/effects after eye contact	: dry.
Symptoms/effects after ingestion	: stinging. Redness. Causes serious eye irritation. redness, itching, tears. : May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: Suspected carcinogen. May damage fertility. May damage the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6

LC50 - Fish [1]	1.41 mg/l Source: National Institute of Technology and Evaluation
EC50 - Crustacea [1]	1.7 mg/l Source: NITE

ALUMINIUM SILICATE1327-36-2

LC50 - Fish [1]	10000 mg/l Source: ECHA
-----------------	-------------------------

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.68609-97-2

LC50 - Fish [1]	0.002 mg/l Source: Ecological Structure Activity Relationships
EC50 96h - Algae [1]	0.003 mg/l Source: Ecological Structure Activity Relationships

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1

LC50 - Fish [1]	672 mg/l Source: ECHA
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Quartz(SiO2)14808-60-7

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

ALUMINIUM SILICATE1327-36-2

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.68609-97-2

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK108-10-1

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

MICA12001-26-2

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

12.3. Bioaccumulative potential

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane 25068-38-6

Partition coefficient n-octanol/water (Log Pow)	2821 Source: National Institute of Technology and Evaluation
---	--

4-Methyl-2-pentanone ; Methylisobutyl ketone, MIBK 108-10-1

Partition coefficient n-octanol/water (Log Pow)	1.31 Source: ChemIDPlus
---	-------------------------

12.4. Mobility in soil

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2

Mobility in soil	12830 Source: Quantitative Structure Activity Relation
------------------	--

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1263	1263	1263
UN Proper Shipping Name		
TINTA	PAINT	Paint
Transport document description		
Not applicable	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (60°C c.c.)	UN 1263 Paint, 3, III
Transport hazard class(es)		
3	3	3
Danger labels		
3	3	3
		

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

11/13

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

		
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
30	Not applicable	Not applicable
Packing group		
III	III	III
Special provisions		
163,223,367	163,223,367,955	A3,A72,A192
Dangerous for the environment		
Yes	Yes	Yes

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

CLEAR 76 WET SURFACE N2680 LC 00000 A COMPONENT

16111605

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net