

WEGPOXI N2912 B COMPONENT

Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 11/14/2023 Revision date: 4/13/2026 Version: 13.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : WEGPOXI N2912 B COMPONENT
Product code : 13387413
Type of product : Catalyst
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Uses in coatings - Curing agent for component A.

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Acute toxicity (oral), Category 4
Acute toxicity (dermal), Category 4
Acute toxicity (inhalation:dust,mist) Category 4
Skin corrosion/irritation, Category 1A
Skin sensitisation, Category 1
Germ cell mutagenicity, Category 1A
Carcinogenicity, Category 1A
Specific target organ toxicity — Repeated exposure, Category 2
Hazardous to the aquatic environment - Acute Hazard, Category 3
Hazardous to the aquatic environment - Chronic Hazard, Category 3

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H340 - May cause genetic defects.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

Precautionary statements (GHS BR)

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P310 - Immediately call a POISON CENTER or a doctor.
P312 - Call a POISON CENTER or a doctor if you feel unwell.
P314 - Get medical advice or attention as appropriate.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
4,4'-METHYLENEBISCYCLOHEXYLAMINE	CAS-No.: 1761-71-3	40 – 50	Acute Tox. 4 (Oral), H302 Acute Tox. 5 (Dermal), H313 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	CAS-No.: 6864-37-5	10 – 20	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Inhalation), H331 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1A, H314 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED	CAS-No.: 135108-88-2	5 – 10	Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic 3, H412
Cyclohex-1,2-ylenediamine	CAS-No.: 694-83-7	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Industrial secret	-	5 – 10	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1A, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
FURFURYL ALCOHOL	CAS-No.: 98-00-0	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
SOLVENT BENZYL ALCOHOL	CAS-No.: 100-51-6	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	CAS-No.: 90-72-2	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
SOLVENT METHYL ISOBUTYL KETONE	CAS-No.: 108-10-1	1 – 5	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 2, H305

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
Nafta solvente (petróleo), aromático leve	CAS-No.: 64742-95-6	0.5 – 1	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting because of corrosive effects.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Swallowing a small quantity of this material presents some health hazard. Causes severe skin burns and eye damage. May cause an allergic skin reaction.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Harmful in contact with skin. Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering). Cracking of the skin.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye burns. May cause destruction of eye tissue.
Symptoms/effects after ingestion	: Harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. The vapours are denser than air and may travel along the
-------------	---

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Explosion hazard : ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. In case of fire, corrosive gases come free.
: Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.

Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Other information : On exposure to high temperature, may decompose, releasing toxic gases. In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.

Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment : Prevent dispersion by moistening spill with water or foam. Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Clear up rapidly by scoop or vacuum. Absorb spillage to prevent material damage. Take up liquid spill into absorbent material.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Flammable vapours may accumulate in the container.

Precautions for safe handling

: Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not eat, drink or smoke when using this product. When heated, material emits highly irritating vapours, affecting the eyes. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures

: Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials

: combustible materials.

Packaging materials

: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

FURFURYL ALCOHOL 98-00-0

USA - OSHA - Occupational Exposure Limits

Local name	Furfuryl alcohol
OSHA PEL TWA	200 mg/m ³ 50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Corrosionproof clothing.

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Skin and body protection:

Long sleeved protective clothing. Or chemical resistant apron. Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless
Odour	: characteristic
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 60 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 0.95 – 1.05 g/cm³
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2

Boiling point	130 – 135 °C
Flash point	≥ 160 °C
Vapour pressure	0.075 mm Hg

FURFURYL ALCOHOL98-00-0

Boiling point	171 °C Source: ICSC
---------------	---------------------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

4,4'-METHYLENEBISCYCLOHEXYLAMINE1761-71-3

Boiling point	320 °C
Flash point	> 93.3 °C

Cyclohex-1,2-ylenediamine694-83-7

Boiling point	183 °C
Flash point	75 °C
Vapour pressure	0.407 mm Hg

FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2

Boiling point	220 °C
Flash point	> 200 °C
Vapour pressure	0.055 Pa

Nafta solvente (petróleo), aromático leve64742-95-6

Boiling point	135 – 210 °C Source: NLM
Flash point	< 41 °C Source: IUCLID
Vapour pressure	8 hPa at 20°C Source: IUCLID

SOLVENT METHYL ISOBUTYL KETONE108-10-1

Boiling point	116.5 °C Source: CHemIDplus
Flash point	14 °C Source: ICSC
Auto-ignition temperature	460 °C Source: ICSC
Vapour pressure	2.1 kPa at 20°C Source: ICSC

SOLVENT BENZYL ALCOHOL100-51-6

Boiling point	205 °C
Flash point	93 °C
Auto-ignition temperature	436 °C
Vapour pressure	13.2 Pa at 20°C Source: ICSC

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)6864-37-5

Boiling point	342 °C
Flash point	175 – 176 °C
Auto-ignition temperature	280 – 285 °C
Vapour pressure	0.08 Pa

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

WEGPOXI N2912 B COMPONENT

ATE BR (oral)	504.532 mg/kg bodyweight
ATE BR (dermal)	1116.379 mg/kg bodyweight
ATE BR (dust,mist)	2.105 mg/l/4h

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)

LD50 oral rat	1200 mg/kg
LD50 dermal rat	1280 mg/kg

4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

LD50 oral rat	1000 mg/kg Source: EU ICLID
LD50 dermal rabbit	2110 mg/kg

Cyclohex-1,2-ylenediamine (694-83-7)

LD50 oral rat	4556 mg/kg Source: National Library of Medicine
LD50 dermal rat	1870 mg/kg bodyweight
LC50 Inhalation - Rat	1230 mg/l

Nafta solvente (petróleo), aromático leve (64742-95-6)

LD50 oral rat	8400 mg/kg Source: RTECS
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	5.16 mg/l Source: ECHA

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

SOLVENT BENZYL ALCOHOL (100-51-6)

LD50 oral rat	1610 mg/kg Source: OECD SIDS
LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	> 4.178 mg/l

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine) (6864-37-5)

LD50 oral rat	550 mg/kg
LD50 dermal rabbit	200 mg/kg
LC50 Inhalation - Rat	0.42 mg/l

Skin corrosion/irritation : Causes severe skin burns.

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)

pH	11
----	----

4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

pH	11.6
----	------

Cyclohex-1,2-ylenediamine (694-83-7)

pH	11.3
----	------

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine) (6864-37-5)

pH	11
----	----

Serious eye damage/irritation : Assumed to cause serious eye damage

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)

pH	11
----	----

4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)

pH	11.6
----	------

Cyclohex-1,2-ylenediamine (694-83-7)

pH	11.3
----	------

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine) (6864-37-5)

pH	11
----	----

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

FURFURYL ALCOHOL (98-00-0)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

SOLVENT METHYL ISOBUTYL KETONE (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not available

STOT-single exposure : Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

FURFURYL ALCOHOL (98-00-0)	
STOT-single exposure	May cause respiratory irritation.
Cyclohex-1,2-ylenediamine (694-83-7)	
STOT-single exposure	May cause respiratory irritation.
Nafta solvente (petróleo), aromático leve (64742-95-6)	
STOT-single exposure	May cause respiratory irritation.
SOLVENT METHYL ISOBUTYL KETONE (108-10-1)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.	
FURFURYL ALCOHOL (98-00-0)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
4,4'-METHYLENEBISCYCLOHEXYLAMINE (1761-71-3)	
NOAEL (subacute, oral, animal/male, 28 days)	15 mg/kg bodyweight
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED (135108-88-2)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Industrial secret	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
SOLVENT METHYL ISOBUTYL KETONE (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
SOLVENT BENZYL ALCOHOL (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
Aspiration hazard : Not available	
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (90-72-2)	
Viscosity, kinematic	154.639 mm²/s
Nafta solvente (petróleo), aromático leve (64742-95-6)	
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'
SOLVENT BENZYL ALCOHOL (100-51-6)	
Viscosity, kinematic	4.851 mm²/s
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine) (6864-37-5)	
Viscosity, kinematic	126.316 mm²/s

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled.
Swallowing a small quantity of this material presents some health hazard. Causes severe

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Symptoms/effects after inhalation	: skin burns and eye damage. May cause an allergic skin reaction. : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Harmful in contact with skin. Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering). Cracking of the skin.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye burns. May cause destruction of eye tissue.
Symptoms/effects after ingestion	: Harmful if swallowed. Ingestion may cause nausea and vomiting. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects. Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2

LC50 - Fish [1]	447.821 mg/l
EC50 96h - Algae [1]	34.812 mg/l Source: ECOSAR

4,4'-METHYLENEBISCYCLOHEXYLAMINE1761-71-3

LC50 - Fish [1]	46 – 100 mg/l Source: IUCLID
-----------------	------------------------------

Cyclohex-1,2-ylenediamine694-83-7

LC50 - Fish [1]	524.851 mg/l Source: Ecological Structure Activity Relationships
EC50 96h - Algae [1]	29.551 mg/l Source: Ecological Structure Activity Relationships

FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2

LC50 - Fish [1]	63 mg/l
EC50 - Crustacea [1]	15.4 mg/l
EC50 72h - Algae [1]	43.9 mg/l

Nafta solvente (petróleo), aromático leve64742-95-6

LC50 - Fish [1]	9.22 mg/l Source: IUCLID
EC50 - Crustacea [1]	6.14 mg/l Source: IUCLID
EC50 72h - Algae [1]	19 mg/l Source: IUCLID

SOLVENT METHYL ISOBUTYL KETONE108-10-1

LC50 - Fish [1]	672 mg/l Source: ECHA
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna

SOLVENT BENZYL ALCOHOL100-51-6

LC50 - Fish [1]	10 mg/l
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Raphidocelis subcapitata (previous names:

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

SOLVENT BENZYL ALCOHOL100-51-6	
	Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76.828 mg/l Test organisms (species): other:
NOEC chronic fish	48.897 mg/l Test organisms (species): other: Duration: '30 d'
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)6864-37-5	
EC50 - Crustacea [1]	4.6 mg/l

12.2. Persistence and degradability

WEGPOXI N2912 B COMPONENT	
Persistence and degradability	Not rapidly degradable
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2	
Persistence and degradability	Not rapidly degradable
FURFURYL ALCOHOL98-00-0	
Persistence and degradability	Not rapidly degradable
4,4'-METHYLENEBISCYCLOHEXYLAMINE1761-71-3	
Persistence and degradability	Not rapidly degradable
Cyclohex-1,2-ylenediamine694-83-7	
Persistence and degradability	Not rapidly degradable
FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED135108-88-2	
Persistence and degradability	Not rapidly degradable
Nafta solvente (petróleo), aromático leve64742-95-6	
Persistence and degradability	Not rapidly degradable
Industrial secret	
Persistence and degradability	Not rapidly degradable
SOLVENT METHYL ISOBUTYL KETONE108-10-1	
Persistence and degradability	Not rapidly degradable
SOLVENT BENZYL ALCOHOL100-51-6	
Persistence and degradability	Not rapidly degradable
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)6864-37-5	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL90-72-2	
Partition coefficient n-octanol/water (Log Pow)	0.77
4,4'-METHYLENEBISCYCLOHEXYLAMINE1761-71-3	
Partition coefficient n-octanol/water (Log Pow)	3.26
Cyclohex-1,2-ylenediamine694-83-7	
Partition coefficient n-octanol/water (Log Pow)	0.09

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Nafta solvente (petróleo), aromático leve64742-95-6

Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID

SOLVENT METHYL ISOBUTYL KETONE108-10-1

Partition coefficient n-octanol/water (Log Pow) 1.31 Source: ChemIDPlus

SOLVENT BENZYL ALCOHOL100-51-6

Partition coefficient n-octanol/water (Log Pow) 1.1

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)6864-37-5

Partition coefficient n-octanol/water (Log Pow) 2.5

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available
Other adverse effects : May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

SECTION 13: Disposal considerations

Waste treatment methods : Must follow special treatment according to local regulation.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1263	1263	1263
UN Proper Shipping Name		
MATERIAL RELACIONADO COM TINTAS	PAINT RELATED MATERIAL	Paint related material
Transport document description		
Not applicable	UN 1263 PAINT RELATED MATERIAL, 3, III (60°C c.c.)	UN 1263 Paint related material, 3, III
Transport hazard class(es)		
3	3	3
Danger labels		
3	3	3
		

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
30	Not applicable	Not applicable
Packing group		
III	III	III
Special provisions		
163,223,367	163,223,367,955	A3,A72,A192
Dangerous for the environment		
No	No	No

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI N2912 B COMPONENT

13387413

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 4/13/2026

BLV - Biological limit value

TRGS - Technical Rules for Hazardous Substances

TLM - Median Tolerance Limit

IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

17/17