

# LACKPOXI N 1198 R T WHITE COMPONENT A

## Safety Data Sheet

According to ABNT NBR 14725: 2023  
Issue date: 4/24/2025 Revision date: 5/28/2025 Version: 2.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : LACKPOXI N 1198 R T WHITE COMPONENT A  
Product code : 14475463  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

<b>24-HOUR EMERGENCY - AMBIPAR</b>	0800 117 2020		
<b>CHEMTREC international number</b>	+1-703-527-3887 e 1-800-424-9300		
<b>Country</b>	<b>City</b>	<b>Local Number</b>	<b>Toll-Free Number</b>
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
Russia			8(800)100-63-46
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 1  
Germ cell mutagenicity, Category 1B  
Carcinogenicity, Category 1B  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Repeated exposure, Category 2  
Aspiration hazard, Category 1  
Hazardous to the aquatic environment - Acute Hazard, Category 2  
Hazardous to the aquatic environment - Chronic Hazard, Category 2

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P310 - Immediately call a POISON CENTER or a doctor.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
MIXED XYLENES	CAS-No.: 1330-20-7	10 – 20	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
ethylbenzene	CAS-No.: 100-41-4	5 – 10	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
SOLVENT ISOBUTHANOL	CAS-No.: 78-83-1	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
Light aromatic naphtha (petroleum) solvent	CAS-No.: 64742-95-6	1 – 5	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
FORMALDEHYDE DO UREA RPW, BUTYLATED	CAS-No.: 68002-19-7	1 – 5	Aquatic Chronic 4, H413
SOLVENT 1-METHOXY-2-PROPANOL	CAS-No.: 107-98-2	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336
SOLVENT BUTANOL	CAS-No.: 71-36-3	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6	1 – 5	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313
HEAVY AROMATIC NAPHTA	CAS-No.: 64742-94-5	0.5 – 1	Flam. Liq. 4, H227 Acute Tox. 5 (Dermal), H313 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.

### 4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May cause severe burns. Causes serious eye damage. May cause respiratory irritation. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering). Causes severe burns.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye damage. redness, itching, tears.

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema.

Chronic symptoms : May cause cancer. May cause heritable genetic damage.

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical, CO<sub>2</sub>, or water spray or regular foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.

Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

### 5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.

Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Other information : In case of fire, corrosive and harmful gases come free.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

#### 6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.

Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Harmful to aquatic life. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. When heated, material emits highly irritating vapours, affecting the eyes. Do not get in eyes, on skin, or on clothing. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.
- Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- Incompatible materials : combustible materials.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

MIXED XYLENES 1330-20-7	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

<b>MIXED XYLENES 1330-20-7</b>	
OSHA PEL TWA	435 mg/m <sup>3</sup> 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>ethylbenzene 100-41-4</b>	
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Ethyl benzene
OSHA PEL TWA	435 mg/m <sup>3</sup> 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>SOLVENT ISOBUTHANOL 78-83-1</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Isobutanol
ACGIH® TLV® TWA	50 ppm
Remark (ACGIH)	TLV® Basis: Skin & eye irr
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Isobutyl alcohol
OSHA PEL TWA	300 mg/m <sup>3</sup> 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>SOLVENT BUTANOL 71-36-3</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butanol
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	n-Butyl alcohol
OSHA PEL TWA	300 mg/m <sup>3</sup> 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>SOLVENT 1-METHOXY-2-PROPANOL 107-98-2</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	1-Methoxy-2-propanol
ACGIH® TLV® TWA	50 ppm
ACGIH® TLV® STEL	100 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SOLVENT 1-METHOXY-2-PROPANOL 107-98-2

Regulatory reference	ACGIH 2024
----------------------	------------

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

#### Eye protection:

Wear closed safety glasses

#### Skin and body protection:

Safety shoes

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white
Odour	: characteristic
Odour threshold	: Not available
pH	: Not applicable
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 31 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1.35 – 1.45 g/cm <sup>3</sup>

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)



# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

Solubility	: Material insoluble in water. Water: Material insoluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 95 – 105 ku/kg
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

### MIXED XYLENES1330-20-7

Boiling point	139.6 °C
Flash point	30 °C (ASTM D 93)
Auto-ignition temperature	488 °C
Vapour pressure	4.8 kPa 55°C

### ethylbenzene100-41-4

Boiling point	136.1 °C Atm. press.: 1013,3 mBar Decomposition: 'no'
Flash point	23 °C Atm. press.: 1013 hPa
Auto-ignition temperature	432 °C Source: ICSC
Vapour pressure	9.52 mbar Temp.: 20 °C

### Light aromatic naphtha (petroleum) solvent64742-95-6

Boiling point	165.5 (156 – 175) °C
Flash point	40 °C
Vapour pressure	≤ 240 kPa Temp.: 37,8 °C

### SOLVENT BUTANOL71-36-3

Flash point	36 °C
-------------	-------

### SOLVENT 1-METHOXY-2-PROPANOL107-98-2

Flash point	31 °C
-------------	-------

### 2-methoxy-1-methylethyl acetate108-65-6

Boiling point	145.8 °C Atm. press.: 760 mm Hg Decomposition: 'no'
Flash point	45.5 °C Atm. press.: 101,3 kPa
Auto-ignition temperature	315 °C Source: International Uniform Chemical Information Database
Vapour pressure	3.75 mm Hg Source: National Institute of Technology and Evaluation

### HEAVY AROMATIC NAPHTHA64742-94-5

Boiling point	174 – 193 °C
---------------	--------------

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### HEAVY AROMATIC NAPHTHA64742-94-5

Flash point	65 °C
Auto-ignition temperature	461 °C
Vapour pressure	4100 Pa Temp.: 25 °C

### 9.2. Data relevant with regard to physical hazard classes

No additional information available

### 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available

#### MIXED XYLENES (1330-20-7)

LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
--------------------	---

#### ethylbenzene (100-41-4)

LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm Source: ECHA, Harmonized classification of EU CLP

#### Light aromatic naphtha (petroleum) solvent (64742-95-6)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	5.16 mg/l Source: ECHA

#### 2-methoxy-1-methylethyl acetate (108-65-6)

LD50 oral rat	8532 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### 2-methoxy-1-methylethyl acetate (108-65-6)

LD50 dermal rabbit	> 5000 mg/kg Source: International Uniform Chemical Information Database
--------------------	--

### HEAVY AROMATIC NAPHTA (64742-94-5)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:
-----------------	---

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
--------------------	---

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### MIXED XYLENES (1330-20-7)

pH	7
----	---

### SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

pH	4 – 8
----	-------

Serious eye damage/irritation : Causes serious eye damage.  
pH: Not applicable

### MIXED XYLENES (1330-20-7)

pH	7
----	---

### SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

pH	4 – 8
----	-------

Respiratory or skin sensitisation : Not available  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

### MIXED XYLENES (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

### ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### HEAVY AROMATIC NAPHTA (64742-94-5)

NOAEL (animal/male, F0/P)	35 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
---------------------------	---

NOAEL (animal/female, F0/P)	125 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
-----------------------------	--

Reproductive toxicity : Not available  
STOT-single exposure : May cause respiratory irritation.

### MIXED XYLENES (1330-20-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### SOLVENT ISOBUTHANOL (78-83-1)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

### SOLVENT BUTANOL (71-36-3)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SOLVENT 1-METHOXY-2-PROPANOL (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### MIXED XYLENES (1330-20-7)

LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
----------------------------	---

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

### ethylbenzene (100-41-4)

NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
----------------------------	--

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

### 2-methoxy-1-methylethyl acetate (108-65-6)

NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

### HEAVY AROMATIC NAPHTHA (64742-94-5)

LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
--	---

NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
--	--

Aspiration hazard : May be fatal if swallowed and enters airways.

### LACKPOXI N 1198 R T WHITE COMPONENT A

Viscosity, kinematic	1.979 – 2.349 mm <sup>2</sup> /s
----------------------	----------------------------------

### MIXED XYLENES (1330-20-7)

Viscosity, kinematic	≈ 0.76 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
----------------------	--

### Light aromatic naphtha (petroleum) solvent (64742-95-6)

Viscosity, kinematic	< 1 mm <sup>2</sup> /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
----------------------	---

### 2-methoxy-1-methylethyl acetate (108-65-6)

Viscosity, kinematic	1.182 mm <sup>2</sup> /s
----------------------	--------------------------

## 11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May cause severe burns. Causes serious eye damage. May cause respiratory irritation. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering). Causes severe burns.
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye damage. redness, itching, tears.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Risk of lung oedema.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

<b>MIXED XYLENES1330-20-7</b>	
LC50 - Fish [1]	≈ 2.6 mg/l
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
ErC50 algae	≈ 2.2 mg/l
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
<b>ethylbenzene100-41-4</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
<b>Light aromatic naphtha (petroleum) solvent64742-95-6</b>	
LC50 - Fish [1]	9.22 mg/l Source: IUCLID
EC50 - Crustacea [1]	6.14 mg/l Source: IUCLID
EC50 72h - Algae [1]	19 mg/l Source: IUCLID
<b>2-methoxy-1-methylethyl acetate108-65-6</b>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
<b>HEAVY AROMATIC NAPHTA64742-94-5</b>	
LC50 - Fish [1]	0.58 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	0.76 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	2.9 mg/l Test organisms (species): other:
LC50 - Fish [2]	6.1 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### HEAVY AROMATIC NAPHTHA64742-94-5

gairdneri)

## 12.2. Persistence and degradability

### LACKPOXI N 1198 R T WHITE COMPONENT A

Persistence and degradability Not rapidly degradable

### MIXED XYLENES1330-20-7

Persistence and degradability Not rapidly degradable

### ethylbenzene100-41-4

Persistence and degradability Not rapidly degradable

### Light aromatic naphtha (petroleum) solvent64742-95-6

Persistence and degradability Not rapidly degradable

### SOLVENT ISOBUTHANOL78-83-1

Persistence and degradability Not rapidly degradable

### FORMALDEHYDE DO UREA RPW, BUTYLATED68002-19-7

Persistence and degradability Not rapidly degradable

### SOLVENT BUTANOL71-36-3

Persistence and degradability Not rapidly degradable

### SOLVENT 1-METHOXY-2-PROPANOL107-98-2

Persistence and degradability Not rapidly degradable

### 2-methoxy-1-methylethyl acetate108-65-6

Persistence and degradability Not rapidly degradable

### HEAVY AROMATIC NAPHTHA64742-94-5

Persistence and degradability Not rapidly degradable

## 12.3. Bioaccumulative potential

### ethylbenzene100-41-4

Partition coefficient n-octanol/water (Log Pow) 3.15 Source: HSDB

### Light aromatic naphtha (petroleum) solvent64742-95-6

Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID

### 2-methoxy-1-methylethyl acetate108-65-6

Partition coefficient n-octanol/water (Log Pow) 0.43 Source: International Uniform Chemical Information Database

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Hazardous to the ozone layer

: Not available

Other adverse effects

: May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025




### SECTION 13: Disposal considerations

Regional waste regulation	: Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

### SECTION 14: Transport information

#### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
<b>UN number</b>		
1263	1263	1263
<b>UN Proper Shipping Name</b>		
TINTA	PAINT	Paint
<b>Transport document description</b>		
Not applicable	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (31°C c.c.)	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS
<b>Transport hazard class(es)</b>		
3	3	3
<b>Danger labels</b>		
3	3	3
		
<b>Subsidiary risk</b>		
Not applicable	Not applicable	Not applicable
<b>Risk Number</b>		
30	Not applicable	Not applicable
<b>Packing group</b>		
III	III	III
<b>Special provisions</b>		
163,223,367	163,223,367,955	A3,A72,A192
<b>Dangerous for the environment</b>		
Yes	Yes	Yes

#### 14.2 Other informations

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# LACKPOXI N 1198 R T WHITE COMPONENT A

14475463

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 5/28/2025

### SECTION 15: Regulatory information

#### 15.1. National regulations

Brazil Local Regulations : Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

### SECTION 16: Other information

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)