

LACKTHERM 1319 WAT H

Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 9/5/2022 Revision date: 1/16/2026 Version: 13.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : LACKTHERM 1319 WAT H
Product code : 10001660
Type of product : Varnish
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Impregnation

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Acute toxicity (oral), Category 5

Acute toxicity (inhalation:vapour) Category 4

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)

:



Signal word (GHS BR)

: Warning

Hazard statements (GHS BR)

: H303 - May be harmful if swallowed

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

Precautionary statements (GHS BR)

: P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or a doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice or attention.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards which do not result in classification

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
SOLVENT BUTYL GLYCOL (N)	CAS-No.: 111-76-2	10 – 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 5 (Dermal), H313 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
TRIETHYLAMINE	CAS-No.: 121-44-8	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Skin Corr. 1, H314 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Seek medical attention immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: Harmful if inhaled. Causes serious eye irritation.
Symptoms/effects after inhalation	: May cause headache, nausea and irritation of respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Causes serious eye irritation. stinging. redness, itching, tears.
Symptoms/effects after ingestion	: May be harmful if swallowed. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).
Unsuitable extinguishing media	: Do not use a heavy water stream.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

5.2. Specific hazards arising from the chemical

- Fire hazard : In case of fire and/or explosion do not breathe fumes.
- Explosion hazard : No direct explosion hazard.

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
- Other information : On exposure to high temperature, may decompose, releasing toxic gases. In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

- Protective equipment : Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Collect leaking and spilled liquid in sealable containers as far as possible. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Keep only in original container. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.
- Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep cool. Protect from sunlight.
- Packaging materials : Always store product in container of same material as original container.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TRIETHYLAMINE 121-44-8

USA - OSHA - Occupational Exposure Limits

Local name	Triethylamine
OSHA PEL TWA	100 mg/m ³
	25 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Materials for protective clothing:

Use protective apron

Hand protection:

Protective gloves made of PVC

Eye protection:

Wear closed safety glasses

Skin and body protection:

It is recommended the use of apron barber type to protecting upper limbs, trunk and lower limbs in case of splash. Safety shoes

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

Colour	: Levemente amarelo
Odour	: characteristic
Odour threshold	: Not available
pH	: 8 – 10
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 100 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1 – 1.04 g/cm ³
Solubility	: In water, material soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: 230 °C
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 15 – 17 Seconds à 25°C - CF4
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

TRIETHYLAMINE121-44-8

Boiling point	88 – 90 °C at 1013 hPa Source: ECHA
Flash point	-11 °C Source: ICSC
Auto-ignition temperature	230 °C Source: HSDB
Vapour pressure	7.2 kPa at 20°C Source: ICSC

SOLVENT BUTYL GLYCOL (N)111-76-2

Boiling point	168.4 °C Source: HSDB
Flash point	63 °C Source: ECHA
Auto-ignition temperature	230 °C Source: ECHA
Vapour pressure	0.88 mm Hg at 25°C Source: hSDB

9.2. Data relevant with regard to physical hazard classes

VOC Total (g/l)	: 165.08 g/l
VOC Total (lb/gal)	: 1.38 lb/gal

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: On exposure to high temperature, may decompose, releasing corrosive gases.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

Incompatible materials	: Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed.
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Inhalation:vapour: Harmful if inhaled.

LACKTHERM 1319 WAT H

ATE BR (oral)	2870.066 mg/kg bodyweight
ATE BR (vapours)	16.544 mg/l/4h

TRIETHYLAMINE (121-44-8)

LD50 oral rat	730 mg/kg Source: ECHA
LD50 dermal rabbit	580 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	3496 ppm Source: ECHA

SOLVENT BUTYL GLYCOL (N) (111-76-2)

LD50 dermal rat	> 2000 mg/kg Source: ECHA
-----------------	---------------------------

Skin corrosion/irritation	: Causes skin irritation. pH: 8 – 10
---------------------------	---

TRIETHYLAMINE (121-44-8)

pH	12.5 Source: ECHA
----	-------------------

Serious eye damage/irritation	: Causes serious eye irritation. pH: 8 – 10
-------------------------------	--

TRIETHYLAMINE (121-44-8)

pH	12.5 Source: ECHA
----	-------------------

Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not available

SOLVENT BUTYL GLYCOL (N) (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not available
STOT-single exposure	: Not available
STOT-repeated exposure	: Not available
Aspiration hazard	: Not available

LACKTHERM 1319 WAT H

Viscosity, kinematic	14.423 – 17 mm ² /s
----------------------	--------------------------------

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Harmful if inhaled. Causes serious eye irritation.
Symptoms/effects after inhalation	: May cause headache, nausea and irritation of respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Causes serious eye irritation. stinging. redness, itching, tears.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

Symptoms/effects after ingestion : May be harmful if swallowed. Ingestion may cause nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

TRIETHYLAMINE¹²¹⁻⁴⁴⁻⁸

LC50 - Fish [1]	24 mg/l Source: ECHA
EC50 72h - Algae [1]	8 mg/l Source: ECHA

SOLVENT BUTYL GLYCOL (N)¹¹¹⁻⁷⁶⁻²

LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
EC50 72h - Algae [1]	911 mg/l Source: ECHA

12.2. Persistence and degradability

LACKTHERM 1319 WAT H

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

TRIETHYLAMINE¹²¹⁻⁴⁴⁻⁸

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

SOLVENT BUTYL GLYCOL (N)¹¹¹⁻⁷⁶⁻²

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

TRIETHYLAMINE¹²¹⁻⁴⁴⁻⁸

Partition coefficient n-octanol/water (Log Pow)	1.45 Source: HSDB
---	-------------------

SOLVENT BUTYL GLYCOL (N)¹¹¹⁻⁷⁶⁻²

Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA
---	-------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Waste treatment methods : Must follow special treatment according to local regulation.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
Not regulated for transport		
UN Proper Shipping Name		
Not regulated	Not regulated	Not regulated
Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
Danger labels		
Not regulated	Not regulated	Not regulated
Subsidiary risk		
Not regulated	Not regulated	Not regulated
Risk Number		
Not regulated	Not regulated	Not regulated
Packing group		
Not regulated	Not regulated	Not regulated
Special provisions		
Not regulated	Not regulated	Not regulated
Dangerous for the environment		
Not regulated	Not regulated	Not regulated

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1319 WAT H

10001660

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/16/2026

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net