

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 4/24/2025 Revision date: 1/30/2026 Version: 2.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-THANE SRD 50 1 R ALUMINUM A COMPONENT  
Product code : 14787355  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating providing surfaces with protection, waterproofing, finishing and resistance, etc.

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |
| Germany                              |             |                                  | 0800-181-7059           |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Skin corrosion/irritation, Category 2  
Germ cell mutagenicity, Category 1B  
Carcinogenicity, Category 1B  
Specific target organ toxicity — Repeated exposure, Category 2  
Aspiration hazard, Category 1  
Hazardous to the aquatic environment - Acute Hazard, Category 2  
Hazardous to the aquatic environment - Chronic Hazard, Category 2

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects  
Precautionary statements (GHS BR) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
P302+P352 - IF ON SKIN: Wash with plenty of water.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.  
Rinse skin with water .  
P308+P313 - IF exposed or concerned: Get medical advice or attention.  
P314 - Get medical advice or attention as appropriate.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                  | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------|------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% | CAS-No.: 1330-20-7     | 10 – 20       | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 3, H412 |
| n-butyl acetate                                                       | CAS-No.: 123-86-4      | 10 – 20       | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412                                                                                                                                                                                                         |
| ISOPENTYL ACETATE                                                     | CAS-No.: 123-92-2      | 10 – 20       | Flam. Liq. 3, H226<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412                                                                                                                                                                                                                            |
| SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM                                | CAS-No.: 64742-95-6    | 5 – 10        | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Muta. 1B, H340<br>Carc. 1B, H350<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411                                                                    |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

| Name                                                 | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                            |
|------------------------------------------------------|------------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sec-butyl acetate                                    | CAS-No.: 105-46-4      | 1 – 5         | Flam. Liq. 2, H225<br>Acute Tox. 5 (Oral), H303                                                                                                                      |
| Aluminium                                            | CAS-No.: 7429-90-5     | 1 – 5         | Flam. Sol. 1, H228<br>Pyr. Liq. 1, H250<br>Water-react. 2, H261<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                  |
| ALIPHATIC HYDROCARBON                                | CAS-No.: 64742-47-8    | 1 – 5         | Flam. Liq. 3, H226<br>Acute Tox. 5 (Dermal), H313<br>Acute Tox. 3 (Inhalation:vapour), H331<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE     | CAS-No.: 41556-26-7    | 0.25 – 0.5    | Flam. Liq. 4, H227<br>Acute Tox. 5 (Oral), H303<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                            |
| METIL AND 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE | CAS-No.: 82919-37-7    | 0.1 – 0.25    | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                               |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.                                                                                                                                                    |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing.                                                                                                                                            |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact  | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                                                                                                             |
| First-aid measures after ingestion    | : Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.                                                                                                                                    |

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.                      |
| Symptoms/effects after inhalation   | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering).                                                                    |
| Symptoms/effects after eye contact  | : May cause eye irritation. stinging. Redness.                                                                                          |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract. Risk of lung oedema.                                                                     |
| Chronic symptoms                    | : May cause cancer. May cause heritable genetic damage.                                                                                 |

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

- Suitable extinguishing media : Dry chemical, CO<sub>2</sub>, or water spray or regular foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
- Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

#### 5.3. Special protective actions for fire-fighters

- Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
- Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

##### 6.1.2. For emergency responders

- Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Equip cleanup crew with proper protection.
- Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and materials for containment and cleaning up

- For containment : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

Take up liquid spill into absorbent material.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

- : Flammable vapours may accumulate in the container.
- : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures

- : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Incompatible materials

Packaging materials

- : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- : combustible materials.
- : Always store product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### ISOPENTYL ACETATE 123-92-2

#### USA - OSHA - Occupational Exposure Limits

|                                |                                  |
|--------------------------------|----------------------------------|
| Local name                     | Isomyl acetate                   |
| OSHA PEL TWA                   | 525 mg/m <sup>3</sup><br>100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1         |

### 8.2. Appropriate engineering controls

Appropriate engineering controls

- : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

**Personal protective equipment:**

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC

#### Eye protection:

Wear closed safety glasses

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                                                 |                                                                      |
|-------------------------------------------------|----------------------------------------------------------------------|
| Physical state                                  | : Liquid                                                             |
| Appearance                                      | : Liquid.                                                            |
| Colour                                          | : Aluminium                                                          |
| Odour                                           | : characteristic                                                     |
| Odour threshold                                 | : Not available                                                      |
| pH                                              | : Not applicable                                                     |
| Melting point                                   | : Not available                                                      |
| Freezing point                                  | : Not available                                                      |
| Boiling point                                   | : Not available                                                      |
| Flash point                                     | : 24 °C                                                              |
| Relative evaporation rate (butylacetate=1)      | : Not available                                                      |
| Flammability                                    | : Not available                                                      |
| Explosive limits                                | : Not available                                                      |
| Vapour pressure                                 | : Not available                                                      |
| Relative vapour density at 20°C                 | : Not available                                                      |
| Relative density                                | : Not available                                                      |
| Density                                         | : 0.94 – 1.04 g/cm³                                                  |
| Solubility                                      | : Material insoluble in water.<br>Water: Material insoluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                                                      |
| Auto-ignition temperature                       | : Not available                                                      |
| Decomposition temperature                       | : Not available                                                      |
| Viscosity, kinematic                            | : Not available                                                      |
| Viscosity, dynamic                              | : 65 – 70 ku/kg                                                      |
| Particle size                                   | : Not applicable                                                     |
| Particle size distribution                      | : Not applicable                                                     |
| Particle shape                                  | : Not applicable                                                     |
| Particle aspect ratio                           | : Not applicable                                                     |
| Particle specific surface area                  | : Not applicable                                                     |

### n-butyl acetate123-86-4

|                           |                                 |
|---------------------------|---------------------------------|
| Boiling point             | 126.2 °C Atm. press.: 1013 hPa  |
| Flash point               | 27 °C Atm. press.: 1013 hPa     |
| Auto-ignition temperature | 420 °C Source: ICSC             |
| Vapour pressure           | 11.5 mm Hg at 25°C Source: hSDB |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM64742-95-6

|                 |                              |
|-----------------|------------------------------|
| Boiling point   | 135 – 210 °C Source: NLM     |
| Flash point     | < 41 °C Source: IUCLID       |
| Vapour pressure | 8 hPa at 20°C Source: IUCLID |

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7

|                           |                                |
|---------------------------|--------------------------------|
| Boiling point             | 138 °C Source: ICSC            |
| Flash point               | 30 °C (ASTM D 93)              |
| Auto-ignition temperature | ≥ 528 °C Source: SRC           |
| Vapour pressure           | 8.84 mm Hg at 25°C Source: SRC |

### sec-butyl acetate105-46-4

|                 |                               |
|-----------------|-------------------------------|
| Boiling point   | 112 °C Source: HSDB           |
| Flash point     | 17 °C Source: ICSC            |
| Vapour pressure | 1.33 kPa at 20°C Source: ICSC |

### Aluminium7429-90-5

|                           |                      |
|---------------------------|----------------------|
| Boiling point             | 2327 °C Source: HSDB |
| Auto-ignition temperature | 590 °C Source: ICSC  |
| Vapour pressure           | 1 Temp.: 1284 °C     |

### ALIPHATIC HYDROCARBON64742-47-8

|                           |                                       |
|---------------------------|---------------------------------------|
| Boiling point             | 146 – 299 °C Atm. press.: 101,325 kPa |
| Flash point               | 29 – 70 °C Atm. press.: 101,325 kPa   |
| Auto-ignition temperature | 236 °C Source: ICSC                   |
| Vapour pressure           | 1 – 3.7 kPa Temp.: 37,8 °C            |

### ISOPENTYL ACETATE123-92-2

|                           |                                |
|---------------------------|--------------------------------|
| Boiling point             | 142 °C                         |
| Flash point               | 25 °C Source: ECHA             |
| Auto-ignition temperature | 379 °C Source: ECHA            |
| Vapour pressure           | 4.5 mm Hg at 20°C Source: ECHA |

### BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE41556-26-7

|                 |                                                                                  |
|-----------------|----------------------------------------------------------------------------------|
| Boiling point   | > 350 °C at 1013 hPa Source: International Uniform Chemical Information Database |
| Flash point     | 92 °C Source: International Uniform Chemical Information Database                |
| Vapour pressure | 0.000001 mm Hg at 20°C Source: National Institute of Technology and Evaluation   |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### 9.3. Further safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                                          |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.                    |
| Hazardous decomposition products   | : May liberate toxic gases.                                                                                                                                                                        |
| Incompatible materials             | : Materiais plásticos solúveis em Xileno. Não armazenar com materiais explosivos, gases inflamáveis e/ou tóxicos, substâncias oxidantes, corrosivas e materiais que possam. Combustible materials. |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                                        |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                                               |
| Handling temperature               | : No additional information available                                                                                                                                                              |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                 |
|-----------------------------|-----------------|
| Acute toxicity (oral)       | : Not available |
| Acute toxicity (dermal)     | : Not available |
| Acute toxicity (inhalation) | : Not available |

#### n-butyl acetate (123-86-4)

|                                 |                            |
|---------------------------------|----------------------------|
| LD50 oral rat                   | 3200 ml/kg Source: ECHA    |
| LD50 dermal rabbit              | > 17600 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Vapours) | 1802 mg/l Source: ECHA     |

#### SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)

|                                 |                           |
|---------------------------------|---------------------------|
| LD50 oral rat                   | 8400 mg/kg Source: RTECS  |
| LD50 dermal rat                 | > 2000 mg/kg Source: ECHA |
| LD50 dermal rabbit              | > 2000 mg/kg              |
| LC50 Inhalation - Rat (Vapours) | 5.16 mg/l Source: ECHA    |

#### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|                             |                                                         |
|-----------------------------|---------------------------------------------------------|
| LD50 oral rat               | 3523 mg/kg Source: ECHA                                 |
| LD50 dermal rabbit          | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
| LC50 Inhalation - Rat [ppm] | 5922 ppm                                                |

#### sec-butyl acetate (105-46-4)

|                             |                               |
|-----------------------------|-------------------------------|
| LD50 oral rat               | 3200 mg/kg Source: ChemIDplus |
| LC50 Inhalation - Rat [ppm] | 24000 ppm Source: ChemIDplus  |

#### Aluminium (7429-90-5)

|                                   |                            |
|-----------------------------------|----------------------------|
| LD50 oral rat                     | > 15900 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Dust/Mist) | > 0.888 mg/l Source: ECHA  |

#### ALIPHATIC HYDROCARBON (64742-47-8)

|               |                                                                               |
|---------------|-------------------------------------------------------------------------------|
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral) |
|---------------|-------------------------------------------------------------------------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### ALIPHATIC HYDROCARBON (64742-47-8)

|                                   |                                                                                                                                                    |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
|                                   | Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)                                                                 |
| LD50 dermal rabbit                | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat             | > 5.28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -                                              |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.2 mg/l Source: IUCLID                                                                                                                          |

### ISOPENTYL ACETATE (123-92-2)

|                    |                                 |
|--------------------|---------------------------------|
| LD50 dermal rabbit | > 5000 mg/kg Source: ChemIDPLUS |
|--------------------|---------------------------------|

### BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE (41556-26-7)

|               |                                                                               |
|---------------|-------------------------------------------------------------------------------|
| LD50 oral rat | 2369 – 3920 mg/kg Source: International Uniform Chemical Information Database |
|---------------|-------------------------------------------------------------------------------|

Skin corrosion/irritation : Causes skin irritation.  
pH: Not applicable

### n-butyl acetate (123-86-4)

|    |                                         |
|----|-----------------------------------------|
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
|----|-----------------------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### ISOPENTYL ACETATE (123-92-2)

|    |                |
|----|----------------|
| pH | Not applicable |
|----|----------------|

Serious eye damage/irritation : Not available  
pH: Not applicable

### n-butyl acetate (123-86-4)

|    |                                         |
|----|-----------------------------------------|
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
|----|-----------------------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|    |   |
|----|---|
| pH | 7 |
|----|---|

### ISOPENTYL ACETATE (123-92-2)

|    |                |
|----|----------------|
| pH | Not applicable |
|----|----------------|

Respiratory or skin sensitisation : Not available  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)

|            |                      |
|------------|----------------------|
| IARC group | 3 - Not classifiable |
|------------|----------------------|

### Aluminium (7429-90-5)

|                           |                                                                                                                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F0/P) | 1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### ALIPHATIC HYDROCARBON (64742-47-8)

|                           |                                                                                                                                                           |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F0/P) | ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)] |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|

Reproductive toxicity : Not available  
STOT-single exposure : Not available

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

|                                                                                             |                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>n-butyl acetate (123-86-4)</b>                                                           |                                                                                                                                                                                         |
| STOT-single exposure                                                                        | May cause drowsiness or dizziness.                                                                                                                                                      |
| <b>SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)</b>                                  |                                                                                                                                                                                         |
| STOT-single exposure                                                                        | May cause respiratory irritation.                                                                                                                                                       |
| <b>REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)</b>    |                                                                                                                                                                                         |
| STOT-single exposure                                                                        | May cause respiratory irritation.                                                                                                                                                       |
| STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure. |                                                                                                                                                                                         |
| <b>n-butyl acetate (123-86-4)</b>                                                           |                                                                                                                                                                                         |
| LOAEL (oral, rat, 90 days)                                                                  | 500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)                                                                                         |
| NOAEL (oral, rat, 90 days)                                                                  | 125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)                                                                                         |
| <b>REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)</b>    |                                                                                                                                                                                         |
| LOAEL (oral, rat, 90 days)                                                                  | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure                                                                      | May cause damage to organs through prolonged or repeated exposure.                                                                                                                      |
| <b>Aluminium (7429-90-5)</b>                                                                |                                                                                                                                                                                         |
| NOAEL (subchronic, oral, animal/male, 90 days)                                              | 1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)                                            |
| NOAEL (subchronic, oral, animal/female, 90 days)                                            | 1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)                                          |
| <b>ALIPHATIC HYDROCARBON (64742-47-8)</b>                                                   |                                                                                                                                                                                         |
| NOAEL (oral, rat, 90 days)                                                                  | 750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)                                               |
| NOAEL (dermal, rat/rabbit, 90 days)                                                         | ≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)                                                                            |

Aspiration hazard : May be fatal if swallowed and enters airways.

|                                                                                          |                                                                        |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| <b>W-THANE SRD 50 1 R ALUMINUM A COMPONENT</b>                                           |                                                                        |
| Viscosity, kinematic                                                                     | 1.888 – 2.249 mm²/s                                                    |
| <b>n-butyl acetate (123-86-4)</b>                                                        |                                                                        |
| Viscosity, kinematic                                                                     | 0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'   |
| <b>SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM (64742-95-6)</b>                               |                                                                        |
| Viscosity, kinematic                                                                     | < 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  |
| <b>REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50% (1330-20-7)</b> |                                                                        |
| Viscosity, kinematic                                                                     | ≈ 0.76 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' |

### 11.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.                      |
| Symptoms/effects after inhalation   | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering).                                                                    |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| Symptoms/effects after eye contact | : May cause eye irritation. stinging. Redness.                      |
| Symptoms/effects after ingestion   | : May cause irritation to the digestive tract. Risk of lung oedema. |
| Chronic symptoms                   | : May cause cancer. May cause heritable genetic damage.             |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                                           |
|-----------------------------------------------------------|---------------------------------------------------------------------------|
| Ecology - general                                         | : Toxic to aquatic life with long lasting effects. Toxic to aquatic life. |
| Hazardous to the aquatic environment, short-term (acute)  | : Toxic to aquatic life.                                                  |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects.                        |

#### n-butyl acetate123-86-4

|                      |                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]      | 18 mg/l Test organisms (species): Pimephales promelas                                                                                    |
| EC50 - Crustacea [1] | 44 mg/l Test organisms (species): Daphnia sp.                                                                                            |
| EC50 72h - Algae [1] | 397 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| LOEC (chronic)       | 47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |
| NOEC (chronic)       | 23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                                                       |

#### SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM64742-95-6

|                      |                          |
|----------------------|--------------------------|
| LC50 - Fish [1]      | 9.22 mg/l Source: IUCLID |
| EC50 - Crustacea [1] | 6.14 mg/l Source: IUCLID |
| EC50 72h - Algae [1] | 19 mg/l Source: IUCLID   |

#### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7

|                      |                                                                                                            |
|----------------------|------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]      | 2.6 mg/l Source: ECHA                                                                                      |
| EC50 - Crustacea [1] | 3.4 mg/l Test organisms (species): Ceriodaphnia dubia                                                      |
| ErC50 algae          | 2.2 mg/l                                                                                                   |
| LOEC (chronic)       | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'                                         |
| NOEC chronic fish    | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |

#### Aluminium7429-90-5

|                      |                                                                                                                                           |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EC50 72h - Algae [1] | 1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)  |

#### ALIPHATIC HYDROCARBON64742-47-8

|                 |                         |
|-----------------|-------------------------|
| LC50 - Fish [1] | 2.4 mg/l Source: ECOTOX |
|-----------------|-------------------------|

#### ISOPENTYL ACETATE123-92-2

|                      |                      |
|----------------------|----------------------|
| LC50 - Fish [1]      | 36 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 42 mg/l Source: ECHA |

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE41556-26-7

|                      |                                                                       |
|----------------------|-----------------------------------------------------------------------|
| LC50 - Fish [1]      | 0.97 mg/l Source: International Uniform Chemical Information Database |
| EC50 96h - Algae [1] | 0.017 mg/l Source: Ecological Structure Activity Relationships        |

### METIL AND 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE82919-37-7

|                      |                           |
|----------------------|---------------------------|
| LC50 - Fish [1]      | 0.996 mg/l                |
| EC50 96h - Algae [1] | 0.615 mg/l Source: ECOSAR |

## 12.2. Persistence and degradability

### W-THANE SRD 50 1 R ALUMINUM A COMPONENT

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### n-butyl acetate123-86-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM64742-95-6

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### sec-butyl acetate105-46-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### Aluminium7429-90-5

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ALIPHATIC HYDROCARBON64742-47-8

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### ISOPENTYL ACETATE123-92-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE41556-26-7

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### METIL AND 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE82919-37-7

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

## 12.3. Bioaccumulative potential

### n-butyl acetate123-86-4

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.78 Source: HSDB |
|-------------------------------------------------|-------------------|

### SOLVENT NAPHTHA (PETROLEUM) LIGHT AROM64742-95-6

|                                                 |                        |
|-------------------------------------------------|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 2.1 – 6 Source: IUCLID |
|-------------------------------------------------|------------------------|

### REACTION MASS OF ETHYLBENZENE (100-41-4)50% AND XYLENE (1330-20-7)50%1330-20-7

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.15 Source: HSDB |
|-------------------------------------------------|-------------------|

### sec-butyl acetate105-46-4

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.72 Source: HSDB |
|-------------------------------------------------|-------------------|

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

### ALIPHATIC HYDROCARBON64742-47-8

Partition coefficient n-octanol/water (Log Pow) 3.3 – 6 Source: IUCLID

### ISOPENTYL ACETATE123-92-2

Partition coefficient n-octanol/water (Log Pow) 2.13 Source: ICSC

### BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE41556-26-7

Partition coefficient n-octanol/water (Log Pow) 0.37 Source: International Uniform Chemical Information Database

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

## SECTION 13: Disposal considerations

Waste treatment methods : Must follow special treatment according to local regulation.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                                                                | IMDG                                                                                                                                                                       | IATA                                                                                  |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>UN number</b>                                                                    |                                                                                                                                                                            |                                                                                       |
| 1263                                                                                | 1263                                                                                                                                                                       | 1263                                                                                  |
| <b>UN Proper Shipping Name</b>                                                      |                                                                                                                                                                            |                                                                                       |
| TINTA                                                                               | PAINT                                                                                                                                                                      | Paint                                                                                 |
| <b>Transport document description</b>                                               |                                                                                                                                                                            |                                                                                       |
| Not applicable                                                                      | UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (24°C c.c.)                                                                                              | UN 1263 Paint, 3, III                                                                 |
| <b>Transport hazard class(es)</b>                                                   |                                                                                                                                                                            |                                                                                       |
| 3                                                                                   | 3                                                                                                                                                                          | 3                                                                                     |
| <b>Danger labels</b>                                                                |                                                                                                                                                                            |                                                                                       |
| 3                                                                                   | 3                                                                                                                                                                          | 3                                                                                     |
|  | <br> |  |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

14/16

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

|                                      |                 |                |
|--------------------------------------|-----------------|----------------|
| <b>Subsidiary risk</b>               |                 |                |
| Not applicable                       | Not applicable  | Not applicable |
| <b>Risk Number</b>                   |                 |                |
| 30                                   | Not applicable  | Not applicable |
| <b>Packing group</b>                 |                 |                |
| III                                  | III             | III            |
| <b>Special provisions</b>            |                 |                |
| 163,223,367                          | 163,223,367,955 | A3,A72,A192    |
| <b>Dangerous for the environment</b> |                 |                |
| Yes                                  | Yes             | Yes            |

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.  
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-THANE SRD 50 1 R ALUMINUM A COMPONENT

14787355

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/30/2026

BLV - Biological limit value

TRGS - Technical Rules for Hazardous Substances

TLM - Median Tolerance Limit

IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

---

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)