

W-COAT FEM RD



PRODUCT DESCRIPTION		
	Polyester resin-based base coat with high weathering resistance.	
RECOMMENDED USE		
	Suitable for painting painted wheels.	
CHARACTERISTICS		
	Color	Gray.
	Gloss	Gloss
	VOC content	494.01 g/l
	Volume Solids	15 ± 2% (ISO 3233)
	Solids Content	27.5 ± 7.5 %
	Flash Point	28 °C
	Shelf Life	12 months
	Dry Film Thickness	30 µm - 40 µm
	Theoretical Coverage	without dilution at a dry film thickness of 35 µm. Loss factors during application are not considered.
	Specific Gravity	Min: 0.9 Max: 1.001 g/cm³
	Viscosity	16 - 20" CF4
	Supply Viscosity	16 - 20" CF4
DRYING		
	Drying	<u>25 °C</u>
	Flash off	10 - 20 min
	Oven Drying	<u>160 °C</u>
	Final	20 min
SURFACE PREPARATION		
	Standard Surface Preparation	
	The performance of this product is related to the degree of surface preparation. In case of doubts, for more information, consult WEG's Technical Department.	
	For more information, consult the WEG Coatings Technical Department.	
APPLICATION PREPARATION		
	Thinner	Not applicable.
	Dilution	Ready to use.
	Notes	No dilution is required. Product ready to use. If necessary, consult the WEG Technical Department.
	Pot Life	Not relevant.
APPLICATION METHODS		
	Conventional Spray Gun	Conventional or Electrostatic Spray Gun.
	Cleaning of the equipments:	Not applicable.
SAFETY PRECAUTIONS		
	Product developed for industrial use intended for handling by qualified professionals. Carefully read	



all information contained in the SDS of this product, available at: www.weg.net.

Store in a covered and well-ventilated place. Keep the container tightly closed and away from sources of heat or ignition.

Use only in well-ventilated areas, avoiding the accumulation of flammable vapors. Keep the product away from heat and sources of ignition.

Do not inhale mists/vapors/aerosols generated during handling and/or application. Use protective gloves/protective clothing/eye protection/face protection.

Empty containers and materials with paint residues must be disposed of according to current legislation. Take care of the environment.

NOTE

The information contained in this technical bulletin is based on the experience and knowledge acquired in the field by WEG's technical team.

In the event of using the product without prior consultation with WEG regarding its suitability for the purpose for which the customer intends to use it, the customer acknowledges that the use will be at their own exclusive responsibility, and WEG is not liable for the behavior, safety, suitability, or durability of the product.

Some information mentioned in this bulletin is only an estimate and may vary due to factors beyond the manufacturer's control. Therefore, WEG does not guarantee and assumes no responsibility for performance, efficiency, or any material or personal damages resulting from the incorrect use of the products in question or from the information contained in this Technical Bulletin.

The information contained in this technical bulletin is subject to periodic modifications, without prior notice, due to our policy of continuous improvement and evolution of our products and services, providing quality solutions to meet the needs of our customers.
