

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT



Safety Data Sheet

According to ABNT NBR 14725: 2023
Issue date: 5/6/2026 Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT
Product code : 19381325
Type of product : Paint
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 – Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR 0800 117 2020

CHEMTREC international number +1-703-527-3887 e 1-800-424-9300

| Country | City | Local Number | Toll-Free Number |
|---------|--------|---------------|------------------|
| Austria | Vienna | +43-1-3649237 | |
| Austria | | | 0800 293702 |
| China | | 400 120 4937 | |
| France | | +33-975181407 | |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| | | | |
|----------------|-----------|------------------|------------------|
| Germany | | | 0800-181-7059 |
| India | Bangalore | +91 8071 279 207 | |
| India | | | 000 800 1007 141 |
| Italy | Milan | +39-02 4555 7031 | |
| Italy | | | 800 789 767 |
| Netherlands | | +31-85 888 0596 | |
| South Africa | | | 080-001-4676 |
| United Kingdom | London | +44 20 3807 3798 | |
| South korea | | | 080-880-0454 |
| Japan | | | 0800-300-5842 |

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Acute toxicity (dermal), Category 5
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2
Skin sensitisation, Category 1
Carcinogenicity, Category 1B
Hazardous to the aquatic environment - Acute Hazard, Category 2
Hazardous to the aquatic environment - Chronic Hazard, Category 3

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H313 - May be harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H350 - May cause cancer.
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS BR) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|--|------------------------|---------------|---|
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | CAS-No.: 25068-38-6 | 20 – 40 | Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Quartz(SiO ₂) | CAS-No.: 14808-60-7 | 10 – 20 | Skin Irrit. 2, H315 Skin Sens. 1, H317 |
| ALUMINIUM SILICATE | CAS-No.: 1327-36-2 | 10 – 20 | Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation:dust,mist), H332 |
| MIXED XYLENES | CAS-No.: 1330-20-7 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412 |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| Name | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023) |
|---------------------------------|------------------------|---------------|--|
| 2-methoxy-1-methylethyl acetate | CAS-No.: 108-65-6 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Aquatic Acute 3, H402 |
| SOLVENT ISOBUTHANOL | CAS-No.: 78-83-1 | 1 – 5 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335 |
| ethylbenzene | CAS-No.: 100-41-4 | 1 – 5 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| LEAD SULFOCHROMATE YELLOW | CAS-No.: 1344-37-2 | 0.25 – 0.5 | Carc. 1B, H350 Repr. 1A, H360 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. People with over sensibility problems are not allowed to work or be exposed to the product. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| First-aid measures after ingestion | : Do NOT induce vomiting. Rinse mouth out with water. |

4.2. Most important symptoms and effects, acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause an allergic skin reaction. Causes serious eye irritation. |
| Symptoms/effects after inhalation | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact | : stinging. Redness. Causes serious eye irritation. redness, itching, tears. |
| Symptoms/effects after ingestion | : May cause irritation to the digestive tract. |
| Chronic symptoms | : May cause cancer. |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
- Incompatible materials : combustible materials.
- Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| SOLVENT ISOBUTHANOL 78-83-1 | |
|---|--------------------------|
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Isobutyl alcohol |
| OSHA PEL TWA | 300 mg/m ³ |
| | 100 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

8.2. Appropriate engineering controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

Skin and body protection:

Long sleeved protective clothing. Or chemical resistant apron. Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

| | |
|---|---------------------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Colour | : Green |
| Odour | : characteristic |
| Odour threshold | : Not available |
| pH | : Not available |
| Melting point | : Not available |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flash point | : 31 °C |
| Relative evaporation rate (butylacetate=1) | : Not available |
| Flammability | : Not available |
| Explosive limits | : Not available |
| Vapour pressure | : Not available |
| Relative vapour density at 20°C | : Not available |
| Relative density | : Not available |
| Density | : 1.499 – 1.6 g/cm ³ |
| Solubility | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| Viscosity, kinematic | : 110 – 140 ku/kg |
| Particle size | : Not applicable |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| | |
|--------------------------------|------------------|
| Particle size distribution | : Not applicable |
| Particle shape | : Not applicable |
| Particle aspect ratio | : Not applicable |
| Particle specific surface area | : Not applicable |

2-methoxy-1-methylethyl acetate108-65-6

| | |
|---------------------------|--|
| Boiling point | 145.8 °C Atm. press.: 760 mm Hg Decomposition: 'no' |
| Flash point | 45.5 °C Atm. press.: 101,3 kPa |
| Auto-ignition temperature | 315 °C Source: International Uniform Chemical Information Database |
| Vapour pressure | 3.75 mm Hg Source: National Institute of Technology and Evaluation |

MIXED XYLENES1330-20-7

| | |
|---------------------------|--------------------------------|
| Boiling point | 138 °C Source: ICSC |
| Flash point | 30 °C (ASTM D 93) |
| Auto-ignition temperature | ≥ 528 °C Source: SRC |
| Vapour pressure | 8.84 mm Hg at 25°C Source: SRC |

Quartz(SiO2)14808-60-7

| | |
|---------------|------------------------|
| Boiling point | 2230 °C Source: GESTIS |
|---------------|------------------------|

ethylbenzene100-41-4

| | |
|---------------------------|---|
| Boiling point | 136.1 °C Atm. press.: 1013,3 mBar Decomposition: 'no' |
| Flash point | 23 °C Atm. press.: 1013 hPa |
| Auto-ignition temperature | 432 °C Source: ICSC |
| Vapour pressure | 9.52 mbar Temp.: 20 °C |

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6

| | |
|---------------|----------|
| Boiling point | > 260 °C |
| Flash point | > 249 °C |

SOLVENT ISOBUTHANOL78-83-1

| | |
|---------------------------|------------------------------------|
| Boiling point | 108 °C Source: ChemIDPlus |
| Flash point | 28 °C Source: ECHA |
| Auto-ignition temperature | 415 °C Source: ECHA |
| Vapour pressure | 1.2 kPa at 20°C Source: CHemIDplus |

9.2. Data relevant with regard to physical hazard classes

| | |
|--------------------|---------------|
| VOC Total (g/l) | : 315.02 g/l |
| VOC Total (lb/gal) | : 2.63 lb/gal |

9.3. Further safety characteristics

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 10: Stability and reactivity

| | |
|------------------------------------|---|
| Chemical stability | : In use may form flammable/explosive vapour-air mixture. |
| Conditions to avoid | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products | : May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases. |
| Incompatible materials | : Combustible materials. |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials. |
| Reactivity | : The product is non-reactive under normal conditions of use, storage and transport. |
| Handling temperature | : No additional information available |

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|--|
| Acute toxicity (oral) | : Not available |
| Acute toxicity (dermal) | : May be harmful in contact with skin. |
| Acute toxicity (inhalation) | : Not available |

| WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT | |
|---|--|
| ATE BR (dermal) | 4765.659 mg/kg bodyweight |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| LD50 oral rat | 8532 mg/kg Source: International Uniform Chemical Information Database |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LD50 dermal rabbit | > 5000 mg/kg Source: International Uniform Chemical Information Database |
| MIXED XYLENES (1330-20-7) | |
| LD50 oral rat | 3523 mg/kg Source: ECHA |
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
| LC50 Inhalation - Rat [ppm] | 5922 ppm |
| LEAD SULFOCHROMATE YELLOW (1344-37-2) | |
| LD50 oral rat | > 10000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| ethylbenzene (100-41-4) | |
| LD50 oral rat | ≈ 3500 mg/kg bodyweight Animal: rat |
| LD50 dermal rabbit | > 20000 mg/kg Source: ECHA |
| LC50 Inhalation - Rat [ppm] | 4000 ppm |
| ALUMINIUM SILICATE (1327-36-2) | |
| LD50 oral rat | > 2000 mg/kg Source: ECHA |
| LD50 dermal rabbit | > 5000 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Dust/Mist) | > 2.07 mg/l Source: ECHA |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6) | |
| LD50 oral rat | > 2000 mg/kg Source: ECHA |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

LD50 dermal rat > 2000 mg/kg Source: CHEMIDPLUS

SOLVENT ISOBUTHANOL (78-83-1)

LD50 oral rat 2460 mg/kg Source: ECHA

LD50 dermal rabbit 2460 mg/kg Source: ECHA

LC50 Inhalation - Rat (Vapours) 19.6 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.

MIXED XYLENES (1330-20-7)

pH 7

Quartz(SiO2) (14808-60-7)

pH 7

ALUMINIUM SILICATE (1327-36-2)

pH 4 – 8 Source: GESTIS

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

pH 4.5 – 4.7

Serious eye damage/irritation : Causes serious eye irritation.

MIXED XYLENES (1330-20-7)

pH 7

Quartz(SiO2) (14808-60-7)

pH 7

ALUMINIUM SILICATE (1327-36-2)

pH 4 – 8 Source: GESTIS

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (25068-38-6)

pH 4.5 – 4.7

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not available

Carcinogenicity : May cause cancer.

MIXED XYLENES (1330-20-7)

IARC group 3 - Not classifiable

Quartz(SiO2) (14808-60-7)

IARC group 1 - Carcinogenic to humans

ethylbenzene (100-41-4)

IARC group 2B - Possibly carcinogenic to humans

Reproductive toxicity : Not available

STOT-single exposure : Not available

MIXED XYLENES (1330-20-7)

STOT-single exposure May cause respiratory irritation.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| SOLVENT ISOBUTHANOL (78-83-1) | |
|---|---|
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
| STOT-repeated exposure | : Not available |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| MIXED XYLENES (1330-20-7) | |
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| LEAD SULFOCHROMATE YELLOW (1344-37-2) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| ethylbenzene (100-41-4) | |
| NOAEL (oral, rat, 90 days) | 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not available |
| WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT | |
| Viscosity, kinematic | 110 – 140 mm ² /s |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| Viscosity, kinematic | 1.182 mm ² /s |
| MIXED XYLENES (1330-20-7) | |
| Viscosity, kinematic | ≈ 0.76 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)' |
| ethylbenzene (100-41-4) | |
| Viscosity, kinematic | 0.739 mm ² /s |
| SOLVENT ISOBUTHANOL (78-83-1) | |
| Viscosity, kinematic | 5 mm ² /s |

11.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause an allergic skin reaction. Causes serious eye irritation. |
| Symptoms/effects after inhalation | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering). Cracking of the skin. Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact | : stinging. Redness. Causes serious eye irritation. redness, itching, tears. |
| Symptoms/effects after ingestion | : May cause irritation to the digestive tract. |
| Chronic symptoms | : May cause cancer. |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate 108-65-6

| | |
|----------------------|--|
| LC50 - Fish [1] | 100 mg/l Test organisms (species): <i>Oryzias latipes</i> |
| EC50 - Crustacea [1] | 500 mg/l Test organisms (species): <i>Daphnia magna</i> |
| EC50 72h - Algae [1] | 1000 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>) |
| NOEC (chronic) | ≥ 100 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d' |
| NOEC chronic fish | 47.5 mg/l Test organisms (species): <i>Oryzias latipes</i> Duration: '14 d' |

MIXED XYLENES 1330-20-7

| | |
|----------------------|---|
| LC50 - Fish [1] | 2.6 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 3.4 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i> |
| ErC50 algae | 2.2 mg/l |
| LOEC (chronic) | 3.16 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d' |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>) Duration: '56 d' |

LEAD SULFOCHROMATE YELLOW 1344-37-2

| | |
|----------------------|--|
| LC50 - Fish [1] | > 100 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>) |
| EC50 - Crustacea [1] | > 100 mg/l Test organisms (species): <i>Daphnia magna</i> |
| EC50 72h - Algae [1] | > 100 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>) |
| NOEC (chronic) | 0.7 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d' |

ethylbenzene 100-41-4

| | |
|----------------------|---|
| LC50 - Fish [1] | 5.1 mg/l Test organisms (species): <i>Menidia menidia</i> |
| EC50 72h - Algae [1] | 5.4 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>) |
| EC50 72h - Algae [2] | 4.9 mg/l Test organisms (species): <i>Skeletonema costatum</i> |
| EC50 96h - Algae [1] | 3.6 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>) |
| EC50 96h - Algae [2] | 7.7 mg/l Test organisms (species): <i>Skeletonema costatum</i> |
| LOEC (chronic) | 1.7 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i> Duration: '7 d' |
| NOEC (chronic) | 0.96 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i> Duration: '7 d' |

ALUMINIUM SILICATE 1327-36-2

| | |
|-----------------|-------------------------|
| LC50 - Fish [1] | 10000 mg/l Source: ECHA |
|-----------------|-------------------------|

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6 | |
|---|---|
| LC50 - Fish [1] | 1.41 mg/l Source: National Institute of Technology and Evaluation |
| EC50 - Crustacea [1] | 1.7 mg/l Source: NITE |
| SOLVENT ISOBUTHANOL78-83-1 | |
| LC50 - Fish [1] | 1430 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 1100 mg/l Source: ECHA |
| EC50 72h - Algae [1] | 593 mg/l Source: ECHA |

12.2. Persistence and degradability

| WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT | |
|---|------------------------|
| Persistence and degradability | Not rapidly degradable |
| 2-methoxy-1-methylethyl acetate108-65-6 | |
| Persistence and degradability | Not rapidly degradable |
| MIXED XYLENES1330-20-7 | |
| Persistence and degradability | Not rapidly degradable |
| Quartz(SiO2)14808-60-7 | |
| Persistence and degradability | Not rapidly degradable |
| LEAD SULFOCHROMATE YELLOW1344-37-2 | |
| Persistence and degradability | Not rapidly degradable |
| ethylbenzene100-41-4 | |
| Persistence and degradability | Not rapidly degradable |
| ALUMINIUM SILICATE1327-36-2 | |
| Persistence and degradability | Not rapidly degradable |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6 | |
| Persistence and degradability | Not rapidly degradable |
| SOLVENT ISOBUTHANOL78-83-1 | |
| Persistence and degradability | Not rapidly degradable |

12.3. Bioaccumulative potential

| 2-methoxy-1-methylethyl acetate108-65-6 | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 0.43 Source: International Uniform Chemical Information Database |
| MIXED XYLENES1330-20-7 | |
| Partition coefficient n-octanol/water (Log Pow) | 3.15 Source: HSDB |
| ethylbenzene100-41-4 | |
| Partition coefficient n-octanol/water (Log Pow) | 3.15 Source: HSDB |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane25068-38-6 | |
| Partition coefficient n-octanol/water (Log Pow) | 2821 Source: National Institute of Technology and Evaluation |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

SOLVENT ISOBUTHANOL78-83-1

Partition coefficient n-octanol/water (Log Pow) 0.8 Source: ChemIDPlus

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available



SECTION 13: Disposal considerations

Waste treatment methods : Must follow special treatment according to local regulation.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT | IMDG | IATA |
|---|---|----------------|
| UN number | | |
| 1263 | 1263 | 1263 |
| UN Proper Shipping Name | | |
| TINTA | PAINT | Not applicable |
| Transport document description | | |
| Not applicable | UN 1263 PAINT, 3, III (31°C c.c.) | UN 1263 |
| Transport hazard class(es) | | |
| 3 | 3 | Not applicable |
| Danger labels | | |
| 3 | 3 | Not applicable |
|  |  | Not applicable |
| Subsidiary risk | | |
| Not applicable | Not applicable | Not applicable |
| Risk Number | | |
| 30 | Not applicable | Not applicable |
| Packing group | | |
| III | III | Not applicable |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

| Special provisions | | |
|-------------------------------|-----------------|----------------|
| 163,223,367 | 163,223,367,955 | Not applicable |
| Dangerous for the environment | | |
| No | No | No |

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations : Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms : CAS-No. - Chemical Abstracts Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

WEGPOXI WET SURFACE 89 PW MX T GREEN POSEIDON 50736 A COMPONENT

19381325

Safety Data Sheet

According to ABNT NBR 14725: 2023

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

16/16