



W-LUBI DSR 47 AEROSOL



PRODUCT DESCRIPTION

Wax-like corrosion inhibiting solution, based on saturated hydrocarbons, hydrophobic action, preventing moisture permeation through the film and its effects on the metal. Its chemical composition promotes bonding between the organic film and the substrate, leaving a thin protective layer on the surface. Aerosol version allows easy application in hard-to-reach areas.

RECOMMENDED USE

Indicated as a release agent for valve, flange, and equipment coating paints, where removal is necessary for maintenance, composing double-protection plans.

Suitable for tools, hinges, nuts, spare parts, and other equipment as temporary corrosion protection. Surface temperature up to 140°F.

PACKAGING

Single Component Packaging of approximately 0.053 US gal

CHARACTERISTICS

Volume Solids 30 ± 2% (ISO 3233)
Shelf Life 12 months

SURFACE PREPARATION

Standard Surface Preparation

The performance of this product is related to the degree of surface preparation. In case of doubts, for more information, consult WEG's Technical Department.

Accumulated dirt must be removed using a dry brush, and soluble salts must be removed by washing with fresh water under high pressure.

APPLICATION PREPARATION

Mixing Shake the can well with circular movements before and during application. Perform a small test of the applicator by pressing the valve a few times on any surface and checking the jet pattern. Spray at 3.9-7.9 in from the surface using uniform, crossed movements to cover the desired area.

Thinner Not applicable.

Dilution Ready to use.

APPLICATION PERFORMANCE

Substrate temperature, climatic and environmental conditions during application and curing, as well as applied film thickness, may affect drying time.

SAFETY PRECAUTIONS

Product developed for industrial use intended for handling by qualified professionals. Carefully read all information contained in the SDS of this product, available at: www.weg.net.
 Store in a covered and well-ventilated place. Keep the container tightly closed and away from sources of heat or ignition.
 Use only in well-ventilated areas, avoiding the accumulation of flammable vapors. Keep the product away from heat and sources of ignition.
 Do not inhale mists/vapors/aerosols generated during handling and/or application. Use protective gloves/protective clothing/eye protection/face protection.
 Empty containers and materials with paint residues must be disposed of according to current legislation. Take care of the environment.

NOTE

The information contained in this technical bulletin is based on the experience and knowledge acquired in the field by WEG's technical team.
 In the event of using the product without prior consultation with WEG regarding its suitability for the purpose for which the customer intends to use it, the customer acknowledges that the use will be at their own exclusive responsibility, and WEG is not liable for the behavior, safety, suitability, or durability of the product.
 Some information mentioned in this bulletin is only an estimate and may vary due to factors beyond the manufacturer's control. Therefore, WEG does not guarantee and assumes no responsibility for performance, efficiency, or any material or personal damages resulting from the incorrect use of the products in question or from the information contained in this Technical Bulletin.



The information contained in this technical bulletin is subject to periodic modifications, without prior notice, due to our policy of continuous improvement and evolution of our products and services, providing quality solutions to meet the needs of our customers.
