

LACKTHERM 1317/230 H

Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 2/27/2024 Revision date: 1/13/2026 Version: 8.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : LACKTHERM 1317/230 H
Product code : 17609020
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Impregnation

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059
India	Bangalore	+91 8071 279 207	

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

India		000 800 1007 141
Italy	Milan	+39-02 4555 7031
Italy		800 789 767
Netherlands		+31-85 888 0596
South Africa		080-001-4676
United Kingdom	London	+44 20 3807 3798
South korea		080-880-0454
Japan		0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2A
Carcinogenicity, Category 2
Reproductive toxicity, Category 2
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Specific target organ toxicity — Repeated exposure, Category 1
Hazardous to the aquatic environment - Acute Hazard, Category 2
Hazardous to the aquatic environment - Chronic Hazard, Category 2

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer.
H361 - Suspected of damaging fertility or the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS BR)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

hearing protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice or attention.

P312 - Call a POISON CENTER or a doctor if you feel unwell.

P314 - Get medical advice or attention as appropriate.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice or attention.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media to extinguish.

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
STYRENE MONOMER	CAS-No.: 100-42-5	20 – 40	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
STYRENE MONOMER	CAS-No.: 100-42-5	10 – 20	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT SE 3, H335

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
			STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure. Causes serious eye irritation. May cause respiratory irritation.
Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.
Chronic symptoms	: Suspected carcinogen. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

Precautionary measures fire	: Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions	: Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

Protection during firefighting	: protective equipment, including respiratory protection.
Other information	: Use self-contained breathing apparatus and chemically protective clothing.
	: In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment	: Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.
Emergency procedures	: Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	: Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Flammable vapours may accumulate in the container.
Precautions for safe handling	: Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.
Incompatible materials	: combustible materials.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
----------------------------------	--

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC

Eye protection:

Wear closed safety glasses

Skin and body protection:

Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: amber
Odour	: characteristic
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

Freezing point	: Not available
Boiling point	: Not available
Flash point	: 40 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1.09 (1.05 – 1.09) g/cm³ (25°C)
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 210 – 250 cP (25°C)
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

STYRENE MONOMER100-42-5

Boiling point	145 °C Source: ICSC
Flash point	31 °C Source: ICSC
Auto-ignition temperature	490 °C Source: ICSC
Vapour pressure	0.67 kPa at 20°C Source: ICSC

STYRENE MONOMER100-42-5

Boiling point	145 °C Source: ICSC
Flash point	31 °C Source: ICSC
Auto-ignition temperature	490 °C Source: ICSC
Vapour pressure	0.67 kPa at 20°C Source: ICSC

9.2. Data relevant with regard to physical hazard classes

VOC content	: Free
VOC Total (g/l)	: 451.38 g/l
VOC Total (lb/gal)	: 3.77 lb/gal

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

Handling temperature : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not available
Acute toxicity (dermal) : Not available
Acute toxicity (inhalation) : Not available

STYRENE MONOMER (100-42-5)

LD50 oral rat	5000 mg/kg Source: ECHA
LD50 oral	> 6000 mg/kg bodyweight Animal: hamster, Syrian, Animal sex: male
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.8 mg/l Source: ECHA

STYRENE MONOMER (100-42-5)

LD50 oral rat	5000 mg/kg Source: ECHA
LD50 oral	> 6000 mg/kg bodyweight Animal: hamster, Syrian, Animal sex: male
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.8 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not available
Germ cell mutagenicity : Not available
Carcinogenicity : Suspected of causing cancer.

STYRENE MONOMER (100-42-5)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

STYRENE MONOMER (100-42-5)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : May cause respiratory irritation.

STYRENE MONOMER (100-42-5)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STYRENE MONOMER (100-42-5)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

STYRENE MONOMER (100-42-5)

LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat
LOAEC (inhalation, rat, vapour, 90 days)	0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat
NOAEL (subchronic, oral, animal/male, 90 days)	10 mg/kg bodyweight Animal: mouse, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

STYRENE MONOMER (100-42-5)

LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat
LOAEC (inhalation, rat, vapour, 90 days)	0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat
NOAEL (subchronic, oral, animal/male, 90 days)	10 mg/kg bodyweight Animal: mouse, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

LACKTHERM 1317/230 H

Viscosity, kinematic	192.661 – 229.358 mm ² /s
----------------------	--------------------------------------

STYRENE MONOMER (100-42-5)

Viscosity, kinematic	0.77 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	--

STYRENE MONOMER (100-42-5)

Viscosity, kinematic	0.77 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	--

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure. Causes serious eye irritation. May cause respiratory irritation.
Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: stinging. Redness. Causes serious eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.
Chronic symptoms	: Suspected carcinogen. Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

STYRENE MONOMER100-42-5

LC50 - Fish [1]	10 mg/l Source: ECHA
EC50 - Crustacea [1]	4.7 mg/l Source: ECHA
EC50 72h - Algae [1]	4.9 mg/l Source: ECHA
EC50 96h - Algae [1]	6.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

STYRENE MONOMER100-42-5

LC50 - Fish [1]	10 mg/l Source: ECHA
EC50 - Crustacea [1]	4.7 mg/l Source: ECHA

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

STYRENE MONOMER100-42-5

EC50 72h - Algae [1]	4.9 mg/l Source: ECHA
EC50 96h - Algae [1]	6.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

LACKTHERM 1317/230 H

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

STYRENE MONOMER100-42-5

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

STYRENE MONOMER100-42-5

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

STYRENE MONOMER100-42-5

Partition coefficient n-octanol/water (Log Pow)	2.95 Source: HSDB, ChemIDplus
---	-------------------------------

STYRENE MONOMER100-42-5

Partition coefficient n-octanol/water (Log Pow)	2.95 Source: HSDB, ChemIDplus
---	-------------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1263	1263	1263
UN Proper Shipping Name		
TINTA	PAINT	Paint

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

Transport document description		
Not applicable	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (40°C c.c.)	UN 1263 Paint, 3, III
Transport hazard class(es)		
3	3	3
Danger labels		
3	3	3
	 	
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
30	Not applicable	Not applicable
Packing group		
III	III	III
Special provisions		
163,223,367	163,223,367,955	A3,A72,A192
Dangerous for the environment		
Yes	Yes	Yes

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

LACKTHERM 1317/230 H

17609020

Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 1/13/2026

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net