

REACTIVE AGGREGATE CREETY ES

Safety Data Sheet

According to ABNT NBR 14725: 2023
Issue date: 10/8/2025 Version: 1.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Substance
Trade name : REACTIVE AGGREGATE CREETY ES
Product code : 18956231
Type of product : Fillers
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for maintenance sector

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREETY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
Russia			8(800)100-63-46
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Skin corrosion/irritation, Category 1

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)

:



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS BR)

: P260 - Do not breathe dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or a doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Name

: AGREGADO REATIVO CREETY ES

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREETY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Name	GHS Product identifier	Conc. (% w/w)	Classification according to GHS BR (ABNT NBR 14725: 2023)
Silicon dioxide	CAS-No.: 14808-60-7	60 – 80	Not classified
White Cement	CAS-No.: 65997-15-1	20 – 40	Skin Corr. 1, H314
Hydrated Lime	CAS-No.: 1305-62-0	5 – 10	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Skin Corr. 1, H314 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting because of corrosive effects.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Causes serious eye burns. May cause destruction of eye tissue.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. earth, sand, dry chemical powder or foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: In case of fire, corrosive gases come free.
-------------	---

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREEPY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Explosion hazard : No direct explosion hazard.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Other information : In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Stop leak without risks if possible. Using a clean shovel, put the material in a dry container and cover without compressing it.

Methods for cleaning up : Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : When heated, material emits highly irritating vapours, affecting the eyes. Keep only in original container. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.

Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store locked up.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREEPY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Silicon dioxide 14808-60-7

USA - ACGIH - Occupational Exposure Limits

Local name	Silica, crystalline, quartz
ACGIH® TLV® TWA	0.025 mg/m³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025

White Cement 65997-15-1

USA - ACGIH - Occupational Exposure Limits

Local name	Portland cement
ACGIH® TLV® TWA	1 mg/m³ (E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica, R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm func; resp symptoms; asthma. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Portland cement
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction) 50 mppcf (Silicates (less than 1% crystalline silica))
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1 and OSHA Annotated Table Z-3 Mineral Dusts

Hydrated Lime 1305-62-0

USA - ACGIH - Occupational Exposure Limits

Local name	Calcium hydroxide
ACGIH® TLV® TWA	5 mg/m³
Remark (ACGIH)	TLV® Basis: Eye, URT, & skin irr
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Calcium hydroxide
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Corrosionproof clothing.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

5/11

REACTIVE AGGREGATE CREETY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

Eye protection:

Wear closed safety glasses

Skin and body protection:

Safety shoes

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: white
Odour	: characteristic
Odour threshold	: Not available
pH	: 5.5 – 8
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 1700 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not applicable
Relative density	: Not available
Density	: 1.6 g/cm³
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
Viscosity, kinematic	: Not applicable
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle specific surface area	: Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREETY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Silicon dioxide14808-60-7

Boiling point	2230 °C Source: GESTIS
---------------	------------------------

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: On exposure to high temperature, may decompose, releasing corrosive gases.
Incompatible materials	: No additional information available.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available

Hydrated Lime (1305-62-0)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 6.04 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)

Skin corrosion/irritation	: Causes severe skin burns. pH: 5.5 – 8
---------------------------	--

White Cement (65997-15-1)

pH	12
----	----

Hydrated Lime (1305-62-0)

pH	12.4 Source: HSDB
----	-------------------

Serious eye damage/irritation	: Assumed to cause serious eye damage pH: 5.5 – 8
-------------------------------	--

White Cement (65997-15-1)

pH	12
----	----

Hydrated Lime (1305-62-0)

pH	12.4 Source: HSDB
----	-------------------

Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREETY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Silicon dioxide (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not available

STOT-single exposure : Not available

STOT-repeated exposure : Not available

Hydrated Lime (1305-62-0)

NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	--

Aspiration hazard : Not available

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.

Symptoms/effects after skin contact : Highly corrosive to skin. Causes severe burns. irritation (itching, redness, blistering).

Symptoms/effects after eye contact : Causes serious eye burns. May cause destruction of eye tissue.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Hydrated Lime1305-62-0

LC50 - Fish [1]	50.6 mg/l Source: EHCA
EC50 - Crustacea [1]	49.1 mg/l Source: ECHA
EC50 72h - Algae [1]	184.57 mg/l Source: EHCA
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosa Duration: '14 d'

12.2. Persistence and degradability

REACTIVE AGGREGATE CREETY ES

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Silicon dioxide14808-60-7

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

White Cement65997-15-1

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Hydrated Lime1305-62-0

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREEPY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer

: Not available

Other adverse effects

: May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

SECTION 13: Disposal considerations

Waste treatment methods

: Must follow special treatment according to local regulation.

Sewage disposal recommendations

: Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.

Additional information

: Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
2735	2735	2735
UN Proper Shipping Name		
AMINAS, CORROSIVAS, LÍQUIDAS, N.E. (White Cement)	AMINES, LIQUID, CORROSIVE, N.O.S. (White Cement)	Amines, liquid, corrosive, n.o.s. (White Cement)
Transport document description		
Not applicable	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (White Cement), 8, II	UN 2735 Amines, liquid, corrosive, n.o.s. (White Cement), 8, II
Transport hazard class(es)		
8	8	8
Danger labels		
8 	8 	8 
Subsidiary risk		
Not applicable	Not applicable	Not applicable
Risk Number		
80	Not applicable	Not applicable
Packing group		
II	II	II

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

9/11

REACTIVE AGGREGATE CREEPY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Special provisions		
274	274	A3,A803
Dangerous for the environment		
No	No	No

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

REACTIVE AGGREGATE CREEPY ES

18956231

Safety Data Sheet

According to ABNT NBR 14725: 2023

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.