

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

Safety Data Sheet

According to ABNT NBR 14725: 2023
Issue date: 4/29/2025 Version: 1.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT
Product code : 10204812
Type of product : Paint
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for industrial sector

1.4. Supplier's details

WEG TINTAS LTDA - GRUPO WEG

Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

1.5. Emergency phone number

Emergency number :

24-HOUR EMERGENCY - AMBIPAR		0800 117 2020	
CHEMTREC international number		+1-703-527-3887 e 1-800-424-9300	
Country	City	Local Number	Toll-Free Number
Austria	Vienna	+43-1-3649237	
Austria			0800 293702
China		400 120 4937	
France		+33-975181407	
Germany			0800-181-7059

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

India	Bangalore	+91 8071 279 207	
India			000 800 1007 141
Italy	Milan	+39-02 4555 7031	
Italy			800 789 767
Netherlands		+31-85 888 0596	
Russia			8(800)100-63-46
South Africa			080-001-4676
United Kingdom	London	+44 20 3807 3798	
South korea			080-880-0454
Japan			0800-300-5842

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3
Acute toxicity (dermal), Category 5
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2
Germ cell mutagenicity, Category 1B
Carcinogenicity, Category 1B
Reproductive toxicity, Category 1B
Specific target organ toxicity — Single exposure, Category 3, Narcosis
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Specific target organ toxicity — Repeated exposure, Category 2
Hazardous to the aquatic environment - Acute Hazard, Category 2
Hazardous to the aquatic environment - Chronic Hazard, Category 2

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour
H313 - May be harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects.
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS BR) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P312 - Call a POISON CENTER or a doctor if you feel unwell.
P314 - Get medical advice or attention as appropriate.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
MIXED XYLENES	CAS-No.: 1330-20-7	20 – 40	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
SOLVENT ACETATO DE ETILA	CAS-No.: 141-78-6	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
ETHYL ACETATE	CAS-No.: 141-78-6	5 – 10	Flam. Liq. 2, H225

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
			Eye Irrit. 2A, H319 STOT SE 3, H336
Light aromatic naphtha (petroleum) solvent	CAS-No.: 64742-95-6	5 – 10	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Ethyl Alcohol, Anhydrous Alcohol, AEAC	CAS-No.: 64-17-5	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
SOLVENT BUTYL GLYCOL (N)	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
N-METHYLPYRROLIDONE SOLVENT (N)	CAS-No.: 872-50-4	0.25 – 0.5	Flam. Liq. 4, H227 Acute Tox. 5 (Oral), H303 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H335

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: May cause eye irritation. stinging. Redness.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage. May damage fertility. May damage the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically
--------------------	-------------------------

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes.
Explosion hazard : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective actions for fire-fighters

- Precautionary measures fire : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.
Firefighting instructions : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

- Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Equip cleanup crew with proper protection.
Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment. Toxic to aquatic life. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

Absorb spillage to prevent material damage. Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Flammable vapours may accumulate in the container.

Precautions for safe handling

: Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Ensure good ventilation of the work station. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures

: Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ensure adequate ventilation, especially in confined areas. Store locked up. Store in tightly closed, leak-proof containers.

Storage conditions

: Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials

: combustible materials.

Packaging materials

: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SOLVENT ACETATO DE ETILA 141-78-6

USA - ACGIH - Occupational Exposure Limits

Local name	Ethyl acetate
ACGIH® TLV® TWA	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m ³ 400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

SOLVENT BUTYL GLYCOL (N) 111-76-2

USA - ACGIH - Occupational Exposure Limits

Local name	2-Butoxyethanol (EGBE)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

SOLVENT BUTYL GLYCOL (N) 111-76-2	
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m³
	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
MIXED XYLENES 1330-20-7	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
N-METHYLPYRROLIDONE SOLVENT (N) 872-50-4	
USA - ACGIH - Biological Exposure Indices	
Local name	N-Methyl-2-pyrrolidone
BEI	100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2024
ETHYL ACETATE 141-78-6	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH® TLV® TWA	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

WEG TINTAS LTDA – GRUPO WEG.

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

Ethyl Alcohol, Anhydrous Alcohol, AEAC 64-17-5

USA - ACGIH - Occupational Exposure Limits

Local name	Ethanol
ACGIH® TLV® STEL	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Ethyl alcohol (Ethanol)
OSHA PEL TWA	1900 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC

Eye protection:

Wear closed safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

Colour	: white
Odour	: characteristic
Odour threshold	: Not available
pH	: Not applicable
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 31 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 1.12 – 1.32 g/cm³
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: 50 – 60 Seconds
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

Light aromatic naphtha (petroleum) solvent64742-95-6

Boiling point	165.5 (156 – 175) °C
Flash point	40 °C
Vapour pressure	≤ 240 kPa Temp.: 37,8 °C

MIXED XYLENES1330-20-7

Boiling point	139.6 °C
Flash point	30 °C (ASTM D 93)
Auto-ignition temperature	488 °C
Vapour pressure	4.8 kPa 55°C

N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

Boiling point	204.3 °C at 1015.8 hPa Source: ECHA
Flash point	91 °C Source: ECHA
Auto-ignition temperature	245 °C Source: ECHA
Vapour pressure	0.32 hPa at 20°C Source: ECHA

Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

Boiling point	78.5 – 101.325 °C kPa (760 mm Hg)
Flash point	15 °C (vaso fechado)
Auto-ignition temperature	423 °C
Vapour pressure	5.9 kPa (44mmHg) a 20 °C

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: In use may form flammable/explosive vapour-air mixture.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours.
Hazardous decomposition products	: May liberate toxic gases.
Incompatible materials	: Combustible materials.
Possibility of hazardous reactions	: Liquids/vapours may ignite or react with other materials.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: May be harmful in contact with skin.
Acute toxicity (inhalation)	: Not available

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

ATE BR (dermal)	4794.667 mg/kg bodyweight
-----------------	---------------------------

Light aromatic naphtha (petroleum) solvent (64742-95-6)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	5.16 mg/l Source: ECHA

MIXED XYLENES (1330-20-7)

LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
--------------------	---

N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)

LD50 oral rat	4150 mg/kg Source: ECHA
LD50 dermal rat	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.1 mg/l Source: ECHA

Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

LD50 oral rat	7060 mg/kg Source: ECHA
LD50 oral	8300 mg/kg bodyweight Animal: mouse
LC50 Inhalation - Rat (Vapours)	116.9 mg/l Source: ECHA

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
---------------------------	---

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

MIXED XYLENES (1330-20-7)	
pH	7
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
pH	8.5 – 10
Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)	
pH	6 – 8
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
MIXED XYLENES (1330-20-7)	
pH	7
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
pH	8.5 – 10
Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)	
pH	6 – 8
Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
SOLVENT BUTYL GLYCOL (N) (111-76-2)	
IARC group	3 - Not classifiable
MIXED XYLENES (1330-20-7)	
IARC group	3 - Not classifiable
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
NOAEL (chronic, oral, animal/male, 2 years)	≈ 89 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)
NOAEL (chronic, oral, animal/female, 2 years)	≈ 221 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)
Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)	
IARC group	1 - Carcinogenic to humans
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
LOAEL (animal/female, F0/P)	500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/male, F0/P)	≥ 500 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/female, F0/P)	350 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
SOLVENT ACETATO DE ETILA (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

MIXED XYLENES (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
STOT-single exposure	May cause respiratory irritation.
ETHYL ACETATE (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
MIXED XYLENES (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
LOAEL (dermal, rat/rabbit, 90 days)	1653 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	826 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)	
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified.
W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT	
Viscosity, kinematic	50 – 60 mm ² /s
Light aromatic naphtha (petroleum) solvent (64742-95-6)	
Viscosity, kinematic	< 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
MIXED XYLENES (1330-20-7)	
Viscosity, kinematic	≈ 0.76 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
N-METHYLPYRROLIDONE SOLVENT (N) (872-50-4)	
Viscosity, kinematic	1.613 mm ² /s

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May cause severe burns. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Causes skin irritation. irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: May cause eye irritation. stinging. Redness.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: May cause cancer. May cause heritable genetic damage. May damage fertility. May damage the unborn child.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

Light aromatic naphtha (petroleum) solvent64742-95-6

LC50 - Fish [1] 9.22 mg/l Source: IUCLID

EC50 - Crustacea [1] 6.14 mg/l Source: IUCLID

EC50 72h - Algae [1] 19 mg/l Source: IUCLID

MIXED XYLENES1330-20-7

LC50 - Fish [1] ≈ 2.6 mg/l

EC50 - Crustacea [1] > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia

ErC50 algae ≈ 2.2 mg/l

LOEC (chronic) 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

NOEC chronic fish > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

LC50 - Fish [1] 500 mg/l Source: ECHA

EC50 72h - Algae [1] 600.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

EC50 72h - Algae [2] 672.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

LOEC (chronic) 25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

NOEC (chronic) 12.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

LC50 - Fish [1] > 100 mg/l Source: SIDS 2005

ErC50 algae 275 mg/l Source: ECHA

NOEC (chronic) 9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

12.2. Persistence and degradability

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

Persistence and degradability Not rapidly degradable

SOLVENT ACETATO DE ETILA141-78-6

Persistence and degradability Not rapidly degradable

Light aromatic naphtha (petroleum) solvent64742-95-6

Persistence and degradability Not rapidly degradable

SOLVENT BUTYL GLYCOL (N)111-76-2

Persistence and degradability Not rapidly degradable

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

MIXED XYLENES1330-20-7

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

ETHYL ACETATE141-78-6

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Light aromatic naphtha (petroleum) solvent64742-95-6

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

N-METHYLPYRROLIDONE SOLVENT (N)872-50-4

Partition coefficient n-octanol/water (Log Pow)	-0.46 Source: ECHA
---	--------------------

Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC
---	--------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Regional waste regulation	: Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1263	1263	1263
UN Proper Shipping Name		
TINTA	PAINT	Paint
Transport document description		
Not applicable	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

	HAZARDOUS (31°C c.c.)		
Transport hazard class(es)			
3	3	3	
Danger labels			
3	3	3	
			
Subsidiary risk			
Not applicable	Not applicable	Not applicable	
Risk Number			
30	Not applicable	Not applicable	
Packing group			
III	III	III	
Special provisions			
163,223,367	163,223,367,955	A3,A72,A192	
Dangerous for the environment			
Yes	Yes	Yes	

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net

W-LACK ERA 17 3 WHITE RAL 9003 MONOCOMPONENT

10204812

Safety Data Sheet

According to ABNT NBR 14725: 2023

VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: tintas@weg.net - www.weg.net