

CERTIFICATE OF COMPLIANCE

Certificate Number E202315
Report Reference E202315-19991019
Date 2020-November-11

Issued to: WEG DRIVES & CONTROLS - AUTOMACAO LTDA
AV PREFEITO WALDEMAR GRUBBA
3000
VILA LALAU
JARAGUA DO SUL SC, 89256-900 BR

This is to certify that representative samples of MOTOR CONTROLLERS, MAGNETIC
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL60947-1 & CSA C22.2 No. 60947-1, Low-Voltage Switchgear and Controlgear - Part 1: General Rules.

UL60947-4-1 & CSA C22.2 No. 60947-4-1, LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR — PART 4-1: CONTACTORS AND MOTOR-STARTERS — ELECTROMECHANICAL CONTACTORS AND MOTOR-STARTERS.

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E202315
Report Reference E202315-19991019
Date 2020-November-11

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Open type, reversing and nonreversing 2-pole, 3-pole contactors, Cat. No. CWM followed by 9, 12, 18, 25, 32, 40, 50, 65, 80, 95 or 105, may be followed by N, may be followed by P or S, followed by –00, -01, -10, or -11, followed by -20 or -30, followed by -C, -D, -U, -V, -X or –Y, followed by three characters related to the coil voltage.

Open type, reversing and nonreversing 4-pole contactors, Cat. No. CWM followed by 18, may be followed by N, may be followed by P or S, followed by –00, -01, -10, or -11, followed by -20 or -30 or -40 or -04 or -22, followed by -C, -D, -U, -V, -X or –Y, followed by three characters related to the coil voltage

Accessories –

Interlock Block , Models BLIM 9-105, BLIM.02 9-105;

Connector Links, Models GA67.1D, GA67.2D, GA-117D, GA-317.1D, GA-317.2D, GA-317.3D, GA-317.10D, JBL-RW407D;

Easy Connect Modules, Models EC-SD-15, EC-SD-22, EC-SD-25, EC-SD-30, EC-R-7.5, EC-R-11, EC-R-18.5;

Plastic Joint, Model MA-105

Coils, Models BCA4-25, BCC-25, BCA4-40, BECC4-40, BCA-105 or BECC-105, followed by three characters related to the coil voltage



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>