

# W-POXI GALVANIC SP COMPONENT B

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Issue date: 1/16/2026 Revision date: 2/20/2026 Version: 2.0



### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : W-POXI GALVANIC SP COMPONENT B  
Product code : 19158087  
Type of product : Paint  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating for industrial sector

#### 1.4. Supplier's details

##### WEG TINTAS LTDA - GRUPO WEG

##### Guaramirim - Santa Catarina / Brasil

Rodovia BR 280 – Km 50, 6.918 – Bloco A. Caixa D'Água – 89270-000 - +55 (47) 3276-4000

##### Mauá - São Paulo / Brasil

Rua Dr. Ulysses Guimarães, nº 918 – Bloco A. Loteamento Industrial Coral 09372-050 – Fone: +55 (11) 4547-6100

##### Cabo de Santo Agostinho - Pernambuco / Brasil

Via VII, 314 Distrito Industrial DIPER – 54590-000 - Fone: +55 (81) 3512-3000

##### Betim - Minas Gerais / Brasil

Avenida Juiz Marco Tulio Isaac, 2994 Betim Industrial – 32671-198, Fone: +55 (31) 3268-0687 / +55 (31) 3268-0686

##### Macaé - Rio de Janeiro / Brasil

Rua Itacolomi, 528 – Quadra H – Lote 11 Cabiúnas – 27977-340

##### Atotonilco de Tula - Estado de Hidalgo / México

Av. Hidalgo, lote 40, 41, 42 y 43 - Parque Industrial Bicentenario, CP 42980 - Fone: +52 (55) 5321-4231

##### Buenos Aires - Provincia de Buenos Aires / Argentina

Av. José Melián, 2983 - Parque Industrial Burzaco, B1852 - Fone: +54 (11) 4299-8000

#### 1.5. Emergency phone number

Emergency number :

|                                      |             |                                  |                         |
|--------------------------------------|-------------|----------------------------------|-------------------------|
| <b>24-HOUR EMERGENCY - AMBIPAR</b>   |             | 0800 117 2020                    |                         |
| <b>CHEMTREC international number</b> |             | +1-703-527-3887 e 1-800-424-9300 |                         |
| <b>Country</b>                       | <b>City</b> | <b>Local Number</b>              | <b>Toll-Free Number</b> |
| Austria                              | Vienna      | +43-1-3649237                    |                         |
| Austria                              |             |                                  | 0800 293702             |
| China                                |             | 400 120 4937                     |                         |
| France                               |             | +33-975181407                    |                         |
| Germany                              |             |                                  | 0800-181-7059           |

##### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

|                |           |                  |                  |
|----------------|-----------|------------------|------------------|
| India          | Bangalore | +91 8071 279 207 |                  |
| India          |           |                  | 000 800 1007 141 |
| Italy          | Milan     | +39-02 4555 7031 |                  |
| Italy          |           |                  | 800 789 767      |
| Netherlands    |           | +31-85 888 0596  |                  |
| South Africa   |           |                  | 080-001-4676     |
| United Kingdom | London    | +44 20 3807 3798 |                  |
| South korea    |           |                  | 080-880-0454     |
| Japan          |           |                  | 0800-300-5842    |

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 3  
Acute toxicity (oral), Category 5  
Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 1  
Specific target organ toxicity — Single exposure, Category 3, Narcosis  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

### 2.2. GHS Label elements, including precautionary statements

#### GHS BR labelling

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H226 - Flammable liquid and vapour  
H303 - May be harmful if swallowed  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS BR)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

P310 - Immediately call a POISON CENTER or a doctor.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                              | GHS Product identifier | Conc. (% w/w) | Classification according to GHS BR (ABNT NBR 14725: 2023)                                                                                                             |
|---------------------------------------------------|------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sec-butyl acetate                                 | CAS-No.: 105-46-4      | 50 – 60       | Flam. Liq. 2, H225<br>Acute Tox. 5 (Oral), H303                                                                                                                       |
| Ethyl Alcohol, Anhydrous Alcohol, AEAC            | CAS-No.: 64-17-5       | 20 – 40       | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319                                                                                                                              |
| SOLVENT ISOBUTHANOL                               | CAS-No.: 78-83-1       | 20 – 40       | Flam. Liq. 3, H226<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H336<br>STOT SE 3, H335       |
| phosphoric acid ... %, orthophosphoric acid ... % | CAS-No.: 7664-38-2     | 1 – 5         | Acute Tox. 5 (Oral), H303<br>Acute Tox. 5 (Dermal), H313<br>Skin Corr. 1, H314<br>Aquatic Acute 3, H402                                                               |
| 2-butoxyethyl acetate; butylglycol acetate        | CAS-No.: 112-07-2      | 1 – 5         | Flam. Liq. 4, H227<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Aquatic Acute 3, H402<br>Aquatic Chronic 3, H412 |

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Seek medical attention immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a POISON CENTER/doctor.

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

|                                       |                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. |
| First-aid measures after eye contact  | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.                                                                          |
| First-aid measures after ingestion    | : If you feel unwell, seek medical advice.                                                                                                                                                                  |

### 4.2. Most important symptoms and effects, acute and delayed

|                                     |                                                                                                                                                                                        |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.                                                                                      |
| Symptoms/effects after inhalation   | : Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. |
| Symptoms/effects after skin contact | : Causes skin irritation. irritation (itching, redness, blistering).                                                                                                                   |
| Symptoms/effects after eye contact  | : stinging. Redness. Causes serious eye damage. redness, itching, tears.                                                                                                               |
| Symptoms/effects after ingestion    | : May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.                                                                   |

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

|                    |                         |
|--------------------|-------------------------|
| Notes to physician | : Treat symptomatically |
|--------------------|-------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Suitable extinguishing media   | : Dry chemical, CO2, or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                   |

### 5.2. Specific hazards arising from the chemical

|                  |                                                                                                                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard      | : Flammable liquid and vapour. The vapours are denser than air and may travel along the ground. Distance ignition possible. Agitation can cause build up of electrostatic charge. Vapours may cause fire/explosion if source of ignition is present. In case of fire and/or explosion do not breathe fumes. |
| Explosion hazard | : Vapours may form explosive mixture with air. Prolonged exposure to fire may cause containers to rupture/explode.                                                                                                                                                                                          |

### 5.3. Special protective actions for fire-fighters

|                                |                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary measures fire    | : Keep container closed when not in use. This product is not to be used under conditions of poor ventilation.                                                                                                                                                                                                                                 |
| Firefighting instructions      | : Get the package away from the fire if this can be done without risk. Fight fire from a safe distance or use hoses with support or cannon engine. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.                                                                                                                                                                                                                                                                  |
| Other information              | : In case of fire, corrosive and harmful gases come free.                                                                                                                                                                                                                                                                                     |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                                                                                                                                                                                                                                                    |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures | : Eliminate every possible source of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid contact with skin and eyes. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### 6.1.1. For non-emergency personnel

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Protective equipment | : Wear recommended personal protective equipment. |
|----------------------|---------------------------------------------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Emergency procedures : No flames, no sparks. Eliminate all sources of ignition. Do not touch or walk on the spilled product. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

### 6.1.2. For emergency responders

Protective equipment : Use self-contained breathing apparatus and chemically protective clothing. Gloves. Wear security glasses which protect from splashes. Self-contained breathing apparatus. Total impervious protective suits, gloves, and boots must be worn to prevent any contact with the product. Corrosionproof suit. Equip cleanup crew with proper protection.

Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be grounded. Evacuate unnecessary personnel. Stop leak if safe to do so.

## 6.2. Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and materials for containment and cleaning up

For containment : Stop leak without risks if possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Absorb spillage to prevent material damage. Clean contaminated surfaces with an excess of water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Flammable vapours may accumulate in the container.

Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle carefully. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear personal protective equipment. When heated, material emits highly irritating vapours, affecting the eyes. Keep only in original container. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas.

Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight.

Incompatible materials : combustible materials.

Packaging materials : Always store product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### SOLVENT ISOBUTHANOL 78-83-1

#### USA - OSHA - Occupational Exposure Limits

|              |                       |
|--------------|-----------------------|
| Local name   | Isobutyl alcohol      |
| OSHA PEL TWA | 300 mg/m <sup>3</sup> |
|              | 100 ppm               |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

### SOLVENT ISOBUTHANOL 78-83-1

Regulatory reference (US-OSHA)

OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves made of PVC. Nitrile rubber gloves

#### Eye protection:

Wear closed safety glasses

#### Skin and body protection:

Safety shoes

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

|                                            |                     |
|--------------------------------------------|---------------------|
| Physical state                             | : Liquid            |
| Appearance                                 | : Liquid.           |
| Colour                                     | : Colourless        |
| Odour                                      | : characteristic    |
| Odour threshold                            | : Not available     |
| pH                                         | : Not available     |
| Melting point                              | : Not available     |
| Freezing point                             | : Not available     |
| Boiling point                              | : Not available     |
| Flash point                                | : 31 °C             |
| Relative evaporation rate (butylacetate=1) | : Not available     |
| Flammability                               | : Not available     |
| Explosive limits                           | : Not available     |
| Vapour pressure                            | : Not available     |
| Relative vapour density at 20°C            | : Not available     |
| Relative density                           | : Not available     |
| Density                                    | : 0.81 – 0.91 g/cm³ |

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Solubility                                      | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available                |
| Auto-ignition temperature                       | : Not available                |
| Decomposition temperature                       | : Not available                |
| Viscosity, kinematic                            | : Not available                |
| Particle size                                   | : Not applicable               |
| Particle size distribution                      | : Not applicable               |
| Particle shape                                  | : Not applicable               |
| Particle aspect ratio                           | : Not applicable               |
| Particle specific surface area                  | : Not applicable               |

### phosphoric acid ... %, orthophosphoric acid ... %7664-38-2

|                 |                                 |
|-----------------|---------------------------------|
| Boiling point   | 296.5 °C Atm. press.: 983 hPa   |
| Vapour pressure | 0.03 mm Hg at 20°C Source: ECHA |

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                           |                               |
|---------------------------|-------------------------------|
| Boiling point             | 78.5 °C Source: HSDB          |
| Flash point               | 13 °C Source: HSDB            |
| Auto-ignition temperature | 400 °C Source: ICSC           |
| Vapour pressure           | 5.8 kPa at 20 °C Source: ICSC |

### 2-butoxyethyl acetate; butylglycol acetate112-07-2

|                           |                                  |
|---------------------------|----------------------------------|
| Boiling point             | 192.3 °C Source: ECHA            |
| Flash point               | 78 °C Source: ECHA               |
| Auto-ignition temperature | 270 °C Source: ECHA              |
| Vapour pressure           | 0.375 mm Hg at 20°C Source: HSDB |

### SOLVENT ISOBUTHANOL78-83-1

|                           |                                    |
|---------------------------|------------------------------------|
| Boiling point             | 108 °C Source: ChemIDPlus          |
| Flash point               | 28 °C Source: ECHA                 |
| Auto-ignition temperature | 415 °C Source: ECHA                |
| Vapour pressure           | 1.2 kPa at 20°C Source: CHemIDplus |

### sec-butyl acetate105-46-4

|                 |                               |
|-----------------|-------------------------------|
| Boiling point   | 112 °C Source: HSDB           |
| Flash point     | 17 °C Source: ICSC            |
| Vapour pressure | 1.33 kPa at 20°C Source: ICSC |

## 9.2. Data relevant with regard to physical hazard classes

No additional information available

## 9.3. Further safety characteristics

No additional information available

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

### SECTION 10: Stability and reactivity

|                                    |                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chemical stability                 | : In use may form flammable/explosive vapour-air mixture.                                                                                                                       |
| Conditions to avoid                | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with hot surfaces. High temperature. Avoid formation of vapours. |
| Hazardous decomposition products   | : May liberate toxic gases. On exposure to high temperature, may decompose, releasing corrosive gases.                                                                          |
| Incompatible materials             | : Combustible materials.                                                                                                                                                        |
| Possibility of hazardous reactions | : Liquids/vapours may ignite or react with other materials.                                                                                                                     |
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                                                                                            |
| Handling temperature               | : No additional information available                                                                                                                                           |

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

|                             |                                |
|-----------------------------|--------------------------------|
| Acute toxicity (oral)       | : May be harmful if swallowed. |
| Acute toxicity (dermal)     | : Not available                |
| Acute toxicity (inhalation) | : Not available                |

#### W-POXI GALVANIC SP COMPONENT B

|               |                           |
|---------------|---------------------------|
| ATE BR (oral) | 3693.952 mg/kg bodyweight |
|---------------|---------------------------|

#### phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

|                    |                         |
|--------------------|-------------------------|
| LD50 oral rat      | 3500 mg/kg Source: ECHA |
| LD50 dermal rabbit | 2740 mg/kg Source: ECHA |

#### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|                                 |                                     |
|---------------------------------|-------------------------------------|
| LD50 oral rat                   | 7060 mg/kg Source: ECHA             |
| LD50 oral                       | 8300 mg/kg bodyweight Animal: mouse |
| LC50 Inhalation - Rat (Vapours) | 116.9 mg/l Source: ECHA             |

#### 2-butoxyethyl acetate; butylglycol acetate (112-07-2)

|                             |                         |
|-----------------------------|-------------------------|
| LD50 oral rat               | 1180 mg/kg Source: ECHA |
| LD50 dermal rabbit          | 1500 mg/kg Source: ECHA |
| LC50 Inhalation - Rat [ppm] | > 400 ppm Source: ECHA  |

#### SOLVENT ISOBUTHANOL (78-83-1)

|                                 |                         |
|---------------------------------|-------------------------|
| LD50 oral rat                   | 2460 mg/kg Source: ECHA |
| LD50 dermal rabbit              | 2460 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Vapours) | 19.6 mg/l Source: ECHA  |

#### sec-butyl acetate (105-46-4)

|                             |                               |
|-----------------------------|-------------------------------|
| LD50 oral rat               | 3200 mg/kg Source: ChemIDplus |
| LC50 Inhalation - Rat [ppm] | 24000 ppm Source: ChemIDplus  |

|                           |                           |
|---------------------------|---------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
|---------------------------|---------------------------|

#### phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

|    |   |
|----|---|
| pH | 1 |
|----|---|

#### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |                        |
|----|------------------------|
| pH | 7 Source: chemicalbook |
|----|------------------------|

#### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

Serious eye damage/irritation : Causes serious eye damage.

### phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

|    |   |
|----|---|
| pH | 1 |
|----|---|

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|    |                        |
|----|------------------------|
| pH | 7 Source: chemicalbook |
|----|------------------------|

Respiratory or skin sensitisation : Not available

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|            |                            |
|------------|----------------------------|
| IARC group | 1 - Carcinogenic to humans |
|------------|----------------------------|

Reproductive toxicity : Not available

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

### SOLVENT ISOBUTHANOL (78-83-1)

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
|----------------------|----------------------------------------------------------------------|

STOT-repeated exposure : Not available

### Ethyl Alcohol, Anhydrous Alcohol, AEAC (64-17-5)

|                                                |                                                                                                                          |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/male, 90 days) | < 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|

|                                                  |                                                                                                                            |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| NOAEL (subchronic, oral, animal/female, 90 days) | > 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|

Aspiration hazard : Not available

### SOLVENT ISOBUTHANOL (78-83-1)

|                      |                      |
|----------------------|----------------------|
| Viscosity, kinematic | 5 mm <sup>2</sup> /s |
|----------------------|----------------------|

## 11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Causes skin irritation. irritation (itching, redness, blistering).

Symptoms/effects after eye contact : stinging. Redness. Causes serious eye damage. redness, itching, tears.

Symptoms/effects after ingestion : May cause irritation to the digestive tract. May be harmful if swallowed. Ingestion may cause nausea and vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

### phosphoric acid ... %, orthophosphoric acid ... %7664-38-2

|                 |                        |
|-----------------|------------------------|
| LC50 - Fish [1] | 75.1 mg/l Source: ECHA |
|-----------------|------------------------|

|                      |                       |
|----------------------|-----------------------|
| EC50 - Crustacea [1] | 100 mg/l Source: ECHA |
|----------------------|-----------------------|

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

### phosphoric acid ... %, orthophosphoric acid ... %7664-38-2

|                      |                       |
|----------------------|-----------------------|
| EC50 72h - Algae [1] | 100 mg/l Source: ECHA |
|----------------------|-----------------------|

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                 |                                                                  |
|-----------------|------------------------------------------------------------------|
| LC50 - Fish [1] | > 100 mg/l Source: SIDS 2005                                     |
| ErC50 algae     | 275 mg/l Source: ECHA                                            |
| NOEC (chronic)  | 9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d' |

### 2-butoxyethyl acetate; butylglycol acetate112-07-2

|                 |                                 |
|-----------------|---------------------------------|
| LC50 - Fish [1] | 28 mg/l Source: ECHA, OECD SIDS |
| ErC50 algae     | 1570 mg/l Source: ECHA          |

### SOLVENT ISOBUTHANOL78-83-1

|                      |                        |
|----------------------|------------------------|
| LC50 - Fish [1]      | 1430 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 1100 mg/l Source: ECHA |
| EC50 72h - Algae [1] | 593 mg/l Source: ECHA  |

## 12.2. Persistence and degradability

### W-POXI GALVANIC SP COMPONENT B

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### phosphoric acid ... %, orthophosphoric acid ... %7664-38-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### 2-butoxyethyl acetate; butylglycol acetate112-07-2

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### SOLVENT ISOBUTHANOL78-83-1

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

### sec-butyl acetate105-46-4

|                               |                        |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

## 12.3. Bioaccumulative potential

### Ethyl Alcohol, Anhydrous Alcohol, AEAC64-17-5

|                                                 |                    |
|-------------------------------------------------|--------------------|
| Partition coefficient n-octanol/water (Log Pow) | -0.32 Source: ICSC |
|-------------------------------------------------|--------------------|

### 2-butoxyethyl acetate; butylglycol acetate112-07-2

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.51 Source: ECHA |
|-------------------------------------------------|-------------------|

### SOLVENT ISOBUTHANOL78-83-1

|                                                 |                        |
|-------------------------------------------------|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 0.8 Source: ChemIDPlus |
|-------------------------------------------------|------------------------|

### sec-butyl acetate105-46-4

|                                                 |                   |
|-------------------------------------------------|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.72 Source: HSDB |
|-------------------------------------------------|-------------------|

## WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer

: Not available

Other adverse effects

: May cause pH changes in aqueous ecological systems. Before neutralisation, the product may represent a danger to aquatic organisms.

## SECTION 13: Disposal considerations

Waste treatment methods

: Must follow special treatment according to local regulation.

Sewage disposal recommendations

: Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.

Additional information

: Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

### 14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT                                                                                | IMDG                                                                                | IATA                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>UN number</b>                                                                    |                                                                                     |                                                                                       |
| 1263                                                                                | 1263                                                                                | 1263                                                                                  |
| <b>UN Proper Shipping Name</b>                                                      |                                                                                     |                                                                                       |
| MATERIAL RELACIONADO COM TINTAS                                                     | PAINT RELATED MATERIAL                                                              | Paint related material                                                                |
| <b>Transport document description</b>                                               |                                                                                     |                                                                                       |
| Not applicable                                                                      | UN 1263 PAINT RELATED MATERIAL, 3, III<br>(31°C c.c.)                               | UN 1263 Paint related material, 3, III                                                |
| <b>Transport hazard class(es)</b>                                                   |                                                                                     |                                                                                       |
| 3                                                                                   | 3                                                                                   | 3                                                                                     |
| <b>Danger labels</b>                                                                |                                                                                     |                                                                                       |
| 3                                                                                   | 3                                                                                   | 3                                                                                     |
|  |  |  |
| <b>Subsidiary risk</b>                                                              |                                                                                     |                                                                                       |
| Not applicable                                                                      | Not applicable                                                                      | Not applicable                                                                        |
| <b>Risk Number</b>                                                                  |                                                                                     |                                                                                       |
| 30                                                                                  | Not applicable                                                                      | Not applicable                                                                        |
| <b>Packing group</b>                                                                |                                                                                     |                                                                                       |
| III                                                                                 | III                                                                                 | III                                                                                   |
| <b>Special provisions</b>                                                           |                                                                                     |                                                                                       |
| 163,223,367                                                                         | 163,223,367,955                                                                     | A3,A72,A192                                                                           |

WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |

Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)

# W-POXI GALVANIC SP COMPONENT B

19158087

## Safety Data Sheet

According to ABNT NBR 14725: 2023

Revision date: 2/20/2026

### Dangerous for the environment

|    |    |    |
|----|----|----|
| No | No | No |
|----|----|----|

### 14.2 Other informations

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.  
Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.  
Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.  
Law No. 12.305, of August 2, 2010 (National Policy on Solid Waste)

## SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstracts Service number  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
BCF - Bioconcentration factor  
EC50 - Median effective concentration  
LC50 - Median lethal concentration  
VOC - Volatile Organic Compounds  
LD50 - Median lethal dose  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
COD - Chemical oxygen demand (COD)  
ATE - Acute Toxicity Estimate  
IMDG - International Maritime Dangerous Goods  
IATA - International Air Transport Association  
EC-No. - European Community number  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
IOELV - Indicative Occupational Exposure Limit Value  
BLV - Biological limit value  
TRGS - Technical Rules for Hazardous Substances  
TLM - Median Tolerance Limit  
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.

### WEG TINTAS LTDA – GRUPO WEG.

Guaramirim-SC | Mauá-SP | Cabo de Santo Agostinho-PE | Betim-MG | Macaé-RJ |  
Buenos Aires – Argentina | Atotonilco de Tula - México

E-mail: [tintas@weg.net](mailto:tintas@weg.net) - [www.weg.net](http://www.weg.net)