

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023
Issue date: 1/29/2024 SAP export date: 1/29/2024 Version: 1.0



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA
Product code : 16589851
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Electrostatic powder paint for surface coating.

1.4. Supplier's details

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG
Rodovia BR 280 - km 50 CEP 89270-000, Guaramirim - Santa Catarina - Brasil

1.5. Emergency phone number

Emergency number :
SPILL/TOXICOLOGY WGRA 0800 720 8000
CHEMTREC international number + 1 703-741-5970

| Country | City | Local Number | Toll-Free Number |
|----------------|-----------|------------------|------------------|
| Austria | Vienna | 43-13649237 | |
| China | | 4001-204937 | |
| France | | 33-975181407 | |
| Germany | Frankfurt | 49-69643508409 | 0800-181-7059 |
| India | | 000-800-100-7141 | 000-800-100-7141 |
| Italy | Milan | 39-0245557031 | 800-789-767 |
| Italy | | 800-789-767 | |
| Netherlands | | 31-858880596 | |
| Russia | | 8-800-100-6346 | 8-800-100-6346 |
| South Africa | | 0-800-983-611 | 0-800-983-611 |
| United Kingdom | London | 44-870-8200418 | |
| United Kingdom | | 44-2038073798 | |
| South korea | | | 080-880-0468 |
| Japan | tokyo | | 0800-300-5842 |

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725:2023)

Hazardous to the aquatic environment - Chronic Hazard, Category 3

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard statements (GHS BR) : H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS BR) : P273 - Avoid release to the environment.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | GHS Product identifier | Conc. |
|----------------------|------------------------|---------|
| ANTIOXIDANT ADDITIVE | CAS-No.: 36443-68-2 | 0.1 – 1 |

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : If you feel unwell, seek medical advice.
First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects after inhalation : Dust of the product, if present, may cause respiratory irritation after an excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact : None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing.
Symptoms/effects after eye contact : None under normal conditions. Dust from this product may cause eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. earth, sand, dry chemical powder or foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : May be harmful to aquatic organisms, to flora, to soil organisms. Clean up any spills as soon as possible, using an absorbent material to collect it. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Harmful to aquatic life with long lasting effects. Do not allow product to spread into the environment. Do not allow to enter drains or water courses.

6.3. Methods and materials for containment and cleaning up

For containment : Using a clean shovel, put the material in a dry container and cover without compressing it. Stop leak without risks if possible.
Methods for cleaning up : Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep only in original container. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in tightly closed, leak-proof containers.
Storage conditions : Store in a well-ventilated place. Keep cool.
Packaging materials : Store always product in container of same material as original container.

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

| | |
|--|----------------------------|
| Physical state | : Solid |
| Appearance | : Dusty powder. |
| Colour | : |
| Odour | : slight |
| Odour threshold | : Not available |
| pH | : Not applicable |
| Melting point | : Not available |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flash point | : Not applicable |
| Relative evaporation rate (butylacetate=1) | : Not available |
| Flammability | : Not available |
| Explosive limits | : 50 – 70 g/m ³ |
| Vapour pressure | : Not available |
| Relative vapour density at 20°C | : Not applicable |
| Relative density | : Not available |

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

| | |
|---|---|
| Density | : 1.29 g/cm ³ |
| Solubility | : Insoluble in water, partially soluble in some solvents and thinners oxygen as acetone, ethyl acetate, methyl ethyl, ketone, among others. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Auto-ignition temperature | : Not applicable |
| Decomposition temperature | : 300 °C |
| Viscosity, kinematic | : Not applicable |
| Viscosity, dynamic | : Not applicable |
| Particle size | : 25 — 60 µm |
| Particle size distribution | : Not available |
| Particle shape | : Not available |
| Particle aspect ratio | : Not available |
| Particle specific surface area | : Not available |

ANTIOXIDANT ADDITIVE (36443-68-2)

| | |
|-------------|--------|
| Flash point | 150 °C |
|-------------|--------|

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

| | |
|------------------------------------|--|
| Chemical stability | : Stable under normal conditions of use. |
| Conditions to avoid | : Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| Hazardous decomposition products | : No hazardous decomposition products known at room temperature. |
| Incompatible materials | : |
| Possibility of hazardous reactions | : None under normal use. |
| Reactivity | : The product is non-reactive under normal conditions of use, storage and transport. |
| Handling temperature | : No additional information available |

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|--------------------|
| Acute toxicity (oral) | : Not available |
| Acute toxicity (dermal) | : Not available |
| Acute toxicity (inhalation) | : Not available |
| Skin corrosion/irritation | : Not available |
| | pH: Not applicable |

ANTIOXIDANT ADDITIVE (36443-68-2)

| | |
|----|---|
| pH | 7 |
|----|---|

| | |
|-------------------------------|--------------------|
| Serious eye damage/irritation | : Not available |
| | pH: Not applicable |

ANTIOXIDANT ADDITIVE (36443-68-2)

| | |
|----|---|
| pH | 7 |
|----|---|

| | |
|-----------------------------------|-----------------|
| Respiratory or skin sensitisation | : Not available |
| Germ cell mutagenicity | : Not available |
| Carcinogenicity | : Not available |

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

| | |
|------------------------|-----------------|
| Reproductive toxicity | : Not available |
| STOT-single exposure | : Not available |
| STOT-repeated exposure | : Not available |
| Aspiration hazard | : Not available |

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

| | |
|----------------------|----------------|
| Viscosity, kinematic | Not applicable |
|----------------------|----------------|

11.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Dust of the product, if present, may cause respiratory irritation after an excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : None under normal conditions. Dust may cause irritation in skin folds or by contact in combination with tight clothing. |
| Symptoms/effects after eye contact | : None under normal conditions. Dust from this product may cause eye irritation. |
| Symptoms/effects after ingestion | : None under normal conditions. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Hazardous to the aquatic environment, short-term (acute) | : Not available |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |

12.2. Persistence and degradability

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

ANTIOXIDANT ADDITIVE (36443-68-2)

| | |
|-------------------------------|------------------------|
| Persistence and degradability | Not rapidly degradable |
|-------------------------------|------------------------|

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

| | |
|------------------------------|-----------------|
| Hazardous to the ozone layer | : Not available |
|------------------------------|-----------------|

SECTION 13: Disposal considerations

| | |
|--|---|
| Regional waste regulation | : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010. |
| Waste treatment methods | : Must follow special treatment according to local regulation. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations. |
| Additional information | : Do not re-use empty containers. |

PAUMAR S.A. INDÚSTRIA E COMÉRCIO - GRUPO WEG Rua Dr. Ulisses Guimarães, 918 - 09372-050 - Mauá - SP - Fone: + 55 (11) 4547-6100 Rodovia Br 280 - Km 50, 6.918 - Bloco A - 89270-000 - Guaramirim - SC - Fone: + 55 (47) 3276-4000 Rua Via VII, 314 - 54590-000 - Cabo de Santo Agostinho - PE - Fone: + 55 (81) 3512-3000 PULVERLUX S.A. - Grupo WEG - Calle Melian 2983 - CP 1852 - Parque Ind. Almirante Brown - Burzaco - Pcia Buenos Aires - Fone +54 (11)4299-8000

EMERGÊNCIA: +55 0800 117 2020 - E-mail: tintas@weg.net - www.weg.net

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

| ANTT | IMDG | IATA |
|--------------------------------------|----------------|----------------|
| UN number | | |
| Not applicable | Not applicable | Not applicable |
| UN Proper Shipping Name | | |
| Not applicable | Not applicable | Not applicable |
| Transport hazard class(es) | | |
| Not applicable | Not applicable | Not applicable |
| Danger labels | | |
| Not applicable | Not applicable | Not applicable |
| Subsidiary risk | | |
| Not applicable | Not applicable | Not applicable |
| Risk Number | | |
| Not applicable | Not applicable | Not applicable |
| Packing group | | |
| Not applicable | Not applicable | Not applicable |
| Special provisions | | |
| Not applicable | Not applicable | Not applicable |
| Dangerous for the environment | | |
| No | Not applicable | Not applicable |

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Standard ABNT NBR 14725.

Federal Decree no. 10.088, of 5 November 2019 – Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of Brazil.

Ministerial Order no. 2.770, of 5 September 2022 – Approves the new wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials

Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

POLITHERM 49 WF TF R ME- ALUMINUM 11140 MA

Safety Data Sheet

According to ABNT NBR 14725:2023

SECTION 16: Other information

Abbreviations and acronyms

: CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF - Bioconcentration factor
EC50 - Median effective concentration
LC50 - Median lethal concentration
VOC - Volatile Organic Compounds
LD50 - Median lethal dose
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
COD - Chemical oxygen demand (COD)
ATE - Acute Toxicity Estimate
IMDG - International Maritime Dangerous Goods
IATA - International Air Transport Association
EC-No. - European Community number
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class
IOELV - Indicative Occupational Exposure Limit Value
BLV - Biological limit value
TRGS - Technical Rules for Hazardous Substances
TLM - Median Tolerance Limit
IARC - International Agency for Research on Cancer

Important information, but not specifically described in the previous sections: This MSDS was prepared based on current knowledge about the handling of the product under normal conditions of use, according to the application specified on the packaging and recommended usage in Section 1 of this MSDS. Any other use of the product involving its combination with other materials, as well as forms of use different from those indicated, are the user's responsibility. The company advises that the handling of any chemical substance requires prior knowledge of its hazards by the user. In the workplace it is responsibility of the company user of the product to provide training of its employees and contractors about the possible risks arising from exposure to the chemical. We reserve the right to change the information contained in this document without prior notice, due to the improvement and continuous evolution of the product and technical knowledge.